

CoCoA 5.1.3 Manual

February 19, 2016

Contents

I	Alphabetical List of Commands	21
I-0	Special Characters	23
I-0.1	operators, shortcuts	23
I-1	A	25
I-1.1	abs	25
I-1.2	adj	25
I-1.3	AffHilbert [OBSOLESCENT]	26
I-1.4	AffHilbertFn	26
I-1.5	AffHilbertSeries	26
I-1.6	AffPoincare [OBSOLESCENT]	27
I-1.7	alias	27
I-1.8	aliases	28
I-1.9	AllReducedGroebnerBases	28
I-1.10	AlmostQR	28
I-1.11	and	29
I-1.12	append	30
I-1.13	apply	30
I-1.14	ApproxSolve	30
I-1.15	ascii	31
I-1.16	AsINT	32
I-1.17	AsRAT	32
I-2	B	33
I-2.1	BaseRing	33
I-2.2	BBasis5	33
I-2.3	BettiDiagram	34
I-2.4	BettiMatrix	34
I-2.5	binomial	35
I-2.6	BinomialRepr, BinomialReprShift	35
I-2.7	block	36
I-2.8	BlockMat	37
I-2.9	BlockMat2x2	37
I-2.10	Bool01	38

I-2.11	break	38
I-2.12	BringIn	39
I-3	C	41
I-3.1	Call [OBSOLETE]	41
I-3.2	CanonicalHom	41
I-3.3	CanonicalRepr	42
I-3.4	CartesianProduct, CartesianProductList	42
I-3.5	Cast [OBSOLETE]	43
I-3.6	ceil	43
I-3.7	CFApprox	43
I-3.8	CFApproximants	44
I-3.9	characteristic	44
I-3.10	CharPoly	44
I-3.11	CheckArgTypes	45
I-3.12	ciao	45
I-3.13	ClearDenom	46
I-3.14	close	46
I-3.15	CloseLog	46
I-3.16	CoCoA-4 mode	47
I-3.17	CocoaLimits	47
I-3.18	CocoaPackagePath	47
I-3.19	codomain	48
I-3.20	CoeffEmbeddingHom	48
I-3.21	coefficients	48
I-3.22	CoefficientsWRT	49
I-3.23	CoeffListWRT	50
I-3.24	CoeffOfTerm	50
I-3.25	CoeffRing	51
I-3.26	ColMat	51
I-3.27	colon	52
I-3.28	ColumnVectors [OBSOLETE]	52
I-3.29	Comp [OBSOLETE]	53
I-3.30	Comparison Operators	53
I-3.31	CompleteToOrd [OBSOLESCENT]	53
I-3.32	compts	53
I-3.33	ComputeElimFirst	54
I-3.34	concat	54
I-3.35	ConcatAntiDiag	55
I-3.36	ConcatDiag	55
I-3.37	ConcatHor	56
I-3.38	ConcatHorList	56
I-3.39	ConcatLists	56

I-3.40	ConcatVer	57
I-3.41	ConcatVerList	57
I-3.42	content	58
I-3.43	ContentFreeFactor	58
I-3.44	ContentWRT	59
I-3.45	ContFrac	59
I-3.46	ContFracToRat	59
I-3.47	count	60
I-3.48	CpuTime	60
I-3.49	CRT	60
I-3.50	CRTPoly	61
I-3.51	CurrentRing	61
I-3.52	CurrentTypes	62
I-3.53	cyclotomic	62
I-4	D	63
I-4.1	dashes	63
I-4.2	date	63
I-4.3	DecimalStr	63
I-4.4	define	64
I-4.5	DefiningIdeal	66
I-4.6	deg	66
I-4.7	den	67
I-4.8	DensePoly	67
I-4.9	Depth	67
I-4.10	deriv	69
I-4.11	DerivationAction	69
I-4.12	describe	69
I-4.13	det	70
I-4.14	DF	70
I-4.15	DiagMat	71
I-4.16	diff	71
I-4.17	dim	72
I-4.18	discriminant	72
I-4.19	distrib	73
I-4.20	div	73
I-4.21	DivAlg	73
I-4.22	domain	74
I-5	E	75
I-5.1	E_ [OBSOLETE]	75
I-5.2	eigenfactors	75
I-5.3	eigenvectors	76

I-5.4	elim	76
I-5.5	ElimMat	77
I-5.6	EmbeddingHom	77
I-5.7	EqSet	78
I-5.8	Equality Test	78
I-5.9	EquiIsoDec	78
I-5.10	error	79
I-5.11	eval	80
I-5.12	EvalHilbertFn	80
I-5.13	EvalQuasiPoly	81
I-5.14	exponents	81
I-5.15	Ext	81
I-5.16	ExternalLibs	83
I-6	F	85
I-6.1	factor	85
I-6.2	factorial	85
I-6.3	FactorMultiplicity	86
I-6.4	FGLM5	86
I-6.5	fields	87
I-6.6	first	87
I-6.7	FirstNonZero	87
I-6.8	FirstNonZeroPosn	88
I-6.9	flatten	88
I-6.10	FloatApprox	89
I-6.11	FloatStr	89
I-6.12	floor	90
I-6.13	FloorLog2, FloorLog10, FloorLogBase	90
I-6.14	FloorSqrt	91
I-6.15	for	91
I-6.16	foreach	92
I-6.17	format	93
I-6.18	FrbAlexanderDual	93
I-6.19	FrbAssociatedPrimes	94
I-6.20	FrbIrreducibleDecomposition	94
I-6.21	FrbMaximalStandardMonomials	94
I-6.22	FrbPrimaryDecomposition	95
I-6.23	func	95
I-6.24	Function [OBSOLETE]	95
I-6.25	functions [OBSOLETE]	96
I-6.26	FVector	96
I-7	G	97

I-7.1	GBasis	97
I-7.2	GBasisTimeout	97
I-7.3	GBM	98
I-7.4	gcd	98
I-7.5	GCDFreeBasis	99
I-7.6	GenericPoints	99
I-7.7	GenRepr	100
I-7.8	gens	100
I-7.9	GensAsCols, GensAsRows	101
I-7.10	Get	102
I-7.11	GetCol	102
I-7.12	GetCols	103
I-7.13	GetEnv	103
I-7.14	GetErrMesg	103
I-7.15	GetRow	104
I-7.16	GetRows	104
I-7.17	GFanRelativeInteriorPoints	104
I-7.18	gin	105
I-7.19	GradingDim	105
I-7.20	GradingMat	105
I-8	H	107
I-8.1	HColon	107
I-8.2	HGBM	107
I-8.3	hilbert [OBSOLESCE]	108
I-8.4	HilbertBasisKer	108
I-8.5	HilbertFn	109
I-8.6	HilbertPoly	109
I-8.7	HilbertSeries	110
I-8.8	HilbertSeriesMultiDeg	111
I-8.9	HilbertSeriesShifts	112
I-8.10	homog	112
I-8.11	HomogElimMat	113
I-8.12	HSaturation	113
I-8.13	HVector	113
I-9	I	115
I-9.1	ID [OBSOLETE]	115
I-9.2	ideal	115
I-9.3	IdealAndSeparatorsOfPoints	116
I-9.4	IdealAndSeparatorsOfProjectivePoints	117
I-9.5	IdealOfPoints	118
I-9.6	IdealOfProjectivePoints	119

I-9.7	IdentityMat	120
I-9.8	if	120
I-9.9	ILogBase	121
I-9.10	image [OBSOLESCENT]	121
I-9.11	implicit	122
I-9.12	ImplicitHypersurface	122
I-9.13	ImplicitPlot	123
I-9.14	ImplicitPlotOn	123
I-9.15	ImportByRef, ImportByValue	124
I-9.16	in	124
I-9.17	incr, decr	125
I-9.18	indent	125
I-9.19	indet	126
I-9.20	IndetIndex	126
I-9.21	IndetName	127
I-9.22	indets	127
I-9.23	IndetSubscripts	128
I-9.24	IndetSymbols	129
I-9.25	InducedHom	129
I-9.26	InitialIdeal	130
I-9.27	insert [OBSOLESCENT]	130
I-9.28	Interpolate	131
I-9.29	interreduce, interreduced	132
I-9.30	intersection	132
I-9.31	IntersectList	132
I-9.32	inverse	133
I-9.33	InverseSystem	133
I-9.34	IO.SprintTrunc	134
I-9.35	iroot	134
I-9.36	IsAntiSymmetric	134
I-9.37	IsConstant	135
I-9.38	IsContained	135
I-9.39	IsDefined	135
I-9.40	IsDiagonal	136
I-9.41	IsDivisible	136
I-9.42	IsElem	136
I-9.43	IsEven, IsOdd	137
I-9.44	IsFactorClosed	137
I-9.45	IsField	137
I-9.46	IsFiniteField	138
I-9.47	IsFractionField	138
I-9.48	IsHomog	139
I-9.49	IsIn	139

I-9.50	IsIndet	140
I-9.51	IsInjective	140
I-9.52	IsInRadical	141
I-9.53	IsInSubalgebra [OBSOLETE]	141
I-9.54	IsInvertible	141
I-9.55	IsIrred	142
I-9.56	IsLexSegment	142
I-9.57	IsMaximal	142
I-9.58	IsNumber [OBSOLETE]	143
I-9.59	IsOne	143
I-9.60	IsPositiveGrading	143
I-9.61	IsPrimary	144
I-9.62	IsPrime	144
I-9.63	IsProbPrime	145
I-9.64	IsPthPower	145
I-9.65	IsQQ	145
I-9.66	isqrt	146
I-9.67	IsQuotientRing	146
I-9.68	IsStable	146
I-9.69	IsStdGraded	146
I-9.70	IsStronglyStable	147
I-9.71	IsSubset	147
I-9.72	IsSurjective	147
I-9.73	IsSymmetric	148
I-9.74	IsTerm	148
I-9.75	IsTermOrdering	149
I-9.76	IsTree5	149
I-9.77	IsTrueGCDDomain	150
I-9.78	IsZero	150
I-9.79	IsZeroCol, IsZeroRow	151
I-9.80	IsZeroDim	151
I-9.81	IsZeroDivisor	151
I-9.82	IsZZ	152
I-9.83	It	152
I-10	J	155
I-10.1	jacobian	155
I-10.2	JanetBasis	155
I-11	K	157
I-11.1	ker	157
I-12	L	159
I-12.1	last	159

I-12.2	LaTeX	159
I-12.3	LC	160
I-12.4	lcm	160
I-12.5	len	161
I-12.6	LexMat	161
I-12.7	LexSegmentIdeal	162
I-12.8	LF	162
I-12.9	LinearSimplify	163
I-12.10	LinKer	163
I-12.11	LinKerBasis	164
I-12.12	LinKerModP [OBSOLETE]	164
I-12.13	LinSol [OBSOLETE]	165
I-12.14	LinSolve	165
I-12.15	LM	166
I-12.16	log [OBSCOLESCENT]	166
I-12.17	LogCardinality	166
I-12.18	LPosn	167
I-12.19	LPP	167
I-12.20	LT	168
I-13	M	169
I-13.1	MakeCheck	169
I-13.2	MakeMatByRows, MakeMatByCols	169
I-13.3	MakeSet	170
I-13.4	MakeTerm	170
I-13.5	MakeTermOrd	170
I-13.6	MantissaAndExponent10	171
I-13.7	MantissaAndExponent2	172
I-13.8	Manual	172
I-13.9	MapDown [OBSOLETE]	173
I-13.10	matrix	173
I-13.11	max	174
I-13.12	MaxBy	174
I-13.13	MayerVietorisTreeN1	175
I-13.14	min	175
I-13.15	MinBy	176
I-13.16	MinGens	176
I-13.17	MinGensGeneral [OBSCOLESCENT]	177
I-13.18	minimalize	177
I-13.19	minimalized	177
I-13.20	MinimalPresentation	178
I-13.21	minors	178
I-13.22	MinPoly	178

I-13.23	MinPowerInIdeal	179
I-13.24	MinSubsetOfGens	179
I-13.25	mod	180
I-13.26	Mod2Rat [OBSOLETE]	180
I-13.27	ModuleElem	180
I-13.28	ModuleOf	181
I-13.29	monic	181
I-13.30	monomials	182
I-13.31	MonsInIdeal	182
I-13.32	multiplicity	182
I-14	N	185
I-14.1	NewFractionField	185
I-14.2	NewFreeModule	185
I-14.3	NewId [OBSOLETE]	186
I-14.4	NewLine [OBSCOLESCENT]	186
I-14.5	NewList	186
I-14.6	NewMat	187
I-14.7	NewMatFilled	187
I-14.8	NewPolyRing	188
I-14.9	NewQuotientRing	188
I-14.10	NewRingFp	189
I-14.11	NewRingTwinFloat	189
I-14.12	NewWeylAlgebra	190
I-14.13	NextPrime	190
I-14.14	NextProbPrime	190
I-14.15	NF	191
I-14.16	NFsAreZero [OBSOLETE]	191
I-14.17	NmzComputation	192
I-14.18	NmzDiagInvariants	192
I-14.19	NmzEhrhartRing	193
I-14.20	NmzFiniteDiagInvariants	193
I-14.21	NmzHilbertBasis	194
I-14.22	NmzIntClosureMonIdeal	194
I-14.23	NmzIntClosureToricRing	195
I-14.24	NmzIntersectionValRings	195
I-14.25	NmzNormalToricRing	195
I-14.26	NmzSetVerboseDefault	196
I-14.27	NmzTorusInvariants	196
I-14.28	NonZero	196
I-14.29	not	197
I-14.30	NR	197
I-14.31	num	198

I-14.32	NumCols	198
I-14.33	NumCompts	198
I-14.34	NumGens	199
I-14.35	NumIndets	199
I-14.36	NumPartitions	199
I-14.37	NumRows	200
I-14.38	NumTerms	200
I-15	O	201
I-15.1	one	201
I-15.2	OpenIFile	201
I-15.3	OpenIString	202
I-15.4	OpenLog	202
I-15.5	OpenOFile	203
I-15.6	OpenOString	204
I-15.7	OpenSocket	204
I-15.8	Option [OBSOLETE]	205
I-15.9	or	205
I-15.10	OrdMat	205
I-16	P	207
I-16.1	Packages	207
I-16.2	panel [OBSOLETE]	207
I-16.3	panels [OBSOLETE]	207
I-16.4	partitions	208
I-16.5	permutations	208
I-16.6	PerpIdealOffForm	208
I-16.7	pfaffian	209
I-16.8	PkgName	209
I-16.9	PlotPoints	210
I-16.10	PlotPointsOn	210
I-16.11	poincare [OBSOLESCENT]	211
I-16.12	PoincareMultiDeg [OBSOLETE]	211
I-16.13	PoincareShifts [OBSOLETE]	211
I-16.14	PolyAlgebraHom	211
I-16.15	PolyRingHom	212
I-16.16	PowerMod	212
I-16.17	PreImage	213
I-16.18	PreprocessPts	213
I-16.19	PrimaryDecomposition	214
I-16.20	PrimaryDecomposition0	215
I-16.21	PrimaryDecompositionGTZ0	215
I-16.22	PrimaryHilbertSeries	215

I-16.23	PrimaryPoincare [OBSOLESCENT]	217
I-16.24	PrimitiveRoot	217
I-16.25	print	217
I-16.26	print on	218
I-16.27	PrintBettiDiagram	218
I-16.28	PrintBettiMatrix	219
I-16.29	println	219
I-16.30	PrintRes	219
I-16.31	product	220
I-16.32	protect	220
I-16.33	PthRoot	221
I-17	Q	223
I-17.1	QQ	223
I-17.2	quit	223
I-17.3	QuotientBasis	224
I-17.4	QuotientingHom	224
I-17.5	QZP	224
I-18	R	227
I-18.1	radical	227
I-18.2	RadicalOfUnmixed	227
I-18.3	random	228
I-18.4	randomize	228
I-18.5	randomized	229
I-18.6	RandomSubset	229
I-18.7	RandomSubsetIndices	230
I-18.8	RandomTuple	230
I-18.9	RandomTupleIndices	231
I-18.10	rank [OBSOLESCENT]	231
I-18.11	RationalAffinePoints	231
I-18.12	RationalProjectivePoints	232
I-18.13	RationalSolve	232
I-18.14	RatReconstructByContFrac, RatReconstructByLattice	232
I-18.15	RatReconstructPoly	233
I-18.16	RatReconstructWithBounds	234
I-18.17	ReadExpr	234
I-18.18	RealRootRefine	234
I-18.19	RealRoots	235
I-18.20	RealRootsApprox	236
I-18.21	record	236
I-18.22	record field selector	237
I-18.23	ReducedGBasis	237

I-18.24	ref	237
I-18.25	RefineGCDFreeBasis	238
I-18.26	reg	238
I-18.27	RegularityIndex	239
I-18.28	RelNotes	240
I-18.29	ReloadMan	240
I-18.30	remove	240
I-18.31	repeat	241
I-18.32	res	241
I-18.33	Reset [OBSOLETE]	242
I-18.34	ResetPanels [OBSOLETE]	242
I-18.35	resultant	242
I-18.36	return	243
I-18.37	reverse, reversed	243
I-18.38	RevLexMat	244
I-18.39	RingElem	244
I-18.40	RingEnv [OBSOLETE]	245
I-18.41	RingID	245
I-18.42	RingOf	246
I-18.43	RingQQ	246
I-18.44	RingQQt	247
I-18.45	RingSet [OBSOLETE]	247
I-18.46	RingsOf	248
I-18.47	RingZZ	248
I-18.48	rk	249
I-18.49	RMap [OBSOLESCECENT]	249
I-18.50	RootBound	249
I-18.51	round	250
I-18.52	RowMat	250

I-19 S 251

I-19.1	saturate	251
I-19.2	ScalarProduct	251
I-19.3	ScientificStr	252
I-19.4	seed	252
I-19.5	SeparatorsOfPoints	253
I-19.6	SeparatorsOfProjectivePoints	254
I-19.7	SetRow	255
I-19.8	SetStackSize	255
I-19.9	shape	255
I-19.10	sign	256
I-19.11	SimplestBinaryRatBetween	257
I-19.12	SimplestRatBetween	257

I-19.13	SimplexInfo	257
I-19.14	SimplicialHomology	258
I-19.15	size [OBSOLETE]	259
I-19.16	skip	259
I-19.17	SmoothFactor	259
I-19.18	sort	260
I-19.19	SortBy	260
I-19.20	sorted	261
I-19.21	SortedBy	261
I-19.22	source	262
I-19.23	SourceRegion	262
I-19.24	spaces	263
I-19.25	sprint	263
I-19.26	SqFreeFactor	264
I-19.27	StableBBasis5	264
I-19.28	StableIdeal	265
I-19.29	StarPrint, StarSprint	265
I-19.30	starting	266
I-19.31	StdDegLexMat	266
I-19.32	StdDegRevLexMat	267
I-19.33	StronglyStableIdeal	267
I-19.34	SubalgebraMap [OBSOLETE]	268
I-19.35	SubalgebraRepr	268
I-19.36	submat	268
I-19.37	submodule	269
I-19.38	SubmoduleCols, SubmoduleRows	269
I-19.39	subsets	270
I-19.40	subst	270
I-19.41	sum	271
I-19.42	support	271
I-19.43	swap	272
I-19.44	SwapRows	272
I-19.45	sylvester	273
I-19.46	SymbolRange	273
I-19.47	syz	274
I-19.48	SyzOfGens	275
I-20	T	277
I-20.1	tag	277
I-20.2	tagged	277
I-20.3	tail	278
I-20.4	TensorMat	278
I-20.5	TgCone	278

I-20.6	TimeFrom	279
I-20.7	TimeOfDay	279
I-20.8	TmpChainCanonicalHom	279
I-20.9	TmpNBM	280
I-20.10	TopLevel	280
I-20.11	TopLevelFunctions	281
I-20.12	toric	281
I-20.13	transposed	282
I-20.14	try	283
I-20.15	tuples	284
I-20.16	type	284
I-21	U	285
I-21.1	UnivariateIndetIndex	285
I-21.2	UniversalGroebnerBasis	285
I-21.3	unprotect	286
I-21.4	Unset [OBSOLETE]	286
I-21.5	untagged	286
I-21.6	use	287
I-22	V	289
I-22.1	valuation [OBSOLETE]	289
I-22.2	VersionInfo	289
I-23	W	291
I-23.1	wdeg	291
I-23.2	WeightsMatrix [OBSOLESCENT]	291
I-23.3	while	292
I-23.4	WithoutNth	292
I-23.5	WLog [OBSOLETE]	292
I-24	X	295
I-24.1	XelMat	295
I-25	Z	297
I-25.1	zero	297
I-25.2	ZeroMat	297
I-25.3	ZPQ	298
I-25.4	ZZ	298
II	The CoCoA Programming Language	301
II-1	Introduction to CoCoA Programming	303
II-1.1	An Overview of CoCoA Programming	303

II-2	Language Elements	305
II-2.1	Character Set and Special Symbols	305
II-2.2	Identifiers	305
II-2.3	Reserved Names	306
II-2.4	Comments	306
II-3	Operators	307
II-3.1	CoCoA Operators	307
II-3.2	Algebraic Operators	307
II-3.3	Relational Operators	308
II-3.4	Selection Operators	308
II-3.5	Range Operator	308
II-4	Evaluation and Assignment	311
II-4.1	Evaluation	311
II-4.2	Assignment	311
II-5	Flow Control: Conditional Statements and Loops	313
II-5.1	All CoCoA commands	313
II-5.2	Commands and Functions for Branching	313
II-5.3	Commands and Functions for Loops	313
II-6	Input/Output	315
II-6.1	Introduction to IO	315
II-6.2	Standard IO	315
II-6.3	File IO	315
II-6.4	String IO	316
II-6.5	Commands and Functions for IO	317
II-7	CoCoA Packages	319
II-7.1	Introduction to Packages	319
II-7.2	First Example of a Package	319
II-7.3	Package Essentials	320
II-7.4	Global Aliases	320
II-7.5	Sharing Your Package	320
II-7.6	Commands and Functions for Packages	320
II-7.7	Supported Packages	321
II-7.8	Galois Package	321
II-7.9	Integer Programming	321
II-7.10	Algebra of Invariants	321
II-7.11	Special Varieties	321
II-7.12	Statistics	322
II-7.13	Geometrical Theorem-Proving	322
II-7.14	Typevectors	322

II-7.15	Conductor	322
II-7.16	Matrix Normal Form	323
II-7.17	CantStop	323
II-7.18	Control	323
II-8	Linked libraries	325
II-8.1	CoCoALib	325
II-8.2	GMP	325
II-8.3	GSL	325
II-8.4	Frobby	325
II-8.5	Normaliz	325
II-9	Migrating from CoCoA-4 and keeping up-to-date	327
II-9.1	Changes in the CoCoA language	327
II-9.2	Recent changes in the CoCoA-5 language	328
II-9.3	Obsolete and obsolescent functions	328
III	CoCoA datatypes	331
III-1	BOOL	333
III-1.1	Introduction to BOOL	333
III-1.2	Commands and Functions for BOOL	333
III-1.3	Commands and Functions returning BOOL	333
III-2	INT	335
III-2.1	Introduction to INT	335
III-2.2	Commands and Functions for INT	335
III-2.3	Commands and Functions returning INT	337
III-3	RAT	339
III-3.1	Introduction to RAT	339
III-3.2	Commands and Functions for RAT	339
III-3.3	Commands and Functions returning RAT	340
III-4	STRING	341
III-4.1	String Literals	341
III-4.2	String Operations	341
III-4.3	Commands and Functions for STRING	342
III-4.4	Commands and Functions returning STRING	342
III-5	LIST	345
III-5.1	Introduction to LIST	345
III-5.2	List Constructors	346
III-5.3	Commands and Functions for LIST	346
III-5.4	Commands and Functions returning LIST	349

III-6	RECORD	351
III-6.1	Introduction to RECORD	351
III-6.2	Commands and Functions for RECORD	352
III-6.3	Commands and Functions returning RECORD	352
III-7	FUNCTION	355
III-7.1	Introduction to FUNCTION	355
III-7.2	FUNCTIONs are first class objects	355
III-7.3	Commands and Functions for FUNCTION	355
III-7.4	Commands and Functions returning FUNCTION	356
III-8	TYPE	357
III-8.1	Commands and Functions for TYPE	357
III-8.2	Commands and Functions returning TYPE	357
III-9	RING	359
III-9.1	Introduction to RING	359
III-9.2	Polynomial Rings	359
III-9.3	Coefficient Rings	360
III-9.4	Indeterminates	360
III-9.5	Orderings	360
III-9.6	Module Orderings	361
III-9.7	Quotient Rings	361
III-9.8	Commands and Functions for RING	362
III-9.9	Commands and Functions returning RING	363
III-10	RINGHOM	365
III-10.1	Introduction to RINGHOM	365
III-10.2	Composition of RINGHOM	365
III-10.3	Commands and Functions for RINGHOM	366
III-10.4	Commands and Functions returning RINGHOM	366
III-11	RINGELEM	367
III-11.1	Introduction to RINGELEM	367
III-11.2	Evaluation of Polynomials	368
III-11.3	Commands and Functions for RINGELEM	368
III-11.4	Commands and Functions returning RINGELEM	370
III-12	IDEAL	373
III-12.1	Commands and Functions for IDEAL	373
III-12.2	Commands and Functions returning IDEAL	374
III-13	MAT	377
III-13.1	Introduction to MAT	377
III-13.2	Commands and Functions for MAT	377

III-13.3	Commands and Functions returning MAT	379
III-14	MODULE	381
III-14.1	Commands and Functions for MODULE	381
III-14.2	Commands and Functions returning MODULE	382
III-15	MODULEELEM	383
III-15.1	Introduction to MODULEELEM	383
III-15.2	Commands and Functions for MODULEELEM	383
III-15.3	Commands and Functions returning MODULEELEM	384
III-16	Creating new types	385
III-16.1	Tagging an Object	385
III-16.2	Printing a Tagged Object	385
III-16.3	Commands and Functions for Tags	386

Part I

Alphabetical List of Commands

Chapter I-0

Special Characters

I-0.1 operators, shortcuts

syntax

```
A := B    A:variable, B:OBJECT
A = B     A,B:OBJECT
A <> B    A,B:OBJECT
[...]     LIST
[..|...]  LIST
L[N]      N: INT, L: LIST
A..B      A,B: INT or A,B:indeterminates
R.F       R:RECORD and F field name
R ::= ... R:variable
A >< B     A,B: LIST
M : N     M, N: MODULE or IDEAL
R/I       R: RING, I: IDEAL
S[N]      N: INT, S: STRING
***E***   E:expression
?S        S: STRING
<< S     S: STRING
```

Description

“A := B;” compute “B” then assign the result to “A” “A = B” test whether “A” and “B” are equal “A <> B” test whether “A” and “B” are not equal “[...]” build a new list (see “List Constructors” ([III-5.2 pg.346](#))) “[..|...]” build a new list (see “List Constructors” ([III-5.2 pg.346](#))) “L[N]” access “N”-th entry of list “L” (indexes start from 1) “A..B” is the “Range Operator” ([II-3.5 pg.308](#)) “R.F” “record field selector” ([I-18.22 pg.237](#)) for field named “F” of record “R” “R ::= ” for the special ring syntax (“NewPolyRing” ([I-14.8 pg.188](#)))

“A >< B” equivalent to “CartesianProduct(A, B)”, “CartesianProductList([A,B])” “M : N” equivalent to “colon(M, N)” “R/I” equivalent to “NewQuotientRing(R,I)” “S[N]” access “N”-th char of string “L” (indexes start from 1) “***E***” interpret “E” in “CoCoA-4 mode” ([I-3.16 pg.47](#)) “\$<< S\$” OBSOLESCENT equivalent to “source(S)”

“? string” prints the manual page for “string”, or a list of matching manual pages

See Also: colon([I-3.27 pg.52](#)), List Constructors([III-5.2 pg.346](#)), CartesianProduct, CartesianProductList([I-3.4 pg.42](#)), NewPolyRing([I-14.8 pg.188](#)), NewQuotientRing([I-14.9 pg.188](#)), record field selector([I-18.22 pg.237](#)), Range Operator([II-3.5 pg.308](#)), source([I-19.22 pg.262](#)), Manual([I-13.8 pg.172](#)), Character Set and Special Symbols([II-2.1 pg.305](#)), CoCoA Operators([II-3.1 pg.307](#))

Chapter I-1

A

I-1.1 abs

syntax

```
abs(N: INT): INT
abs(N: RAT): RAT
abs(N: RINGELEM): RINGELEM
```

Description

This function returns the absolute value of “N”. If “N” is a “RINGELEM” then it must belong to an ordered ring.

example

```
/**/ abs(-3);
3

/**/ abs(-2/3);
2/3
```

I-1.2 adj

syntax

```
adj(M: MAT): MAT
```

Description

This function returns the classical adjoint of the square matrix “M”.

example

```
/**/ Use R := QQ[t,x,y,z];
/**/ adj(mat([[x,y,z],[t,y,x],[x,x^2,x*y]]));
matrix( /*RingWithID(44, "QQ[t,x,y,z]")*/
  [[-x^3 +x*y^2, -x*y^2 +x^2*z, x*y -y*z],
  [-t*x*y +x^2, x^2*y -x*z, -x^2 +t*z],
  [t*x^2 -x*y, -x^3 +x*y, -t*y +x*y]])

/**/ Z5 := NewRingFp(5);
/**/ adj(matrix(Z5, [[1,2],[3,1]]));
matrix( /*FFp(5)*/
  [[1, -2],
  [2, 1]])
```

See Also: `inverse`([I-9.32](#) pg.133)

I-1.3 AffHilbert [OBSOLESCENT]

syntax

[OBSOLESCENT]

Description

Renamed “AffHilbertFn” ([I-1.4](#) pg.26).

I-1.4 AffHilbertFn

syntax

```
AffHilbertFn(R: RING): TAGGED("$hp.Hilbert")
AffHilbertFn(R: RING, N: INT): INT
```

Description

The first form of this function computes the affine Hilbert function for R. The second form computes the N-th value of the affine Hilbert function. The weights of the indeterminates of R must all be 1. For repeated evaluations of the Hilbert function, use “EvalHilbertFn” ([I-5.12](#) pg.80) instead of “AffHilbertFn(R, N)” in order to speed up execution.

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ AffHilbertFn(R/ideal(z^4-1, x*z^4-y-3));
H(0) = 1
H(1) = 3
H(t) = 4t - 2   for t >= 2
```

See Also: `AffHilbertSeries`([I-1.5](#) pg.26), `EvalHilbertFn`([I-5.12](#) pg.80), `HilbertPoly`([I-8.6](#) pg.109), `HVector`([I-8.13](#) pg.113), `HilbertSeries`([I-8.7](#) pg.110)

I-1.5 AffHilbertSeries

syntax

```
AffHilbertSeries(TAGGED("Quotient")):TAGGED("$hp.PSeries")
```

Description

This function computes the affine Hilbert-Poincare series of M. The grading must be a positive Z^1 -grading (i.e. “GradingMat” ([I-7.20](#) pg.105) must have a single row with positive entries), and the ordering must be degree compatible. In the standard case, i.e. the weights of all indeterminates are 1, the result is simplified so that the power appearing in the denominator is the dimension of M + 1.

It used to be called “AffPoincare [OBSOLESCENT]” ([I-1.6](#) pg.27).

NOTES:

(i) the coefficient ring must be a field.

(ii) these functions produce tagged objects: they cannot safely be (non-)equality to other values.

For further details on affine Hilbert functions see the book: Kreuzer, Robbiano "Computer Commutative Algebra II", Section 5.6.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ AffHilbertSeries(R/ideal(z^4-1, x*z^4-y-3));
(1 +x +x^2 +x^3) / (1-x)^2
```

See Also: AffHilbertFn(I-1.4 pg.26), HilbertSeries(I-8.7 pg.110)

I-1.6 AffPoincare [OBSOLESCENT]

syntax

[OBSOLESCENT]

Description

Renamed "AffHilbertSeries" (I-1.5 pg.26).

I-1.7 alias

syntax

```
alias B_1,...,B_r
```

where each B_i is a "{\it binding}" of the form: Identifier := \$PackageName

Description

This function is for declaring both global and local aliases for package names. Recall that package names are meant to be long in order to avoid conflicts between the names of functions that are read into a CoCoA session. However, it is inconvenient to have to type out the long package name when referencing a function. So the user chooses an alias to take the place of the package name; the alias is just a means to avoid typing.

1. Global aliases. To avoid typing the full package name as a prefix to package functions, one may declare a short global alias during a CoCoA session. A list of the global aliases is produced by the function "aliases" (I-1.8 pg.28). For examples, see the chapter on packages in the manual, in particular the section, "Global Aliases" (II-7.4 pg.320). Online, enter "?global aliases".

2. Local aliases. A local alias has the same syntax as a global alias, however it appears inside a package definition. The local aliases work only inside the package and do not conflict with any global aliases already defined. In fact, in order to avoid conflicts, global aliases are not recognized within a package. For examples, again look in the chapter for packages.

example

```
/**/ alias LL := $abcd;
/**/ aliases();

Coclib      = $coclib
Approx      = $approx
(...)
TP          = $contrib/thmproving
TV          = $contrib/typevectors
LL          = $abcd
```

See Also: [aliases\(I-1.8 pg.28\)](#), [Introduction to Packages\(II-7.1 pg.319\)](#)

I-1.8 aliases

syntax

```
aliases():TAGGED("aliases")
```

Description

This function prints a list of global aliases for packages. Aliases are formed with the function “[alias](#)” ([I-1.7 pg.27](#)).

example

```
/**/ alias LL := $abcd;
/**/ aliases();

Coclib      = $coclib
Approx      = $approx
(...)
TP          = $contrib/thmproving
TV          = $contrib/typevectors
LL          = $abcd
```

See Also: [alias\(I-1.7 pg.27\)](#), [Introduction to Packages\(II-7.1 pg.319\)](#)

I-1.9 AllReducedGroebnerBases

syntax

```
AllReducedGroebnerBases(I: IDEAL): LIST of IDEAL
```

Description

Returns all reduced Groebner bases of the IDEAL “I” as a LIST of ideals.

example

```
-- The ideal in [Sturmfels, Example 3.9] has 360 marked reduced Groebner bases
/**/ Use R := QQ[a,b,c];
/**/ I := ideal(a^5+b^3+c^2-1, b^2+a^2+c-1, c^3+a^6+b^5-1);
/**/ l:=AllReducedGroebnerBases(I);
/**/ len(l);
360
```

See Also: [UniversalGroebnerBasis\(I-21.2 pg.285\)](#)

I-1.10 AlmostQR

syntax

```
AlmostQR(M: MAT): RECORD
```

Description

This function computes the decomposition of the matrix into an orthogonal and an upper triangular matrix with 1 on the diagonal. [*“orthogonal”* meaning that $Q^T * Q$ is a diagonal matrix]

The auxiliary (possibly slow!) function “`Mat.SimplifySquareFactorsInAQR`” modifies Q and R in the decomposition so that the entries of the diagonal matrix $Q^T * Q$ are squarefree rationals.

— example —

```

/**/ M := matrix(QQ, [ [4, -2, 3], [3, 2, -2], [0, 0, 3] ]);
/**/ Dec := AlmostQR(M);
/**/ Dec;
record[Q := matrix(QQ,
  [[4, -42/25, 0],
   [3, 56/25, 0],
   [0, 0, 3]])
, R := matrix(QQ,
  [[1, -2/25, 6/25],
   [0, 1, -17/14],
   [0, 0, 1]])
]

/**/ $mat.SimplifySquareFactorsInAQR(ref Dec);
/**/ Dec;
record[Q := matrix(QQ,
  [[4/5, -3/5, 0],
   [3/5, 4/5, 0],
   [0, 0, 1]])
, R := matrix(QQ,
  [[5, -2/5, 6/5],
   [0, 14/5, -17/5],
   [0, 0, 3]])
, SqDiag := [1, 1, 1]]

```

See Also: [Matrix Normal Form](#)([II-7.16](#) pg.323)

I-1.11 and

— syntax —

```

A and B      (where A, B: BOOL, return BOOL)

```

Description

This operator represents the logical conjunction of “A” and “B”. CoCoA first evaluates “A”; if that gives “false” then the result is “false”, and “B” is not evaluated. Otherwise if “A” gives “true” then “B” is evaluated, and its value is the final result.

— example —

```

/**/ A := -1;
/**/ A >= 0 and FloorSqrt(A) < 10; --> calls FloorSqrt only if A >= 0
false

```

See Also: [or](#)([I-15.9](#) pg.205), [not](#)([I-14.29](#) pg.197)

I-1.12 `append`

syntax

```
append(ref L: LIST, E: OBJECT)
```

Description

Append the object “E” to the list “L”; this call returns nothing!

NOTE: the old CoCoA-4 syntax “Append(L, E)” is still allowed, but produces a warning; replace the call by “append(ref L, E)”.

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ L := [1,2,3];
/**/ append(ref L, 4);
/**/ L;
[1, 2, 3, 4]
```

See Also: ref(I-18.24 pg.237), concat(I-3.34 pg.54), ConcatLists(I-3.39 pg.56), remove(I-18.30 pg.240)

I-1.13 `apply`

syntax

```
apply(phi: RINGHOM, X: RINGELEM): RINGELEM
apply(phi: RINGHOM, X: LIST): LIST
apply(phi: RINGHOM, X: MAT): MAT
```

Description

Apply homomorphism “phi” to all elements in second argument “X” (“RINGELEM”, “LIST”, or “MAT”)

When “X” is of type “RINGELEM” this is equivalent to the natural syntax “phi(X)”.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ S := QQ[x[1..3]];
/**/ phi := PolyAlgebraHom(R, S, indets(S));
/**/ apply(phi, [x^2-y, z-2]);
[x[1]^2 -x[2], x[3] -2]

/**/ apply(phi, x^2-y); -- same as phi(x^2-y)
x[1]^2 -x[2]
/**/ phi(x^2-y);
x[1]^2 -x[2]
```

See Also: PolyAlgebraHom(I-16.14 pg.211), CanonicalHom(I-3.2 pg.41)

I-1.14 `ApproxSolve`

syntax

```
ApproxSolve(L: LIST of RINGELEM): LIST of LIST of RAT
```

Description

This function returns the list of real solutions (points) of a 0-dimensional polynomial system “L”. Works only if with rational coefficients. Approximate coordinates are given for non-rational solutions.

See also “RationalSolve” ([I-18.13 pg.232](#))

example

```

/**/ Use QQ[x,y,z];
/**/ L := [x^3-y^2+z-1, x-2, (y-3)*(y+2)];
/**/ RationalSolve(L);
[[2, -2, -3], [2, 3, 2]]
/**/ ApproxSolve(L);
[[2, -2, -3], [2, 3, 2]]

/**/ L := [x^3-y^2+1, (y-3)*(y+2), z];
/**/ indent(ApproxSolve(L));
[
  [167001090947516369641767378634802431634869700965461961120334511774287062707365/11579208923731619542
  [2, 3, 0]
]

/**/ L := [x^3-y^2+z-1, x^2-2, (y-3)*(y+2)];
/**/ Pts := ApproxSolve(L);
--> [[17564737135690137373...
/**/ indent([[ DecimalStr(coord,10) | coord in pt] | pt in Pts]);
[
  ["1.4142135624", "-2.0000000000", "2.1715728753"],
  ["1.4142135624", "3.0000000000", "7.1715728753"],
  ["-1.4142135624", "-2.0000000000", "7.8284271247"],
  ["-1.4142135624", "3.0000000000", "12.8284271247"]
]

-- Verify we have an approximate answer:
/**/ indent([ [ FloatStr(eval(f, pt)) | f In L ] | pt In Pts]);
[
  ["-3.2567*10^(-76)", "-6.2932*10^(-77)", "2.3668*10^(-76)"],
  ["-1.3971*10^(-77)", "8.1808*10^(-78)", "2.5541*10^(-77)"],
  ["-3.7110*10^(-77)", "8.1808*10^(-78)", "2.5541*10^(-77)"],
  ["7.7208*10^(-77)", "3.2902*10^(-77)", "-1.2374*10^(-76)"]
]

```

See Also: [LinSolve\(I-12.14 pg.165\)](#), [RationalSolve\(I-18.13 pg.232\)](#)

I-1.15 *ascii*

syntax

```

ascii(N: INT): STRING
ascii(L: LIST of INT): STRING
ascii(S: STRING): LIST of INT

```

Description

In the first form, “*ascii*” returns the character whose ASCII code is “N”.

In the second form, “*ascii*” returns the string whose characters, in order, have the ASCII codes listed in “L”.

The third form is the inverse of the second: it returns the ASCII codes of the characters in “S”.

example

```

/**/  ascii(97);
a

/**/  C := ascii("hello world");
/**/  C;
[104, 101, 108, 108, 111, 32, 119, 111, 114, 108, 100]

/**/  ascii(C);
hello world

```

I-1.16 AsINT

syntax

```

AsINT(N: INT): INT
AsINT(N: RAT): INT
AsINT(N: RINGELEM): INT

```

Description

If the argument is an integer value this function returns this value as an INT, otherwise it throws an error.

example

```

/**/  Use P ::= QQ[x,y];
/**/  type(LC(3*x-y));
RINGELEM
/**/  type(AsINT(LC(3*x-y)));
INT
-- /**/  type(AsINT(LC((3/2)*x-y)));  --> !!! ERROR !!!

```

See Also: AsRAT([I-1.17](#) pg.[32](#))

I-1.17 AsRAT

syntax

```

AsRAT(N: INT): RAT
AsRAT(N: RAT): RAT
AsRAT(N: RINGELEM): RAT

```

Description

If the argument is a rational value this function returns this value as a RAT, otherwise it throws an error. Note that if the argument is actually an integer the result is nevertheless a RAT (with denominator 1).

example

```

/**/  Use P ::= QQ[x,y];
/**/  type(LC(3*x-y));
RINGELEM
/**/  type(AsRAT(LC(3*x-y)));
RAT

```

See Also: AsINT([I-1.16](#) pg.[32](#))

Chapter I-2

B

I-2.1 BaseRing

— syntax —

```
BaseRing(RmodI: (Quotient)RING): RING
BaseRing(K: (Fraction Field)RING): RING
```

Description

This function gives the "base ring" of a given ring; e.g. if "K" was constructed as the fraction field of "R" then "BaseRing(K)" produces "R". All rings in CoCoA are derived from "ZZ" via various steps; "BaseRing" gives the ring which is one step closer to "ZZ".

— example —

```
/**/ Fpx := ZZ/(7)[x];
/**/ Fp := BaseRing(Fpx); --> ZZ/(7)
/**/ BaseRing(Fp) = ZZ;
true
```

See Also: NewFractionField(I-14.1 pg.185), NewQuotientRing(I-14.9 pg.188), NewPolyRing(I-14.8 pg.188)

I-2.2 BBasis5

— syntax —

```
BBasis5(I: IDEAL): LIST
```

Description

***** NOT YET IMPLEMENTED *****

This function is implemented in ApCoCoALib by Stefan Kaspar.

The function "BBasis5" calls the CoCoAServer to compute a Border Basis of zero dimensional ideal I.

— example —

```
Use QQ[x, y], DegLex;
I := ideal([x^2, xy + y2]);
BBasis := BBasis5(I);
```

I-2.3 BettiDiagram

syntax

```
BettiDiagram(X: IDEAL or (quotient)RING or MODULE)
```

Description

This function computes the ("Macaulay-style") Betti diagram for "M".

example

```

/**/ Use R ::= QQ[t,x,y,z];
/**/ I := ideal(x^2-y*t, x*y-z*t, x*y);
/**/ RES := res(I);
/**/ PrintRes(RES);
0 --> R(-5)^2 --> R(-4)^4 --> R(-2)^3
/**/ B := BettiDiagram(RES); indent(B);
record[
  Diagram := matrix(ZZ,
    [[3, 0, 0],
     [0, 4, 2]]),
  FirstShift := 2
]
/**/ PrintBettiDiagram(B);
      0      1      2
-----
2:      3      -      -
3:      -      4      2
-----
Tot:      3      4      2

```

See Also: BettiMatrix(I-2.4 pg.34), PrintRes(I-16.30 pg.219), PrintBettiDiagram(I-16.27 pg.218), PrintBettiMatrix(I-16.28 pg.219)

I-2.4 BettiMatrix

syntax

```
BettiMatrix(M: IDEAL|MODULE|LISTResolution)
```

Description

This function returns the Betti matrix for "M".

example

```

/**/ Use R ::= QQ[t,x,y,z];
/**/ I := ideal(x^2-y*t, x*y-z*t, x*y);
/**/ PrintRes(I);
0 --> R^2(-5) --> R^4(-4) --> R^3(-2)
/**/ BettiMatrix(I);
matrix(ZZ,
  [[0, 0, 0],
   [3, 0, 0],
   [0, 0, 0],
   [0, 4, 0],
   [0, 0, 2]])

```

```

/**/ PrintBettiMatrix(I);
--  -->  -->  --
      0      0      0
      0      0      3
      0      0      0
      0      4      0
      2      0      0
--  -->  -->  --

```

See Also: [PrintRes\(I-16.30 pg.219\)](#), [PrintBettiDiagram\(I-16.27 pg.218\)](#)

I-2.5 binomial

syntax

```

binomial(N: INT, K: INT): INT
binomial(N: RINGELEM, K: INT): RINGELEM

```

Description

This function computes the binomial coefficient, “ N choose K ” according to the formula $(N)(N-1)(N-2)\dots(N-K+1)/K!$

The same formula is used if N is a polynomial. The integer K cannot be negative.

example

```

/**/ binomial(4,2);
6

/**/ binomial(-4,3);
-20

/**/ binomial(x^2+2*y,3);
(1/6)*x^6 +x^4*y +(-1/2)*x^4 +2*x^2*y^2 -2*x^2*y +(4/3)*y^3 +(1/3)*x^2 -2*y^2 +(2/3)*y

/**/ It = ***(x^2+2y)*(x^2+2y-1)*(x^2+2y-2)/6***;
true

```

See Also: [BinomialRepr](#), [BinomialReprShift\(I-2.6 pg.35\)](#)

I-2.6 BinomialRepr, BinomialReprShift

syntax

```

BinomialRepr(N: INT, K: INT): LIST of INT
BinomialReprShift(N: INT, K: INT, Up: INT, Down: INT): INT

where N and K are positive.

```

Description

The function “[BinomialRepr](#)” computes the “ K ”-binomial representation of “ N ”, also called Macaulay representation, i.e. the unique expression

$$N = \text{binomial}(N(K), K) + \text{binomial}(N(K-1), K-1) + \dots + \text{binomial}(N(L), L)$$

where $N(K) > \dots > N(L) \geq 1$, for some L . The value returned is the list “[$N(t) \mid t \text{ in } 1..K$]” where $N(t)=0$ for all $t < L$.

The function call “BinomialReprShift($N,K,up,down$)” computes the integer

$$\begin{aligned} & \text{binomial}(N(K) + up, K + down) + \\ & \text{binomial}(N(K-1) + up, (K-1) + down) + \\ & \dots + \\ & \text{binomial}(N(L) + up, L + down) \end{aligned}$$

It is useful in generalizations of Macaulay’s theorem characterizing Hilbert functions.

— example —

```
/**/ BinRep := BinomialRepr(13,4);
/**/ BinRep;
[1, 3, 4, 5]

/**/ BinomialReprShift(13,4,1,1);
16
```

See Also: [binomial\(I-2.5 pg.35\)](#)

I-2.7 block

— syntax —

```
block C_1; ... ; C_n EndBlock;

where each C_i is a command.
```

Description

The “**block**” command executes the commands as if they were one command. What this means in practice is that CoCoA will not print a string of dashes after executing each “ C_i ”. Thus, “**Block**” is used on-the-fly and not inside user-defined functions. (It has nothing to do with declaration of local variables, for instance, as one might infer from some other computer languages.) The following example should make the use of “**Block**” clear:

— example —

```
/**/ Print "hello "; Print "world";
hello world
-----

/**/ Block
/**/   Print "hello ";
/**/   Print "world";
/**/ EndBlock;
hello world
-----

/**/ Block
/**/   PrintLn GCD([12, 24, 96]);
/**/   PrintLn LCM([12, 24, 96]);
/**/   PrintLn GCD([x+y, x^2-y^2]);
/**/   Print LCM([x+y, x^2-y^2]);
/**/ EndBlock;

12
96
```

```
x + y
x^2 - y^2
-----
```

I-2.8 BlockMat

syntax

```
BlockMat(LIST of LIST of MAT): MAT
```

Description

This function creates a block matrix from a LIST of rows of matrices.

The following restrictions on the sizes of the matrices apply: in each row of matrices “NumRows(M)” must be constant, and for all rows of matrices the total number of columns must be the same.

The function “BlockMat2x2” (I-2.9 pg.37) has a simpler syntax for a 2x2 block matrix.

example

```
/**/ A := RowMat([1,2,3,4]); B := RowMat([0,0]);
-- /**/ BlockMat(A,B, B,A); --> !!! ERROR !!! as expected
/**/ BlockMat2x2(A,B, B,A); // or equivalently
/**/ BlockMat([[A,B], [B,A]]);
matrix(QQ,
  [[1, 2, 3, 4, 0, 0],
   [0, 0, 1, 2, 3, 4]])
```

See Also: ConcatHor(I-3.37 pg.56), ConcatVer(I-3.40 pg.57), ConcatHorList(I-3.38 pg.56), ConcatVerList(I-3.41 pg.57), ConcatDiag(I-3.36 pg.55), ConcatAntiDiag(I-3.35 pg.55), BlockMat2x2(I-2.9 pg.37)

I-2.9 BlockMat2x2

syntax

```
BlockMat2x2(A: MAT,B: MAT,C: MAT,D: MAT): MAT
```

Description

This function creates a block matrix. Each entry is a matrix. Given A, B, C, D matrices, then “BlockMat(A,B,C,D)” returns the matrix

$$\begin{bmatrix} A & B \\ C & D \end{bmatrix}$$

The obvious restrictions on the sizes of the matrices apply:

“NumRows(A) = NumRows(B)” and “NumRows(C) = NumRows(D)”, and “NumCols(A) = NumCols(C)” and “NumCols(B) = NumCols(D)”.

The function “BlockMat” (I-2.8 pg.37) offers more flexibility, but with a heavier syntax.

example

```
/**/ A := matrix([[1,2,3], [4,5,6]]);
/**/ B := matrix([[1,2], [3,4]]);
/**/ C := matrix([[1,1,1], [2,2,2], [3,3,3]]);
/**/ D := matrix([[4,4], [5,5], [6,6]]);
/**/ BlockMat2x2(A,B, C,D);
matrix(QQ,
```

```
[[1, 2, 3, 1, 2],
 [4, 5, 6, 3, 4],
 [1, 1, 1, 4, 4],
 [2, 2, 2, 5, 5],
 [3, 3, 3, 6, 6]])
```

See Also: ConcatHor(I-3.37 pg.56), ConcatVer(I-3.40 pg.57), ConcatDiag(I-3.36 pg.55), ConcatAntiDiag(I-3.35 pg.55), BlockMat(I-2.8 pg.37)

I-2.10 Bool01

syntax

```
Bool01(B: BOOL): INT
```

Description

This function converts a boolean to an integer using the convention: “false” becomes 0, and “true” becomes 1.

example

```
/**/ Id4 := matrix([[Bool01(i=j) | i in 1..4] | j in 1..4]);
/**/ Id4;
matrix(QQ,
 [[1, 0, 0, 0],
 [0, 1, 0, 0],
 [0, 0, 1, 0],
 [0, 0, 0, 1]])
```

I-2.11 break

syntax

```
break
```

Description

This command must be used inside a loop statement (“for”, “foreach”, “repeat”, or “while”). When executed, the current loop statement is terminated and control passes to the command following the loop statement. Thus, in the case of nested loops “break” does “not” break out of all loops back to the “top level” (see “Return”).

example

```
/**/ For I := 5 To 1 Step -1 Do
/**/   For J := 1 To 100 Do
/**/     Print J, " ";
/**/     If J = I Then PrintLn; Break; EndIf;
/**/   EndFor;
/**/ EndFor;
1 2 3 4 5
1 2 3 4
1 2 3
1 2
1
```

See Also: return(I-18.36 pg.243)

I-2.12 BringIn

syntax

```
BringIn(E: OBJECT): OBJECT
```

Description

This function maps a polynomial (or a list, matrix of these) into the current ring, preserving the names of the indeterminates.

This function is not implemented on ideals because might be misleading: one might expect that bringing an ideal from “ $\mathbf{R}[x,y]$ ” into “ $\mathbf{R}[x]$ ” means eliminating “ y ”, while others might expect the ideal generated by mapping the generators. For example in the first case $(x - y, x + y)$ returns the ideal (x) , in the second case returns an error. So, if you want to map the generators of the ideal type “`ideal(BringIn(gens(I)))`”.

– Changing characteristic from non-0 to 0 is NOT YET IMPLEMENTED in CoCoA-5 When mapping from a ring of finite characteristic to one of zero characteristic then consistent choices of image for the coefficients are made (i.e. if two coefficients are equal mod p then their images will be equal).

example

```
/**/ RR := QQ[x[1..4],z,y];
/**/ SS := ZZ[z,y,x[1..2]];
/**/ Use RR;
/**/ F := (x[1]-y-z)^2; F;
x[1]^2 -2*x[1]*z +z^2 -2*x[1]*y +2*z*y +y^2

/**/ Use SS;
/**/ BringIn(F);
z^2 +2*z*y +y^2 -2*z*x[1] -2*y*x[1] +x[1]^2

/**/ Use R := QQ[x,y,z];
/**/ F := (1/2)*x^3 + (34/567)*x*y*z - 890; -- poly with rational coefficients
/**/ Use S := ZZ/(101)[x,y,z];
/**/ BringIn(F);
-50*x^3 -19*x*y*z +19
```

See Also: PolyAlgebraHom(I-16.14 pg.211), apply(I-1.13 pg.30), QZP(I-17.5 pg.224), ZPQ(I-25.3 pg.298)

Chapter I-3

C

I-3.1 Call [OBSOLETE]

syntax

[OBSOLETE]

Description

OBSOLETE: in CoCoA-5 functions can be used directly. See “FUNCTIONs are first class objects” ([III-7.2 pg.355](#)).

I-3.2 CanonicalHom

syntax

CanonicalHom(R: RING, S: RING): RINGHOM

Description

CanonicalHom(R, S) – where R and S are rings, gives the canonical homomorphism from R to S. Currently it works only on the most natural constructions:

```
ZZ -> S      QQ -> S
R -> R/I     R -> FractionFieIs(R)
R -> R[x[1..N]]
```

example

```
/**/ Use R := QQ[x,y];
/**/ RmodI := NewQuotientRing(R, ideal(x^2-1));

/**/ phi := CanonicalHom(R, RmodI);
/**/ phi(x^3*y);
(x*y)
/**/ RingOf(It) = RmodI;
true

/**/ RingElem(RmodI, x^3*y); -- same as phi(x^3*y)
                             -- internally computes CanonicalHom
```

See Also: [NewFractionField\(I-14.1 pg.185\)](#), [NewQuotientRing\(I-14.9 pg.188\)](#), [NewPolyRing\(I-14.8 pg.188\)](#), [CanonicalHom\(I-3.2 pg.41\)](#), [CoeffEmbeddingHom\(I-3.20 pg.48\)](#), [QuotientingHom\(I-17.4 pg.224\)](#), [PolyAlgebraHom\(I-16.14 pg.211\)](#), [PolyRingHom\(I-16.15 pg.212\)](#)

I-3.3 CanonicalRepr

— syntax —

```
CanonicalRepr(f: RINGELEM): RINGELEM
```

Description

Given an element “f” in a quotient ring “R/I” this function returns a representative of “f” in “R”.

— example —

```
/**/ Use R := QQ[a];
/**/ RmodI := R/ideal(a^2-2);
/**/ Use RmodI;
/**/ a^3;
(2*a)
/**/ RingOf(a^3);
RingWithID(9, "RingWithID(7)/ideal(a^2 -2)")
/**/ CanonicalRepr(a^3);
2*a
/**/ RingOf(CanonicalRepr(a^3));
RingWithID(7, "QQ[a]")
```

See Also: [NewQuotientRing\(I-14.9 pg.188\)](#), [DefiningIdeal\(I-4.5 pg.66\)](#)

I-3.4 CartesianProduct, CartesianProductList

— syntax —

```
CartesianProduct(L1: LIST, L2: LIST, L3: LIST, ...): LIST
CartesianProductList(L: LIST of LIST): LIST
L1 >< L2
L1 >< L2 >< ... >< Ln

where each Li is a LIST
```

Description

This command returns the list whose elements form the Cartesian product of L_1, \dots, L_n .

For the N-fold product of a list with itself, one may use “tuples” ([I-20.15 pg.284](#)).

— example —

```
/**/ L1 := [1,2,3];
/**/ L2 := ["a","b"];
/**/ L1 >< L2 >< [5]; -- same as
/**/ CartesianProduct(L1, L2, [5]); -- same as
/**/ CartesianProductList([L1, L2, [5]]); -- this takes a list of lists
[[1, "a", 5], [1, "b", 5], [2, "a", 5], [2, "b", 5], [3, "a", 5], [3, "b", 5]]
-----
/**/ ChessBoard := (1..8)><(1..8); -- Need brackets around 1..8 otherwise
-- we get a parse error.
```

Note that only “<>” is used for “*not equal*” in CoCoA.

See Also: CoCoA Operators([II-3.1](#) pg.307), operators, shortcuts([I-0.1](#) pg.23), tuples([I-20.15](#) pg.284)

I-3.5 Cast [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] To cast INT, RAT, STRING to a polynomial (and more in general to a RINGELEM) use “RingElem” ([I-18.39](#) pg.244).

To cast RINGELEM to INT, RAT use “AsINT” ([I-1.16](#) pg.32), “AsRAT” ([I-1.17](#) pg.32).

To cast LIST to MAT use “matrix” ([I-13.10](#) pg.173). To cast MAT to LIST use “GetRows” ([I-7.16](#) pg.104), “GetCols” ([I-7.12](#) pg.103).

To cast a MODULEELEM to LIST use “compts” ([I-3.32](#) pg.53). To cast a MODULE to MAT use “GensAsCols, GensAsRows” ([I-7.9](#) pg.101). To cast a MAT to MODULE use “SubmoduleCols, SubmoduleRows” ([I-19.38](#) pg.269).

See Also: AsINT([I-1.16](#) pg.32), AsRAT([I-1.17](#) pg.32), gens([I-7.8](#) pg.100), GensAsCols, GensAsRows([I-7.9](#) pg.101), GetCols([I-7.12](#) pg.103), GetRows([I-7.16](#) pg.104), ideal([I-9.2](#) pg.115), matrix([I-13.10](#) pg.173), ModuleElem([I-13.27](#) pg.180), RingElem([I-18.39](#) pg.244), SubmoduleCols, SubmoduleRows([I-19.38](#) pg.269)

I-3.6 ceil

syntax

ceil(X: RAT): INT

Description

This function returns the least integer greater than or equal to “X”.

example

```
/**/  ceil(0.99);
1

/**/  ceil(0.01);
1

/**/  ceil(1);
1

/**/  ceil(-0.99);
0
```

See Also: floor([I-6.12](#) pg.90), round([I-18.51](#) pg.250), num([I-14.31](#) pg.198), den([I-4.7](#) pg.67)

I-3.7 CFApprox

syntax

CFApprox(X: RAT, MaxRelErr: RAT): RAT

Description

“CFApprox” finds the “*simplest*” continued fraction approximant to “X” which is within the maximum specified “*relative error*”.

— example —

```
/**/ CFApprox(1.414213, 10^(-2));
17/12
```

See Also: CFApproximants([I-3.8](#) pg.44), ContFrac([I-3.45](#) pg.59), SimplestRatBetween([I-19.12](#) pg.257)

I-3.8 CFApproximants

— syntax —

```
CFApproximants(X: RAT): LIST of RAT
```

Description

“CFApproximants” returns a list of all continued fraction approximants to the rational “X”.

— example —

```
/**/ CFApproximants(1.414213);
[1, 3/2, 7/5, 17/12, 41/29, 99/70, 239/169, 577/408, 816/577, 1393/985,
 6388/4517, 7781/5502, 14169/10019, 21950/15521, 36119/25540, 58069/41061,
 152257/107662, 210326/148723, 1414213/1000000]
```

See Also: CFApprox([I-3.7](#) pg.43), ContFrac([I-3.45](#) pg.59)

I-3.9 characteristic

— syntax —

```
characteristic(R: RING): INT
```

Description

This function returns the characteristic of the current ring, in the first case, or of the ring R, in the second.

— example —

```
/**/ Use R ::= ZZ/(3)[t];
/**/ S ::= QQ[x,y];
/**/ characteristic(CurrentRing);
3

/**/ characteristic(S);
0
```

See Also: IsFiniteField([I-9.46](#) pg.138), LogCardinality([I-12.17](#) pg.166)

I-3.10 CharPoly

— syntax —

```
CharPoly(M: MAT, X: RINGELEM): RINGELEM
```

Description

This function returns the characteristic polynomial of “M”, square matrix, in the indeterminate “X”.

See also “MinPoly” ([I-13.22](#) pg.178).

example

```
/**/ Use R ::= QQ[x];
/**/ CharPoly(matrix([[1,2,3],[4,5,6],[7,8,9]]), x);
x^3 -15*x^2 -18*x
```

See Also: MinPoly([I-13.22](#) pg.178)

I-3.11 CheckArgTypes

syntax

```
CheckArgTypes(Ltype: LIST of TYPE, Larg: LIST)
```

Description

This function provides a basic type checking for user defined functions: it checks whether the types of the elements in the third argument, a list, correspond to the types in the second list. If so, it returns nothing, otherwise returns an error.

example

```
/**/ -- the following returns an error for the 2nd argument (INT)
/**/ -- CheckArgTypes([RAT, RINGELEM, MAT], [2/3, 20, LexMat(3)]); --> ERROR
--> ERROR: Arg 2 is INT but must be RINGELEM

/**/ -- the following returns nothing
/**/ CheckArgTypes([RAT, [INT,RAT,RINGELEM], MAT], [2/3, 20, LexMat(3)]);

/**/ -- an example of use for type checking
/**/ Define Pow(F, N)
/**/   CheckArgTypes([[INT,RAT,RINGELEM,IDEAL,MAT], INT], [F, N]);
/**/   Return F^N;
/**/ EndDefine; -- Pow
/**/ Pow(x, 3);
x^3
/**/ -- Pow(2, x); --> ERROR
--> ERROR: Arg 2 is RINGELEM but must be INT
```

I-3.12 ciao

syntax

```
ciao
```

Description

This command is used to quit CoCoA. It may be used only at top level.

See Also: quit([I-17.2](#) pg.223)

I-3.13 ClearDenom

syntax

```
ClearDenom(F: RINGELEM): RINGELEM
```

Description

This function clears the denominators of the coefficients in a polynomial over QQ. It simply multiplies by the least common multiple of the denominators.

example

```
/**/ Use QQ[x,y];
/**/ F := (2/3)*x + (4/5)*y;
/**/ ClearDenom(F);
10*x +12*y
```

I-3.14 close

syntax

```
close(D: DEVICE)
```

Description

This function closes the device D.

example

```
D := OpenOFile("my-test"); -- open file for output from CoCoA
Print "test" On D; -- write to my-file
Close(D); -- close the file
Close(DEV.STDIN); -- close the standard input device
-- Bye

(Close(DEV.OUT) suppresses all output to the CoCoA window.)
```

See Also: Introduction to IO([II-6.1](#) pg.315)

I-3.15 CloseLog

syntax

```
CloseLog(D: DEVICE)
```

Description

***** NOT YET IMPLEMENTED *****

This function “OpenLog” ([I-15.4](#) pg.202) opens the output device D and starts to record the output from a CoCoA session on D.

This function closes the device D and stops recording the CoCoA session on D.

See Also: OpenLog([I-15.4](#) pg.202)

I-3.16 CoCoA-4 mode

syntax

```
*** E ***
```

where ‘‘\verb&E&’’ is a CoCoA-4 expression.

Description

CoCoA-5 is not fully backward compatible with CoCoA-4, i.e. some CoCoA-4 programs will be rejected by CoCoA-5. CoCoA-4 mode helps ease the transition to CoCoA-5.

In CoCoA-4 it was not necessary to write explicitly the product between two indeterminates; in CoCoA-5 this is obligatory.

The expression “E” may also contain function calls, but only if the function names begin with a capital letter.

example

```
/**/ Use QQ[x,y,z];
/**/ f := 2*x^2*y - 3*x*y*z - 4*y^2*z + 5*y*z^2 + 6*z^3;
/**/ g := ***2x^2y - 3xyz - 4y^2z + 5yz^2 + 6z^3***; --> C4 mode, more compact!
/**/ f = g;
true
```

See Also: Migrating from CoCoA-4 and keeping up-to-date([II-9 pg.327](#)), not([I-14.29 pg.197](#)), and([I-1.11 pg.29](#)), or([I-15.9 pg.205](#))

I-3.17 CocoaLimits

syntax

```
CocoaLimits(): RECORD
```

Description

***** NOT YET IMPLEMENTED *****

This function returns the maximum allowable characteristic of a CoCoA ring and the maximum allowable exponent in a CoCoA expression. These numbers may vary depending on the platform on which CoCoA is run.

example

```
CocoaLimits();
record[MaxChar := 32767, MaxExp := 2147483647]
-----
```

I-3.18 CocoaPackagePath

syntax

```
CocoaPackagePath(): STRING
```

Description

This function returns the path name of the directory containing the CoCoA libraries. It is platform dependent.

example

```
/**/ CocoaPackagePath();
/Applications/CoCoA-5/packages
```

I-3.19 codomain

syntax

```
codomain(phi: RINGHOM): RING
```

Description

This function returns the domain of the homomorphism “phi”

example

```
/**/ P := NewPolyRing(RingQQ(), "alpha,beta");
/**/ phi := CanonicalHom(RingZZ(), P);
/**/ codomain(phi);
RingWithID(4, "QQ[alpha,beta]")
/**/ psi := CoeffEmbeddingHom(P);
/**/ codomain(psi);
RingWithID(4, "QQ[alpha,beta]")
```

See Also: `codomain`([I-3.19](#) pg.48), `Commands and Functions for RINGHOM`([III-10.3](#) pg.366), `Commands and Functions returning RINGHOM`([III-10.4](#) pg.366)

I-3.20 CoeffEmbeddingHom

syntax

```
CoeffEmbeddingHom(P: RING): RINGHOM
```

Description

This function returns the coefficient embedding homomorphism of the polynomial ring “P”.

It is equivalent to (indeed it is called by) “`CanonicalHom(CoeffRing(P), P)`”.

example

```
/**/ Use P := QQ[x,y];
/**/ phi := CoeffEmbeddingHom(P); -- phi: QQ -> P
/**/ f := 2*x+3*y;
/**/ f/phi(LC(f));
x + (3/2)*y
```

See Also: `CanonicalHom`([I-3.2](#) pg.41)

I-3.21 coefficients

syntax

```
coefficients(F: RINGELEM): LIST
coefficients(F: RINGELEM, S: LIST): LIST
```

Description

This function returns a list of coefficients of “F” in “`CoeffRing(RingOf(F))`”.

Called with one argument “F” it returns the list of all non-zero coefficients; the order being decreasing on the terms in “F” as determined by the term-ordering of “`RingOf(F)`”.

Called with two arguments “F,S” it returns the coefficients of the list of specified terms “S”; their order is determined by the list “S”. If a terms does not appear in “F” then the corresponding coefficient is 0.

The old form (CoCoA-4) “Coefficients(F,x)” for the coefficients of F w.r.t an indeterminate x is now implemented as “CoefficientsWRT” (I-3.22 pg.49) and “CoeffListWRT” (I-3.23 pg.50).

example

```

/**/ Use R := QQ[x,y,z];
/**/ F := 3*x^2*y + 5*y^2 - x*y;
/**/ Coeffs := coefficients(F); Coeffs; -- with one argument
[3, -1, 5]
/**/ phi := CoeffEmbeddingHom(RingOf(F));
/**/ F = ScalarProduct(apply(phi,Coeffs), support(F));
true

/**/ Skeleton := [1, x, y, z, x^2, x*y, y^2, y*z, z^2];
/**/ Coeffs := coefficients(F, Skeleton); Coeffs; -- with two arguments
[0, 0, 0, 0, 0, -1, 5, 0, 0]
/**/ ScalarProduct(apply(phi,Coeffs), Skeleton);
-x*y +5*y^2

/**/ L := CoefficientsWRT(F,[x,y,z]); indent(L); -- similar function
[
  record[PP := y^3, coeff := 5],
  record[PP := x^2*y, coeff := 3],
  record[PP := x*y^5, coeff := -1]
]
/**/ F = sum([X.coeff * X.PP | X In L]);
true

/**/ L := CoeffListWRT(F, y); L; -- similar function
[0, 3*x^2 -x, 5]
/**/ F = sum([L[d+1]*y^d | d in 0..(len(L)-1)]);
true

/**/ R3 := NewFreeModule(R,3);
/**/ V := ModuleElem(R3, ***[3x^2+y, x-5z^3, x+2y]***);
/**/ ConcatLists([coefficients(V[i]) | i In 1..NumCompts(V)]);
[3, 1, -5, 1, 1, 2]

```

See Also: Coefficient Rings(III-9.3 pg.360), CoefficientsWRT(I-3.22 pg.49), CoeffListWRT(I-3.23 pg.50), LC(I-12.3 pg.160), monomials(I-13.30 pg.182), support(I-19.42 pg.271)

I-3.22 CoefficientsWRT

syntax

```

CoefficientsWRT(F: RINGELEM, X: RINGELEM): LIST of RECORD
CoefficientsWRT(F: RINGELEM, S: LIST of RINGELEM): LIST of RECORD

```

Description

The first function returns the list of the coefficients and PPs of “F” seen as a polynomial in “X”; the second function does the same but viewing “F” as a polynomial in all the indeterminates in the set “S”.

Note that coefficients in the result are RINGELEM belonging to “RingOf(F)”.

example

```

/**/ Use R := QQ[x,y,z];
/**/ f := x^3*z+x*y+x*z+y+2*z;
/**/ Cx := CoefficientsWRT(f, x); -- same as...

```

```

/**/ Cx := CoefficientsWRT(f, [x]);
/**/ indent(Cx);
[
  record[PP := x^3, coeff := z],
  record[PP := x, coeff := y + z],
  record[PP := 1, coeff := y + 2*z]
]
/**/ f = sum([M.coeff * M.PP | M In Cx]);
true
/**/ Foreach M In Cx Do Print "  +(", M.coeff, ")*", M.PP; EndForeach;
  +(y + 2*z)*1  +(y + z)*x  +(z)*x^3

/**/ Cxz := CoefficientsWRT(f, [x,z]);
/**/ indent(Cxz);
[
  record[PP := x^3*z, coeff := 1],
  record[PP := x*z, coeff := 1],
  record[PP := x, coeff := y],
  record[PP := z, coeff := 2],
  record[PP := 1, coeff := y]
]

```

See Also: Coefficient Rings([III-9.3](#) pg.360), CoeffListWRT([I-3.23](#) pg.50), coefficients([I-3.21](#) pg.48), CoefOfTerm([I-3.24](#) pg.50), ContentWRT([I-3.44](#) pg.59), LC([I-12.3](#) pg.160), monomials([I-13.30](#) pg.182), support([I-19.42](#) pg.271)

I-3.23 CoeffListWRT

syntax

CoeffListWRT(F: RINGELEM, X: RINGELEM): LIST of RINGELEM

Description

This function returns the list of the coefficients of “F” seen as a univariate polynomial in “X”, an indeterminate or a list of indeterminates. All entries in the returned list are RingElems belonging to “RingOf(F)”.

Note that the returned list is “reversed” from the CoCoA-4 analogue “Coefficients(F,X)” thus to re-use old code you should call “reversed(CoeffListWRT(F,X))”.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ F := 5*y^2 + (3*x^2-x)*y;
/**/ L := CoeffListWRT(F, y); Print L;
[0, 3*x^2 -x, 5]
/**/ F = sum([L[d+1]*y^d | d in 0..(len(L)-1)]);
true

```

See Also: coefficients([I-3.21](#) pg.48), CoefficientsWRT([I-3.22](#) pg.49)

I-3.24 CoeffOfTerm

syntax

CoeffOfTerm(F: RINGELEM, T: RINGELEM): RINGELEM

Description

This function returns the coefficient of the term “T” occurring in “F”. NOTE: In CoCoA 4 the order of the arguments was different.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ F := 5*x*y^2 - 3*z^3;
/**/ CoeffOfTerm(F, x*y^2);
5
/**/ CoeffOfTerm(F, x^3);
0
/**/ CoeffOfTerm(F, z^3);
-3

```

See Also: [coefficients\(I-3.21 pg.48\)](#), [LC\(I-12.3 pg.160\)](#), [exponents\(I-5.14 pg.81\)](#), [MakeTerm\(I-13.4 pg.170\)](#), [monomials\(I-13.30 pg.182\)](#), [support\(I-19.42 pg.271\)](#)

I-3.25 CoeffRing

syntax

```
CoeffRing(R: RING): RING
```

Description

This function returns the ring of coefficients of a polynomial ring.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ S ::= ZZ/(2)[a,b,c];
/**/ CoeffRing(R);
QQ

/**/ CoeffRing(S);
FFp(2)

```

See Also: [characteristic\(I-3.9 pg.44\)](#), [coefficients\(I-3.21 pg.48\)](#), [CurrentRing\(I-3.51 pg.61\)](#), [indets\(I-9.22 pg.127\)](#)

I-3.26 ColMat

syntax

```
ColMat(L: LIST): MAT
ColMat(R: RING, L: LIST): MAT
```

Description

This function returns the matrix whose only column consists of the elements of the list L.

example

```

/**/ ColMat([3,4,5]);
matrix(QQ,
  [[3],
   [4],
   [5]])

```

```

/**/ RingOf(It); -- default ring is QQ
QQ

/**/ ColMat(ZZ, [3,4,5]);
matrix(ZZ,
  [[3],
   [4],
   [5]])
/**/ RingOf(It);
ZZ

```

See Also: `matrix` ([I-13.10](#) pg.173), `BlockMat` ([I-2.8](#) pg.37), `DiagMat` ([I-4.15](#) pg.71), `RowMat` ([I-18.52](#) pg.250), `GensAsCols`, `GensAsRows` ([I-7.9](#) pg.101)

I-3.27 colon

syntax

```

colon(M: IDEAL, N: IDEAL): IDEAL
colon(M: MODULE, N: MODULE): IDEAL

```

Description

This function returns the quotient of M by N: the ideal of all polynomials F such that $F \cdot G$ is in M for all G in N. The command “M : N” is a shortcut for “`colon(M, N)`”.

See also “`HColon`” ([I-8.1](#) pg.107) for non-homogeneous input.

example

```

/**/ Use R := QQ[x,y];
/**/ ideal(x*y, x^2) : ideal(x);
ideal(y, x)

/**/ colon(ideal(x^2, x*y), ideal(x, x-y^2));
ideal(x)

```

See Also: `saturate` ([I-19.1](#) pg.251), `HSaturation` ([I-8.12](#) pg.113), `HColon` ([I-8.1](#) pg.107)

I-3.28 ColumnVectors [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] Essentially replaced by “`GensAsCols`, `GensAsRows`” ([I-7.9](#) pg.101) and “`SubmoduleCols`, `SubmoduleRows`” ([I-19.38](#) pg.269) **See Also:** `GensAsCols`, `GensAsRows` ([I-7.9](#) pg.101), `SubmoduleCols`, `SubmoduleRows` ([I-19.38](#) pg.269)

I-3.29 *Comp* [OBSOLETE]

[OBSOLETE]

syntax

Description

[OBSOLETE] please use “[...]” for accessing entries in a list by index, or the record field selector operator.

See Also: operators, shortcuts(I-0.1 pg.23), record field selector(I-18.22 pg.237)

I-3.30 Comparison Operators

```
A < B
A > B
A <= B
A >= B
return BOOL
```

syntax

Description

These operators perform the corresponding comparison between “A” and “B” returning “true” or “false”; they will signal an error if “A” and “B” are not comparable.

example

```
/**/ "abc" < "def"; -- lex ordering for strings
true
```

See Also: Equality Test(I-5.8 pg.78), operators, shortcuts(I-0.1 pg.23)

I-3.31 CompleteToOrd [OBSCOLESCENT]

[OBSCOLESCENT]

syntax

Description

Renamed “MakeTermOrd” (I-13.5 pg.170).

I-3.32 *compts*

```
compts(V: MODULEELEM): LIST
Comps(V: MODULEELEM): LIST
```

syntax

Description

This function returns the list of components of a ModuleElem V. It is like converting a ModuleElem into a generic list. Note that a ModuleElem is a more structured object than a generic list.

example

```

/**/ use R := QQ[x,y,z];
/**/ R3 := NewFreeModule(R,3);
/**/ V := ModuleElem(R3, ***[3x^2+4y, 2x-5z^3, 2x+2y]***); V;
[3*x^2 +4*y, -5*z^3 +2*x, 2*x +2*y]
/**/ type(V);
MODULEELEM

/**/ compts(V);
[3*x^2 +4*y, -5*z^3 +2*x, 2*x +2*y]
/**/ type(compts(V));
LIST

```

See Also: NumCompts([I-14.33](#) pg.198)

I-3.33 ComputeElimFirst

syntax

```
ComputeElimFirst(I: IDEAL, PP: ElimIndsProd): RINGELEM
```

Description

This function is experimental and dangerous! No guarantees.

Manual is intentionally cryptic. If you think this function is useful for you, write email to Anna M. Bigatti.

example

```

/**/ Use ZZ/(32003)[x,y,t];
/**/ ComputeElimFirst(t, ideal(x^2-t^2, y^3-t^3));
x^6 -y^6

/**/ Use ZZ/(32003)[x,y,t,h];
/**/ ComputeElimFirst(t, ideal(x*h-t^2, y*h^2-t^3));
x^3*h^2 -y^2*h^3

```

See Also: elim([I-5.4](#) pg.76)

I-3.34 concat

syntax

```
concat(L_1: LIST,...,L_n: LIST): LIST
```

Description

This function returns the list obtained by concatenating the lists “ L_1, \dots, L_n ”.

NOTE: to concatenate strings just use “+”.

example

```

/**/ concat([1,2,3],[4,5],[],[6]);
[1, 2, 3, 4, 5, 6]

```

See Also: append([I-1.12](#) pg.30), ConcatLists([I-3.39](#) pg.56), String Operations([III-4.2](#) pg.341)

I-3.35 ConcatAntiDiag

syntax

```
ConcatAntiDiag(A: MAT, B: MAT): MAT
```

Description

This function creates a simple block matrix. The two entries are matrices. ConcatAntiDiag(A, B) will return a matrix of the form

$$\begin{bmatrix} 0 & A \\ B & 0 \end{bmatrix}$$

example

```
/**/ A := mat([[1,2,3], [4,5,6]]);
/**/ B := mat([[101,102], [103,104]]);
/**/ ConcatAntiDiag(A, B);
matrix(QQ,
  [[0, 0, 1, 2, 3],
   [0, 0, 4, 5, 6],
   [101, 102, 0, 0, 0],
   [103, 104, 0, 0, 0]])
```

See Also: BlockMat(I-2.8 pg.37), ConcatDiag(I-3.36 pg.55), ConcatHor(I-3.37 pg.56), ConcatVer(I-3.40 pg.57)

I-3.36 ConcatDiag

syntax

```
ConcatDiag(A: MAT, B: MAT): MAT
```

Description

This function creates a simple block matrix. The two entries are matrices. ConcatDiag(A, B) will return a matrix of the form

$$\begin{bmatrix} A & 0 \\ 0 & B \end{bmatrix}$$

example

```
/**/ A := mat([[1,2,3], [4,5,6]]);
/**/ B := mat([[101,102], [103,104]]);
/**/ ConcatDiag(A, B);
matrix(QQ,
  [[1, 2, 3, 0, 0],
   [4, 5, 6, 0, 0],
   [0, 0, 0, 101, 102],
   [0, 0, 0, 103, 104]])
```

See Also: BlockMat(I-2.8 pg.37), ConcatAntiDiag(I-3.35 pg.55), ConcatHor(I-3.37 pg.56), ConcatVer(I-3.40 pg.57), DiagMat(I-4.15 pg.71)

I-3.37 ConcatHor

syntax

```
ConcatHor(A: MAT, B: MAT): MAT
```

where A and B have the same number of rows

Description

This function creates a simple block matrix. The two entries are matrices with the same number of rows. ConcatHor(A, B) will return a matrix of the form

$$\begin{bmatrix} | & A & B & | \end{bmatrix}$$

example

```
/**/ A := mat([[1,2,3], [4,5,6]]);
/**/ B := mat([[101,102], [103,104]]);
/**/ ConcatHor(A, B);
matrix(QQ,
  [[1, 2, 3, 101, 102],
   [4, 5, 6, 103, 104]])
```

See Also: BlockMat(I-2.8 pg.37), MakeMatByRows, MakeMatByCols(I-13.2 pg.169), ConcatAntiDiag(I-3.35 pg.55), ConcatDiag(I-3.36 pg.55), ConcatHorList(I-3.38 pg.56), ConcatVer(I-3.40 pg.57), RowMat(I-18.52 pg.250)

I-3.38 ConcatHorList

syntax

```
ConcatHorList(L: LIST of MAT): MAT
```

where the matrices in L have the same number of rows

Description

This function creates a simple block matrix. The entries in the list are matrices with the same number of rows. ConcatHorList(L) will return a matrix of the form

$$\begin{bmatrix} | & L[1] & L[2] & \dots & L[N] & | \end{bmatrix}$$

example

```
/**/ L := [ mat([[1,2,3], [4,5,6]]), mat([[101,102], [103,104]]) ];
/**/ ConcatHorList(L);
matrix(QQ,
  [[1, 2, 3, 101, 102],
   [4, 5, 6, 103, 104]])
```

See Also: BlockMat(I-2.8 pg.37), MakeMatByRows, MakeMatByCols(I-13.2 pg.169), ConcatAntiDiag(I-3.35 pg.55), ConcatDiag(I-3.36 pg.55), ConcatHor(I-3.37 pg.56), ConcatVerList(I-3.41 pg.57), RowMat(I-18.52 pg.250)

I-3.39 ConcatLists

syntax

```
ConcatLists(L: LIST of LISTS): LIST
```


Description

This function takes 1 argument, a list whose entries are lists, and returns the concatenation of its entries.

example

```
/**/ L := [[1,2],["abc","def"],[3,4]];
/**/ ConcatLists(L);
[1, 2, "abc", "def", 3, 4]
```

See Also: [append\(I-1.12 pg.30\)](#), [concat\(I-3.34 pg.54\)](#)

I-3.40 ConcatVer

syntax

```
ConcatVer(A: MAT, B: MAT): MAT
```

where A and B have the same number of columns

Description

This function creates a simple block matrix. The two entries are matrices with the same number of columns. ConcatVer(A, B) will return a matrix of the form

$$\begin{pmatrix} | & A & | \\ | & B & | \end{pmatrix}$$

example

```
/**/ A := mat([[1,2,3], [4,5,6]]);
/**/ B := mat([[101,102,103]]);
/**/ ConcatVer(A, B);
matrix(QQ,
  [[1, 2, 3],
   [4, 5, 6],
   [101, 102, 103]])
```

See Also: [BlockMat\(I-2.8 pg.37\)](#), [ColMat\(I-3.26 pg.51\)](#), [MakeMatByRows](#), [MakeMatByCols\(I-13.2 pg.169\)](#), [ConcatAntiDiag\(I-3.35 pg.55\)](#), [ConcatDiag\(I-3.36 pg.55\)](#), [ConcatHor\(I-3.37 pg.56\)](#), [ConcatVerList\(I-3.41 pg.57\)](#)

I-3.41 ConcatVerList

syntax

```
ConcatVerList(L: LIST of MAT): MAT
```

where the matrices in L have the same number of columns

Description

This function creates a simple block matrix. The entries in the list are matrices with the same number of columns. ConcatVer(L) will return a matrix of the form

$$\begin{pmatrix} | & L[1] & | \\ | & L[2] & | \\ | & \dots & | \end{pmatrix}$$

example

```

/**/ L := [ mat([[1,2,3], [4,5,6]]), mat([[101,102,103]]) ];
/**/ ConcatVerList(L);
matrix(QQ,
  [[1, 2, 3],
   [4, 5, 6],
   [101, 102, 103]])

```

See Also: BlockMat([I-2.8 pg.37](#)), ColMat([I-3.26 pg.51](#)), MakeMatByRows, MakeMatByCols([I-13.2 pg.169](#)), ConcatAntiDiag([I-3.35 pg.55](#)), ConcatDiag([I-3.36 pg.55](#)), ConcatVer([I-3.40 pg.57](#)), ConcatHorList([I-3.38 pg.56](#))

I-3.42 content

syntax

```
content(F: RINGELEM): RINGELEM
```

Description

This function returns the content of F (i.e. a gcd of its coefficients).

The returned value is a RingElem in RingOf(F).

example

```

/**/ Use R := QQ[x,y,z];
/**/ F := *** 1234x^3z + 3456xyz^3 + 5678y^2z ***;
/**/ content(F);
2
/**/ RingOf(It);
QQ

```

See Also: ContentWRT([I-3.44 pg.59](#)), coefficients([I-3.21 pg.48](#))

I-3.43 ContentFreeFactor

syntax

```
ContentFreeFactor(F: RINGELEM): RECORD
```

Description

This function returns a factorization of the multivariate polynomial F into content-free factors; it works by calling ContentWRT repeatedly. The multiplicities will always be 1.

example

```

/**/ Use R := QQ[x,y,z];
/**/ F := 2*(x+1)*(y+2)*(x+y);
/**/ indent(ContentFreeFactor(F));
record[
  RemainingFactor := 2,
  factors := [y +2, x +1, x +y],
  multiplicities := [1, 1, 1]
]

```

See Also: ContentWRT([I-3.44 pg.59](#)), factor([I-6.1 pg.85](#)), SqFreeFactor([I-19.26 pg.264](#))

I-3.44 ContentWRT

syntax

```
ContentWRT(F: RINGELEM, X: RINGELEM): RINGELEM
ContentWRT(F: RINGELEM, L: LIST of RINGELEM): RINGELEM
```

Description

This function returns the content of F (i.e. a gcd of its coefficients) seen as a polynomial in X, indet or list of indeterminates. The returned value is a RingElem in RingOf(F).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ F := x^3*z + x*y*z^3 + 2*z;
/**/ Cx := CoefficientsWRT(F, x);
/**/ indent(Cx);
[
  record[PP := 1, coeff := 2*z],
  record[PP := x, coeff := y*z^3],
  record[PP := x^3, coeff := z]
]
/**/ ContentWRT(F, x);
z
/**/ ContentWRT(F, [x]);
z
```

See Also: CoefficientsWRT(I-3.22 pg.49), content(I-3.42 pg.58), monomials(I-13.30 pg.182)

I-3.45 ContFrac

syntax

```
ContFrac(X: RAT): LIST of INT
```

Description

“ContFrac” returns a list of the continued fraction “*quotients*” for the given rational number “X”.

example

```
/**/ ContFrac(1.414213);
[1, 2, 2, 2, 2, 2, 2, 2, 1, 1, 4, 1, 1, 1, 1, 2, 1, 6]
```

See Also: CFApprox(I-3.7 pg.43), CFApproximants(I-3.8 pg.44), ContFracToRat(I-3.46 pg.59)

I-3.46 ContFracToRat

syntax

```
ContFracToRat(L: LIST of INT): RAT
```

Description

“ContFracToRat” returns the rational number equal to the continued fraction whose quotients are given as input. The quotients must all be integers, only the very first may be non-positive.

example

```
/**/ ContFracToRat([1, 2, 2, 2, 2, 2, 2, 2]);
577/408
```

See Also: ContFrac([I-3.45 pg.59](#)), CFAprox([I-3.7 pg.43](#)), CFAproximants([I-3.8 pg.44](#))

I-3.47 count

syntax

```
count(L: LIST, E: OBJECT): INT
```

Description

This function counts the number of occurrences of the object E in the list L.

example

```
/**/ L := [1,2,3,2,[2,3]];
/**/ count(L,2);
2

/**/ count(L,[2,3]);
1

/**/ count(L,"a");
0
```

See Also: distrib([I-4.19 pg.73](#)), len([I-12.5 pg.161](#))

I-3.48 CpuTime

syntax

```
CpuTime(): RAT
```

Description

This function returns a “RAT” whose value is the user CPU usage in seconds since the start of the program: this is the amount of time the processor has dedicated to your computation, and may be rather less than the real elapsed time if the computer is also busy with other tasks.

The most common usage is with “TimeFrom” ([I-20.6 pg.279](#)) as shown in the example.

example

```
/**/ StartTime := CpuTime(); -- time in seconds since the start (a RAT)
/**/ --
/**/ -- .... long computation ....
/**/ --
/**/ PrintLn "Computation time: ", TimeFrom(StartTime);
```

You can use “DecimalStr” ([I-4.3 pg.63](#)) to see the value of “CpuTime” in a more easily comprehensible form.

See Also: TimeFrom([I-20.6 pg.279](#)), DecimalStr([I-4.3 pg.63](#))

I-3.49 CRT

syntax

```
CRT(R1: INT, M1: INT, R2: INT, M2: INT): RECORD
```

Description

This function combines two residue-modulus pairs “(R1,M1)” and “(R2,M2)” using the Chinese Remainder Theorem to produce a single residue-modulus pair “(R,M)” such that “ $R = R1 \bmod M1$ ” and “ $R = R2 \bmod M2$ ”, and “ $|R| < M$ ”. The moduli “M1” and “M2” must be coprime (hence “ $M = M1*M2$ ”).

— example —

```
/**/ CRT(2,3, 4,5);
record[modulus := 15, residue := -1]
```

See Also: CRTPoly(I-3.50 pg.61), RatReconstructByContFrac, RatReconstructByLattice(I-18.14 pg.232)

I-3.50 CRTPoly

— syntax —

```
CRTPoly(f1: RINGELEM, M1: INT, f2: RINGELEM, M2: INT): RECORD
```

Description

This function combines residue-modulus pairs “(f1,M1)” and “(f2,M2)” using the Chinese Remainder Theorem to produce a single residue-modulus pair “(f,M)” such that “f” is a polynomial (with coefficients in “QQ”), “ $f = f1 \bmod M1$ ” and “ $f = f2 \bmod M2$ ”, and all coefficients of “f” are smaller than “M”. The moduli “M1” and “M2” must be coprime (hence “ $M = M1*M2$ ”).

— example —

```
/**/ CRTPoly(x-y, 331, x+y, 10093);
record[modulus := 3340783, residue := x +676232*y]
/**/ mod(676232, 331);
330
/**/ mod(676232, 10093);
1
```

See Also: CRT(I-3.49 pg.60), RatReconstructPoly(I-18.15 pg.233)

I-3.51 CurrentRing

— syntax —

```
CurrentRing
```

Description

This is a top-level SYSTEM VARIABLE containing the current ring.

NOTE: in CoCoA-4 it used to be a function (namely “CurrentRing()”), now it is a top-level “*variable*” which needs to be imported in functions... but beware: this is to be considered BAD STYLE ;-)

— example —

```
/**/ Use R := QQ[x,y];
/**/ Use S := ZZ/(3)[t];
/**/ CurrentRing;
RingDistrMPolyClean(FFp(3), 1)

/**/ Use R;
/**/ CurrentRing;
RingDistrMPolyClean(QQ, 2)
```

```

/**/ Define MyIndets1()
/**/   TopLevel CurrentRing; -- importing a top-level (global) variable
/**/   Return indets(CurrentRing);
/**/ EndDefine;

/**/ Define MyIndets2(val)
/**/   Return indets(RingOf(val)); -- cleaner: depends only on the argument
/**/ EndDefine;

/**/ MyIndets1();
[x, y]

/**/ MyIndets2(ideal(x));
[x, y]

```

See Also: [RingOf\(I-18.42 pg.246\)](#), [TopLevel\(I-20.10 pg.280\)](#)

I-3.52 CurrentTypes

— syntax —

```
CurrentTypes(): LIST of TYPE
```

Description

This function lists all CoCoA data types.

— example —

```

/**/ CurrentTypes();
[BOOL, ERROR, FUNCTION, ...]

```

I-3.53 cyclotomic

— syntax —

```
cyclotomic(n: INT, x: RINGELEM): RINGELEM
```

Description

This function computes the n-th cyclotomic polynomial (in the indeterminate x).

— example —

```

/**/ Use QQ[z];
/**/ cyclotomic(4,z);
z^2 + 1

```

Chapter I-4

D

I-4.1 dashes

syntax

```
dashes()
```

Description

This function returns a string of dashes:

example

```
/**/ dashes(); 1+1;
-----
2
```

I-4.2 date

syntax

```
date() : INT
```

Description

This function returns the date.

Note that from version 5.0.4 the result is an INT and the date is in the form YYYYMMDD. See also “TimeOfDay” ([I-20.7 pg.279](#)).

example

```
/**/ date();
20130530
```

See Also: TimeOfDay([I-20.7 pg.279](#))

I-4.3 DecimalStr

syntax

```
DecimalStr(X: INT|RAT|RINGELEM): STRING
DecimalStr(X: INT|RAT|RINGELEM, NumDigits: INT): STRING
```



```

1234
/**/ strange(1, 4, "a", 5, 10);
100
/**/ -- strange(1,2); --> ERROR

```

2. SCOPE. Every variable defined or modified by the command sequence “C” is considered local to the function unless the variable is global or relative to a “ref” parameter. See “TopLevel” ([I-20.10 pg.280](#)) for the use of global variables. See “ref” to learn about calling a function “*by reference*”, i.e. so that the function can change the value of an existing variable.

example

```

/**/ Define Example_1(L)
/**/   L := L + 5;
/**/   Return L;
/**/ EndDefine;

/**/ L := 0;
/**/ Example_1(L);
5
/**/ L; -- L is unchanged despite the function call.
0

```

3. VARIABLE NUMBER OF PARAMETERS. It is also possible to have some optional arguments or a variable number of arguments:

example

```

-- OPTIONAL ARGUMENTS must be in the last positions

/**/ define deg0(f, opt x)
/**/   if f=0 then return 0; endif;
/**/   if IsDefined(x) then return deg(f,x); endif;
/**/   return deg(f);
/**/ enddefine;

/**/ use P ::= QQ[x,y,z];
/**/ deg0(zero(P));
0
/**/ deg0(x^2+y);
2
/**/ deg0(x^2+y, y);
1

-- VARIABLE number of ARGUMENTS

/**/ Define MySum(...) --> arguments are in the LIST "ARGV"
/**/   If len(ARGV) = 0 Then Return 12345;
/**/   Else
/**/     ans := 0;
/**/     Foreach N In ARGV Do ans := ans+N; EndForeach;
/**/   EndIf;
/**/   Return ans;
/**/ EndDefine;

/**/ MySum(1,2,3,4,5);
15
/**/ MySum();
12345

```

The old statement, “`Help S;`” is OBSOLETE!

See Also: `return`([I-18.36](#) pg.243), `TopLevel`([I-20.10](#) pg.280), `ref`([I-18.24](#) pg.237)

I-4.5 DefiningIdeal

syntax

```
DefiningIdeal(S: RING): IDEAL
```

Description

When “`S`” is a quotient ring, say “`S = R/I`”, this function returns “`I`”, the ideal which defines “`S`”.

example

```
/**/ Use R := QQ[x,y,z];
/**/ S := R/ideal(x);
/**/ DefiningIdeal(S);
ideal(x)
```

See Also: `CanonicalRepr`([I-3.3](#) pg.42), `InducedHom`([I-9.25](#) pg.129), `NewQuotientRing`([I-14.9](#) pg.188)

I-4.6 deg

syntax

```
deg(F: RINGELEM): INT
deg(F: RINGELEM, X: RINGELEM): INT
```

Description

The first form of this function returns the “*standard degree*” of “`F`” (see “`wdeg`” ([I-23.1](#) pg.291) for the “*weighted degree*”). The second form returns the exponent of the indeterminate “`X`” in “`F`”.

For the degree of a ring or quotient, see “`multiplicity`” ([I-13.32](#) pg.182).

example

```
/**/ Use R := QQ[x,y,z];
/**/ deg(x*y^2+y);
3

/**/ deg(x*y^2+y, x);
1

/**/ Ws := RowMat([2,3,1]);
/**/ P := NewPolyRing(QQ, "x,y,z", MakeTermOrd(Ws), 1);
/**/ Use P;
/**/ deg(x*y^2+y);
3
/**/ wdeg(x*y^2+y);
[8]
/**/ deg(x*y^2+y, x);
1
/**/ deg(x*y^2+y, x);
2
```

See Also: `wdeg`([I-23.1](#) pg.291), `NewPolyRing`([I-14.8](#) pg.188), `multiplicity`([I-13.32](#) pg.182)

I-4.7 den

syntax

```
den(X: INT|RAT): INT
den(X: RINGELEM): RINGELEM
```

Description

This function returns the denominator of the argument “X”. If “X” is a “RINGELEM” in “FractionField(R)”, then “den(X)” is a RingElem in “R”.

NOTE: In CoCoA 4 the numerator and denominator could also be found using the suffixes “.Num” and “.Den”; this fragile syntax is now obsolete.

example

```
/**/ den(3);
1

/**/ P := QQ[x,y];
/**/ F := NewFractionField(P);
/**/ Use F;
/**/ den(x/(x+y));
x +y
/**/ RingOf(It);
RingWithID(4, "QQ[x,y]")
```

See Also: num([I-14.31](#) pg.198)

I-4.8 DensePoly

syntax

```
DensePoly(R: RING, N: INT): RINGELEM
```

Description

This function returns the sum of all power-products of (standard) degree N.

example

```
/**/ Use R := QQ[x,y];
/**/ DensePoly(R,3);
x^3 + x^2*y + x*y^2 + y^3

/**/ Ws := RowMat([2,3]);
/**/ P := NewPolyRing(QQ, "x,y", MakeTermOrd(Ws), 1);
/**/ Use P;
/**/ DensePoly(P,1); // NOTE: standard degree!!
y +x
```

See Also: randomize([I-18.4](#) pg.228), randomized([I-18.5](#) pg.229)

I-4.9 Depth

syntax

```
Depth(I: IDEAL, M: TAGGED("Quotient")): INT
Depth(M: TAGGED("Quotient")): INT
```

Description

***** NOT YET IMPLEMENTED *****

This function calculates the depth of M in the ideal I , i.e. the length of a maximal I -regular sequence in M . In the second form, where I is not specified, it assumes that I is the maximal ideal generated by the indeterminates, i.e. “`ideal(Indets())`”.

Note that if M is homogeneous and I is the maximal ideal, then it uses the Auslander-Buchsbaum formula “`depth_I(M) = N - pd(M)`” where N is the number of indeterminates and `pd` is the projective dimension, otherwise it returns “`min{N | $\text{Ext}^N(R/I, M) \neq 0$ }`” using the function “`Ext`” ([I-5.15 pg.81](#)).

example

```
Use R := QQ[x,y,z];
Depth(R/ideal(0)); -- the (x,y,z)-depth of the entire ring is 3
3
-----
I := ideal(x^5,y^3,z^2);
-- one can check that it is zerodimensional and CM this way
dim(R/I);
0
-----
Depth(R/I);
0
-----

N := Module([x^2,y], [x+z,0]);
Depth(I, R^2/N); --- a max reg sequence would be (z^2,y^3)
2
-----
Use R := QQ[x,y,z,t,u,v];
-- Cauchy-Riemann system in three complex vars!
N := Module([x,y], [-y,x], [z,t], [-t,z], [u,v], [-v,u]);
--- is it CM?
Depth(R^2/N);
3
-----
dim(R^2/N);
3
-----
--- yes!

M := Module([x,y,z], [t,v,u]);
Res(R^3/M);
0 --> R^2(-1) --> R^3
-----
Depth(R^3/M); -- using Auslander Buchsbaum 6-1=5
5
-----
dim(R^3/M); -- not CM
6
-----
Depth(ideal(x,y,z,t), R^2/N);
2
-----
```

See Also: [res\(I-18.32 pg.241\)](#), [Ext\(I-5.15 pg.81\)](#)

I-4.10 deriv

syntax

```
deriv(F: RINGELEM, X: RINGELEM): RINGELEM
```

Description

This function returns the derivative of F with respect to the indeterminate X .

example

```
/**/ Use R := QQ[x,y];
/**/ deriv(x*y^2, x);
y^2

/**/ Define Jac(F) --> The Jacobian matrix for a polynomial.
/**/ Return matrix([[deriv(F, X) | X In Indets(RingOf(F))]]);
/**/ EndDefine;

/**/ Jac(x*y^2);
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[y^2, 2*x*y]])

/**/ FrF := NewFractionField(R);
/**/ Use FrF;
/**/ deriv((x*y^2)/(x-1), x);
(-y^2)/(x^2 -2*x +1)
```

See Also: [jacobian\(I-10.1 pg.155\)](#)

I-4.11 DerivationAction

syntax

```
DerivationAction(D: RINGELEM, P: RINGELEM)
```

Description

Thanks to Enrico Carlini.

Given the polynomial “ P ” and the derivation “ D ”, this function computes the action of “ D ” on “ P ”.

For the sake of simplicity Forms/Polynomials and Derivations live in the same ring, the distinction between them is purely formal.

example

```
/**/ Use R := QQ[x,y,z];
/**/ DerivationAction(x*y*z, x^3+x*y*z);
1
```

See Also: [InverseSystem\(I-9.33 pg.133\)](#), [PerpIdealOfForm\(I-16.6 pg.208\)](#)

I-4.12 describe

syntax

```
describe X: OBJECT
```

Description

This command gives some information about the object “X”. For instance, if “X” is a CoCoA-5 function, it prints out the definition, and if “X” is a package name (prefixed with a “\$”), it prints out the exported names.

example

```

/**/ Define succ(N) Return N+1; EndDefine;
/**/ describe succ;
Define succ(N) Return N+1 EndDefine

/**/ describe $chebyshev;
The package $chebyshev exports the following names:
* ChebyshevPoly
* ChebyshevPoly2

```

I-4.13 det

syntax

```
det(M: MAT): RINGELEM
```

Description

This function returns the determinant of the matrix “M”.

example

```

/**/ Use R ::= QQ[x];
/**/ M := mat(R, [[x,x^2], [x,x^3]]);
/**/ det(M);
x^4 -x^3

/**/ det(mat(QQ, [[1,2], [0,5]]));
5

```

See Also: minors(I-13.21 pg.178)

I-4.14 DF

syntax

```
DF(F: RINGELEM): RINGELEM
```

Description

Same as “LF” (I-12.8 pg.162), but does not throw an error if the argument is zero or if the “GradingDim” (I-7.19 pg.105) of the polynomial ring is 0. As defined in Kreuzer-Robbiano book II (Definition 4.2.8).

example

```

/**/ Use R ::= QQ[x,y];
/**/ DF(x^2 -x*y +2*x -1);
x^2 -x*y

/**/ Use R ::= QQ[x,y], Lex; -- GradingDim is 0: everything is homogeneous
/**/ DF(x^2 -x*y +2*x -1);
x^2 -x*y +2*x -1

/**/ P := NewPolyRing(QQ, IndetSymbols(R), mat([[1,4],[1,0]]), 1);
/**/ Use P;

```

```

/**/ DF(x^2 -x*y);
-x*y
/**/ DF(x^4 +x^2 -y);
x^4 -y

```

See Also: [LF\(I-12.8 pg.162\)](#)

I-4.15 DiagMat

— syntax —

```

DiagMat(L: LIST): MAT
DiagMat(R: RING, L: LIST): MAT

```

Description

This function returns the diagonal matrix whose diagonal are the elements of the list L.

— example —

```

/**/ DiagMat([3,4,5]);
matrix(
[
[3, 0, 0],
[0, 4, 0],
[0, 0, 5]
])

/**/ DiagMat(QQ,[5,6,7]);
matrix(
[
[5, 0, 0],
[0, 6, 0],
[0, 0, 7]
])

-- fast implementation for high powers of a diagonal matrix
/**/ Define PowerDiag(M, Exp)
/**/   If not(IsDiagonal(M)) Then
/**/     error("PowerDiag: matrix must be diagonal");
/**/   EndIf;
/**/   Return DiagMat([ M[I, I]^Exp | I In 1..NumRows(M) ]);
/**/ EndDefine;

/**/ PowerDiag(IdentityMat(QQ,3), 200000000);
matrix(QQ,
[[1, 0, 0],
[0, 1, 0],
[0, 0, 1]])

```

See Also: [BlockMat\(I-2.8 pg.37\)](#), [IsDiagonal\(I-9.40 pg.136\)](#), [ColMat\(I-3.26 pg.51\)](#), [RowMat\(I-18.52 pg.250\)](#)

I-4.16 diff

— syntax —

```

diff(L: LIST, M: LIST): LIST

```

Description

This function returns the list obtained by removing all the elements of M from L.

example

```
/**/ L := [1,2,3,2,[2,3]];
/**/ M := [1,2];
/**/ diff(L, M);
[3, [2, 3]]
```

See Also: [remove\(I-18.30 pg.240\)](#)

I-4.17 dim

syntax

```
dim(R: RING or TAGGED("Quotient")): INT
```

Description

This function computes the dimension of R.

The coefficient ring must be a field.

example

```
/**/ Use R := QQ[x,y,z];
/**/ dim(R/ideal(x));
2

/**/ dim(R/ideal(y^2-x, x*z-y^3));
1
```

I-4.18 discriminant

syntax

```
discriminant(F: RINGELEM): RINGELEM
discriminant(F: RINGELEM, X: RINGELEM): RINGELEM
```

Description

This function computes the discriminant of a polynomial F (with respect to a given indeterminate X, if the polynomial is multivariate). If the polynomial is univariate then there is no need to specify which indeterminate to use.

The discriminant is defined as

$$(-1)^{(N*(N-1)/2)} \det(M) / M[1,1]$$

where $M := \text{Sylvester}(F, \text{deriv}(F, X), X)$ and $N := \deg(F, X)$.

example

```
/**/ Use R := QQ[x,y];
/**/ discriminant(x^2+3*y^2, x);
-12*y^2

/**/ discriminant(x^2+3*y^2, y);
-12*x^2
```


Description

This function performs the division algorithm on X with respect to L . It returns a record with two fields: “Quotients” holding a list of polynomials, and “Remainder” holding the remainder of X upon division by L .

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ F := x^2*y + x*y^2 + y^2;
/**/ L := [x*y-1, y^2-1];
/**/ DivAlg(F, L);
record[quotients := [x + y, 1], remainder := x + y + 1]

/**/ D := It;
/**/ D.quotients;
[x + y, 1]
/**/ D.remainder;
x + y + 1
/**/ ScalarProduct(D.quotients, L) + D.remainder = F;
true

/**/ R2 := NewFreeModule(R,2);
/**/ V := ModuleElem(R2, [x^2+y^2+z^2, x*y*z]);
/**/ L := gens(SubmoduleRows(R2, mat([[x,y], [y,z], [z,x]])));
/**/ D := DivAlg(V, L);
/**/ indent(D);
record[
  quotients := [x, -z^2 + y + z, y*z - y],
  remainder := [z^2, z^3 - y*z - z^2]
]
/**/ sum([D.quotients[i]*L[i] | i in 1..len(L)]) + D.remainder;
[x^2 + y^2 + z^2, x*y*z]

```

See Also: [div\(I-4.20 pg.73\)](#), [mod\(I-13.25 pg.180\)](#), [GenRepr\(I-7.7 pg.100\)](#), [NF\(I-14.15 pg.191\)](#), [NR\(I-14.30 pg.197\)](#)

I-4.22 domain

syntax

```
domain(phi: RINGHOM): RING
```

Description

This function returns the domain of the homomorphism “phi”

example

```

/**/ P := NewPolyRing(RingQQ(), "alpha,beta");
/**/ phi := CanonicalHom(RingZZ(), P);
/**/ domain(phi);
ZZ
/**/ psi := CoeffEmbeddingHom(P);
/**/ domain(psi);
QQ

```

See Also: [codomain\(I-3.19 pg.48\)](#), [Commands and Functions for RINGHOM\(III-10.3 pg.366\)](#), [Commands and Functions returning RINGHOM\(III-10.4 pg.366\)](#)

Chapter I-5

E

I-5.1 E_ [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] Essentially replaced by “gens” ([I-7.8 pg.100](#)) of a FreeModule.

example

```
/**/ Use R := QQ[x,y,z];
/**/ R5 := NewFreeModule(R,5);
/**/ e := gens(R5);
/**/ e[2];
[0, 1, 0, 0, 0]
```

See Also: gens([I-7.8 pg.100](#)), GensAsCols, GensAsRows([I-7.9 pg.101](#))

I-5.2 eigenfactors

syntax

eigenvectors(M: MAT, X: RINGELEM): LIST of RINGELEM

Description

“M” must be a square matrix, and “X” an indeterminate.

This function determines the eigenfactors of “M”, i.e. the irreducible factors of “CharPoly” ([I-3.10 pg.44](#)) of “M”.

example

```
/**/ Use R := QQ[x];
/**/ M := mat([[0,2,0,0],[1,0,0,0],[0,0,0,2],[0,0,1,1]]);
/**/ eigenfactors(M, x);
[x +1, x -2, x^2 -2]
```

I-5.3 eigenvectors

syntax

```
eigenvectors(M: MAT, X: RINGELEM): LIST of RECORD
```

Description

“M” must be a matrix of numbers, and “X” an indeterminate.

This function determines the eigenvalues of “M”, and for each eigenvalue gives a basis of the corresponding eigenspace – note that the basis is probably not orthogonal. For irrational eigenvalues, the minimal polynomial of the eigenvalue is given (as a polynomial in “X”), along with the eigenvectors expressed in terms of a root of the minimal polynomial (represented as “X”).

example

```
/**/ Use R ::= QQ[x];
/**/ M := mat([[1,2,3],[4,5,6],[7,8,9]]);
/**/ eigenvectors(M, x);
[record[MinPoly := x, eigenspace := matrix(QQ,
  [[-1],
   [2],
   [-1]]],
 record[MinPoly := x^2 -15*x -18,
 eigenspace := [[1, (1/8)*x +1/4, (1/4)*x -1/2]]]
]

/**/ M := mat([[0,2,0,0],[1,0,0,0],[0,0,0,2],[0,0,1,0]]);
  eigenvectors(M, x); -- two irrational eigenvalues, each with eigenspace of dimension 2
[record[MinPoly := x^2 -2, eigenspace := [[1, (1/2)*x, 0, 0], [0, 0, 1, (1/2)*x]]]
```

I-5.4 elim

syntax

```
elim(X: RINGELEM, M: IDEAL): IDEAL
elim(L: LIST, M: IDEAL): IDEAL
elim(X: RINGELEM, M: MODULE): MODULE
elim(L: LIST, M: MODULE): MODULE
```

Description

This function returns the ideal or module obtained by eliminating the indeterminate “X”, or all indeterminates in “L”, from “M”. The coefficient ring needs to be a field.

As opposed to this function, there is also the “*modifier*”, “`elim`”, used when constructing a ring (see “Orderings” (III-9.5 pg.360)).

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ E := elim(t, ideal(t^15+t^6+t-x, t^5-y, t^3-z));
/**/ indent(E);
ideal(
  -z^5 +y^3,
  -y^4 -y*z^2 +x*y -z^2,
  -x*y^3*z -y^2*z^3 -x*z^3 +x^2*z -y^2 -y,
  -y^2*z^4 -x^2*y^3 -x*y^2*z^2 -y*z^4 -x^2*z^2 +x^3 -y^2*z -2*y*z -z,
  y^3*z^3 -x*z^3 +y^3 +y^2
)
```

```

/**/ Use R ::= QQ[t,s,x,y,z,w];
/**/ t..x;
[t, s, x]

/**/ elim(t..x, ideal(t-x^2*z*w, x^2-t, y^2*t-w)); -- Note the use of t..x.
ideal(-z*w^2 + w)

/**/ Use R ::= QQ[t[1..2], x[1..4]];
/**/ I := ideal(x[1]-t[1]^4, x[2]-t[1]^2*t[2], x[3]-t[1]*t[2]^3, x[4]-t[2]^4);
/**/ elim(indets(R,"t"), I);
ideal(x[2]^4 -x[1]^2*x[4], -x[3]^4 +x[1]*x[4]^3)

```

See Also: Orderings([III-9.5](#) pg.360)

I-5.5 ElimMat

syntax

```

ElimMat(N: INT, ElimInd: LIST of INT): MAT
ElimMat(W: MAT, ElimInd: LIST of INT): MAT

```

Description

This function returns an “ $N \times N$ ” matrix representing a term ordering for eliminating the indeterminates with indices in “ElimInd”.

If a weight matrix is given, then these weights are included after the first elimination row.

example

```

/**/ ElimMat(3, [2,3]);
matrix(QQ,
  [[0, 1, 1],
   [1, 1, 1],
   [0, 0, -1]])

/**/ ElimMat(mat([[1,5,0]]), [2,3]);
matrix(QQ,
  [[0, 1, 1],
   [1, 5, 0],
   [0, 0, -1]])

```

See Also: elim([I-5.4](#) pg.76), HomogElimMat([I-8.11](#) pg.113)

I-5.6 EmbeddingHom

syntax

```

EmbeddingHom(K: RING): RINGHOM

```

Description

This function returns the embedding homomorphism of the fraction field “K”.

example

```

/**/ Use P ::= QQ[x,y];
/**/ K := NewFractionField(P);

```

```

/**/ phi := EmbeddingHom(K); -- phi: P -> K
/**/ f := 2*x+3*y;
/**/ phi(f);
2*x +3*y
/**/ RingOf(phi(f));
RingWithID(5, "FractionField(RingWithID(4))")

```

See Also: [CanonicalHom\(I-3.2 pg.41\)](#)

I-5.7 EqSet

— syntax —

```
EqSet(L: LIST, M: LIST): BOOL
```

Description

This function returns true if “L” equals “M” as sets, otherwise it returns false.

— example —

```

/**/ L := [1,2,2];
/**/ M := [2,1];
/**/ EqSet(L, M);
true

```

See Also: [intersection\(I-9.30 pg.132\)](#), [IntersectList\(I-9.31 pg.132\)](#), [IsSubset\(I-9.71 pg.147\)](#)

I-5.8 Equality Test

— syntax —

```

A = B
A <> B
return BOOL

```

Description

The first form returns “true” if “A” is equal to “B”, otherwise it returns “false” (or signals an error if they are not comparable). The second form is the same as “not (A=B)”.

— example —

```

/**/ 1=2;
false
/**/ 1<>2;
true

```

See Also: [Comparison Operators\(I-3.30 pg.53\)](#), [operators, shortcuts\(I-0.1 pg.23\)](#)

I-5.9 EquiIsoDec

— syntax —

```
EquiIsoDec(I: IDEAL): LIST of IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

This function computes an equidimensional isoradical decomposition of I , i.e. a list of unmixed ideals I_1, \dots, I_k such that the radical of I is the intersection of the radicals of I_1, \dots, I_k . Redundancies are possible.

NOTE: at the moment, this implementation works only if the coefficient ring is the rationals or has large enough characteristic.

example

```
Use R ::= QQ[x,y,z];
I := intersect(ideal(x-1,y-1,z-1), ideal(x-2,y-2)^2, ideal(x)^3);
H := EquiIsoDec(I);
H;
[ideal(x), ideal(z - 1, y - 1, x - 1), ideal(xy - y^2 - 2x + 2y, x^2 -
y^2 - 4x + 4y, y^2z - y^2 - 4yz + 4y + 4z - 4, y^3 - 5y^2 + 8y - 4, x
- 2)]
-----
T := [radical(J)|J In H];
S := IntersectionList(T);
radical(I) = S;
True
-----
```

See Also: PrimaryDecomposition(I-16.19 pg.214), radical(I-18.1 pg.227), RadicalOfUnmixed(I-18.2 pg.227)

I-5.10 error

syntax

```
error(S: STRING): ERROR
```

Description

This function throws an error containing the given message. For backward compatibility the function may also be called using the name “Error”

example

```
/**/ Define T(N)
/**/   If type(N) <> INT Then error("Argument must be an integer."); EndIf;
/**/   Return mod(N,5);
/**/ EndDefine;

-- /**/ T(1/3); --> !!! ERROR !!!
ERROR: Argument must be an integer.
      If type(N) <> INT Then error("Argument must be an integer."); EndIf;
      ~~~~~

CONTEXT: function T (previously defined at the prompt)
called at top-level

/**/ T(7);
2
```

See Also: try(I-20.14 pg.283), GetErrMesg(I-7.14 pg.103)

I-5.11 eval

syntax

```
eval(E: RINGELEM|MODULEELEM|LIST|MAT, L: LIST): OBJECT
```

Description

This function substitutes “L[I]” for “`indet(I)`” in the expression “E” which must be of type POLY, MODULEELEM, LIST, or MAT. The evaluation takes place in the ring of “E”. For more general substitutions use “`subst`” (I-19.40 pg.270).

If “`len(L)`” is different from “`NumIndets()`” then only the first N substitutions are performed, where N is the minimum of the two values.

example

```
/**/ Use QQ[x,y];
/**/ eval(x^2+y, [2, 3]);
7
/**/ eval(x^2+y, [2]);
y +4

/**/ F := x*(x-1)*(x-2)*y*(y-1)*(y-2)/36;
/**/ P := [1/2, -2/3];
/**/ eval(F, P);
-5/162
/**/ eval([x+y,x-y], [2,1]);
[3, 1]
/**/ eval([x+y,x-y], [x^2,y^2]);
[x^2 + y^2, x^2 - y^2]
/**/ eval([x+y,x-y], [y]);
[2*y, 0]
```

See Also: Evaluation of Polynomials(III-11.2 pg.368), PolyAlgebraHom(I-16.14 pg.211), subst(I-19.40 pg.270)

I-5.12 EvalHilbertFn

syntax

```
EvalHilbertFn(H:TAGGED("$hp.Hilbert"), N: INT): INT
```

Description

This function evaluates the Hilbert function H at N. If H is the Hilbert function of a quotient R/I, then the value returned is the same as that returned by “`HilbertFn(R/I, N)`” but time is saved since the Hilbert function does not need to be recalculated at each call.

example

```
/**/ Use R ::= QQ[w,x,y,z];
/**/ I := ideal(z^2-x*y, x*z^2+w^3);
/**/ H := HilbertFn(R/I);
/**/ H;
H(0) = 1
H(1) = 4
H(t) = 6t - 3 for t >= 2

/**/ EvalHilbertFn(H,1);
4
```



```
/**/ EvalHilbertFn(H,2);
9
```

See Also: HilbertFn(I-8.5 pg.109), HilbertPoly(I-8.6 pg.109)

I-5.13 EvalQuasiPoly

syntax

```
EvalQuasiPoly(QP: LIST of RINGELEM, N: RINGELEM): RINGELEM
```

Description

example

```
/**/ M := Mat(ZZ, [ [0, 2, 1], [0, -2, 3], [2, -2, 3] ]);
/**/ Cinput := record[integral_closure := M, grading := Mat([[1,1,1]]) ];
/**/ C := NmzComputation(Cinput, ["HilbertSeries"]);
/**/ CHQ := C.HilbertQuasiPolynomial; indent(CHQ);
[
  (8/9)*t^2 +2*t +1,
  (8/9)*t^2 +(14/9)*t +5/9,
  (8/9)*t^2 +(16/9)*t +8/9
]
/**/ EvalQuasiPoly(CHQ,151);
20503
```

See Also: NmzComputation(I-14.17 pg.192), NmzHilbertBasis(I-14.21 pg.194), NmzNormalToricRing(I-14.25 pg.195), NmzIntClosureMonIdeal(I-14.22 pg.194), NmzSetVerboseDefault(I-14.26 pg.196)

I-5.14 exponents

syntax

```
exponents(F: RINGELEM): LIST of INT
```

Description

This function returns the list of exponents of the leading term of “F”. The inverse function is “MakeTerm” (I-13.4 pg.170).

This function was called “log” up to version CoCoA-5.1.2.

example

```
/**/ use R ::= QQ[x,y,z];
/**/ F := x^3*y^2*z^5 + x^2*y + x*z^4;
/**/ exponents(F);
[3, 2, 5]
```

See Also: LPP(I-12.19 pg.167), LT(I-12.20 pg.168), MakeTerm(I-13.4 pg.170)

I-5.15 Ext

syntax

```
Ext(I: INT, M:TAGGED("Quotient"), Q:TAGGED("Quotient")): TAGGED("Quotient")
Ext(I: LIST, M:TAGGED("Quotient"), Q:TAGGED("Quotient")): TAGGED("$ext.ExtList")
```

Description

***** NOT YET IMPLEMENTED *****

In the first form the function computes the I -th Ext module of M and N . It returns a presentation of $Ext_R^I(M, N)$ as a quotient of a free module.

IMPORTANT: the only exception to the type of M or N (or even of the output) is when they are either a zero module or a free module. In these cases their type is indeed MOD.

It computes Ext via a presentation of the quotient of the two modules $Ker(Phi*_I)$ and $Im(Phi*_{I-1})$, where

- Phi_I is the I -th map in the free resolution of M
- $Phi*_I$ is the map $Hom(Phi_I, N)$ in the dual of the free resolution.

Main differences with the previous version include:

- SHIFTS have been removed, consequently only standard homogeneous modules and quotients are supported
- as a consequence of 1), the type “Tagged(“Shifted”)” has been removed. Ext will just be a “Tagged(“Quotient”)”
- The former functions Presentation(), HomPresentation() and KerPresentation() have been removed
- The algorithm uses Res() to compute the maps needed, and not SyzOfGens anylonger, believed to cause troubles
- The function “Ext” always has THREE variables, see syntax...

In the second form the variable I is a LIST of nonnegative integers. In this case the function Ext prints all the Ext modules corresponding to the integers in I . The output is of special type “Tagged(“\$ext.ExtList”)” which is basically just the list of pairs $(J, Ext^J(M, N)) | J \in I$ in which the first element is an integer of I and the second element is the corresponding Ext module.

VERY IMPORTANT: CoCoA cannot accept the ring R as one of the inputs, so if you want to calculate the module $Ext_R^I(M, R)$ you need to type something like

```
“Ext(I, M, ideal(1));”
```

or

```
“Ext(I, M, R^1);”
```

or

```
“Ext(I, M, R/ideal(0));”
```

NOTE: The input is pretty flexible in terms of what you can use for M and N . For example they can be zero modules or free modules. See some examples below.

example

```
Use R := QQ[x,y,z];
I := ideal(x^5, y^3, z^2);
ideal(0) : (I);
ideal(0)
-----
$hom.Hom(R^1/Module(I), R^1); -- from Hom package
Module([[0]])
-----
Ext(0, R/I, R^1); --- all those things should be isomorphic
Module([[0]])
-----
Ext(0..4, R/I, R/ideal(0)); -- another way to define the ring R as a quotient
Ext^0 = Module([[0]])

Ext^1 = Module([[0]])

Ext^2 = Module([[0]])
```

```

Ext^3 = R^1/Module([[x^5], [y^3], [z^2]])

Ext^4 = Module([[0]])

-----
N := Module([x^2,y], [x+z,0]);
Ext(0..4, R/I, R^2/N);
Ext^0 = Module([[0]])

Ext^1 = Module([[0]])

Ext^2 = R^2/Module([[0, x + z], [y, 0], [0, z^2], [z^2, 0], [0, y^3], [x^5, 0]])

Ext^3 = R^2/Module([[x + z, 0], [0, z^2], [z^2, 0], [y^3, 0], [0, x^5], [0, y]])

Ext^4 = Module([[0]])

-----

```

Since version 4.7.3 the output modules are presented minimally.

See Also: [res\(I-18.32 pg.241\)](#), [Depth\(I-4.9 pg.67\)](#), [MinimalPresentation\(I-13.20 pg.178\)](#)

I-5.16 ExternalLibs

— syntax —

```
ExternalLibs(): LIST of STRING
```

Description

This function returns the list of the names of the linked libraries.

— example —

```

/**/ ExternalLibs();
["BOOST", "FROBBY", "GSL", "NORMALIZ"]

```

See Also: [Frobby\(II-8.4 pg.325\)](#), [Normaliz\(II-8.5 pg.325\)](#)

Chapter I-6

F

I-6.1 factor

syntax

```
factor(F: RINGELEM): RECORD
```

Description

This function factorizes a polynomial into irreducibles in its ring of definition. Multivariate factorization is not yet supported over finite fields. To factorize an integer use “SmoothFactor” ([I-19.17 pg.259](#)). (For information about the algorithm, consult John Abbott’s papers)

NOTE: in older versions of CoCoA-5 the field names were “Factors” and “Exponents”.

example

```
/**/ Use R ::= QQ[x,y];
/**/ F := 4*x^8 + 4*x^6 + x^4 + 4*x^2 + 4;
/**/ FacInfo := factor(F);
/**/ indent(FacInfo);
record[
  RemainingFactor := 1,
  factors := [2*x^4-4*x^3+5*x^2-4*x+2, 2*x^4+4*x^3+5*x^2+4*x+2],
  multiplicities := [1, 1]
]
/**/ G := product([FacInfo.factors[i]^FacInfo.multiplicities[i]
  | i In 1..len(FacInfo.factors)]);
/**/ F = G * FacInfo.RemainingFactor;
true

/**/ factor((8*x^2 +16*x +8)/27);
record[factors := [x +1], multiplicities := [2], RemainingFactor := 8/27]

/**/ factor(2*x^2-4); -- over a finite field the factors are monic
record[factors := [x^2 -2], multiplicities := [1], RemainingFactor := 2]
-----
```

See Also: SmoothFactor([I-19.17 pg.259](#)), SqFreeFactor([I-19.26 pg.264](#)), ContentFreeFactor([I-3.43 pg.58](#))

I-6.2 factorial

syntax

```
factorial(N: INT): INT
```



```
Use QQ[x, y, z], Ord(M);
-- New basis (Lex)
BringIn(GBNew);
```

I-6.5 fields

syntax

```
fields(R: RECORD): LIST
```

Description

This function returns a list of all of the fields of the record “R”. It is particularly useful when you want to know if a record field has been defined

example

```
/**/ rec := record[name := "David", number := 3728852, data := ["X","Y"] ];
/**/ fields(rec);
["data", "name", "number"]

/**/ rec.data;
["X", "Y"]

/**/ "surname" IsIn fields(rec);
false
```

See Also: [record\(I-18.21 pg.236\)](#)

I-6.6 first

syntax

```
first(L: LIST): OBJECT
first(L: LIST, N: INT): OBJECT
```

Description

In the first form the function returns the first element of the list L, same as “L[1]”. In the second form, it returns the list of the first N elements of L, same as “[L[i] | i in 1..N]”

example

```
/**/ L := [1,2,3,4,5];
/**/ first(L);
1

/**/ first(L,3);
[1, 2, 3]
```

See Also: [last\(I-12.1 pg.159\)](#)

I-6.7 FirstNonZero

syntax

```
FirstNonZero(V: MODULEELEM): RINGELEM
```

Description

This function returns the first non-zero entry of V . If it is handed a zero `MODULEELEM` then an error is signalled.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ R5 := NewFreeModule(R,5);
/**/ V := ModuleElem(R5, [0, 0, x^2+y*z, 0, z^2]);

/**/ FirstNonZero(V);
x^2 +y*z

/**/ FirstNonZeroPosn(V);
2
```

See Also: `FirstNonZeroPosn`([I-6.8](#) pg.88), `IsZero`([I-9.78](#) pg.150), `NonZero`([I-14.28](#) pg.196)

I-6.8 FirstNonZeroPosn

syntax

```
FirstNonZeroPosn(V: MODULEELEM): RINGELEM
```

Description

This function returns the index of the first non-zero entry of V . If it is handed a zero `MODULEELEM` then an error is signalled.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ R5 := NewFreeModule(R,5);
/**/ V := ModuleElem(R5, [0, 0, x^2+y*z, 0, z^2]);

/**/ FirstNonZero(V);
x^2 +y*z

/**/ FirstNonZeroPosn(V);
2
```

See Also: `FirstNonZero`([I-6.7](#) pg.87), `IsZero`([I-9.78](#) pg.150), `NonZero`([I-14.28](#) pg.196)

I-6.9 flatten

syntax

```
flatten(L: LIST): LIST
flatten(L: LIST, N: INT): LIST
```

Description

Components of lists may be lists themselves, i.e., lists may be nested. With one argument this function returns the list obtained from the list “ L ” by removing all nesting, bringing all elements “*to the top level*”. With the optional second argument, “ N ”, nesting is removed down “ N ” levels. Thus, the elements of “ $M := \text{flatten}(L, 1)$ ” are formed as follows: go through the elements of “ L ” one at a time; if an elements is not a list, add it to “ M ”; if an element is a list, add all of its elements to “ M ”. Recursively, “ $\text{Flatten}(L, N) = \text{Flatten}(\text{Flatten}(L, N-1), 1)$ ”. For “ N ” large, depending on “ L ”, “ $\text{Flatten}(L, N)$ ” gives the same result as “ $\text{Flatten}(L)$ ”.

example

```

/**/ flatten([1,["a","b",[2,3,4],"c","d"],5,6]);
[1, "a", "b", 2, 3, 4, "c", "d", 5, 6]

/**/ L := [1,2, [3,4], [5, [6,7,[8,9]]]];
/**/ flatten(L,1);
[1, 2, 3, 4, 5, [6, 7, [8, 9]]]

/**/ flatten(It,1);
[1, 2, 3, 4, 5, 6, 7, [8, 9]]

/**/ flatten(L,2); -- same as flatten(flatten(L,1),1)
[1, 2, 3, 4, 5, 6, 7, [8, 9]]

/**/ flatten(L,3); -- same as flatten(L)
[1, 2, 3, 4, 5, 6, 7, 8, 9]

```

I-6.10 FloatApprox

syntax

```
FloatApprox(X: INT|RAT|RINGELEM, PrecBits: INT): RAT
```

Description

This function computes an approximation of the form $M * 2^E$ to a rational number “X” where the mantissa satisfies $2^{(B-1)} \leq |M| < 2^B - 1$ where B is the specified bit precision. It gives 0 when applied to 0.

The updated version of this function is not backward compatible with the old one; you must replace the 2nd arg by the number of bits you want in the mantissa (see “FloorLog2, FloorLog10, FloorLogBase” (I-6.13 pg.90)). The old fn is obsolescent and is now called “FloatApprox10”.

example

```

/**/ FloatApprox(1/3, 10);
683/2048

/**/ FloatApprox(1/3, 20);
699051/2097152

/**/ FloatApprox(123456789,8);
123207680

```

See Also: CFAprox(I-3.7 pg.43), FloatStr(I-6.11 pg.89), MantissaAndExponent2(I-13.7 pg.172)

I-6.11 FloatStr

syntax

```
FloatStr(X: INT|RAT|RINGELEM): STRING
FloatStr(X: INT|RAT|RINGELEM, Prec: INT): STRING
```

Description

This function produces a decimal string representation of the rational number “X”. The optional second argument “Prec” says how many significant decimal digits to produce; the default value is 5.

The aim is to produce an easily readable result.

example

```

/**/ FloatStr(2/3);      -- last printed digit is rounded
0.66667

/**/ FloatStr(7^510);    -- no arbitrary limit on exponent range
1.0000*10^431

/**/ FloatStr(1/81, 50); -- precision of mantissa specified by user
0.012345679012345679012345679012345679012345679012346

/**/ FloatStr(987654/321);
3076.8

```

See Also: `DecimalStr`([I-4.3](#) pg.63), `ScientificStr`([I-19.3](#) pg.252), `FloatApprox`([I-6.10](#) pg.89), `MantissaAndExponent10`([I-13.6](#) pg.171)

I-6.12 floor

syntax

```
floor(X: RAT): INT
```

Description

This function returns the greatest integer less than or equal to “X”.

example

```

/**/ floor(0.99);
0

/**/ floor(1.01);
1

/**/ floor(-1);
-1

/**/ floor(-0.01);
-1

```

See Also: `ceil`([I-3.6](#) pg.43), `round`([I-18.51](#) pg.250), `num`([I-14.31](#) pg.198), `den`([I-4.7](#) pg.67)

I-6.13 FloorLog2, FloorLog10, FloorLogBase

syntax

```

FloorLog2(X: RAT): INT
FloorLog10(X: RAT): INT
FloorLogBase(X: RAT, base: INT): INT

```

Description

These functions compute the integer part (floor) of the logarithm of a rational number in a given base. “FloorLog2(X)” is just shorthand for “FloorLogBase(X,2)”; similarly for “FloorLog10”.

NOTE: The signs of “X” and “base” are ignored.

These functions were called “ILogBase” up to version CoCoA-5.1.2.

example

```

/**/ FloorLog2(128);
7
/**/ FloorLog10(999);
2
/**/ FloorLogBase(128,2);
7
/**/ FloorLogBase(81.5,3);
4

```

I-6.14 FloorSqrt

syntax

```
FloorSqrt(N: INT): INT
```

Description

This function computes the square root of an integer. If the argument is not a perfect square it returns the integer part of the square root.

This function was called “**isqrt**” up to version CoCoA-5.1.2.

example

```

/**/ FloorSqrt(16);
4
/**/ FloorSqrt(99);
9
-- /**/ FloorSqrt(-1); --> !!! ERROR !!!
ERROR: Value must be non-negative
FloorSqrt(-1);
~~~~~

```

I-6.15 for

syntax

```

For I := N_1 To N_2 Do C EndFor
For I := N_1 To N_2 Step D Do C EndFor

```

where I is a dummy variable, N₁, N₂, and D are integer expressions,
and C is a sequence of commands.

Description

In the first form, the variable “I” is assigned the values “N₁, N₁+1, ..., N₂” in succession. After each assignment, the command sequence “C” is executed. The second form is the same, except that “I” is assigned the values “N₁, N₁+D, N₁+2D”, and so on, until the limit “N₂” is passed. If “N₂ < N₁”, then the command sequence “C” is not executed.

NOTE: Large values for “N₁, N₂”, or “D” are not permitted; typically they should lie in the range about -10^9 to $+10^9$.

example

```

/**/ For N := 1 To 5 Do Print 2^N, " "; EndFor;
2 4 8 16 32

```

```

/**/ for n := 1 to 20 step 3 do print n, " "; endfor;
1 4 7 10 13 16 19

/**/ For N := 10 To 1 Step -2 Do Print N, " "; EndFor;
10 8 6 4 2

/**/ For N := 5 To 3 Do Print N, " "; endfor; -- no output

```

Loops can be nested.

example

```

/**/ Define MySort(ref L)
/**/   For I := 1 To len(L)-1 Do
/**/     M := I;
/**/     For J := I+1 To len(L) Do
/**/       If L[J] < L[M] Then M := J; EndIf;
/**/     EndFor;
/**/     If M <> I Then
/**/       C := L[M];
/**/       L[M] := L[I];
/**/       L[I] := C;
/**/     EndIf;
/**/   EndFor;
/**/ EndDefine;

/**/ M := [5,3,1,4,2];
/**/ MySort(ref M);
/**/ M;
[1, 2, 3, 4, 5]

```

(Note that “ref L” is used so that the function can change the value of the variable referenced by L. See “ref”.)

See Also: [foreach\(I-6.16 pg.92\)](#), [repeat\(I-18.31 pg.241\)](#), [while\(I-23.3 pg.292\)](#)

I-6.16 foreach

syntax

```

foreach X in L do CMDS endforeach
where ‘\verb&X&’ is a dummy variable, ‘\verb&L&’ is a LIST

```

Description

The dummy variable “X” is assigned the value of each component of “L” in turn. After each assignment the command sequence “CMDS” is executed.

example

```

/**/ foreach N In 1..10 Do -- NOTE: 1..10 gives the list [1,...,10].
/**/   print N^2, " ";
/**/ endforeach;
1 4 9 16 25 36 49 64 81 100

/**/ Use R ::= QQ[x,y,z];
/**/ F := x^2*y + 3*y^2*z - z^3;
/**/ J := [deriv(F, X) | X In indets(R)];
/**/ J;
[2*x*y, x^2 + 6*y*z, 3*y^2 - 3*z^2]

```

```

/**/  Foreach X In J Do
/**/    PrintLn X^2;
/**/  EndForeach;
4*x^2*y^2
x^4 +12*x^2*y*z +36*y^2*z^2
9*y^4 -18*y^2*z^2 +9*z^4

```

See Also: [for\(I-6.15 pg.91\)](#), [repeat\(I-18.31 pg.241\)](#), [while\(I-23.3 pg.292\)](#)

I-6.17 *format*

— syntax —

```
format(E: OBJECT, N: INT): STRING
```

Description

Like Sprint, this function converts the value of E into a string. If the string has fewer than N characters, then spaces are added to the front to make the length N.

— example —

```

/**/  L := [5^n | n In 0..7];
/**/  Foreach F In L Do print Format(F,8); EndForeach;
      1      5      25      125      625      3125      15625      78125

/**/  M := Format(L,20);
/**/  M; -- "Format" does not truncate
[1, 5, 25, 125, 625, 3125, 15625, 78125]
/**/  type(L);
LIST
/**/  type(M);
STRING

```

See Also: [IO.SprintTrunc\(I-9.34 pg.134\)](#), [LaTeX\(I-12.2 pg.159\)](#), [sprint\(I-19.25 pg.263\)](#)

I-6.18 *FrbAlexanderDual*

— syntax —

```

FrbAlexanderDual(I: IDEAL): LIST
FrbAlexanderDual(I: IDEAL, T: RINGELEM): LIST

```

Description

Using the “Frobby” ([II-8.4 pg.325](#)) library linked with CoCoALib. Thanks to Bjarke Roune.

— example —

```

/**/  I := ideal(x^2, x*y, y^2, z^2);
/**/  FrbAlexanderDual(I);
ideal(x^2*y*z, x*y^2*z)

/**/  FrbAlexanderDual(I, x^2*y^2*z^5);
ideal(x^2*y*z^4, x*y^2*z^4)

```

See Also: [Frobby\(II-8.4 pg.325\)](#), [FrbPrimaryDecomposition\(I-6.22 pg.95\)](#), [PrimaryDecomposition\(I-16.19 pg.214\)](#)

I-6.19 FrbAssociatedPrimes

syntax

```
FrbAssociatedPrimes(I: IDEAL): LIST
```

Description

Using the “Frobby” (II-8.4 pg.325) C++ library by Bjarke Roune.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x^2, x*y, y^2, z^2);
/**/ FrbAssociatedPrimes(I);
[ideal(x, y, z)]
```

See Also: Frobby(II-8.4 pg.325), FrbIrreducibleDecomposition(I-6.20 pg.94), FrbPrimaryDecomposition(I-6.22 pg.95)

I-6.20 FrbIrreducibleDecomposition

syntax

```
FrbIrreducibleDecomposition(I: IDEAL): LIST
```

Description

Using the “Frobby” (II-8.4 pg.325) C++ library by Bjarke Roune.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x^2, x*y, y^2, z^2);
/**/ FrbIrreducibleDecomposition(I);
[ideal(x, y^2, z^2), ideal(x^2, y, z^2)];

-- *** missing manual for these function: volunteers? ;- ) ***
FrbDimension
FrbMultigradedHilbertPoincareNumerator
FrbTotalDegreeHilbertPoincareNumerator
```

See Also: Frobby(II-8.4 pg.325), FrbAssociatedPrimes(I-6.19 pg.94), FrbIrreducibleDecomposition(I-6.20 pg.94)

I-6.21 FrbMaximalStandardMonomials

syntax

```
FrbMaximalStandardMonomials(I: IDEAL): LIST
```

Description

Using the “Frobby” (II-8.4 pg.325) library linked with CoCoALib.

example

```
/**/ I := ideal(x^2, x*y, y^2, z^2);
/**/ FrbMaximalStandardMonomials(I);
ideal(y*z, x*z)
```

See Also: Frobby(II-8.4 pg.325)

I-6.22 FrbPrimaryDecomposition

— syntax —

```
FrbPrimaryDecomposition(I: IDEAL): LIST
```

Description

Using the “Frobby” ([II-8.4 pg.325](#)) C++ library by Bjarke Roune.

— example —

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x^2, x*y^2, z^2);
/**/ FrbPrimaryDecomposition(I);
[ideal(x^2, y^2, z^2), ideal(x, z^2)]
```

See Also: [Frobby\(II-8.4 pg.325\)](#), [FrbAssociatedPrimes\(I-6.19 pg.94\)](#), [FrbIrreducibleDecomposition\(I-6.20 pg.94\)](#), [PrimaryDecomposition\(I-16.19 pg.214\)](#)

I-6.23 func

— syntax —

```
Func ... EndFunc
  returns FUNCTION
```

Description

This syntactic structure defines a function without giving it a name; anonymous functions can be passed as parameters and assigned to variables. Note that “Func...EndFunc” can be used inside function definitions.

— example —

```
/**/ square := Func(x) Return x^2; EndFunc;
/**/ square(3);
9

/**/ SortedBy(["zzz", "x", "yy"], Func(x,y) Return len(x)>len(y); EndFunc);
["zzz", "yy", "x"]
```

See Also: [define\(I-4.4 pg.64\)](#), [TopLevel\(I-20.10 pg.280\)](#), [ImportByRef](#), [ImportByValue\(I-9.15 pg.124\)](#)

I-6.24 Function [OBSOLETE]

— syntax —

```
[OBSOLETE]
```

Description

[OBSOLETE] In CoCoA-5 functions are “first class objects”, and so may be passed like any other value – the operator “Function” serves no purpose.

In CoCoA-4 it was possible to have a variable and a function with the same name; the operator “Function” was used to instruct CoCoA-4 to search for the function of the given name, e.g. to pass it as an argument to another function.

See Also: [FUNCTIONs are first class objects\(III-7.2 pg.355\)](#), [SortBy\(I-19.19 pg.260\)](#), [SortedBy\(I-19.21 pg.261\)](#)

I-6.25 functions [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] please use the command “`describe`” ([I-4.12](#) pg.69).

I-6.26 FVector

syntax

FVector(A: LIST): RECORD

Description

This function computes the f-Vector of a simplicial complex described by a list of top faces.

Package GeomModelling, by Elisa Palezzato.

example

```

/**/ Use QQ[x[1..5]], DegLex;
/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4], x[3]*x[4]*x[5]]; -- list top faces
/**/ FVector(L);
[1, 5, 7, 3]

```

See Also: SimplexInfo([I-19.13](#) pg.257)

Chapter I-7

G

I-7.1 GBasis

syntax

```
GBasis(I: IDEAL|MODULE): LIST
```

Description

This function returns a list whose components form a Groebner basis for the ideal (or module) “I” with respect to the term-ordering of the polynomial ring of “I”.

If “I” is a variable then the result is stored in “I” for later use.

For the reduced Groebner basis, use the command “ReducedGBasis” ([I-18.23](#) pg.237).

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x^4-x^2, x^3-y);
/**/ GBasis(I);
[-x^2 +x*y, -x*y +y^2, y^3 -y]
```

See Also: [GBasisTimeout\(I-7.2](#) pg.97)

I-7.2 GBasisTimeout

syntax

```
GBasisTimeout(I: IDEAL, SECONDS: INT): LIST
GBasisTimeout(M: MODULE, SECONDS: INT): LIST
```

Description

***** NOT YET IMPLEMENTED *****

Same as “GBasis” ([I-7.1](#) pg.97), but it will stop and return an error if the computation is not completed.

For dealing with errors see “try” ([I-20.14](#) pg.283).

example

```
Use R ::= QQ[t,x,y,z];
I := ideal(t^3-x, t^4-y, t^5-z);
J := I^5; Time G := GBasisTimeout(J, 1);
ERROR: Time expired: use $gb.Complete to complete the computation
```

```
CONTEXT: Error(GBasisTimeout_Err)
-----
J := I^5; Time G := GBasisTimeout(J, 10);
Cpu time = 1.96, User time = 2
-----
```

See Also: [GBasis\(I-7.1 pg.97\)](#), [try\(I-20.14 pg.283\)](#)

I-7.3 GBM

syntax

```
GBM(L: LIST): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

This function computes the intersection of ideals corresponding to zero-dimensional schemes: GBM is for affine schemes, and “HGBM” ([I-8.2 pg.107](#)) for projective schemes. The list L must be a list of ideals. The function “IntersectList” ([I-9.31 pg.132](#)) should be used for computing the intersection of a collection of general ideals.

The name GBM comes from the name of the algorithm used: Generalized Buchberger-Moeller.

example

```
/**/ Use P := QQ[x,y,z];
/**/ I1 := IdealOfPoints(P, mat([[1,2,1], [0,1,0]])); -- a simple affine scheme
/**/ I2 := IdealOfPoints(P, mat([[1,1,1], [2,0,1]]))^2;-- another affine scheme

***** NOT YET IMPLEMENTED *****
      GBM([I1, I2]);                                -- intersect the ideals
ideal(xz + yz - z^2 - x - y + 1,
      z^3 - 2z^2 + z,
      yz^2 - 2yz - z^2 + y + 2z - 1,
      y^2z - y^2 - yz + y,
      xy^2 + y^3 - 2x^2 - 5xy - 5y^2 + 2z^2 + 8x + 10y - 4z - 6,
      x^2y - y^3 + 2x^2 + 2xy + 4y^2 - 3z^2 - 8x - 8y + 6z + 5,
      x^3 + y^3 - 7x^2 - 5xy - 4y^2 + 5z^2 + 16x + 10y - 10z - 7,
      y^4 - 2y^3 - 4x^2 - 8xy - 3y^2 + 4z^2 + 16x + 16y - 8z - 12)
-----
```

See Also: [IdealAndSeparatorsOfPoints\(I-9.3 pg.116\)](#), [IdealAndSeparatorsOfProjectivePoints\(I-9.4 pg.117\)](#), [IdealOfPoints\(I-9.5 pg.118\)](#), [IdealOfProjectivePoints\(I-9.6 pg.119\)](#), [HGBM\(I-8.2 pg.107\)](#)

I-7.4 gcd

syntax

```
gcd(F: INT,G: INT): INT
gcd(L: LIST of INT): INT
```

```
gcd(F: RINGELEM, G: RINGELEM): RINGELEM
gcd(L: LIST of RINGELEM): RINGELEM
```

Description

This function returns the greatest common divisor of “F₁, . . . , F_n” or of the elements in the list L. For the calculation of the GCDs and LCMs of polynomials, the coefficient ring must be a field.

example

```

/**/ Use R ::= QQ[x,y];
/**/ F := x^2-y^2;
/**/ G := (x+y)^3;
/**/ gcd(F, G);
-x -y

/**/ gcd([3*4,3*8,6*16]);
12

```

See Also: [div\(I-4.20 pg.73\)](#), [mod\(I-13.25 pg.180\)](#), [lcm\(I-12.4 pg.160\)](#)

I-7.5 GCDFreeBasis

syntax

```

GCDFreeBasis(L: LIST of INT): LIST of INT

```

Description

This function returns a GCD free basis of a set of integers; you can think of this as the set of all numbers (except 1) obtainable by performing GCD and exact division operations.

Given a set $N = [N_1, \dots, N_k]$ we seek a basis $G = [G_1, \dots, G_s]$ such that each N_i is a product of powers of the G_j , and the G_j are pairwise coprime; the set G is called a GCD free basis for N . In general the set G is not uniquely defined.

example

```

/**/ GCDFreeBasis([factorial(20), factorial(10)]);
[46189, 4, 14175]

```

See Also: [gcd\(I-7.4 pg.98\)](#)

I-7.6 GenericPoints

syntax

```

GenericPoints(R: RING, NumPoints: INT): LIST
GenericPoints(R: RING, NumPoints: INT, RandomRange: INT): LIST

```

Description

“GenericPoints” returns a list of NumPoints generic projective points with integer coordinates; it is not guaranteed that these points are distinct. RandomRange specifies the largest value any coordinate may take. If the second argument is omitted, the largest value possible is 100 (or P-1 where P is the characteristic of the coefficient ring).

example

```

/**/ Use R ::= QQ[x,y]; GenericPoints(R,7);
[[1, 0], [0, 1], [1, 1], [12, 59], [6, 63], [12, 80], [17, 63]]

/**/ GenericPoints(R,7,500);
[[1, 0], [0, 1], [1, 1], [220, 162], [206, 452], [98, 106], [403, 449]]

/**/ Use R ::= ZZ/(5)[x,y,z];
/**/ GenericPoints(R,7);
[[1, 0, 0], [0, 1, 0], [0, 0, 1], [1, 1, 1], [2, 1, 1], [2, 2, 4], [3, 1, 3]]

```

```

/**/ GenericPoints(R,7,500);
[[1, 0, 0], [0, 1, 0], [0, 0, 1], [1, 1, 1], [1, 4, 2], [1, 3, 2], [2, 3, 3]]

```

I-7.7 GenRepr

syntax

```

GenRepr(X: RINGELEM, I: IDEAL): LIST of RINGELEM
GenRepr(X: MODULEELEM, I: MODULE): LIST of RINGELEM

```

Description

This function returns a list giving a representation of X in terms of generators for I . Let the generators for I be “ $[G_1, \dots, G_t]$ ”. If X is in I , then “GenRepr” will return a list “ $[F_1, \dots, F_t]$ ” such that

$$X = F_1 G_1 + \dots + F_t G_t.$$

If X is not in I , then “GenRepr” returns the empty list, $[]$.

example

```

/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x+y^2, x^2-x*y);
/**/ GenRepr(x^3-x^2*y-y^3-x*y, I);
[-y, x]
/**/ -y*gens(I)[1] + x*gens(I)[2];
x^3 -x^2*y -y^3 -x*y
/**/ GenRepr(x+y, I); -- x+y is not in I
[]

/**/ K := NewFractionField(NewPolyRing(QQ, "a"));
/**/ Use R ::= K[x,y];
/**/ L := [x+y^2, x^2-x*y];
/**/ GenRepr((a-2)*L[1] - (x-a)*L[2], ideal(L));
[a -2, -x +a]

/**/ R3 := NewFreeModule(R,3);
/**/ V1 := ModuleElem(R3, [x, y, y^2]);
/**/ V2 := ModuleElem(R3, [x-y, 0, x^2]);
/**/ V := x^2*V1 - y^2*V2;
/**/ M := submodule(R3, [V1, V2]);
--/**/ GenRepr(V, M); -- NOT YET IMPLEMENTED *****
--[x^2, -y^2]

```

See Also: DivAlg(I-4.21 pg.73), IsIn(I-9.49 pg.139), NF(I-14.15 pg.191), syz(I-19.47 pg.274), SyzOfGens(I-19.48 pg.275)

I-7.8 gens

syntax

```

gens(I: IDEAL): LIST
gens(M: MODULE): LIST

```

Description

This function returns a list of polynomials which generate the ideal I or the module M. The list is not necessarily minimal.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(y^2-x^3, x*y);
/**/ gens(I);
[-x^3 +y^2, x*y]

/**/ gens(I^2);
[x^6 -2x^3*y^2 +y^4, -x^4*y +x*y^3, x^2*y^2]

/**/ R3 := NewFreeModule(R, 3);
/**/ e := gens(R3); // canonical basis
/**/ e[2];
[0, 1, 0]

/**/ M := SubmoduleRows(R3, mat([[x,y,z], [x-1,0,z]]));
/**/ gens(M);
[[x, y, z], [x -1, 0, z]]
/**/ shape(It);
[MODULEELEM, MODULEELEM]
/**/ GensAsRows(M);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[x, y, z],
   [x -1, 0, z]])

```

See Also: GensAsCols, GensAsRows([I-7.9 pg.101](#)), minimalize([I-13.18 pg.177](#)), minimalized([I-13.19 pg.177](#))

I-7.9 GensAsCols, GensAsRows

syntax

```

GensAsRows(M: MODULE): MAT
GensAsCols(M: MODULE): MAT

```

Description

These functions returns a matrix which generate the module M with the components as row (or columns) of a matrix.

The generators are not necessarily minimal.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ R3 := NewFreeModule(R, 3);
/**/ L := [[x,y,z], [x-1,0,z]];
/**/ M := SubmoduleRows(R3, mat(L));
/**/ gens(M);
[[x, y, z], [x -1, 0, z]]
/**/ shape(It);
[MODULEELEM, MODULEELEM]

/**/ GensAsRows(M);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[x, y, z],
   [x -1, 0, z]])

```

```

/**/ GensAsCols(M);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[x, x -1],
   [y, 0],
   [z, z]])

```

See Also: gens(I-7.8 pg.100), SubmoduleCols, SubmoduleRows(I-19.38 pg.269)

I-7.10 Get

syntax

```
Get(D: DEVICE, N: INT): LIST of INT
```

Description

***** NOT YET IMPLEMENTED *****

This function reads N characters from D and returns the list of their ASCII codes.

example

```

D := OpenIFile("io.cpkg"); -- open the file "io.cpkg"
Get(D,10); -- get the first 10 characters
[45, 45, 32, 105, 111, 100, 101, 118, 46, 112]
-----
ascii(It); convert the ASCII code to characters
-- iodev.p
-----
ascii(Get(D,10)); -- get the next 10 characters and convert
kg : 0.1 :
-----
Close(D);

```

The instruction “Get(DEV.STDIN,3)”, for instance, will read 3 characters typed in by the user. Clever use of this function can be used to prompt a user for input to a function, although it is usually easier for functions to take input directly as arguments. NOTE: this function does not work properly under the GUI Interface.

See Also: Introduction to IO(II-6.1 pg.315), OpenIFile(I-15.2 pg.201), OpenOFile(I-15.5 pg.203), OpenIString(I-15.3 pg.202), OpenOString(I-15.6 pg.204)

I-7.11 GetCol

syntax

```
GetCol(M: MAT, K: INT): LIST
```

Description

This function makes a list containing the entries of the “K”-th column of “M”.

example

```

/**/ M := mat([[1,2], [3,4]]);
/**/ GetCol(M,2);
[2, 4]

```

See Also: GetRow(I-7.15 pg.104), GetCols(I-7.12 pg.103)

I-7.12 GetCols

syntax

```
GetCols(M: MAT): LIST of LIST
```

Description

This function produces a list of lists containing the columns of “M”.

example

```
/**/ M := mat([[1,2], [3,4]]);
/**/ GetCols(M);
[[1, 3], [2, 4]]
```

See Also: GetCol([I-7.11](#) pg.102), GetRows([I-7.16](#) pg.104)

I-7.13 GetEnv

syntax

```
GetEnv(S: STRING): STRING
```

Description

This function returns the value of system shell variables

example

```
/**/ GetEnv("HOME");
/Users/bigatti

/**/ GetEnv("COCOARC");
/Users/bigatti/.cocoarc

/**/ GetEnv("COCOA_PACKAGES");
/Applications/CoCoA-4.7/packages
```

I-7.14 GetErrMsg

syntax

```
GetErrMsg(E: ERROR): STRING
```

Description

This function returns the string containing the error message associated with an error.

example

```
/**/ ErrMsg := "";

Try
  F := 1/0;
UponError E Do
  ErrMsg := GetErrMsg(E);
EndTry; -- no error is thrown with Try .. UponError .. EndTry
```

```
/**/ ErrMsg;
Division by zero or by a zero-divisor
```

See Also: [try\(I-20.14 pg.283\)](#), [error\(I-5.10 pg.79\)](#)

I-7.15 GetRow

— syntax —

```
GetRow(M: MAT, K: INT): LIST
```

Description

This function makes a list containing the entries of the “K”-th row of “M”.

— example —

```
/**/ M := mat([[1,2], [3,4]]);
/**/ GetRow(M,2);
[3, 4]
```

See Also: [GetRows\(I-7.16 pg.104\)](#), [SetRow\(I-19.7 pg.255\)](#)

I-7.16 GetRows

— syntax —

```
GetRows(M: MAT): LIST of LIST
```

Description

This function produces a list of lists containing the rows of “M”.

— example —

```
/**/ M := mat([[1,2], [3,4]]);
/**/ GetRows(M);
[[1, 2], [3, 4]]
```

See Also: [GetRow\(I-7.15 pg.104\)](#)

I-7.17 GFanRelativeInteriorPoints

— syntax —

```
GFanRelativeInteriorPoints(EqMat: MAT, IneqMat: MAT): MAT
```

Description

These function returns a matrix ...

— example —

```
/**/ GFanRelativeInteriorPoints(matrix([[1,2,3]]), matrix([[1,0,2], [2,-1,-1]]));
matrix(ZZ,
  [[2],
   [5],
   [-1]])
```


I-7.18 *gin*

syntax

```
gin(I: IDEAL): IDEAL
gin(I: IDEAL, VerboseFlag: STRING): IDEAL
```

Description

These functions return the [probabilistic] *gin* (generic initial ideal) of the ideal “*I*”. It is obtained by computing twice the leading term ideal of $g(I)$, where g is a random change of coordinates with integer coefficients in the range $[-10^6, 10^6]$ using *TwinFloats* (see “*NewRingTwinFloat*” ([I-14.11](#) pg.189)) to allow a much wider range of coefficients than a direct computation over the rationals (use second argument to see the *TwinFloat* precision needed).

example

```
/**/ Use R := QQ[x,y,z], DegRevLex;
/**/ gin(ideal(y^2-x*z, x^2*z-y*z^2)); -- computed twice using TwinFloats
ideal(x^2, x*y^2, y^4)

/**/ gin(ideal(y^7-x^4*z^3, x^5*z-y*z^5), "verbose");
-- trying with FloatPrecision 64
-- trying with FloatPrecision 64
ideal(x^6, x^5*y^2, x^4*y^4, x^3*y^6, x^2*y^8, x*y^10, y^12)
```

See Also: *NewRingTwinFloat*([I-14.11](#) pg.189)

I-7.19 *GradingDim*

syntax

```
GradingDim(P): INT
```

Description

This function returns the grading dimension of a polynomial ring, i.e. how many of the rows of *OrderMatrix* are to be taken as specifying the grading.

example

```
/**/ OrdM := MakeTermOrd(RowMat([2,3]));
/**/ P := NewPolyRing(QQ, "x,y", OrdM, 1);
/**/ GradingDim(P);
1
```

See Also: *NewPolyRing*([I-14.8](#) pg.188), *GradingMat*([I-7.20](#) pg.105)

I-7.20 *GradingMat*

syntax

```
WeightsMatrix(R: RING): MAT
```

Description

This function returns the grading matrix (or weights matrix) for the polynomials ring “*R*”.

example

```
/**/ OrdM := MakeTermOrd(RowMat([2,3])); OrdM;
matrix(ZZ,
  [[2, 3],
   [0, -1]])
/**/ P := NewPolyRing(QQ, "x,y", OrdM, 1); -- GradingDim = 1
/**/ GradingMat(P);
matrix(ZZ,
  [[2, 3]])

/**/ Use P;
/**/ deg(x*y);
2
/**/ wdeg(x*y);
[5]
```

See Also: [deg\(I-4.6 pg.66\)](#), [wdeg\(I-23.1 pg.291\)](#), [GradingDim\(I-7.19 pg.105\)](#), [NewPolyRing\(I-14.8 pg.188\)](#)

Chapter I-8

H

I-8.1 HColon

syntax

```
HColon(M: IDEAL, N: IDEAL): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

The function “colon” ([I-3.27 pg.52](#)) returns the quotient of M by N: the ideal of all polynomials F such that $F \cdot G$ is in M for all G in N.

This function computes the same ideal using a Hilbert-driven algorithm. It differs from “colon” ([I-3.27 pg.52](#)) only when the input is non-homogeneous, in which case, “HColon” may be faster.

example

```
Use R := QQ[x,y];
ideal(xy, x^2) : ideal(x);
ideal(y, x)
-----
colon(ideal(x^2, xy), ideal(x, x-y^2));
ideal(x)
-----
HColon(ideal(x^2, xy), ideal(x, x-y^2));
ideal(x)
-----
```

See Also: [HSaturation\(I-8.12 pg.113\)](#), [saturate\(I-19.1 pg.251\)](#), [HColon\(I-8.1 pg.107\)](#), [colon\(I-3.27 pg.52\)](#)

I-8.2 HGBM

syntax

```
HGBM(L: LIST): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

This function computes the intersection of ideals corresponding to zero-dimensional schemes: “GBM” ([I-7.3 pg.98](#)) is for affine schemes, and HGBM for projective schemes. The list L must be a list of ideals. The function “IntersectList” ([I-9.31 pg.132](#)) should be used for computing the intersection of a collection of general ideals.

The name GBM comes from the name of the algorithm used: Generalized Buchberger-Moeller. The prefix H comes from Homogeneous since ideals of projective schemes are necessarily homogeneous.

example

```
Use QQ[x[0..2]];
I1 := IdealOfProjectivePoints([[1,2,1], [0,1,0]]); -- simple projective scheme
I2 := IdealOfProjectivePoints([[1,1,1], [2,0,1]])^2; -- another projective scheme
HGBM(I1, I2); -- intersect the ideals
ideal(x[0]^3 - x[0]x[1]^2 - 5x[0]^2x[2] + x[1]^2x[2] + 8x[0]x[2]^2 - 4x[2]^3,
x[0]^2x[1] + x[0]x[1]^2 - 3x[0]x[1]x[2] - x[1]^2x[2] + 2x[1]x[2]^2,
x[0]x[1]^3 - 2x[0]^2x[2]^2 - 5x[0]x[1]x[2]^2 - 4x[1]^2x[2]^2 +
8x[0]x[2]^3 + 10x[1]x[2]^3 - 8x[2]^4,
x[0]x[1]^2x[2] + x[1]^3x[2] - 2x[0]^2x[2]^2 - 5x[0]x[1]x[2]^2
- 5x[1]^2x[2]^2 + 8x[0]x[2]^3 + 10x[1]x[2]^3 - 8x[2]^4,
x[1]^4x[2] - 2x[1]^3x[2]^2 - 4x[0]^2x[2]^3 - 8x[0]x[1]x[2]^3
- 3x[1]^2x[2]^3 + 16x[0]x[2]^4 + 16x[1]x[2]^4 - 16x[2]^5)
-----
```

See Also: [IdealAndSeparatorsOfPoints\(I-9.3 pg.116\)](#), [IdealAndSeparatorsOfProjectivePoints\(I-9.4 pg.117\)](#), [IdealOfPoints\(I-9.5 pg.118\)](#), [IdealOfProjectivePoints\(I-9.6 pg.119\)](#), [GBM\(I-7.3 pg.98\)](#)

I-8.3 hilbert [OBSOLESCE]

syntax

[OBSOLESCE]

Description

Renamed as “HilbertFn” ([I-8.5 pg.109](#)).

I-8.4 HilbertBasisKer

syntax

HilbertBasisKer(M: MAT): LIST

where M is a matrix over ZZ.

Description

This function returns a list whose components are lists (of non-negative integers) representing the Hilbert basis for the monoid of elements with non-negative coordinates in the kernel of M.

example

```
/**/ M := mat([[1,-2,3,4], [1, 0, 0, -1]]);
/**/ HilbertBasisKer(M);
[[0, 3, 2, 0], [1, 4, 1, 1], [2, 5, 0, 2]]

/**/ M * transposed(mat(It));
matrix(QQ,
[[0, 0, 0],
[0, 0, 0]])
```

See Also: [LinKerBasis\(I-12.11 pg.164\)](#)

I-8.5 HilbertFn

syntax

```
HilbertFn(R: RING|IDEAL): TAGGED("$hp.Hilbert")
HilbertFn(R: RING|IDEAL, N: INT): INT
```

Description

The first form of this function computes the Hilbert function for R. The second form computes the N-th value of the Hilbert function. The weights of the indeterminates of R must all be 1. If the input is not homogeneous, the Hilbert function of the corresponding leading term (initial) ideal or module is calculated. For repeated evaluations of the Hilbert function, use “EvalHilbertFn” (I-5.12 pg.80) instead of “HilbertFn(R, N)” in order to speed up execution.

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ HilbertFn(R/ideal(z^2-x*y, x*z^2+t^3));
H(0) = 1
H(1) = 4
H(t) = 6*t -3    for t >= 2

/**/ R2 := NewFreeModule(R, 2);
/**/ MGens := matrix(R, [[x^3,y^3], [x*y^2,0], [0,z^3]]);
/**/ M := SubmoduleRows(R2, MGens);
/**/ HilbertFn(M);
H(0) = 0
H(1) = 0
H(2) = 0
H(3) = 3
H(4) = 12
H(t) = (1/3)*t^3 +(3/2)*t^2 +(-101/6)*t +35    for t >= 5

/**/ HilbertFn(M,3);
3
/**/ HilbertFn(M,5);
30
```

See Also: EvalHilbertFn(I-5.12 pg.80), HilbertPoly(I-8.6 pg.109), HVector(I-8.13 pg.113), HilbertSeries(I-8.7 pg.110)

I-8.6 HilbertPoly

syntax

```
HilbertPoly(R: RING or TAGGED("Quotient")): RINGELEM in the ring QQt.
```

Description

This function returns the Hilbert polynomial for R as a polynomial in the standard CoCoA ring “QQt” (= QQ[t]).

The weights of the indeterminates of “R” must all be 1, and the coefficient ring must be a field.

If the input is not homogeneous, the Hilbert polynomial of the corresponding leading term (initial) ideal or module is calculated. For the Hilbert *function*, see “HilbertFn” (I-8.5 pg.109).

example

```

/**/ Use R ::= QQ[w,x,y,z];
/**/ I := ideal(z^2-x*y, x*z^2+w^3);
/**/ HilbertFn(R/I);
H(0) = 1
H(1) = 4
H(t) = 6*t-3   for t >= 2

/**/ F := HilbertPoly(R/I);
/**/ F; -- a polynomial in the ring Qt
6*t-3

/**/ T := indet(RingOf(F), 1);
/**/ subst(F, T, 3);
15

```

See Also: EvalHilbertFn(I-5.12 pg.80), HilbertFn(I-8.5 pg.109), HVector(I-8.13 pg.113), HilbertSeries(I-8.7 pg.110), RingQQt(I-18.44 pg.247)

I-8.7 HilbertSeries

syntax

```
HilbertSeries(M: MODULE|IDEAL|RING):TAGGED("$hp.PSeries")
```

Description

This function computes the Hilbert-Poincare series of “M”. The input, “M”, must be homogeneous (with respect to the first row of the weights matrix). In the standard case, i.e. the weights of all indeterminates are 1, the result is simplified so that the power appearing in the denominator is the dimension of “M”.

NOTE: for the local case see “PrimaryHilbertSeries” (I-16.22 pg.215).

NOTES:

- (i) the coefficient ring must be a field.
- (ii) these functions produce tagged objects: they cannot safely be tested for (non-)equality to other values.

Starting from release 4.7.5 the input may also be an ideal.

For more information, see the article: A.M. Bigatti, “Computations of Hilbert-Poincare Series” J. Pure Appl. Algebra, 119/3 (1997), 237–253.

example

```

/**/ Use R ::= QQ[t,x,y,z]; -- standard weights
/**/ HilbertSeries(R/ideal(R,[]));
(1) / (1-t)^4

/**/ HilbertSeries(R/ideal(t^2, x, y^3));
(1 + 2*t + 2*t^2 + t^3) / (1-t)

/**/ R2 := NewFreeModule(R, 2); -- MODULE
/**/ M := SubmoduleRows(R2, matrix(R, [[x^2,0], [0,z^3]]));
/**/ HilbertSeries(M);
(t^2 + t^3) / (1-t)^4

-- /**/ HilbertSeries(R2/M);  -----WORK IN PROGRESS-----

/**/ Ws := RowMat([1,2,3,4]); -- weights and multigradings

```

```

/**/ P := NewPolyRing(QQ, "t,x,y,z", MakeTermOrd(Ws), 1);
/**/ Use P;
/**/ HilbertSeries(P/ideal(t^2, x, y^3));
--- Non-simplified HilbertPoincare' Series ---
(1 - 2*t^2 + t^4 - t^9 + 2*t^11 - t^13) / ( (1-t)*(1-t^2)*(1-t^3)*(1-t^4) )

/**/ HilbertSeries(ideal(t^2, x, y^3));
--- Non-simplified HilbertPoincare' Series ---
(2*t^2 - t^4 + t^9 - 2*t^11 + t^13) / ( (1-t)*(1-t^2)*(1-t^3)*(1-t^4) )

/**/ Ws := mat([[1,2,3,4],[0,0,5,8]]);
/**/ P := NewPolyRing(QQ, "t,x,y,z", MakeTermOrd(Ws), 2);
/**/ Use P;
/**/ HilbertSeries(P/ideal(t^2, x, y^3));
--- Non Simplified Pseries ---
(1 - 2*t[1]^2 + t[1]^4 - t[1]^9*t[2]^15 + 2*t[1]^11*t[2]^15 - t[1]^13*t[2]^15) / ( (1-t[1])^1*(1-t[1]^2)*
(1-t[1]^3*t[2]^15) )

/**/ Ws := mat([[1,2,3,4],[0,0,5,8]]);
/**/ P := NewPolyRing(QQ, "t,x,y,z", MakeTermOrd(Ws), 2);
/**/ Use P;
/**/ HilbertSeries(P/ideal(t^2, y^3));
--- Non-simplified HilbertPoincare' Series ---
(1 - t[1]^2 - t[1]^9*t[2]^15 + t[1]^11*t[2]^15) /
((1-t[1])^1*(1-t[1]^2)*(1-t[1]^3*t[2]^5)*(1-t[1]^4*t[2]^8) )

```

See Also: [dim\(I-4.17 pg.72\)](#), [multiplicity\(I-13.32 pg.182\)](#), [HilbertFn\(I-8.5 pg.109\)](#), [HVector\(I-8.13 pg.113\)](#), [HilbertSeriesShifts\(I-8.9 pg.112\)](#), [HilbertSeriesMultiDeg\(I-8.8 pg.111\)](#), [GradingMat\(I-7.20 pg.105\)](#), [Primary-HilbertSeries\(I-16.22 pg.215\)](#)

I-8.8 HilbertSeriesMultiDeg

syntax

```
HilbertSeriesMultiDeg(RmodI: RING, WM: MAT): TAGGED("$hp.PSeries")
```

Description

This function computes the multigraded Hilbert-Poincare series of “RmodI” wrt the multigrading “WM”. The “I” must be homogeneous wrt the multigrading “WM”.

This function is only a handy shortcut to avoid creating the proper polynomial ring multi-graded with “WM”.

example

```

/**/ Use R := QQ[x,y];
/**/ HilbertSeriesMultiDeg(R/ideal(Indets(R))^2, mat([[1,1]]));
(1 + 2*t) / (1-t)^0

/**/ HilbertSeriesMultiDeg(R/ideal(Indets(R))^2, mat([[1,0],[0,1]]));
--- Non-simplified HilbertPoincare' Series ---
(1 - t[2]^2 - t[1]*t[2] - t[1]^2 + t[1]*t[2]^2 + t[1]^2*t[2])
/ ( (1-t[1])*(1-t[2]) )

```

See Also: [HilbertSeries\(I-8.7 pg.110\)](#)

I-8.9 HilbertSeriesShifts

syntax

```
HilbertSeriesShifts(M: MODULE, ShiftsList: LIST):TAGGED("$hp.PSeries")
HilbertSeriesShifts(M: TAGGED("Quotient"), ShiftsList: LIST)
:TAGGED("$hp.PSeries")
```

Description

This function computes the Hilbert-Poincare series (single-graded) module “M” with shifts “sh”.

This function is only a handy shortcut to avoid creating the proper free module with shifts “sh”.

NOTE: functions producing tagged objects cannot safely be compared for equality with other values.

For more information, see the article: A.M. Bigatti, “Computations of Hilbert-Poincare Series” J. Pure Appl. Algebra, 119/3 (1997), 237–253.

example

```
/**/ Use P ::= QQ[x,y,z];
/**/ F := NewFreeModule(P, ColMat([2,0])); -- P(-2) (+) P(0)
/**/ M := SubmoduleRows(F, mat([[x,y^3], [x-z,0]]));
/**/ HilbertSeries(M);
(2*t^3) / (1-t)^3
/**/ HilbertSeriesShifts(M, [3,1]);
(2*t^4) / (1-t)^3
```

See Also: [dim\(I-4.17 pg.72\)](#), [HilbertFn\(I-8.5 pg.109\)](#), [HVector\(I-8.13 pg.113\)](#), [multiplicity\(I-13.32 pg.182\)](#), [GradingMat\(I-7.20 pg.105\)](#)

I-8.10 homog

syntax

```
homog(V: RINGELEM, X: RINGELEM): RINGELEM
homog(V: MODULEELEM, X: RINGELEM): MODULEELEM
homog(L: LIST, X: RINGELEM): LIST
homog(I: IDEAL, X: RINGELEM): IDEAL
homog(M: MODULE, X: RINGELEM): MODULE
```

Description

This function returns the homogenization of the first arg with respect to the indeterminate “X”, which must have weight 1. The elements of the list “L” are homogenized separately.

NOTE: For an ideal/module the result is the ideal/module containing the homogenizations of all elements (and not simply the homogenizations of the specific generators).

example

```
/**/ Use R ::= QQ[x,y,z,w];
/**/ homog(x^3-y, w);
x^3 -y*w^2

/**/ homog([x^3-y, x^4-z], w);
[x^3 -y*w^2, x^4 -z*w^3]

/**/ I := ideal(x^3-y, x^4-z);
/**/ homog(I, w); -- don't just get the homogenizations of
```



```
-- the generators of I
ideal(x*y -z*w, x^2*z -y^2*w, x^3 -y*w^2, y^3 -x*z^2)
```

See Also: IsHomog([I-9.48 pg.139](#))

I-8.11 HomogElimMat

syntax

```
HomogElimMat(W: MAT, ElimInd: LIST): MAT
```

Description

This function returns a matrix for a term ordering eliminating the indeterminates with indices in “ElimInd” for homogeneous input wrt the weights in the matrix “W”. If you don’t understand what this means use “ElimMat” ([I-5.5 pg.77](#)) instead ;-)

example

```
/**/ HomogElimMat(mat([[1,5,0]]), [2,3]);
matrix(QQ,
  [[1, 5, 0],
   [0, 1, 1],
   [0, 0, -1]])
```

See Also: elim([I-5.4 pg.76](#)), ElimMat([I-5.5 pg.77](#))

I-8.12 HSaturation

syntax

```
HSaturation(I: IDEAL, J: IDEAL): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

This functions returns the saturation of I with respect to J: the ideal of polynomials F such that $F \cdot G$ is in I for all G in J^d for some positive integer d .

It calculates the saturation using a Hilbert-driven algorithm. It differs from “saturate” ([I-19.1 pg.251](#)) only when the input is inhomogeneous, in which case, “HSaturation” may be faster.

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x^4-x, y*x-2*x);
/**/ saturate(I, ideal(x));
ideal(y -2, x^3 -1)

HSaturation(I, ideal(x)); -- ***** NOT YET IMPLEMENTED *****
```

See Also: colon([I-3.27 pg.52](#)), HColon([I-8.1 pg.107](#)), saturate([I-19.1 pg.251](#))

I-8.13 HVector

syntax

```
HVector(R: RING or TAGGED("Quotient")): LIST
```

Description

This function returns the h-vector of M , i.e., the coefficients of the numerator of the simplified Poincare series for M . M can be a module or a quotient.

The weights of the indeterminates of the polynomial ring of M must all be 1, and the coefficient ring must be a field.

If the input is not homogeneous, the Hilbert function of the corresponding leading term (initial) ideal or module is calculated.

example

```
/**/ Use R := QQ[t,x,y,z];  
/**/ HVector(R/ideal(x,y,z)^5);  
[1, 3, 6, 10, 15]  
  
/**/ HilbertSeries(R/ideal(x,y,z)^5);  
(1 + 3t + 6t^2 + 10t^3 + 15t^4) / (1-t)
```

See Also: [HilbertFn\(I-8.5 pg.109\)](#), [HilbertSeries\(I-8.7 pg.110\)](#)

Chapter I-9

I

I-9.1 ID [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] renamed “RingID” ([I-18.41](#) pg.245).

See Also: RingID([I-18.41](#) pg.245)

I-9.2 ideal

syntax

```
ideal(g1: RINGELEM,...,gn: RINGELEM): IDEAL
ideal(L: LIST): IDEAL
ideal(R: RING, L: LIST): IDEAL
```

Description

The first form returns the ideal generated by “ g_1, \dots, g_n ”. The second form returns the ideal generated by the polynomials in “ L ” (a bit more flexible than the first form). The third is the same as the second but works also if “ $L = []$ ”.

example

```
/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x-y^2, x*y-z);
/**/ I;
ideal(-y^2 +x, x*y -z)

/**/ L := [x*y-z, x-y^2];
/**/ J := ideal(L); -- same as ideal(R, L)
/**/ I = J;
true

/**/ ideal(R, []);
ideal()
```

I-9.3 IdealAndSeparatorsOfPoints

syntax

```

IdealAndSeparatorsOfPoints(Points: LIST): RECORD

```

where Points is a list of lists of coefficients representing a set of “*{it distinct}*” points in affine space.

Description

***** NOT YET IMPLEMENTED *****

This function computes the results of “IdealOfPoints” (I-9.5 pg.118) and “SeparatorsOfPoints” (I-9.5 pg.253) together at a cost lower than making the two separate calls. The result is a record with three fields:

```

points      -- the points given as argument
ideal       -- the result of IdealOfPoints
separators  -- the result of SeparatorsOfPoints

```

Thus, if the result is stored in a variable with identifier X, then: X.points will be the input list of points; X.ideal will be the ideal of the set of points, with generators forming the reduced Groebner basis for the ideal; X.separators will be a list of polynomials whose i-th element will take the value 1 on the i-th point and 0 on the others.

NOTE:

- * the current ring must have at least as many indeterminates as the dimension of the space in which the points lie;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned, the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

```

X := IdealAndSeparatorsOfPoints(Pts);
Foreach Element In gens(X.ideal) Do
  PrintLn Element;
EndForeach;

```

For ideals and separators of points in projective space, see “IdealAndSeparatorsOfProjectivePoints” (I-9.4 pg.117).

example

```

Use R := QQ[x,y];
Points := [[1, 2], [3, 4], [5, 6]];
X := IdealAndSeparatorsOfPoints(Points);
X.points;
[[1, 2], [3, 4], [5, 6]]
-----
X.ideal;
ideal(x - y + 1, y^3 - 12y^2 + 44y - 48)
-----
X.separators;
[1/8y^2 - 5/4y + 3, -1/4y^2 + 2y - 3, 1/8y^2 - 3/4y + 1]
-----

```

See Also: GBM(I-7.3 pg.98), HGBM(I-8.2 pg.107), GenericPoints(I-7.6 pg.99), IdealAndSeparatorsOfProjectivePoints(I-9.4 pg.117), IdealOfPoints(I-9.5 pg.118), IdealOfProjectivePoints(I-9.6 pg.119), Interpolate(I-9.28 pg.131), QuotientBasis(I-17.3 pg.224), SeparatorsOfPoints(I-19.5 pg.253), SeparatorsOfProjectivePoints(I-19.6 pg.254)

I-9.4 IdealAndSeparatorsOfProjectivePoints

syntax

```

IdealAndSeparatorsOfProjectivePoints(Points: LIST): RECORD

```

where Points is a list of lists of coefficients representing a set of “{\it distinct}” points in projective space.

Description

***** NOT YET IMPLEMENTED *****

This function computes the results of “IdealOfProjectivePoints” (I-9.6 pg.119) and “SeparatorsOfProjectivePoints” (I-19.6 pg.254) together at a cost lower than making the two separate calls. The result is a record with three fields:

```

points      -- the points given as argument
ideal       -- the result of IdealOfProjectivePoints
separators  -- the result of SeparatorsOfProjectivePoints

```

Thus, if the result is stored in a variable with identifier X, then: X.ideal will be the ideal of the set of points, with generators forming a reduced Groebner basis for the ideal; X.separators will be a list of homogeneous polynomials whose i-th element will be non-zero (actually 1, using the given representatives for the coordinates of the points) on the i-th point and 0 on the others.

NOTE:

- * the current ring must have at least one more indeterminate than the dimension of the projective space in which the points lie, i.e., at least as many indeterminates as the length of an element of the input, Points;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned, the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

```

X := IdealAndSeparatorsOfProjectivePoints(Pts);
Foreach Element In gens(X.ideal) Do
  PrintLn Element;
EndForeach;

```

For ideals and separators of points in affine space, see “IdealAndSeparatorsOfPoints” (I-9.3 pg.116).

example

```

Use R ::= QQ[x,y,z];
Points := [[0,0,1],[1/2,1,1],[0,1,0]];
X := IdealAndSeparatorsOfProjectivePoints(Points);
X.points;
[[0, 0, 1], [1, 1, 1], [0, 1, 0]]
-----
X.ideal;

```

```

ideal(xz - 1/2yz, xy - 1/2yz, x^2 - 1/4yz, y^2z - yz^2)
-----
X.separators;
[-2x + z, x, -2x + y]
-----

Use R ::= QQ[t,x,y,z];
Pts := GenericPoints(20); -- 20 random points in projective 3-space
X := IdealAndSeparatorsOfProjectivePoints(Pts);
Len(Gens(X.Ideal)); -- number of generators in the ideal
17
-----
HilbertFn(R/X.Ideal);
H(0) = 1
H(1) = 4
H(2) = 10
H(t) = 20 for t >= 3
-----
F := X.Separators[3];
[Eval(F, P) | P In Pts];
[0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
-----
Res(R/X.Ideal); -- the resolution of the ideal
0 --> R^10(-6) --> R^24(-5) --> R^15(-4) --> R
-----

```

See Also: HGBM(I-8.2 pg.107), GBM(I-7.3 pg.98), GenericPoints(I-7.6 pg.99), IdealAndSeparatorsOfPoints(I-9.3 pg.116), IdealOfPoints(I-9.5 pg.118), IdealOfProjectivePoints(I-9.6 pg.119), Interpolate(I-9.28 pg.131), QuotientBasis(I-17.3 pg.224), SeparatorsOfPoints(I-19.5 pg.253), SeparatorsOfProjectivePoints(I-19.6 pg.254)

I-9.5 IdealOfPoints

syntax

```
IdealOfPoints(P: RING, Points: MAT): IDEAL
```

where Points is a list of lists of coefficients representing a set of “{\it distinct}” points in affine space.

Description

This function computes the reduced Groebner basis for the ideal of all polynomials which vanish at the given set of points. It returns the ideal generated by that Groebner basis.

NOTE:

- * the current ring must have at least as many indeterminates as the dimension of the space in which the points lie;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned, the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;

For ideals of points in projective space, see “IdealOfProjectivePoints” (I-9.6 pg.119).

example

```
/**/ Use P ::= QQ[x,y];
```

```

/**/ Points := mat([[1, 2], [3, 4], [5, 6]]);
/**/ I := IdealOfPoints(P, Points);
/**/ I;
ideal(x -y +1, y^3 -12*y^2 +44*y -48)

/**/ K := NewFractionField(NewPolyRing(QQ, "a"));
/**/ Use K;
/**/ Points := mat([[1,2,0], [3,4,a], [5,1,6]]);
/**/ Use P := K[x,y,z], Lex;
/**/ I := IdealOfPoints(P, Points);
/**/ indent(I);
ideal(
  z^3 +(-a -6)*z^2 +(6*a)*z,
  y +((-a -12)/(6*a^2 -36*a))*z^2 +((a^2 +72)/(6*a^2 -36*a))*z -2,
  x +((2*a -6)/(3*a^2 -18*a))*z^2 +((-2*a^2 +36)/(3*a^2 -18*a))*z -1
)

```

See Also: GBM([I-7.3](#) pg.98), HGBM([I-8.2](#) pg.107), GenericPoints([I-7.6](#) pg.99), IdealAndSeparatorsOfPoints([I-9.3](#) pg.116), IdealAndSeparatorsOfProjectivePoints([I-9.4](#) pg.117), IdealOfProjectivePoints([I-9.6](#) pg.119), Interpolate([I-9.28](#) pg.131), QuotientBasis([I-17.3](#) pg.224), SeparatorsOfPoints([I-19.5](#) pg.253), SeparatorsOfProjectivePoints([I-19.6](#) pg.254)

I-9.6 IdealOfProjectivePoints

— syntax —

```
IdealOfProjectivePoints(Points: LIST): IDEAL
```

where Points is a list of lists of coefficients representing a set of “{\it distinct}” points in projective space.

Description

***** NOT YET IMPLEMENTED *****

This function computes the reduced Groebner basis for the ideal of all homogeneous polynomials which vanish at the given set of points. It returns the ideal generated by that Groebner basis.

NOTE:

- * the current ring must have at least one more indeterminate than the dimension of the projective space in which the points lie, i.e, at least as many indeterminates as the length of an element of the input, Points;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned, the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

```

I := IdealOfProjectivePoints(Pts);
Foreach Element In gens(I) Do
  PrintLn Element;
EndForeach;

```

For ideals of points in affine space, see “IdealOfPoints” ([I-9.5](#) pg.118).

example

```

Use R ::= QQ[x,y,z];
I := IdealOfProjectivePoints([[0,0,1],[1/2,1,1],[0,1,0]]);
I;
ideal(xz - 1/2yz, xy - 1/2yz, x^2 - 1/4yz, y^2z - yz^2)
-----
I.Gens; -- the reduced Groebner basis
[xz - 1/2yz, xy - 1/2yz, x^2 - 1/4yz, y^2z - yz^2]
-----

```

See Also: GBM([I-7.3](#) pg.98), HGBM([I-8.2](#) pg.107), GenericPoints([I-7.6](#) pg.99), IdealAndSeparatorsOfPoints([I-9.3](#) pg.116), IdealAndSeparatorsOfProjectivePoints([I-9.4](#) pg.117), IdealOfPoints([I-9.5](#) pg.118), Interpolate([I-9.28](#) pg.131), QuotientBasis([I-17.3](#) pg.224), SeparatorsOfPoints([I-19.5](#) pg.253), SeparatorsOfProjectivePoints([I-19.6](#) pg.254)

I-9.7 IdentityMat

syntax

```
IdentityMat(R: RING, N: INT): MAT
```

Description

This function returns the NxN identity matrix with entries in “R”.

example

```

/**/ Id := IdentityMat(QQ,3); Id;
matrix(QQ,
  [[1, 0, 0],
   [0, 1, 0],
   [0, 0, 1]])
/**/ type(Id[1,1]);
RINGELEM
/**/ RingOf(Id[1,1]);
QQ

```

I-9.8 if

syntax

```

If B_1 Then C_1 EndIf
If B_1 Then C_1 Else D EndIf
If B_1 Then C_1 Elif B_2 Then C_2 Elif ... EndIf
If B_1 Then C_1 Elif B_2 Then C_2 Elif ... Else D EndIf

```

where the B_j are boolean expressions,
and the C_j and D are command sequences.

Description

If “B_n” is the first in the sequence of the “B_j” to evaluate to True, then “C_n” is executed. If none of the “B_j” evaluates to True, then “D” is executed if present otherwise nothing is done. The construct, “Elif B_j Then C_j” can be repeated any number of times.

NOTE: “Elsif” is no longer allowed.

example

```

/**/ Define MySign(A)
/**/   If A > 0 Then Return 1;
/**/   Elif A = 0 Then Return 0;
/**/   Else Return -1;
/**/   EndIf;
/**/ EndDefine;

/**/ MySign(3);
1

```

I-9.9 ILogBase

syntax

[OBSOLESCE]

Description

Renamed to “FloorLog2, FloorLog10, FloorLogBase” (I-6.13 pg.90).

I-9.10 image [OBSOLESCE]

syntax

Image(V: OBJECT, F:TAGGED("RMap")): OBJECT

Description

In CoCoA-5 homomorphisms are properly implemented as “RINGHOM” (III-10 pg.365). “Image” was the CoCoA-4 function mimicking homomorphisms, in particular “PolyAlgebraHom” (I-16.14 pg.211).

example

```

/**/ Use D ::= QQ[x,y]; -- domain
/**/ f := x-y; -- a RINGELEM in D

/**/ Use C ::= QQ[a,b,c]; -- codomain

/**/ -- the old trick
/**/ Phi := RMap(a, c^2-a*b); -- OBSOLESCE
/**/ Image(f, Phi); -- OBSOLESCE
a*b -c^2 +a

/**/ -- the proper call
/**/ phi := PolyAlgebraHom(D, C, [a, c^2-a*b]); -- a RINGHOM
/**/ phi(f);
a*b -c^2 +a

```

See Also: PolyAlgebraHom(I-16.14 pg.211), apply(I-1.13 pg.30), BringIn(I-2.12 pg.39), subst(I-19.40 pg.270)

I-9.11 implicit

— syntax —

```
implicit(SubalgebraGens: LIST): IDEAL
implicit(R: RING, SubalgebraGens: LIST): IDEAL
```

Description

This function returns the implicitization of the subalgebra generated by the list “SubalgebraGens”.

If provided with a ring “R”, the result is in “R”, otherwise it is in a newly created ring.

NOTE: Some cases have been optimized: if the input is a list of power-products then use “toric” (I-20.12 pg.281). if you know the answer is a hypersurface then use “ImplicitHypersurface” (I-9.12 pg.122).

— example —

```
/**/ Use S := QQ[s,t];
/**/ implicit([s^3, s^2*t, s*t^2, t^3]);
ideal(x[3]^2 -x[2]*x[4], x[2]*x[3] -x[1]*x[4], x[2]^2 -x[1]*x[3])

/**/ R := QQ[x,y,z,w];
/**/ implicit(R, [s^3, s^2*t, s*t^2, t^3]);
ideal(z^2 -y*w, y*z -x*w, y^2 -x*z)
```

See Also: ImplicitHypersurface(I-9.12 pg.122), ker(I-11.1 pg.157)

I-9.12 ImplicitHypersurface

— syntax —

```
ImplicitHypersurface(ParamDescr: LIST): RINGELEM
ImplicitHypersurface(ParamDescr: LIST, Algo: STRING): RINGELEM
ImplicitHypersurface(R: RING, ParamDescr: LIST): RINGELEM
ImplicitHypersurface(R: RING, ParamDescr: LIST, Algo: STRING): RINGELEM
```

Description

This function returns the implicitization of the hypersurface parametrically described by the list “ParamDescr”.

The algorithms are described in the paper Abbott, Bigatti, Robbiano “*Implicitization of Hypersurfaces*”

If provided with a ring “R”, the result is in “R”, otherwise it is in a newly created ring.

NOTE: it assumes the input is a correct parametric description of a hypersurface in “ $K^{(\text{len}(\text{ParamDescr})+1)}$ ”!!

— example —

```
/**/ P := QQ[x,y,z];
/**/ Use S := QQ[s,t];
/**/ ImplicitHypersurface(P, [s^2, s*t, t^2]);
y^2 -x*z
/**/ ImplicitHypersurface(P, [s^2, s*t, t^2], "Direct");
y^2 -x*z
/**/ ImplicitHypersurface(P, [s^2, s*t, t^2], "ElimTH");
y^2 -x*z
```

See Also: implicit(I-9.11 pg.122)

I-9.13 ImplicitPlot

syntax

```
ImplicitPlot(F: POLY, Xrange: LIST, Yrange: LIST)
```

Description

This function evaluates the first argument, a bivariate polynomial, at a grid of points in the range given by the second and third arguments. The coordinates of the approximate zeroes are output to a file called "CoCoAPlot". See "ImplicitPlotOn" (I-9.14 pg.123) for outputting to another file.

This result can be plotted using your preferred plotting program. For example, start "gnuplot" and then give it the command

```
plot "CoCoAPlot"
```

to see the plot.

example

```
/**/ Use R := QQ[x,y];
/**/ ImplicitPlot(x^2 + y^2 - 200^2, [-256,256], [-256,256]);
Plotting points...10%...20%...30%...40%...50%...60%...70%...80%...90%...100%
800 plotted points have been placed in the file CoCoAPlot
```

See Also: ImplicitPlotOn(I-9.14 pg.123), PlotPoints(I-16.9 pg.210)

I-9.14 ImplicitPlotOn

syntax

```
ImplicitPlotOn(F: POLY, Xrange: LIST, Yrange: LIST, PlotFileName: STRING)
```

Description

This function is the same as "ImplicitPlot" (I-9.13 pg.123) with a fourth argument giving the name of the file to print on.

Note that the last argument is a STRING, the name of the file, and not a DEVICE, as for "print on" (I-16.26 pg.218).

example

```
/**/ Use R := QQ[x,y];
/**/ F := x^2 + y^2 - 100;
/**/ G := ((x+y)^2-1)*(x^2-36);
/**/ H := ((64*y^2-36*x^2)*(36*y^2-64*x^2)*(100*x^2-y^2)-1) * F - 1000^2 * G;

/**/ ImplicitPlotOn(F, [-16,16], [-16,16], "PLOT-circle");
Plotting points...10%...20%...30%...40%...50%...60%...70%...80%...90%...100%
640 plotted points have been placed in the file circle

/**/ ImplicitPlotOn(G, [-16,16], [-16,16], "PLOT-lines");
Plotting points...10%...20%...30%...40%...50%...60%...70%...80%...90%...100%
1502 plotted points have been placed in the file lines

/**/ ImplicitPlotOn(H, [-16,16], [-16,16], "PLOT-curve");
Plotting points...10%...20%...30%...40%...50%...60%...70%...80%...90%...100%
2790 plotted points have been placed in the file curve
```

After having produced the plot files using CoCoA-4, start "gnuplot" and then give it the following commands:

```
plot "circle"
replot "lines"
replot "curve"
```

See Also: [ImplicitPlot\(I-9.13 pg.123\)](#), [PlotPointsOn\(I-16.10 pg.210\)](#)

I-9.15 ImportByRef, ImportByValue

— syntax —

```
ImportByRef X;
ImportByValue X;
  where ‘\verb&X&’ is the name of a variable in the containing scope.
```

Description

****YOU PROBABLY SHOULDN'T USE THESE COMMANDS YET!**** It seems that they can be used only inside anonymous functions (see “func” ([I-6.23 pg.95](#))).

These commands “import” an external variable by reference or value. “ImportByValue” creates a local variable with the given name, and its initial value is taken from the variable of the same name in the context the anonymous function is defined. “ImportByRef” creates a reference to the named variable in the context where the anonymous function is defined.

NOTE: Package variables should be accessed directly (via the fully qualified name); they cannot be imported.

— example —

```
/**/ Define add(X)
/**/   AnonFn := Func(Y) ImportByValue X; Return X+Y; EndFunc;
/**/   Return AnonFn;
/**/ EndDefine;
/**/ add3 := add(3);
/**/ add3(2);
5
```

See Also: [TopLevel\(I-20.10 pg.280\)](#), [func\(I-6.23 pg.95\)](#)

I-9.16 in

— syntax —

```
[X in L | B: BOOL]
[E | X in L]
[E | X in L and B]
  where L: LIST, B: BOOL, E: expression
  returns LIST
```

Description

See “List Constructors” ([III-5.2 pg.346](#)) for a full description.

— example —

```
/**/ [N in 1..10 | IsPrime(N)];
[2, 3, 5, 7]
```

```
/**/ [N^2 | N in 1..10 and IsPrime(N)];
[4, 9, 25, 49]
```

See Also: List Constructors([III-5.2](#) pg.346), IsIn([I-9.49](#) pg.139)

I-9.17 *incr, decr*

syntax

```
incr(ref X: INT)
decr(ref X: INT)
```

Description

“`incr(ref X)`” adds 1 to the value of “X”. “`decr(ref X)`” subtracts 1 from the value of “X”.

These functions are useful when counting objects or adjusting pointers.

example

```
/**/ L := [(10^k-1)/9 | k in 1..99];
/**/ NPrimes := 0;
/**/ Foreach N in L Do
/**/   If IsPrime(N) Then incr(ref NPrimes); EndIf;
/**/ EndForeach;
/**/ PrintLn "The list L contains ", NPrimes, " primes.";
The list L contains 3 primes.
```

I-9.18 *indent*

syntax

```
indent(X: OBJECT)
indent(X: OBJECT, N: INT)
```

Description

This function prints the argument “X” splitting it into several lines: a “LIST” or “IDEAL” is printed one element per line, a “RECORD” one field per line.

The second optional argument is for setting the level of recursive indentation; it is useful for example when printing a list of records.

example

```
/**/ L := [1,2] >< [3,4];
/**/ L;
[[1, 3], [1, 4], [2, 3], [2, 4]]

/**/ indent(L);
[
  [1, 3],
  [1, 4],
  [2, 3],
  [2, 4]
]

/**/ indent(L,2);
```

```
[
  [
    1,
    3
  ],
  --( Further output )--
  [
    2,
    4
  ]
]

/**/ indent(record[B:=1,A:=2]);
record[
  A := 2,
  B := 1
]
```

See Also: [format\(I-6.17 pg.93\)](#)

I-9.19 indet

syntax

```
indet(R: RING, N: INT): RINGELEM
```

Description

This function returns the N-th indeterminate of the current ring.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ indet(R, 2);
y
```

See Also: [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [indets\(I-9.22 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#)

I-9.20 IndetIndex

syntax

```
IndetIndex(X: RINGELEM): INT
```

Description

This function returns the position in which the indeterminate is listed when the corresponding ring was created.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ IndetIndex(y);
2

/**/ Use R ::= QQ[x[1..2,1..2],y[1..2]];
/**/ Indets(R);
[x[1,1], x[1,2], x[2,1], x[2,2], y[1], y[2]]
```

```

/**/ IndetIndex(x[2,1]);
3

/**/ S ::= QQ[a,b,c];
/**/ IndetIndex(RingElem(S, "b"));
2

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetName\(I-9.21 pg.127\)](#), [indets\(I-9.22 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#), [UnivariateIndetIndex\(I-21.1 pg.285\)](#)

I-9.21 IndetName

syntax

```
IndetName(X: RINGELEM): STRING
```

Description

This function returns the name of the indeterminate X as a string (i.e. the letter without the indices).

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ IndetName(indet(R, 2));
y

/**/ type(It);
STRING

/**/ Use R ::= QQ[a, x[1..3]];
/**/ IndetName(Indet(R, 2));
x

/**/ indent(IndetSymbols(R));
[
  record[head := "a", indices := []],
  record[head := "x", indices := [1]],
  record[head := "x", indices := [2]],
  record[head := "x", indices := [3]]
]

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetSymbols\(I-9.24 pg.129\)](#), [NumIndets\(I-14.35 pg.199\)](#)

I-9.22 indets

syntax

```
indets(R: RING): LIST
indets(R: RING, X: STRING): LIST
```

Description

With one argument (a polynomial ring), this function returns the list of indeterminates of that polynomial ring. With two arguments (the second a STRING), it returns the list of all indeterminates whose name is the given string. The indeterminates in the list appear in order of increasing index (see the function “[IndetIndex](#)”).

This function used to be called “IndetsCalled” up to version 5.0.3, and “AllIndetsCalled” in CoCoA-4.

Additionally, up to version 4.7.3 you could get this list just by giving the name, e.g. “Use QQ[x[0..4]]; x;” but this syntax is no longer allowed because it is ambiguous: “x[2];” is different from “X := x; X[2];”

example

```

/**/ S := QQ[x,y,z];
/**/ Use R := QQ[a,b];
/**/ indets(CurrentRing);
[a, b]
/**/ indets(S);
[x, y, z]
/**/ indets(S,"x");
[x]
/**/ RingElem(S,"x"); -- works also if R is not a polynomial ring
x

/**/ Use R := QQ[x[1..4],a[1..2,1..3]];
/**/ indets(R,"x");
[x[1], x[2], x[3], x[4]]
/**/ indets(R,"a");
[a[1,1], a[1,2], a[1,3], a[2,1], a[2,2], a[2,3]]
/**/ indets(R,"b"); -- empty list if no indet has a matching head
[]

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#)

I-9.23 IndetSubscripts

syntax

```
IndetSubscripts(X: RINGELEM): LIST
```

Description

This function returns the subscripts of the name of the argument, an indeterminate (used to be called “IndetInd”).

Please note the difference with “IndetIndex” ([I-9.20 pg.126](#)).

example

```

/**/ Use R := QQ[x[1..3,1..2],y,z];
/**/ IndetSubscripts(x[3,2]);
[3, 2]
/**/ IndetSubscripts(y);
[]
/**/ IndetIndex(RingElem(R, ["x",3,2]));
6
/**/ IndetSubscripts(RingElem(R, ["x",3,2]));
[3, 2]

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [IndetSymbols\(I-9.24 pg.129\)](#), [indets\(I-9.22 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#)

I-9.24 IndetSymbols

syntax

```
IndetSymbols(P: RING): RECORD
```

Description

This function returns the list of the symbols in a polynomial ring. A symbol is a record “with” head (as “IndetName” (I-9.21 pg.127)) and “indices” (as “IndetSubscripts” (I-9.23 pg.128))

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ indent(IndetSymbols(R));
[
  record[head := "x", indices := []],
  record[head := "y", indices := []],
  record[head := "z", indices := []]
]

/**/ Use R ::= QQ[a, x[1..3]];
/**/ indent(IndetSymbols(R));
[
  record[head := "a", indices := []],
  record[head := "x", indices := [1]],
  record[head := "x", indices := [2]],
  record[head := "x", indices := [3]]
]
```

See Also: `indet` (I-9.19 pg.126), `IndetSubscripts` (I-9.23 pg.128), `IndetIndex` (I-9.20 pg.126), `IndetName` (I-9.21 pg.127), `NumIndets` (I-14.35 pg.199), `SymbolRange` (I-19.46 pg.273)

I-9.25 InducedHom

syntax

```
InducedHom(RmodI: RING, phi: RINGHOM): RINGHOM
```

Description

“InducedHom(RmodI, phi)” – where “RmodI” is a QuotientRing, and “phi” is a homomorphism “R --> S” (which must have “BaseRing(RmodI)” as its “domain” (I-4.22 pg.74), and whose “ker” (I-11.1 pg.157) must contain “DefiningIdeal(RmodI)”) gives the homomorphism “R/I --> S” induced by “phi”

“InducedHom(FrF, phi)” – may be partial where “FrF” is a FractionField, gives the homomorphism induced by “phi” (which must have the base ring of FrF as its domain). Note that the resulting homomorphism may be only partial (e.g. if ker(phi) is non-trivial, or if the codomain is not a field).

example

```
/**/ Use R ::= QQ[x,y];
/**/ RmodI := NewQuotientRing(R, ideal(x^2-1));

/**/ Use S ::= QQ[a,b,c];
/**/ SmodJ := NewQuotientRing(S, ideal(a^2-1));

/**/ phi := PolyAlgebraHom(R,S,[a,b]);
/**/ Use R;
/**/ phi(x);
a
```

```

/**/ RingOf(phi(x)) = S;
true
/**/ psi := CanonicalHom(S, SmodJ)(phi); -- composition of homomorphisms
/**/ psi(x);
(a)
/**/ RingOf(psi(x)) = SmodJ;
true

/**/ theta := InducedHom(RmodI, psi);
/**/ Use RmodI;
/**/ theta(x);
(a)

```

See Also: domain(I-4.22 pg.74), codomain(I-3.19 pg.48), Composition of RINGHOM(III-10.2 pg.365), BaseRing(I-2.1 pg.33), DefiningIdeal(I-4.5 pg.66), NewQuotientRing(I-14.9 pg.188), NewFractionField(I-14.1 pg.185), CanonicalHom(I-3.2 pg.41), PolyAlgebraHom(I-16.14 pg.211), PolyRingHom(I-16.15 pg.212)

I-9.26 InitialIdeal

syntax

```
InitialIdeal(I: IDEAL, Inds: LIST): IDEAL
```

Description

The “*initial form*” of a polynomial F is the homogeneous component of F of the lowest degree (in contrast with the “*leading form*”, see “LF” (I-12.8 pg.162), “DF” (I-4.14 pg.70)). The “*initial ideal*” of the ideal “ I ” is the ideal generated by the initial forms of all polynomials in “ I ”. It is also called “*tangent cone*” (which strictly is the variety defined by the initial ideal).

The implementation is based on Lazard’s method (see Kreuzer-Robbiano, Commutative Computer Algebra II, pg.463).

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ InitialIdeal(ideal(x^3-y), [x,y,z]);
ideal(-y)
/**/ TgCone(ideal(x^3+x^2-y^2));
ideal(x^2 -y^2)

/**/ I := ideal(x^3-y*z, y^2-x*z, z^2-x^2*y);
/**/ TgCone(I); -- same as InitialIdeal(I, [x,y,z]);
ideal(y^2 -x*z, z^2, -y*z)

```

See Also: InitialIdeal(I-9.26 pg.130), PrimaryHilbertSeries(I-16.22 pg.215)

I-9.27 insert [OBSOLESCENT]

syntax

```
[OBSOLESCENT] insert(ref L: LIST, N: INT, E: OBJECT)
```

Description

This function inserts “ E ” into “ L ” as the “ N ”-th component. Kept just for backward compatibility, it is strongly discouraged for its intrinsic inefficiency. See “append” (I-1.12 pg.30).

example

```

/**/ L := ["a","b","d","e"];
/**/ insert(ref L,3,"c");
/**/ L;
["a", "b", "c", "d", "e"]

```

See Also: [append\(I-1.12 pg.30\)](#), [remove\(I-18.30 pg.240\)](#)

I-9.28 Interpolate

syntax

Interpolate(Points: LIST, Values: LIST): RINGELEM

where Points is a list of lists of coefficients representing a set of ‘‘{\it distinct}’’ points and Values is a list of the same size containing numbers from the coefficient ring.

Description

***** NOT YET IMPLEMENTED *****

This function returns a multivariate polynomial which takes given values at a given set of points.

NOTE:

- * the current ring must have at least as many indeterminates as the dimension of the space in which the points lie;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned, the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

example

```

X := Interpolate(Pts, Vals);
Foreach Element In X Do
  PrintLn Element;
EndForeach;

Use QQ[x,y];
Points := [[1/2, 2], [3/4, 4], [5, 6/11], [-1/2, -2]];
Values := [1/2,1/3,1/5,-1/2];
F := Interpolate(Points, Values);
F;
-46849/834000y^2 - 1547/52125x + 13418/52125y + 46849/208500
-----
[Eval(F, P) | P In Points] = Values;  -- check
True
-----

```

I-9.29 interreduce, interreduced

syntax

```
interreduce(ref L: LIST of RINGELEM)
interreduced(L: LIST of RINGELEM): LIST of RINGELEM
```

Description

These functions reduce each polynomial using the other polynomials as reduction rules. The process terminates when each is in normal form with respect to the others. The function “**interreduce**” takes a variable containing a list and overwrites that variable with the interreduced list. The second returns an interreduced list without affecting its arguments.

example

```
/**/ interreduced([x^3-x*y^2+y*z, x*y, z]);
[x*y, z, x^3]

/**/ L := [x^3-x*y^2+y*z, x*y, z];
/**/ interreduce(ref L);
/**/ L;
[x*y, z, x^3]
```

I-9.30 intersection

syntax

```
intersection(A: LIST, B: LIST): LIST
intersection(A: IDEAL, B: LIST): LIST
intersection(A: LIST, B: IDEAL): LIST
intersection(A: IDEAL, B: IDEAL): IDEAL
```

Description

This function returns the intersection of “A” and “B”.

The coefficient ring must be a field.

NOTE: To compute the intersection of ideals corresponding to zero-dimensional schemes, see the commands “GBM” (I-7.3 pg.98) and “HGBM” (I-8.2 pg.107).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ intersection(ideal(x,y,z), ideal(x*y));
ideal(x*y)

/**/ intersection(["a","b","c"], ["b","c","d"]);
["b", "c"]
-----
```

See Also: GBM(I-7.3 pg.98), HGBM(I-8.2 pg.107), IntersectList(I-9.31 pg.132)

I-9.31 IntersectList

syntax

```
IntersectionList(L: LIST of LIST): LIST
IntersectionList(L: LIST of IDEAL): IDEAL
IntersectionList(L: LIST of MODULE): MODULE
```

Description

This function returns the intersection of all elements in “L”. Generalizes “[intersection](#)” ([I-9.30](#) pg.132).

— example —

```
/**/ Use R ::= QQ[x,y,z];
/**/ Points := [[0,0],[1,0],[0,1],[1,1]]; -- a list of points in the plane
/**/ IntersectionList([ ideal(x-P[1]*z, y-P[2]*z) | P In Points]);
ideal(y^2 - y*z, x^2 - x*z)

/**/ IntersectionList([ 1..7, 3..10, 0..5 ]);
[3, 4, 5]
```

See Also: [intersection](#)([I-9.30](#) pg.132), [IdealOfProjectivePoints](#)([I-9.6](#) pg.119), [IdealOfPoints](#)([I-9.5](#) pg.118), [HGBM](#)([I-8.2](#) pg.107), [intersection](#)([I-9.30](#) pg.132)

I-9.32 *inverse*

— syntax —

```
inverse(X: MAT): MAT
```

Description

This function computes the multiplicative inverse of its argument. It is included for use when writing `inverse(X)` comes more naturally than writing “ X^{-1} ”, though both notations are functionally equivalent.

— example —

```
/**/ inverse(mat(QQ, [[1,2], [3,4]]));
matrix(QQ,
  [[-2, 1],
   [3/2, -1/2]])
```

See Also: [adj](#)([I-1.2](#) pg.25)

I-9.33 *InverseSystem*

— syntax —

```
InverseSystem(I: IDEAL, D: INT): LIST of RINGELEM
```

Description

Thanks to Enrico Carlini.

Given an ideal of derivations “I”, and an integer “D”, this function computes the degree “D” part of the inverse system of “I”.

For the sake of simplicity Forms/Polynomials and Derivations live in the same ring, the distinction between them is purely formal.

— example —

```
/**/ Use QQ[x,y,z];
/**/ InverseSystem(ideal(x^3+x*y*z), 3);
[z^3, y*z^2, x*z^2, y^2*z, x^2*z, y^3, x*y^2, x^2*y, x^3 - 6*x*y*z]
```

See Also: [DerivationAction](#)([I-4.11](#) pg.69), [PerpIdealOfForm](#)([I-16.6](#) pg.208)

I-9.34 IO.SprintTrunc

syntax

```
$io.SprintTrunc(E: OBJECT, N: INT): STRING
```

Description

***** NOT YET IMPLEMENTED *****

This function works like “`sprint`” (I-19.25 pg.263), turning the value of the expression `E` into a string, but if the string has length greater than `N-1`, it is truncated and the string “...” is concatenated. This function is useful in formatting reports of results.

example

```
Use R ::= QQ[x,y];
I := ideal(x,y);
$io.SprintTrunc(I,4);
Idea...
-----
```

See Also: `format`(I-6.17 pg.93), `sprint`(I-19.25 pg.263)

I-9.35 iroot

syntax

```
iroot(N: INT, R: INT): INT
```

Description

This function computes the `R`-th root of an integer. If the argument is not a perfect `R`-th power it returns the integer part of the root.

example

```
/**/ iroot(25, 2);
5
/**/ iroot(99, 3);
4
/**/ iroot(-1, 3);
-1
```

See Also: `FloorLog2`, `FloorLog10`, `FloorLogBase`(I-6.13 pg.90)

I-9.36 IsAntiSymmetric

syntax

```
IsAntiSymmetric(M: MAT): BOOL
```

Description

This function tests whether the square matrix “`M`” is anti-symmetric.

example

```
/**/ M := mat([[0, 1, 2], [-1, 0, 3], [-2, -3, 0]]);
/**/ IsAntiSymmetric(M);
true
```

See Also: `IsSymmetric`(I-9.73 pg.148)

I-9.37 IsConstant

syntax

```
IsConstant(X: RINGELEM): BOOL
```

Description

This function tests whether the value of a RINGELEM of a polynomial ring actually lies in the image of the coefficient ring. It is equivalent to checking that the degree in each indeterminate is 0.

example

```
/**/ QQx ::= QQ[x];
/**/ Use QQx[y,z];
/**/ IsConstant(y+1);
false
/**/ IsConstant(x+1);
true
```

See Also: [indets\(I-9.22 pg.127\)](#)

I-9.38 IsContained

syntax

```
IsContained(A: IDEAL, B: IDEAL): BOOL
IsContained(A: MODULE, B: MODULE): BOOL
```

Description

This function tests whether A is contained in B. Was “<=” in CoCoA-4: this syntax is no longer supported.

example

```
/**/ Use QQ[x,y,z];
/**/ IsContained(ideal(x), ideal(x+y, x-y));
true
```

See Also: [IsIn\(I-9.49 pg.139\)](#), [IsSubset\(I-9.71 pg.147\)](#)

I-9.39 IsDefined

syntax

```
IsDefined(E)
```

Description

This function returns true if “E” is defined, otherwise it returns false. Typically, it is used to check if a name has already been assigned.

To know if a field in a record has been assigned use “fields” ([I-6.5 pg.87](#)).

example

```
/**/ IsDefined(MyVariable);
false

/**/ MyVariable := 3;
```

```
/**/ IsDefined(MyVariable);
true
```

See Also: [fields\(I-6.5 pg.87\)](#)

I-9.40 IsDiagonal

— [syntax](#) —

```
IsDiagonal(M: MAT): BOOL
```

Description

This function tests whether the square matrix M is diagonal.

— [example](#) —

```
/**/ M := mat([[0, 1, 2], [-1, 0, 3], [-2, -3, 0]]);
/**/ IsDiagonal(M);
false
```

See Also: [IsSymmetric\(I-9.73 pg.148\)](#), [DiagMat\(I-4.15 pg.71\)](#)

I-9.41 IsDivisible

— [syntax](#) —

```
IsDivisible(A: RINGELEM, B: RINGELEM): BOOL
```

Description

This function says whether “A” is divisible by “B”; it returns “true” if so, otherwise “false”.

— [example](#) —

```
/**/ Use QQ[x,y,z];
/**/ IsDivisible(x, x^2*(y-1));
false
/**/ IsDivisible(x^2*(y-1), x);
true
```

See Also: [FactorMultiplicity\(I-6.3 pg.86\)](#)

I-9.42 IsElem

— [syntax](#) —

```
IsElem(A: RINGELEM, B: IDEAL): BOOL
IsElem(A: MODULEELEM, B: MODULE): BOOL
```

Description

This function tests whether A is an element of B. Same as the command “IsIn” ([I-9.49 pg.139](#)), but works on fewer types: it is in CoCoA-5 for compatibility with the C++ function in CoCoALib.

example

```

/**/ Use QQ[x,y,z];
/**/ IsElem(x, ideal(x+y, x-y));
true

/**/ x IsIn ideal(x+y, x-y);
true

```

See Also: [IsIn\(I-9.49 pg.139\)](#)

I-9.43 IsEven, IsOdd

syntax

```

IsEven(N: INT): BOOL
IsOdd(N: INT): BOOL

```

Description

These functions test whether an integer is even or odd.

example

```

/**/ IsEven(3);
false
/**/ IsOdd(3);
true

```

See Also: [IsZero\(I-9.78 pg.150\)](#)

I-9.44 IsFactorClosed

syntax

```

IsFactorClosed(L: LIST of power products): BOOL

```

Description

A set of power products is factor closed iff it contains every factor of every one of its elements. This function checks whether the given set is factor closed (also known as "order-ideal"). It is an error if L is empty.

example

```

/**/ use P := QQ[x,y,z];
/**/ IsFactorClosed([1, x, x^2]);
true
/**/ IsFactorClosed([one(P), y^2]);
false

```

See Also: [QuotientBasis\(I-17.3 pg.224\)](#), [LT\(I-12.20 pg.168\)](#), [TmpNBM\(I-20.9 pg.280\)](#), [IsStronglyStable\(I-9.70 pg.147\)](#)

I-9.45 IsField

syntax

```

IsField(R: RING): BOOL

```

Description

This function tests whether a ring is a field.

example

```
/**/ IsField(ZZ);
false
/**/ IsField(QQ);
true
```

See Also: IsFiniteField(I-9.46 pg.138)

I-9.46 IsFiniteField

syntax

```
IsFiniteField(R: RING): BOOL
```

Description

This function tests whether a ring is a finite field.

example

```
/**/ IsFiniteField(ZZ);
false
/**/ IsFiniteField(QQ);
false
/**/ Fp:=ZZ/(7); IsFiniteField(Fp);
true
```

See Also: IsField(I-9.45 pg.137), IsPthPower(I-9.64 pg.145), LogCardinality(I-12.17 pg.166), PthRoot(I-16.33 pg.221)

I-9.47 IsFractionField

syntax

```
IsFractionField(R: RING): BOOL
```

Description

This function tests whether the ring “R” is a fraction field, i.e. is “QQ” (I-17.1 pg.223) or has been constructed with “NewFractionField” (I-14.1 pg.185).

example

```
/**/ Use R := QQ[x,y];
/**/ K := NewFractionField(R);
/**/ IsFractionField(K);
true;
/**/ BaseRing(K);
RingWithID(3, "QQ[x,y]")
```

See Also: NewFractionField(I-14.1 pg.185), BaseRing(I-2.1 pg.33)

I-9.48 IsHomog

syntax

```
IsHomog(F: RINGELEM|MODULEELEM): BOOL
IsHomog(L: LIST): BOOL
IsHomog(I: IDEAL|MODULE): BOOL
```

Description

The first form of this function returns True if F is homogeneous. The second form returns True if every element of L is homogeneous. Otherwise, they return False. The third form returns True if the ideal/module can be generated by homogeneous elements, and False if not. Homogeneity is with respect to the first row of the weights matrix.

NOTE: when the grading dimension is 0 everything is trivially true. For safety reasons (from version 5.0.3) “IsHomog” throws an error in this case, e.g. “IsHomog(x-1)” gives error instead of a possibly misleading “true”.

example

```
/**/ Use R ::= QQ[x,y];
/**/ IsHomog(x^2-x*y);
true

/**/ IsHomog(x-y^2);
false

/**/ IsHomog([x^2-x*y, x-y^2]);
false

/**/ R := NewPolyRing(QQ, "x,y", mat([[2,3],[1,2]]), 1);
/**/ Use R;
/**/ IsHomog(x^3*y^2+y^4);
true

/**/ R := NewPolyRing(QQ, "x,y", mat([[2,3],[1,2]]), 2);
/**/ Use R;
/**/ IsHomog(x^3*y^2+y^4);
false

/**/ Use R ::= QQ[x,y];
/**/ IsHomog(ideal(x^2+y,y));
true

/**/ Use R ::= QQ[x,y], Lex; -- note: GradingDim = 0
-- /**/ IsHomog(x-1); -- !!! ERROR !!! instead of "true"
```

See Also: [deg\(I-4.6 pg.66\)](#), [wdeg\(I-23.1 pg.291\)](#)

I-9.49 IsIn

syntax

```
X IsIn Y (return BOOL)
```

Description

The semantics of “IsIn” is explained in the following table:

```

-----
| OBJECT      IsIn  LIST    checks if the list contains the object. |
| POLY        IsIn  IDEAL   checks for ideal membership.      |
| MODULEELEM IsIn  MODULE  checks for module membership.     |
| STRING      IsIn  STRING  checks if the first string is a substring |
|                                     of the second one.         |
-----

```

IsIn operator

I-9.50 IsIndet

syntax

```
IsIndet(X: RINGELEM): BOOL
```

Description

This function tests whether “X” is an indeterminate. If so, it returns “true”; otherwise it returns “false”. An error is signalled if “X” is not a “RINGELEM” or if “RingOf(X)” is not a polynomial ring.

example

```

/**/ Use QQ[x,y,z];
/**/ IsIndet(x);
true
/**/ IsIndet(x-1);
false

```

I-9.51 IsInjective

syntax

```
IsInjective(phi: RINGHOM): BOOL
```

Description

This function checks if a RINGHOM is injective.

example

```

/**/ QQxyz ::= QQ[x,y,z];
/**/ QQab  ::= QQ[a,b];

/**/ Use QQab;
/**/ phi := PolyAlgebraHom(QQxyz, QQab, [a+1, a*b+3, b^2]);
/**/ IsInjective(phi);
false
/**/ ker(phi);
ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)
/**/ IsSurjective(phi);
false

/**/ Use QQab;
/**/ PreImage(phi, b);
record[IsInImage := false, ker := ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)]

/**/ indent(PreImage(phi, a^2));
record[
  IsInImage := true,

```

```

OnePreImage := x^2 - 2*x + 1,
ker := ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)
]
/**/ phi(ReadExpr(QQxyz, "x^2 - 2*x + 1"));
a^2
/**/ phi(ReadExpr(QQxyz, "x^2 - 2*x + 1 + (-x^2*z + y^2 + 2*x*z - 6*y - z + 9)"));
a^2

```

See Also: [ker\(I-11.1 pg.157\)](#), [IsSurjective\(I-9.72 pg.147\)](#)

I-9.52 IsInRadical

— syntax —

```

IsInRadical(F: RINGELEM, I: IDEAL): BOOL
IsInRadical(J: IDEAL, I: IDEAL): BOOL

```

Description

This function tests whether the first argument, a polynomial or an ideal, is contained in the radical of the second argument, an ideal.

This function is much faster than asking “F IsIn Radical(I);”.

— example —

```

/**/ Use QQ[x,y,z];
/**/ I := ideal(x^6*y^4, z);
/**/ IsInRadical(x*y, I);
true
/**/ IsInRadical(ideal(x,y), I);
false
/**/ MinPowerInIdeal(x*y, I);
6

```

See Also: [MinPowerInIdeal\(I-13.23 pg.179\)](#), [radical\(I-18.1 pg.227\)](#)

I-9.53 IsInSubalgebra [OBSOLETE]

— syntax —

```
[OBSOLETE]
```

Description

See “SubalgebraRepr” ([I-19.35 pg.268](#)).

See Also: [SubalgebraRepr\(I-19.35 pg.268\)](#)

I-9.54 IsInvertible

— syntax —

```
IsInvertible(f: RINGELEM): BOOL
```

Description

This function tests whether the argument “**f**” is invertible in “**RingOf(f)**”.

example

```
/**/ use R := QQ[x];
/**/ Q := R/ideal(x^2+1);
/**/ use Q;
/**/ IsInvertible(x-2);
true
/**/ 1/(x-2);
((-1/5)*x -2/5)
```

I-9.55 IsIrred

syntax

```
IsIrred(f: RINGELEM): BOOL
```

Description

This function tests whether the argument “**f**” is irreducible in “**RingOf(f)**”.

example

```
/**/ FFp := NewRingFp(7);
/**/ use FFp[x];
/**/ f := x^9+x+1;
/**/ IsIrred(f);
true
```

I-9.56 IsLexSegment

syntax

```
IsLexSegment(I: IDEAL): BOOL
```

Description

This function tests whether the monomial ideal **I** is a lex-segment ideal.

example

```
/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x*y^3, y^4, x^3, x^2*y, x^2*z);
/**/ IsLexSegment(I);
false
```

See Also: [IsStable\(I-9.68 pg.146\)](#), [IsStronglyStable\(I-9.70 pg.147\)](#), [LexSegmentIdeal\(I-12.7 pg.162\)](#)

I-9.57 IsMaximal

syntax

```
IsMaximal(I: IDEAL): BOOL
```

Description

This function determines whether an ideal is maximal. (Not yet implemented for small characteristic)

example

```

/**/ Use P ::= QQ[x,y,z];
/**/ IsMaximal(ideal(x^2+1, (x-5*y+4*z), z^3+z-1));
true
/**/ IsMaximal(ideal(x^2+1, (x-5*y+4*z)*(y-3), z^3+z-1));
false

```

See Also: *IsPrimary*([I-9.61](#) pg.144)

I-9.58 *IsNumber* [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] See “*IsInteger*”, “*IsRational*”

I-9.59 *IsOne*

syntax

IsOne(X: OBJECT): BOOL

Description

This function tests whether its argument is one; the argument can be of almost any type for which “*one*” makes sense.

example

```

/**/ IsOne(23);
false
/**/ IsOne(3/3);
true
/**/ Use R ::= QQ[x,y,z];
/**/ IsOne(1);
false
/**/ IsOne(ideal(x^2, x^2-1));
false

```

See Also: *IsEven*, *IsOdd*([I-9.43](#) pg.137), *one*([I-15.1](#) pg.201), *IsZero*([I-9.78](#) pg.150)

I-9.60 *IsPositiveGrading*

syntax

IsPositiveGrading(M: MAT): BOOL
IsPositiveGrading(M: MAT, N: INT): BOOL

Description

This function determines whether a matrix defines a positive grading, i.e. each column has a non-zero entry and its first non-zero entry is positive.

NOTE: it also requires it has maximal rank (from version CoCoA-5.1.3).

example

```

/**/ IsPositiveGrading(LexMat(5));
true
/**/ IsPositiveGrading(submat(LexMat(5),1..3,1..5)); --only the first 3 rows
false
/**/ IsPositiveGrading(mat([[0,2,3], [1, -1, 0]]));
true
/**/ IsPositiveGrading(mat([[1,1], [0,-1]]));
true
/**/ IsPositiveGrading(mat([[1,1], [0,-1], [-1, 0]])); --not maximal rank
false

```

See Also: [HilbertSeriesMultiDeg\(I-8.8 pg.111\)](#)

I-9.61 IsPrimary

syntax

```
IsPrimary(I: IDEAL): BOOL
```

Description

This function determines whether an ideal is primary.

example

```

/**/ Use P ::= QQ[x,y,z];
/**/ IsPrimary(ideal(x^2, y^2, z));
true
/**/ IsPrimary(ideal(x*(x-1), y^2, z));
false

```

See Also: [PrimaryDecomposition0\(I-16.20 pg.215\)](#)

I-9.62 IsPrime

syntax

```
IsPrime(N: INT): BOOL
```

Description

This function determines whether a positive integer is prime; if N is not positive, an error is signalled. This function may be extremely slow when N is a large prime; in practice it is usually better to call `IsProbPrime`.

For the curious: currently, the function first performs a probabilistic check (Miller-Rabin), if that passes, it then verifies primality (via Lucas test).

example

```

/**/ IsPrime(32003);
true
/**/ IsPrime(10^100);
false

```

See Also: [IsProbPrime\(I-9.63 pg.145\)](#), [NextPrime\(I-14.13 pg.190\)](#)

I-9.63 IsProbPrime

syntax

```
IsProbPrime(N: INT): BOOL
```

Description

This function returns True if its integer argument passes a fairly stringent primality test; otherwise it returns False. There is a very small chance of the function returning True even though the argument is composite; if it returns False, we are certain that the argument is composite. Some people call it a compositeness test.

example

```
/**/ IsProbPrime(2);
true

/**/ IsProbPrime(111111111111111111);
true

/**/ [N in 1..1111 | IsProbPrime((10^N-1)/9)]; -- only five values are known
[2, 19, 23, 317, 1031] -- next might be 49081
```

See Also: IsPrime([I-9.62](#) pg.144), NextProbPrime([I-14.14](#) pg.190)

I-9.64 IsPthPower

syntax

```
IsPthPower(X: RINGELEM): BOOL
```

Description

This function determines whether a polynomial over a finite field (of char p) is a p-th power. If the coefficient ring is not a finite field then an error is signalled.

example

```
/**/ Use ZZ/(7)[x];
/**/ IsPthPower(x^7+3);
true
/**/ IsPthPower(x^6+3);
false
```

See Also: IsFiniteField([I-9.46](#) pg.138), PthRoot([I-16.33](#) pg.221)

I-9.65 IsQQ

syntax

```
IsQQ(R: RING): BOOL
```

Description

This function tests whether a ring is the ring of rationals.

example

```
/**/ R := QQ[x,y];
/**/ IsQQ(CoeffRing(R));
true;
```

See Also: QQ([I-17.1](#) pg.223), RingQQ([I-18.43](#) pg.246), IsZZ([I-9.82](#) pg.152)

I-9.66 isqrt

syntax

[OBSOLESCENT]

Description

Renamed to “FloorSqrt” ([I-6.14](#) pg.91).

I-9.67 IsQuotientRing

syntax

IsQuotientRing(R: RING): BOOL

Description

This function tests whether a ring is a quotient ring; it returns “true” if the ring is a quotient ring.

example

```
/**/ Use R ::= QQ[x,y];
/**/ S := R/ideal(x);
/**/ IsQuotientRing(S);
true;
```

See Also: DefiningIdeal([I-4.5](#) pg.66)

I-9.68 IsStable

syntax

IsStable(I: IDEAL): BOOL

Description

This function tests whether the monomial ideal I is stable.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x*y^3, y^4, x^3, x^2*y, x^2*z);
/**/ IsStable(I);
true
```

See Also: IsLexSegment([I-9.56](#) pg.142), IsStronglyStable([I-9.70](#) pg.147), LexSegmentIdeal([I-12.7](#) pg.162)

I-9.69 IsStdGraded

syntax

IsStdGraded(P: RING): BOOL

Description

This function tests whether “P” is standard graded, “i.e.” “GradingDim” is 1 and all indeterminates in “P” have degree 1.

example

```

/**/ P := QQ[x,y,z];
/**/ IsStdGraded(P);
true
/**/ P := QQ[x,y,z], lex;
/**/ IsStdGraded(P);
false
/**/ P := NewPolyRing(QQ, "x,y", mat([[2,3],[1,2]]), 1);
/**/ IsStdGraded(P);
false

```

See Also: NewPolyRing(I-14.8 pg.188), wdeg(I-23.1 pg.291)

I-9.70 IsStronglyStable

syntax

```
IsStronglyStable(I: IDEAL): BOOL
```

Description

This function tests whether the monomial ideal I is strongly stable (Borel-fixed in characteristic 0).

example

```

/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x*y^3, y^4, x^3, x^2*y, x^2*z);
/**/ IsStronglyStable(I);
true

```

See Also: IsLexSegment(I-9.56 pg.142), IsStable(I-9.68 pg.146)

I-9.71 IsSubset

syntax

```
IsSubset(L: LIST, M: LIST): BOOL
```

Description

This function returns “true” if “MakeSet(L)” is contained in “MakeSet(M)”; otherwise it returns “false”.

example

```

/**/ IsSubset([1,1,2],[1,2,3,"a"]);
true
/**/ IsSubset([1,2],["a","b"]);
false
/**/ IsSubset([], [1,2]);
true

```

See Also: IsContained(I-9.38 pg.135), IsIn(I-9.49 pg.139), EqSet(I-5.7 pg.78), MakeSet(I-13.3 pg.170), subsets(I-19.39 pg.270)

I-9.72 IsSurjective

syntax

```
IsSurjective(phi: RINGHOM): BOOL
```

Description

This function checks if a RINGHOM is surjective.

example

```
/**/ QQxyz := QQ[x,y,z];
/**/ QQab  := QQ[a,b];

/**/ Use QQab;
/**/ phi := PolyAlgebraHom(QQxyz, QQab, [a+1, a*b+3, b^2]);
ideal(-x^2*z +y^2 +2*x*z -6*y -z +9)
/**/ IsSurjective(phi);
false

/**/ PreImage(phi, b);
record[IsInImage := false, ker := ideal(-x^2*z +y^2 +2*x*z -6*y -z +9)]
```

See Also: [ker\(I-11.1 pg.157\)](#), [IsInjective\(I-9.51 pg.140\)](#), [PreImage\(I-16.17 pg.213\)](#)

I-9.73 IsSymmetric

syntax

```
IsSymmetric(M: MAT): BOOL
```

Description

This function tests whether the square matrix “M” is symmetric.

example

```
/**/ M := mat([[1, 2, 3], [2, 4, 5], [3, 5, 6]]);
/**/ IsSymmetric(M);
true
```

See Also: [IsAntiSymmetric\(I-9.36 pg.134\)](#)

I-9.74 IsTerm

syntax

```
IsTerm(X: RINGELEM|MODULEELEM): BOOL
```

Description

The function determines whether X is a term. For a polynomial, a “term” is a power-product, namely, a product of indeterminates. Thus, $x * y^2 * z$ is a term, while $4 * x * y^2 * z$ and $x * y + z^3$ are not. For a vector, a term is a power-product times a standard basis vector, for instance $(0, x * y^2 * z, 0)$.

example

```
/**/ Use R := QQ[x,y,z];
/**/ IsTerm(x+y^2);
false

/**/ IsTerm(x^3*y*z^2);
true

/**/ IsTerm(5*x^3*y*z^2);
```

```

false

/**/ R2 := NewFreeModule(R,2);
--/**/ IsTerm(ModuleElem(R2, [0,x*z])); --***WORK IN PROGRESS***
--true

--/**/ IsTerm(ModuleElem(R2, [x,y])); --***WORK IN PROGRESS***
--false

```

I-9.75 IsTermOrdering

syntax

```
IsTermOrdering(M: MAT): BOOL
```

Description

This function determines whether a square matrix defines a term-ordering, i.e. if its determinant is non-zero and if foreach column the first nonnegative entry is positive.

example

```

/**/ IsTermOrdering(LexMat(5));
true

/**/ IsTermOrdering(StdDegRevLexMat(5));
true

/**/ IsTermOrdering(RevLexMat(5));
false

```

See Also: [NewPolyRing\(I-14.8 pg.188\)](#), [OrdMat\(I-15.10 pg.205\)](#)

I-9.76 IsTree5

syntax

```

IsTree5(L: LIST): [BOOL, LIST ]
IsTree5(L: LIST, "NOOPT"): [BOOL, LIST]
IsTree5(L: LIST, "OPT"): [BOOL, LIST]
IsTree5(L: LIST, "CS_NOOPT"): [BOOL, LIST]
IsTree5(L: LIST, "CS_OPT"): [BOOL, LIST]

```

Description

***** NOT YET IMPLEMENTED *****

This function is implemented in CoCoALib.

This function tests whether the facet complex described by the list L of square free power products is a tree, plus a list which:

- is empty if L is a tree
- contains three elements of a cycle of L if L is not a tree.

Four options "NOOPT", "OPT", "CS_NOOPT", "CS_OPT" are available as second argument, specifying different algorithms; the default is "CS_OPT".

For a full description of the algorithms we refer to the paper by M. Caboara, S. Faridi, and P. Selinger, "Simplicial cycles and the computation of simplicial trees", Journal of Symbolic Computation, vol.42/1-2, pp.77-88 (2006).

example

```
Use R ::= QQ[x,y,z,t];
D := [x*y, y*z, z*t, t*x];
IsTree5(D);
[False, [xy, xt, yt]]
-----
IsTree5([xy, yz, zt]);
[True, [ ]]
```

I-9.77 IsTrueGCDDomain

syntax

```
IsTrueGCDDomain(R: RING): BOOL
```

Description

This function tests whether a ring is a (true) GCD domain but not a field. CoCoA can compute GCDs of elements of a true GCD domain.

example

```
/**/ IsTrueGCDDomain(ZZ);
true
/**/ IsTrueGCDDomain(QQ);
false
```

See Also: [IsField\(I-9.45 pg.137\)](#)

I-9.78 IsZero

syntax

```
IsZero(X: OBJECT): BOOL
```

Description

This function tests whether its argument is zero; the argument can be of almost any type for which “zero” makes sense.

example

```
/**/ IsZero(23);
false
/**/ IsZero(3-3);
true
/**/ Use R ::= QQ[x,y,z];
/**/ IsZero(x^2+3*y-1);
false
/**/ IsZero(ideal(x^2,x*y^3));
false
/**/ F := NewFreeModule(R, 3);
/**/ zero(F);
[0, 0, 0]
/**/ IsZero(zero(F));
```

```

true
/**/ IsZero(matrix([[0,0,0], [0,0,0]]));
true

```

See Also: IsEven, IsOdd(I-9.43 pg.137), IsOne(I-9.59 pg.143), zero(I-25.1 pg.297), ZeroMat(I-25.2 pg.297)

I-9.79 IsZeroCol, IsZeroRow

syntax

```

IsZeroCol(M: MAT, N: INT): BOOL
IsZeroRow(M: MAT, N: INT): BOOL

```

Description

This function tests whether all entries in the “N”-th column(row) of “M” are zero.

example

```

/**/ IsZeroRow(matrix([[1,0,0], [0,0,0]]), 1);
false
/**/ IsZeroCol(matrix([[1,0,0], [0,0,0]]), 2);
true

```

See Also: IsZero(I-9.78 pg.150), ZeroMat(I-25.2 pg.297)

I-9.80 IsZeroDim

syntax

```

IsZeroDim(I: IDEAL): BOOL

```

Description

This function tests whether its argument is zero-dimensional.

example

```

/**/ Use QQ[x,y,z];
/**/ IsZeroDim(ideal(x));
false
/**/ IsZeroDim(ideal(x^3, y^4-x, z-3));
true
/**/ IsZeroDim(ideal(x^2, x*y^3));
false

```

See Also: dim(I-4.17 pg.72)

I-9.81 IsZeroDivisor

syntax

```

IsZeroDivisor(X: RINGELEM): BOOL

```

Description

This function tests whether its argument is a zero-divisor.

example

```

/**/ Use P ::= QQ[x,y,z];
/**/ R := NewQuotientRing(P, ideal(x*y));
/**/ IsZeroDivisor(RingElem(R,x));
true
/**/ colon(ideal(zero(R)), ideal(RingElem(R,x)));
ideal((y))

```

See Also: `colon`([I-3.27](#) pg.52)

I-9.82 IsZZ

syntax

```

IsZZ(R: RING): BOOL

```

Description

This function tests whether a ring is the ring of integers.

example

```

/**/ R ::= QQ[x,y];
/**/ IsZZ(CoeffRing(R));
false
/**/ IsZZ(BaseRing(CoeffRing(R)));
true

```

See Also: `ZZ`([I-25.4](#) pg.298), `RingZZ`([I-18.47](#) pg.248), `IsQQ`([I-9.65](#) pg.145)

I-9.83 It

syntax

```

It

```

Description

“**It**” is a top-level SYSTEM VARIABLE containing the last result computed but not assigned. It is the CoCoA equivalent to GAP’s “**last**”.

When CoCoA evaluates a “*standalone expression*”, the result is assigned to the system variable named “**It**” (and then printed as if in a “`println`” ([I-16.29](#) pg.219) command). You may use “**It**” in expressions just like any other variable.

example

```

/**/ 1+1; -- standalone expression ==> result is saved in "It".
2
/**/ It;
2

/**/ It+1;
3
/**/ It;
3

/**/ X := 17; -- assignment is not a standalone expression, "It" is unchanged
/**/ It;

```



```
3
/**/ X+It;
20
```

See Also: [print\(I-16.25 pg.217\)](#), [println\(I-16.29 pg.219\)](#), [Evaluation and Assignment\(II-4 pg.311\)](#)

Chapter I-10

J

I-10.1 jacobian

syntax

```
jacobian(L: LIST of RINGELEM): MAT
```

Description

This function returns the Jacobian matrix of the polynomials in “L” with respect to all the indeterminates of the current ring.

example

```
/**/ Use R ::= QQ[x,y];
/**/ L := [x-y, x^2-y, x^3-y^2];
/**/ jacobian(L);
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[1, -1],
   [2*x, -1],
   [3*x^2, -2*y]])
```

I-10.2 JanetBasis

syntax

```
JanetBasis(I: IDEAL): LIST of RINGELEM
```

Description

Thanks to Mario Albert.

This function returns the Janet basis of an ideal.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ L := [x-y, x^2-z+1, x^3-y^2];
/**/ JanetBasis(ideal(L));
[x -y, z^2 -3*z +2, y*z -y -z +1, y^2 -z +1]
```

See Also: GBasis([I-7.1](#) pg.97)

Chapter I-11

K

I-11.1 `ker`

[syntax](#)

```
ker(phi: RINGHOM): IDEAL
```

Description

This function returns the kernel of a homomorphism.

[example](#)

```
/**/ R := QQ[x,y,z,w];
/**/ Use S := QQ[s,t];
/**/ phi := PolyAlgebraHom(R, S, [s^3, s^2*t, s*t^2, t^3]);
/**/ ker(phi);
ideal(z^2 -y*t, y*z -x*t, y^2 -x*z)

/**/ SmoJ := NewQuotientRing(S, ideal(ReadExpr(S,"t+s")));
/**/ Use SmoJ;
/**/ psi := PolyAlgebraHom(R, SmoJ, [s^3, s^2*t, s*t^2, t^3]);
/**/ ker(psi);
ideal(x +w, y -w, z +w)

/**/ RmodI := NewQuotientRing(R, ideal(ReadExpr(R,"x+y")));
/**/ ker(InducedHom(RmodI, psi));
ideal((-y +w), (y -w), (z +w))
```

See Also: [PreImage\(I-16.17 pg.213\)](#), [IsInjective\(I-9.51 pg.140\)](#), [IsSurjective\(I-9.72 pg.147\)](#)

Chapter I-12

L

I-12.1 last

syntax

```
last(L: LIST): OBJECT  
last(L: LIST, N: INT): OBJECT
```

Description

In the first form, the function returns the last element of L. In the second form, it returns the list of the last N elements of L.

The CoCoA equivalent to GAP “last” is the variable “It” ([I-9.83 pg.152](#)).

example

```
/**/ L := [1,2,3,4,5];  
/**/ last(L);  
5  
  
/**/ last(L,3);  
[3, 4, 5]
```

See Also: first([I-6.6 pg.87](#)), tail([I-20.3 pg.278](#)), It([I-9.83 pg.152](#))

I-12.2 LaTeX

syntax

```
LaTeX(X: OBJECT): STRING
```

Description

This function returns a string containing the argument formatted in LaTeX. From version 4.7.5 it returns a string, so it can be printed on a file. Can also be called as “**latex**”.

example

```
/**/ Use R ::= QQ[x,y,z];  
/**/ F := x^3+2*y^2*z;  
/**/ LaTeX(F);  
x^{3} + 2y^{2}z  
  
/**/ M := mat([[1,2],[3,4]]);
```

```

/**/ LaTeX(M);
\left( \begin{array}{cc}
1 & 2 \\
3 & 4 \end{array} \right)

/**/ R := QQ[x,y,z];
/**/ LaTeX(ideal(x^2,y+z));
(x^2,
 y +z)

/**/ P := NewFractionField(R);
/**/ Use P;
/**/ F := (x+y)/(1-z)^3;
/**/ LaTeX(F);
\frac{-x-y}{z^3-3z^2+3z-1}

```

See Also: [format\(I-6.17 pg.93\)](#), [sprint\(I-19.25 pg.263\)](#)

I-12.3 LC

— syntax —

```
LC(F: RINGELEM|MODULEELEM): RINGELEM
```

Description

This function returns the leading coefficient of F, as determined by the term-ordering of the ring to which F belongs.

— example —

```

/**/ Use R := QQ[x,y];
/**/ LC(x +3*x^2 -5*y^2);
3

/**/ F := NewFreeModule(R,3);
/**/ LC(ModuleElem(F, [0, 5*y+6*x^2, y^2]));
6

```

See Also: [coefficients\(I-3.21 pg.48\)](#), [CoeffOfTerm\(I-3.24 pg.50\)](#), [LT\(I-12.20 pg.168\)](#)

I-12.4 lcm

— syntax —

```

lcm(N: INT, M: INT): INT
lcm(L: LIST of INT): INT

lcm(F: RINGELEM, G: RINGELEM): RINGELEM
lcm(L: LIST of RINGELEM): RINGELEM

```

Description

This function returns the least common multiple of “F₁, . . . , F_n” or of the elements in the list L. For the calculation of the GCDs and LCMs of polynomials, the coefficient ring must be a field.

example

```

/**/ Use R ::= QQ[x,y];
/**/ F := x^2-y^2;
/**/ G := (x+y)^3;
/**/ lcm(F, G);
-x^4 -2*x^3*y +2*x*y^3 +y^4

/**/ IsDivisible(F*G, It);
true

/**/ lcm(F, G) * gcd(F,G) = F*G;
true

/**/ lcm([3*4,3*8,6*16]);
96

```

See Also: [div\(I-4.20 pg.73\)](#), [mod\(I-13.25 pg.180\)](#), [gcd\(I-7.4 pg.98\)](#)

I-12.5 *len*

syntax

```
len(E: STRING|LIST): INT
```

Description

This function returns the “*length*” of an object, as summarized in the table below:

type	length

STRING	number of bytes in the string
LIST	number of items in the list

The function ‘\verb&len&’	

example

```

/**/ len( [2,3,4] );
3

/**/ len( "string" );
6

```

Previously “*len*” could be applied to other types too; this is no longer supported. See “*NumCompts*” ([I-14.33 pg.198](#)) for module elements, “*NumRows*” ([I-14.37 pg.200](#)) for matrices, and “*NumTerms*” ([I-14.38 pg.200](#)) for polynomials.

See Also: [count\(I-3.47 pg.60\)](#), [NumCompts\(I-14.33 pg.198\)](#), [NumRows\(I-14.37 pg.200\)](#), [NumTerms\(I-14.38 pg.200\)](#)

I-12.6 *LexMat*

syntax

```
LexMat(N: INT): MAT
```

Description

This function return the matrix defining the standard term-ordering "lex".

— example —

```
LexMat(3);
matrix(ZZ, [
  [1, 0, 0],
  [0, 1, 0],
  [0, 0, 1]
])
```

See Also: Orderings([III-9.5](#) pg.360), StdDegLexMat([I-19.31](#) pg.266), StdDegRevLexMat([I-19.32](#) pg.267), RevLexMat([I-18.38](#) pg.244), XelMat([I-24.1](#) pg.295)

I-12.7 LexSegmentIdeal

— syntax —

```
LexSegmentIdeal(L: LIST of power-products): IDEAL
LexSegmentIdeal(I: IDEAL): IDEAL
```

Description

If the argument is a list of power-products L, this function returns the smallest lex-segment ideal containing the power-products in L.

If it is an ideal I, it returns the lex-segment ideal having the same Hilbert function as I.

— example —

```
/**/ Use R ::= QQ[x,y,z];
/**/ LexSegmentIdeal([y^3]);
ideal(y^3, x*z^2, x*y*z, x*y^2, x^2*z, x^2*y, x^3)
/**/ LexSegmentIdeal(ideal(y^3));
ideal(x^3)
```

See Also: IsLexSegment([I-9.56](#) pg.142), StableIdeal([I-19.28](#) pg.265), StronglyStableIdeal([I-19.33](#) pg.267)

I-12.8 LF

— syntax —

```
LF(I: IDEAL): IDEAL
LF(F: RINGELEM): RINGELEM
```

Description

For a polynomial "F" this function returns the leading form, i.e. the sum of all summands having highest degree. It throws an error if the argument is zero or if the "GradingDim" ([I-7.19](#) pg.105) of the polynomial ring is 0 (use "DF" ([I-4.14](#) pg.70) to allow these cases).

For an ideal "I" this function returns the ideal of all the "LF(f)" for "f in I". It throws an error if the "GradingDim" ([I-7.19](#) pg.105) of the polynomial ring is 0.

— example —

```
/**/ Use R ::= QQ[x,y];
/**/ LF(x^2 -x*y +2*x -1);
x^2 -x*y
```

```

/**/ Use R := QQ[x,y], Lex; -- GradingDim is 0: everything is homogeneous
-- /**/ LF(x-1); --> !!! ERROR !!! instead of x-1

/**/ P := NewPolyRing(QQ, IndetSymbols(R), mat([[1,4],[1,0]]), 1);
/**/ Use P;
/**/ LF(x^2 - x*y);
-x*y
/**/ LF(x^4 + x^2 - y);
x^4 -y

```

See Also: DF(I-4.14 pg.70), IsHomog(I-9.48 pg.139), LC(I-12.3 pg.160), LM(I-12.15 pg.166), LPP(I-12.19 pg.167), LT(I-12.20 pg.168)

I-12.9 LinearSimplify

syntax

```
LinearSimplify(F: RINGELEM): RECORD
```

Description

This function returns a “RECORD[LinearChange, SimplePoly]” where “LinearChange” is a linear change of variable and “SimplePoly” is simple (in a heuristic sense). The composition “SimplePoly(LinearChange)” is equal the univariate polynomial “F”.

example

```

/**/ Use QQ[x];
/**/ LinearSimplify((123*x-456)^9-1);
record[LinearChange := 123*x - 456, SimplePoly := x^9 - 1]

/**/ LinearSimplify(x^9-1); -- the heuristic finds no useful simplification
record[LinearChange := x, SimplePoly := x^9 - 1]

```

I-12.10 LinKer

syntax

```
LinKer(M: MAT): MAT
```

Description

This function returns a matrix whose columns representing a basis for the kernel of “M”. Calling the function twice on the same input will not necessarily produce the same output, though in each case, a basis for the kernel is produced.

This function works only on matrices whose entries are in a field (from version CoCoA-5.0.3). The CoCoA-4 function returning a ZZ-basis for the kernel of “M” is not yet implemented.

The output as it was given by CoCoA-4 (the basis of the ker) is now given by “LinKerBasis” (I-12.11 pg.164). See also “HilbertBasisKer” (I-8.4 pg.108).

example

```

/**/ M := mat([[1,2,3,4],[5,6,7,8],[9,10,11,12]]);
/**/ LinKer(M);
matrix(QQ,
  [-1, -2],
  [2, 3],

```

```

    [-1, 0],
    [0, -1]])

/**/ M*It;
matrix(QQ,
    [[0, 0],
     [0, 0],
     [0, 0]])

```

See Also: [LinSolve\(I-12.14 pg.165\)](#), [HilbertBasisKer\(I-8.4 pg.108\)](#)

I-12.11 LinKerBasis

syntax

```
LinKerBasis(M: MAT): LIST
```

Description

This function returns a list whose components are lists representing a basis for the kernel of M. Calling the function twice on the same input will not necessarily produce the same output, though in each case, a basis for the kernel is produced.

This function works only on matrices whose entries are in a field (from version CoCoA-5.0.3). The CoCoA-4 function returning a ZZ-basis for the kernel of “M” is not yet implemented.

example

```

/**/ M := mat([[1,2,3,4],[5,6,7,8],[9,10,11,12]]);
/**/ LinKerBasis(M);
[[-1, 2, -1, 0], [-2, 3, 0, -1]]

/**/ K := NewFractionField(NewPolyRing(QQ, "a,b"));
/**/ Use K;
/**/ M := mat([[1,2,3,a],[5,6,7,a*b]]);
/**/ LinKerBasis(M);
[[-1, 2, -1, 0], [(a*b -3*a)/2, (-a*b +5*a)/4, 0, -1]]

```

See Also: [LinSolve\(I-12.14 pg.165\)](#)

I-12.12 LinKerModP [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] In CoCoA-4 it was difficult to map a matrix into “ZZ/(p)”. Now, in CoCoA-5, we can map the matrix and then call directly “LinKer” ([I-12.10 pg.163](#)) and “LinKerBasis” ([I-12.11 pg.164](#)).

example

```

/**/ Use ZZ/(7);
/**/ M := mat([[1,2,3,4],[5,6,7,8],[9,10,11,12]]); --> by default over QQ
/**/ LinKerBasis(M);
[[-1, 2, -1, 0], [-2, 3, 0, -1]]

```

```

/**/ LinKerBasis(matrix(NewRingFp(3), M)); --> map M into ZZ/(3)
[[-1, -1, -1, 0], [1, 0, 0, -1]]

/**/ LinKer(matrix(CurrentRing, M)); --> map M into CurrentRing ZZ/(7)
matrix( /*RingWithID(9, "FFp(7)")*/
  [[-1, -2],
   [2, 3],
   [-1, 0],
   [0, -1]])
/**/ matrix(CurrentRing, M) * It;
matrix( /*RingWithID(9, "FFp(7)")*/
  [[0, 0],
   [0, 0],
   [0, 0]])

```

See Also: LinKer([I-12.10 pg.163](#)), LinKerBasis([I-12.11 pg.164](#)), LinSolve([I-12.14 pg.165](#))

I-12.13 LinSol [OBSOLETE]

— syntax —

```
[OBSOLETE] use LinSolve
```

Description

[OBSOLETE] Replaced by “LinSolve” ([I-12.14 pg.165](#)) **See Also:** LinSolve([I-12.14 pg.165](#))

I-12.14 LinSolve

— syntax —

```
LinSolve(M: MAT, RHS: MAT): MAT
```

Description

This function finds a solution “X” to the matrix equation “M*X = RHS”. If more than one solution exists, it returns just one of them. If no solution exists then it produces a 0-by-0 matrix. To find all solutions, compute the kernel of “M” using the function “LinKer” ([I-12.10 pg.163](#)).

NOTE: an easy way of converting a list into a column matrix (for the second argument) is to use the function “ColMat” ([I-3.26 pg.51](#)).

— example —

```

/**/ M := mat([[3,1,4],[1,5,9],[2,6,5]]);
/**/ L := [123,456,789];
/**/ LinSolve(M, ColMat(L));
mat([
  [199/5],
  [742/5],
  [-181/5]
])

/**/ M*It;
mat([
  [123],
  [456],

```

```
[789]
])
-----
```

See Also: LinKer([I-12.10](#) pg.163)

I-12.15 LM

syntax

```
LM(X: RINGELEM): RINGELEM
LM(X: MODULEELEM): MODULEELEM
```

Description

This function returns the leading monomial of “X”. The monomial includes the coefficient. To get the leading term of “P”, (which does not include the coefficient), use “LT” ([I-12.20](#) pg.168).

example

```
/**/ Use R ::= QQ[x,y];
/**/ LM(3*x^2*y + y);
3*x^2*y
```

See Also: LC([I-12.3](#) pg.160), LF([I-12.8](#) pg.162), LPP([I-12.19](#) pg.167), LT([I-12.20](#) pg.168)

I-12.16 log [OBSOLESCENT]

syntax

```
[OBSOLESCENT]
```

Description

Renamed to “exponents” ([I-5.14](#) pg.81).

I-12.17 LogCardinality

syntax

```
LogCardinality(Fp: RING): INT
```

Description

This function returns the extension degree of a finite field over its prime field, or equivalently the log (base p) of its cardinality.

example

```
/**/ Fp ::= ZZ/(7);
/**/ Use Fpx ::= Fp[x];
/**/ Fq := Fpx/ideal(x^2+1);
/**/ LogCardinality(Fq);
2
```

See Also: IsFiniteField([I-9.46](#) pg.138), characteristic([I-3.9](#) pg.44)

I-12.18 LPosn

— syntax —

LPosn(V: MODULEELEM): INT

Description

This function returns the position of the leading power-product of “V”.

This function used to be called “LPos” up to version 5.0.3.

— example —

```

/**/ Use R ::= QQ[x,y,z]; -- the default term-ordering is DegRevLex
/**/ R4 := NewFreeModule(R,4); -- the default module ordering is TOPos
/**/ LPosn(ModuleElem(R4, [0, x, y^2, x^2]));
4
/**/ LPP(ModuleElem(R4, [0, x, y^2, x^2]));
x^2
/**/ LT(ModuleElem(R4, [0, x, y^2, x^2]));
[0, 0, 0, x^2]
```

```

Use R ::= QQ[x,y], PosTo;
LT(Vector(x,y^2));
Vector(x, 0)
```

```

-----
LPP(Vector(x,y^2));
x
```

```

-----
LPosn(Vector(x,y^2));
1
-----
```

See Also: LF(I-12.8 pg.162), LM(I-12.15 pg.166), LPP(I-12.19 pg.167), LT(I-12.20 pg.168)

I-12.19 LPP

— syntax —

LPP(X: RINGELEM): RINGELEM
LPP(X: MODULEELEM): RINGELEM

Description

This function returns the leading power-product of “X”; it discards information about which component the power-product appears in.

— example —

```

/**/ Use R ::= QQ[x,y];
/**/ LPP(3*x^2*y+y); -- LPP is the same as LT for polynomials
x^2*y

-- Note the difference between LPP and LT for MODULEELEM.
/**/ R4 := NewFreeModule(R,4); -- the default module ordering is TOPos
/**/ LPP(ModuleElem(R4, [0, x, y^2, x^2]));
x^2
/**/ LT(ModuleElem(R4, [0, x, y^2, x^2]));
[0, 0, 0, x^2]
```

```
/**/ LPosn(ModuleElem(R4, [0, x, y^2, x^2]));
4
```

See Also: LC(I-12.3 pg.160), LF(I-12.8 pg.162), LM(I-12.15 pg.166), LPosn(I-12.18 pg.167), LT(I-12.20 pg.168)

I-12.20 LT

— syntax —

```
LT(I: RINGELEM):  RINGELEM
LT(I: IDEAL):     IDEAL
LT(I: MODULEELEM): MODULEELEM
LT(I: MODULE):    MODULE
```

Description

If E is a polynomial this function returns the leading term of the polynomial E with respect to the term-ordering of the polynomial ring of E . For the leading monomial, which includes the coefficient, use “LM” (I-12.15 pg.166).

— example —

```
/**/ Use R ::= QQ[x,y,z]; -- the default term-ordering is DegRevLex
/**/ LT(y^2-x*z);
y^2

/**/ Use R ::= QQ[x,y,z], Lex;
/**/ LT(y^2-x*z);
x*z
```

If “ E ” is a MODULEELEM, “LT(E)” gives the leading term of “ E ” with respect to the module term-ordering of “ E ”. For the leading monomial, which includes the coefficient, use “LM” (I-12.15 pg.166).

— example —

```
/**/ R3 := NewFreeModule(R,3);
/**/ LT(ModuleElem(R3, [0, x, y^2]));
[0, 0, y^2]

Use R ::= QQ[x,y], PosTo;
V := Vector(0, x, y^2);
LT(V); -- the leading term of V w.r.t. PosTo
Vector(0, x, 0)
-----
```

If “ E ” is an ideal or module, “LT(E)” returns the ideal or module generated by the leading terms of all elements of E , sometimes called the “*initial*” ideal or module.

— example —

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x-y, x-z^2);
/**/ LT(I);
ideal(x, z^2)
```

See Also: LC(I-12.3 pg.160), LF(I-12.8 pg.162), LM(I-12.15 pg.166), LPP(I-12.19 pg.167), Module Orderings(III-9.6 pg.361), Orderings(III-9.5 pg.360)

Chapter I-13

M

I-13.1 MakeCheck

syntax

```
MakeCheck()
```

Description

***** NOT YET IMPLEMENTED *****

This function run a series of tests on the whole system. To get a reliable result you should run this on a “*just opened*” CoCoA because some printouts may mysteriously add some empty spaces which will result in an, apparent, failure of some tests.

example

```
MakeCheck();
```

I-13.2 MakeMatByRows, MakeMatByCols

syntax

```
MakeMatByRows(R: INT, C: INT, L: LIST): MAT  
MakeMatByCols(R: INT, C: INT, L: LIST): MAT
```

Description

These functions create an “RxC” matrix from the list “L”. The first argument “R” is the number of rows, and the second “C” is the number of columns. It is an error if the length of “L” is not “RxC”.

The ring of the matrix is determined from the ring containing the elements of “L”. If “L” contains only integers/rationals then the matrix is over “QQ”.

example

```
/**/ MakeMatByRows(2, 10, 1..20);  
matrix(QQ,  
  [[1, 2, 3, 4, 5, 6, 7, 8, 9, 10],  
   [11, 12, 13, 14, 15, 16, 17, 18, 19, 20]])  
  
/**/ MakeMatByCols(2, 10, 1..20);  
matrix(QQ,  
  [[1, 3, 5, 7, 9, 11, 13, 15, 17, 19],  
   [2, 4, 6, 8, 10, 12, 14, 16, 18, 20]])
```

See Also: BlockMat([I-2.8](#) pg.37), matrix([I-13.10](#) pg.173), NewMat([I-14.6](#) pg.187), ColMat([I-3.26](#) pg.51), RowMat([I-18.52](#) pg.250), DiagMat([I-4.15](#) pg.71), ConcatHor([I-3.37](#) pg.56), ConcatVer([I-3.40](#) pg.57)

I-13.3 MakeSet

syntax

```
MakeSet(L: LIST): LIST
```

Description

This function returns a list obtained by removing duplicates from “L”.

example

```
/**/ MakeSet([2,2,2,1,2,1,1,3,3]);
[2, 1, 3]
```

NOTE: to test two sets for equality use the function “EqSet” ([I-5.7](#) pg.78) instead of a normal equality test (because the latter yields false if the elements are in a different order).

See Also: EqSet([I-5.7](#) pg.78), intersection([I-9.30](#) pg.132), IntersectList([I-9.31](#) pg.132), remove([I-18.30](#) pg.240)

I-13.4 MakeTerm

syntax

```
MakeTerm(R: RING, L: LIST of INT): RINGELEM
```

Description

This function returns the power-product in “R” whose list of exponents is “L”. It is the inverse of “exponents” ([I-5.14](#) pg.81). The length of “L” must be equal to the number of indeterminates in “R”.

This function was called “LogToTerm” up to version CoCoA-5.1.2.

example

```
/**/ use R ::= QQ[x,y,z];
/**/ MakeTerm(R, [2,3,5]);
x^2*y^3*z^5

/**/ exponents(It);
[2, 3, 5]
```

See Also: exponents([I-5.14](#) pg.81)

I-13.5 MakeTermOrd

syntax

```
MakeTermOrd(M: MAT): MAT
MakeTermOrd(M: MAT, GrDim: INT): MAT
```

Description

This function returns a (square) matrix of integers defining a term ordering; the output matrix is built from “M”. The first “GrDim” rows are left unchanged; if “GrDim” is not given then it is taken to be 0.

The input matrix “M” must have rational entries; the first “GrDim” rows must have non-negative integer entries, and they must be linearly independent.

If “M” is not square then rows are appended or eliminated as necessary.

NOTE: this function was called “CompleteToOrd” up to version CoCoA-5.1.2.

example

```

/**/ M := matrix([[1,2,3,4]]);
/**/ MakeTermOrd(M);
[[1, 2, 3, 4],
 [0, 0, 0, -1],
 [0, 0, -1, 0],
 [0, -1, 0, 0]]

/**/ MakeTermOrd(M, LexMat(4));
matrix(QQ,
[[1, 2, 3, 4],
 [1, 0, 0, 0],
 [0, 1, 0, 0],
 [0, 0, 1, 0]])

/**/ MakeTermOrd(matrix([[1,2,0,0]]));
[[1, 2, 0, 0],
 [0, 0, 1, 1],
 [0, 0, 0, -1],
 [0, -1, 0, 0]]

/**/ MakeTermOrd(matrix([[1,2,0,0],[0,0,3,0]]));
matrix(QQ,
[[1, 2, 0, 0],
 [0, 0, 3, 0],
 [0, 0, 0, 1],
 [0, -1, 0, 0]])

/**/ MakeTermOrd(matrix([[1,2,0,0],[0,0,3,0]]), RevLexMat(4));
matrix(QQ,
[[1, 2, 0, 0],
 [0, 0, 3, 0],
 [0, 0, 0, -1],
 [0, -1, 0, 0]])
--> not a term-ordering

```

See Also: LexMat(I-12.6 pg.161), RevLexMat(I-18.38 pg.244), StdDegLexMat(I-19.31 pg.266), StdDegRevLexMat(I-19.32 pg.267)

I-13.6 MantissaAndExponent10

syntax

```
MantissaAndExponent10(X: INT|RAT|RINGELEM, Prec: INT): RECORD
```

Description

This function converts a rational number into a “RECORD” with components named “exponent”, “mantissa” and “NumDigits”.

If “X=0”, all fields of the record are set to zero.

For non-zero “X” the fields give the best representation of the form $M * 10^E$ where “M” has “Prec” decimal digits. The value of “NumDigits” is simply “Prec”. The value of “exponent” is “FloorLog10(X)”, plus 1 if the mantissa “overflows”. The value of “mantissa” is an integer “M” satisfying $10^{(Prec-1)} \leq |M| < 10^{Prec} - 1$

— example —

```

/**/ MantissaAndExponent10(1/2,3);      -- 1/2 = 5.00*10^(-1)
record[NumDigits := 3, exponent := -1, mantissa := 500]

/**/ MantissaAndExponent10(0.99999, 4);  -- 0.99999 rounds up to give 1.000
record[NumDigits := 4, exponent := 0, mantissa := 1000]

```

See Also: DecimalStr(I-4.3 pg.63), FloatApprox(I-6.10 pg.89), FloatStr(I-6.11 pg.89), FloorLog2, FloorLog10, FloorLogBase(I-6.13 pg.90), MantissaAndExponent2(I-13.7 pg.172), ScientificStr(I-19.3 pg.252)

I-13.7 MantissaAndExponent2

— syntax —

```

MantissaAndExponent2(X: INT|RAT|RINGELEM, Prec: INT): RECORD

```

Description

This function converts a rational number into a “RECORD” with components named “exponent”, “mantissa” and “NumDigits”.

If “X=0”, all fields of the record are set to zero.

For non-zero “X” the fields give the best representation of the form $M * 2^E$ where “M” has “Prec” bits. The value of “NumDigits” is simply “Prec”. The value of “exponent” is “FloorLog2(X,2)”, plus 1 if the mantissa “overflows”. The value of “mantissa” is an integer “M” satisfying $2^{(Prec-1)} \leq |M| < 2^{Prec} - 1$

— example —

```

/**/ MantissaAndExponent2(1/2,8);      -- 1/2 = 128*2^(-8)
record[NumDigits := 8, exponent := -1, mantissa := 128]

/**/ MantissaAndExponent2(65535, 10);  -- rounds up
record[NumDigits := 10, exponent := 16, mantissa := 512]

```

See Also: FloatApprox(I-6.10 pg.89), FloorLog2, FloorLog10, FloorLogBase(I-6.13 pg.90), MantissaAndExponent10(I-13.6 pg.171)

I-13.8 Manual

— syntax —

```

? key
?? key

```

Description

These operators are used to search the online help system for information matching a keyword (introduced in CoCoA 4.2).

The commands have the form “?key” and “??key” where “key” is a literal string without quotes. They are case insensitive and ignore blank space before or after “key”. Also, the semicolon usually required at the end of a line of CoCoA input is optional.

The search system is fairly simple. The searching algorithm looks through the title and keywords of each manual page. A page matches if “key” appears as a (case-insensitive) substring of the title/keywords.

The “??” form prints the list of all matches. The “?” form prints the page matching exactly if there is one, otherwise the list of all matches.

example

```

/**/ ?approx
===== [ ApproxSolve ] =====
--> ApproxSolve(L: LIST of RINGELEM): LIST of LIST of RAT

This function returns the list of real solutions (points) of a
  --( Further output )--

===== < No entry for "approx" > =====
All 8 matches for "approx":
? ApproxSolve
? CFApprox
  --( Further output )--

```

I-13.9 MapDown [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] See “AsINT” (I-1.16 pg.32), “AsRAT” (I-1.17 pg.32).

I-13.10 matrix

syntax

```

matrix(L: LIST): MAT
matrix(R: RING, L: LIST): MAT
matrix(R: RING, M: MAT): MAT

```

Description

This function returns a matrix in the ring “R”.

When the input is “L”, a “*rectangular*” LIST of LIST of RINGELEM all in “R” (or INT, or RAT). When the ring is not specified it “guesses” the right ring; if all elements are INT or RAT the resulting matrix is in QQ.

The third form is equivalent to “`apply(CanonicalHom(RingOf(M),R), M)`” (See “`apply`” (I-1.13 pg.30), “`CanonicalHom`” (I-3.2 pg.41)).

example

```

/**/ Use R := QQ[x,y];
/**/ L := [[1,2],[3,4]];
/**/ mat(L);
matrix(QQ,
  [[1, 2],
   [3, 4]])
/**/ mat(R,L);
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[1, 2],
   [3, 4]])
/**/ mat(ZZ,L);

```

```

matrix(ZZ,
  [[1, 2],
   [3, 4]])

/**/ RingOf(mat(R, [[1,2],[3,4]]));
RingWithID(3, "QQ[x,y]")

/**/ M := IdentityMat(ZZ,2);  matrix(QQ, M);
matrix(QQ,
  [[1, 0],
   [0, 1]])

```

See Also: [NewMat\(I-14.6 pg.187\)](#), [ColMat\(I-3.26 pg.51\)](#), [RowMat\(I-18.52 pg.250\)](#), [DiagMat\(I-4.15 pg.71\)](#), [MakeMatByRows](#), [MakeMatByCols\(I-13.2 pg.169\)](#), [ConcatHor\(I-3.37 pg.56\)](#), [ConcatVer\(I-3.40 pg.57\)](#), [BlockMat\(I-2.8 pg.37\)](#)

I-13.11 *max*

syntax

```

max(E_1: OBJECT, ..., E_n: OBJECT): OBJECT
max(L: LIST): OBJECT

```

Description

In the first form, this function returns a maximum of E_1, \dots, E_n . In the second form, it returns a maximum of the objects in the list “L”.

example

```

/**/ max([1,2,3]);
3
/**/ max(1,2,3);
3

/**/ use R := QQ[x,y,z];
/**/ max(x^3*z, x^2*y^2); -- x^2y^2 > x^3z in the default ordering, DegRevLex
x^2*y^2
/**/ min(x^3*z, x^2*y^2);
x^3*z

/**/ use R := QQ[x,y,z], DegLex;
/**/ max(x^3*z, x^2*y^2); -- x^3z < x^2y^2 in DegLex
x^3*z

```

See Also: [min\(I-13.14 pg.175\)](#), [Relational Operators\(II-3.3 pg.308\)](#)

I-13.12 *MaxBy*

syntax

```

MaxBy(L: LIST, LessThanFunc: FUNCTION)

```

Description

This function return a maximum of the elements of the list in L with respect to the comparisons made by LessThanFunc.

The comparison function LessThanFunc takes two arguments and returns true if the first argument is less than the second, otherwise it returns false.

NOTE: to call MaxBy(L, LessThanFunc) inside a function you will need to make the name LessThanFunc accessible using TopLevel LessThanFunc;

NOTE: if both LessThanFunc(A, B) and LessThanFunc(B, A) return true, then A and B are viewed as being equal.

example

```
/**/ Define ByLength(S, T)  -- define the sorting function
/**/   Return len(S) < len(T);
/**/ EndDefine;

/**/ L := ["bird", "mouse", "cat", "elephant"];
/**/ MaxBy(L, ByLength);
elephant

/**/ Define ByLPP(S, T)  return LPP(S) < LPP(T); EndDefine;
/**/ L := [x^5 -1, x^2*y -y -3];
/**/ MaxBy(L, ByLPP);
x^5 -1
```

See Also: MinBy([I-13.15](#) pg.176), func([I-6.23](#) pg.95), SortedBy([I-19.21](#) pg.261), TopLevel([I-20.10](#) pg.280)

I-13.13 MayerVietorisTreeN1

syntax

```
MayerVietorisTreeN1(I: IDEAL): INT
```

Description

Implemented in CoCoALib by Eduardo Saenz-de-Cabezón.

This function returns the list of multidegrees “M” such that the N-1st Betti number of a monomial ideal “I” at multidegree “M” is not zero. It is computed via a version of its Mayer-Vietoris tree.

The length of this list is the number of irreducible components of I, the number of maximal standard monomials, and the number of generators of its Alexander Dual.

example

```
/**/ Use QQ[x,y,z];
/**/ I := ideal(x, y, z)^2;
/**/ MayerVietorisTreeN1(I);
[x^2*y*z, x*y^2*z, x*y*z^2]
```

See Also: Frobbby([II-8.4](#) pg.325)

I-13.14 min

syntax

```
min(E_1: OBJECT,...,E_n: OBJECT): OBJECT
min(L: LIST): OBJECT
```

Description

In the first form, this function returns a minimum of E_1, \dots, E_n . In the second form, it returns a minimum of the objects in the list “L”.

See more examples in “max” ([I-13.11 pg.174](#)).

example

```
/**/ min([1,2,3]);
1
/**/ min(1,2,3);
1
```

See Also: max([I-13.11 pg.174](#)), Relational Operators([II-3.3 pg.308](#))

I-13.15 MinBy

syntax

```
MaxBy(L: LIST, LessThanFunc: FUNCTION)
```

Description

This function return a minimum of the elements of the list in L with respect to the comparisons made by LessThanFunc. (see “MaxBy” ([I-13.12 pg.174](#)) for details)

example

```
/**/ Define ByLength(S, T)    -- define the sorting function
/**/   Return len(S) < len(T);
/**/ EndDefine;

/**/ L := ["bird", "mouse", "cat", "elephant"];
/**/ MaxBy(L, ByLength);
cat
```

See Also: MaxBy([I-13.12 pg.174](#)), func([I-6.23 pg.95](#)), SortedBy([I-19.21 pg.261](#)), TopLevel([I-20.10 pg.280](#))

I-13.16 MinGens

syntax

```
MinGens(M: IDEAL|MODULE): LIST
```

Description

If “M” is a homogeneous ideal or module, this function returns a list of minimal generators for “M” (not necessarily a subset of “gens(M)”).

For non-homogeneous input use “MinSubsetOfGens” ([I-13.24 pg.179](#)).

NOTE: the coefficient ring must be a field.

example

```
/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x-y, (x-y)^4, z+y, (z+y)^2);
/**/ MinGens(I);
[y + z, x + z]

/**/ R3 := NewFreeModule(R, 3);
/**/ MGens := matrix(R, [[x,y,z], [x^2,0,z^2], [2*x^2,x*y,z^2+x*z]]);
/**/ M := SubmoduleRows(R3, MGens);
/**/ gens(M);
[[x, y, z], [x^2, 0, z^2], [2*x^2, x*y, x*z + z^2]]
```



```
/**/ MinGens(M);
[[x, y, z], [0, x*y, x*z -z^2]]
```

See Also: `minimalize`([I-13.18](#) pg.177), `minimalized`([I-13.19](#) pg.177), `MinSubsetOfGens`([I-13.24](#) pg.179)

I-13.17 *MinGensGeneral* [OBSOLESCENT]

syntax

[OBSOLESCENT]

Description

Just renamed “`MinSubsetOfGens`” ([I-13.24](#) pg.179) (more expressive).

See Also: `MinSubsetOfGens`([I-13.24](#) pg.179)

I-13.18 *minimalize*

syntax

```
minimalize(ref X: IDEAL)
minimalize(ref X: MODULE)
```

Description

Similar to “`minimalized`” ([I-13.19](#) pg.177), but modifies the argument “`X`” and returns `NULL`.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x^2-y^2, z^4-y^4, x^2-z^2);
/**/ I;
ideal(x^2 -y^2, -y^4 +z^4, x^2 -z^2)
/**/ minimalize(ref I); -- returns NULL and modifies I
/**/ I;
ideal(x^2 -z^2, y^2 -z^2)
```

See Also: `MinGens`([I-13.16](#) pg.176), `MinSubsetOfGens`([I-13.24](#) pg.179), `minimalized`([I-13.19](#) pg.177)

I-13.19 *minimalized*

syntax

```
minimalized(E: IDEAL): IDEAL
minimalized(E: MODULE): MODULE
```

Description

It works only in the homogeneous case: for the inhomogeneous case see “`MinSubsetOfGens`” ([I-13.24](#) pg.179).

This function returns the ideal (or submodule) generated by a set of minimal generators of “`E`” (with minimal cardinality). The minimal set of generators is not necessarily a subset of the given generators.

The coefficient ring is assumed to be a field.

The similar function “`minimalize`” ([I-13.18](#) pg.177) performs the same operation, but modifies the argument (“`ref`” ([I-18.24](#) pg.237)) and returns `NULL`.

example

```

/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x^2-y^2, z^4-y^4, x^2-z^2);
/**/ I;
ideal(x^2 -y^2, -y^4 +z^4, x^2 -z^2)
/**/ minimalized(I);
ideal(x^2 -z^2, y^2 -z^2)
/**/ I; -- not modified
ideal(x^2 -y^2, -y^4 +z^4, x^2 -z^2)

```

See Also: [MinGens\(I-13.16 pg.176\)](#), [MinSubsetOfGens\(I-13.24 pg.179\)](#), [minimalize\(I-13.18 pg.177\)](#)

I-13.20 MinimalPresentation

syntax

```
MinimalPresentation(Q:TAGGED):TAGGED
```

where Q is a quotient module of the type R^s/M

Description

***** NOT YET IMPLEMENTED *****

Given a quotient module of the type R^s/M , or a zero module, this function computes an isomorphic quotient, R^t/N , minimally presented [using the algortihm in Kreuzer-Robbiano II].

example

```

Use R := QQ[x,y,z];
MinimalPresentation(R^3/Module([[x,1,1], [x,2,2]]));
R^2/Module([[x, 0]])
-----

```

I-13.21 minors

syntax

```
minors(M: MAT, N: INT): LIST
```

Description

This function returns the list of all determinants of $N \times N$ submatrices of M.

example

```

/**/ M := mat([[1,2,3], [-1,2,4]]);
/**/ minors(M, 2);
[4, 7, 2]

```

See Also: [det\(I-4.13 pg.70\)](#)

I-13.22 MinPoly

syntax

```
MinPoly(M: MAT, X: RINGELEM): RINGELEM
```

Description

Thanks to Maria-Laura Torrente.

This function returns the minimal polynomial of the matrix “M” in the indeterminate “X” (with “M” a square matrix whose entries lie in the coefficient ring of “X”, or in the same ring of “X” but not dependent on “X”). See also “CharPoly” (I-3.10 pg.44).

example

```
/**/ Use R ::= QQ[x];
/**/ MinPoly(matrix([[0,0,1],[0,0,0],[0,0,0]]), x);
x^2
/**/ CharPoly(matrix([[0,0,1],[0,0,0],[0,0,0]]), x);
x^3
```

See Also: CharPoly(I-3.10 pg.44)

I-13.23 MinPowerInIdeal

syntax

```
MinPowerInIdeal(F: RINGELEM, I: IDEAL): INT
```

Description

This function returns the minimum power of F, the first argument, in the ideal I, the second argument. If F is not in the radical I then -1 is returned.

example

```
/**/ Use QQ[x,y,z];
/**/ I := ideal(x^6*y^4, z);
/**/ IsInRadical(x*y, I);
true

/**/ MinPowerInIdeal(x*y, I);
6
```

See Also: IsInRadical(I-9.52 pg.141), radical(I-18.1 pg.227)

I-13.24 MinSubsetOfGens

syntax

```
MinSubsetOfGens(M: IDEAL|MODULE): LIST
```

Description

This function returns a subset “S” of “gens(M)” which is minimal in the sense that no proper subset of “S” generates “M”.

NOTE: in general there might be other subsets with smaller cardinality.

If “M” is a homogeneous ideal or module, the function “MinGens” (I-13.16 pg.176) is much faster (but may return a generating set which is not a subset of “gens(M)”).

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x-1, (x-y)^4, z+y, (z+y)^2);
```

```
/**/ MinSubsetOfGens(I);
[x -1, x^4 -4*x^3*y +6*x^2*y^2 -4*x*y^3 +y^4, y +z]
```

See Also: [MinGens\(I-13.16 pg.176\)](#), [minimalize\(I-13.18 pg.177\)](#), [minimalized\(I-13.19 pg.177\)](#)

I-13.25 mod

syntax

```
mod(N: INT, D: INT): INT
```

Description

We define the quotient “Q” and remainder “R” to be integers which satisfy $N = Q * D + R$ with $0 \leq R < |D|$. Then “div(N, D)” returns “Q” while “mod(N, D)” returns “R”.

NOTE: To perform the division algorithm on a polynomial, use “NR” ([I-14.30 pg.197](#)) (normal remainder) to find the remainder, or “DivAlg” ([I-4.21 pg.73](#)) to get both the quotients and the remainder.

example

```
/**/ div(10,3);
3
/**/ mod(10,3);
1
```

See Also: [div\(I-4.20 pg.73\)](#), [DivAlg\(I-4.21 pg.73\)](#), [GenRepr\(I-7.7 pg.100\)](#), [NF\(I-14.15 pg.191\)](#), [NR\(I-14.30 pg.197\)](#)

I-13.26 Mod2Rat [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] See “RatReconstructWithBounds” ([I-18.16 pg.234](#)).

I-13.27 ModuleElem

syntax

```
ModuleElem(M: MODULE, L: LIST): MODULEELEM
```

Description

This function returns the MODULEELEM (called “Vector” in CoCoA-4) in the module “M” whose components are the components of the list L.

example

```
/**/ Use R ::= QQ[x];
/**/ R3 := NewFreeModule(R,3);
/**/ V := ModuleElem(R3, [1, x, x^2]); V;
[1, x, x^2]
/**/ type(V);
MODULEELEM
```

```
/**/ zero(R3);
[0, 0, 0]
```

See Also: SubmoduleCols, SubmoduleRows([I-19.38](#) pg.269)

I-13.28 ModuleOf

syntax

```
ModuleOf(M: MODULE): MODULE
```

Description

This function returns the module on which the object E is defined.

NOTE: A module contains many information and two separate rings, even when defined with the same commands, are not "equal". When a module is printed only a few informations are shown, so different modules might look the same.

example

```
/**/ Use R ::= QQ[x];
/**/ R3 := NewFreeModule(R,3);
/**/ V := ModuleElem(R3, [1, x, x^2]); V;
[1, x, x^2]
/**/ type(V);
MODULEELEM
/**/ ModuleOf(V) = R3;
true
/**/ ModuleOf(V);
FreeModule(RingDistrMPolyClean(QQ, 1), 3)
```

See Also: submodule([I-19.37](#) pg.269)

I-13.29 monic

syntax

```
monic(F: RINGELEM): RINGELEM
```

Description

This function returns "F" divided by its leading coefficient (see "LC" ([I-12.3](#) pg.160)) or, if "F" is zero, it returns just zero.

example

```
/**/ Use R ::= QQ[x,y];
/**/ F := 4*x^5-y^2;
/**/ monic(F);
x^5 +(-1/4)*y^2

/**/ Use R ::= ZZ[x,y];
/**/ F := 4*x^5-y^2;
-- /**/ monic(F); --> !!! ERROR !!! can't invert coefficients over ZZ
ERROR: Inexact division
monic(L); -- can't invert coefficient ...
~~~~~
```

```

/**/ Use P ::= ZZ/(5)[x,y];
/**/ F := 2*x^2+4*y^3;
/**/ monic(F);
y^3 -2*x^2

```

See Also: [LC\(I-12.3 pg.160\)](#)

I-13.30 monomials

syntax

```
monomials(F: RINGELEM|MODULEELEM): LIST
```

Description

This function returns the list of monomials of F . The function “support” ([I-19.42 pg.271](#)) returns the list of terms (monomials without coefficients).

example

```

/**/ Use R ::= QQ[x,y];
/**/ F := 3*x^2*y +5*y^3 -x*y^5;
/**/ monomials(F);
[-x*y^5, 3*x^2*y, 5*y^3]

/**/ support(F);
[x*y^5, x^2*y, y^3]

Monomials(Vector(3*x^2*y+y,5*x*y+4)); ---**WORK IN PROGRESS**
[Vector(3x^2y, 0), Vector(0, 5xy), Vector(y, 0), Vector(0, 4)]

```

See Also: [coefficients\(I-3.21 pg.48\)](#), [support\(I-19.42 pg.271\)](#)

I-13.31 MonsInIdeal

syntax

```
MonsInIdeal(I: IDEAL): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

This function returns the ideal generated by all monomials in the original ideal I .

example

```

Use R ::= QQ[x,y,z];
I := ideal(xy^3+z^2, y^5-z^3, xz-y^2-x^3, x^4-xz^2+y^3);
MonsInIdeal(I);
ideal(z^3, yz^2, x^2z^2, x^5z, x^4yz, x^5y, x^2y^2z, x^7, x^4y^2,
      xy^3z, y^4z, xy^4, x^3y^3, y^5)
-----

```

I-13.32 multiplicity

syntax

```
multiplicity(R: RING): INT
```

Description

This function computes the multiplicity (or degree) of M , i.e., the leading coefficient of the Hilbert polynomial multiplied by the factorial of the degree of the Hilbert polynomial. M can be a module or a quotient.

— *example* —

```
/**/ Use R := QQ[t,x,y,z];  
/**/ multiplicity(R/ideal(x,y,z)^5);  
35
```

See Also: [HilbertFn\(I-8.5 pg.109\)](#), [HilbertSeries\(I-8.7 pg.110\)](#), [HVector\(I-8.13 pg.113\)](#)

Chapter I-14

N

I-14.1 NewFractionField

syntax

```
NewFractionField(R: RING): RING
```

Description

NOTE: calling twice “NewFractionField” will produce two different rings, even with identical input: equality test is performed on the pointers. See “RingID” (I-18.41 pg.245).

example

```
/**/ K := NewFractionField(NewPolyRing(QQ, "a,b"));
/**/ Use K;
/**/ M := mat([[1,2,3,a],[5,6,7,a*b]]);
/**/ LinKerBasis(M);
[[-1, 2, -1, 0], [(a*b -3*a)/2, (-a*b +5*a)/4, 0, -1]]
```

See Also: NewQuotientRing(I-14.9 pg.188), RingID(I-18.41 pg.245), den(I-4.7 pg.67), num(I-14.31 pg.198)

I-14.2 NewFreeModule

syntax

```
NewFreeModule(R: RING, N: INT): MODULE
NewFreeModule(R: RING, Shifts: MAT): MODULE
```

Description

This function returns a free module which can be used as any programming variable.

NOTE: as for rings, calling twice “NewFreeModule” will produce two different modules, even with identical input: equality test is performed on the pointers.

This function does accept shifts from version CoCoA-5.0.4.

example

```
/**/ F := NewFreeModule(R, 3);
/**/ zero(F);
[0, 0, 0]
/**/ type(zero(F)); -- is NOT a LIST
MODULEELEM
/**/ gens(F);
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
```

```

/**/ F := NewFreeModule(R, matrix([[1],[2],[3]])); -- shifts
/**/ [wdeg(e) | e in gens(F)];
[[1], [2], [3]]

```

See Also: [BaseRing\(I-2.1 pg.33\)](#), [RingOf\(I-18.42 pg.246\)](#)

I-14.3 NewId [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE]

I-14.4 NewLine [OBSOLESCENT]

syntax

NewLine(): STRING

Description

This function is “*OBSOLESCENT*” and exists only for backward compatibility with old CoCoA code. It returns a string containing just a newline; in CoCoA-5 it is simpler to write “`\n`”.

example

```

/**/ str1 := "Line 1" + NewLine() + "Line 2"; --> old CoCoA-4 way
/**/ str2 := "Line 1\nLine 2";               --> more compact in CoCoA-5
/**/ str1 = str2;
True
/**/ Print str2;
Line 1
Line2

```

See Also: [String Literals\(III-4.1 pg.341\)](#), [println\(I-16.29 pg.219\)](#), [ascii\(I-1.15 pg.31\)](#)

I-14.5 NewList

syntax

NewList(N: INT): LIST
 NewList(N: INT, E: OBJECT): LIST

Description

The first form returns a list of length “N” filled with 0 (“INT”). The second form returns a list of length “N”, filled with copies of “E”.

example

```

/**/ NewList(4,"a");
["a", "a", "a", "a"]

```

```
/**/ NewList(4);
[0, 0, 0, 0]
```

See Also: List Constructors([III-5.2](#) pg.346)

I-14.6 NewMat

syntax

```
NewMat(R: RING, M: INT, N: INT): MAT
```

Description

This function is kept for CoCoA-4 nostalgia: better use “ZeroMat” ([I-25.2](#) pg.297).

example

```
/**/ Use S ::= QQ[x,y,z];
/**/ NewMat(S,2,3);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[0, 0, 0],
   [0, 0, 0]])
/**/ ZeroMat(S,2,3);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[0, 0, 0],
   [0, 0, 0]])
```

See Also: matrix([I-13.10](#) pg.173), NewMatFilled([I-14.7](#) pg.187)

I-14.7 NewMatFilled

syntax

```
NewMatFilled(M: INT, N: INT, Val: INT|RAT|RINGELEM): MAT
```

Description

This function returns an “MxN” matrix, filled with “Val”. If “Val” is an integer or rational the ring of the matrix is defined in “RingQQ” ([I-18.43](#) pg.246).

example

```
/**/ Use S ::= QQ[x,y,z];
/**/ NewMatFilled(1,3,x);
matrix( /*RingDistrMPolyClean(QQ, 3)*/
  [[x, x, x]])

/**/ NewMatFilled(1,3, 0);
matrix(QQ,
  [[0, 0, 0]])
/**/ ZeroMat(QQ, 1, 3); --> same as NewMatFilled(1,3, 0)
matrix(QQ,
  [[0, 0, 0]])
```

See Also: NewMat([I-14.6](#) pg.187), matrix([I-13.10](#) pg.173)

I-14.8 NewPolyRing

syntax

```
NewPolyRing(CoeffRing: RING, IndetNames: STRING/LIST): RING
NewPolyRing(CoeffRing: RING, IndetNames: STRING/LIST, OrdMat: MAT, GradingDim: INT): RING
```

Description

This function returns a polynomial ring which can be used as any programming variable (assigned with “:=”).

The “:=” syntax starts the input method for a new polynomial ring, with the special interpretation of brackets and symbols (i.e. $R ::= \mathbb{Q}\mathbb{Q}[x]$ is not read as $X := LL[i]$). The pre-defined orderings for the “:=” syntax are “Lex” (no grading), “DegLex”, “DegRevLex” (standard grading). For more orderings use the “NewPolyRing” function call (see also “ElimMat” (I-5.5 pg.77)).

NOTE: calling “NewPolyRing” twice with the same arguments gives two “different rings”, therefore incompatible. See “RingID” (I-18.41 pg.245).

NOTE: the syntax with all indet names in one string is new in CoCoA-5.1.2.

example

```
/**/ R ::= QQ[x,y,alpha]; -- is equivalent to
/**/ R := NewPolyRing(QQ, "x,y,alpha"); -- in "define/enddefine" use "RingQQ()"

/**/ R ::= QQ[x,y], DegRevLex; -- is equivalent to
/**/ R := NewPolyRing(QQ, "x,y", StdDegRevLexMat(2), 1);

/**/ OrdM := matrix([[2,3,1],[0,0,-1],[0,-1,0]]);
/**/ P := NewPolyRing(QQ, "x[1],x[2],x[9]", OrdM, 1); -- 3 indeterminates
/**/ [wdeg(X) | X in indets(P)];
[[2], [3], [1]]

/**/ P2 := NewPolyRing(RingZZ(), IndetSymbols(P)); -- same indet names as P
/**/ Indets(P2);
[x[1], x[2], x[9]]

/**/ P3 := NewPolyRing(P2, SymbolRange("alpha", -2,2));
/**/ indets(P3);
[alpha[-2], alpha[-1], alpha[0], alpha[1], alpha[2]]
```

See Also: ElimMat(I-5.5 pg.77), RingID(I-18.41 pg.245), IndetSymbols(I-9.24 pg.129), SymbolRange(I-19.46 pg.273), GradingDim(I-7.19 pg.105)

I-14.9 NewQuotientRing

syntax

```
NewQuotientRing(R: RING, I: IDEAL): RING
R/I
```

Description

NOTE: calling twice “NewQuotientRing” will produce two different rings, even with identical input: equality test is performed on the pointers. See “RingID” (I-18.41 pg.245).

example

```
/**/ Use Qi ::= QQ[i];
/**/ CC := Qi/ideal(i^2+1); -- sort of ;-)
```

```

/**/ Use CC[x];
/**/ (x+i)^2;
(2*i*x +x^2 -1)

/**/ R ::= QQ[x,y,z];
/**/ S := NewQuotientRing(R, ideal(indet(R,1)-3));
/**/ Use S;
/**/ (x+y)^2;
(y^2 +6*y +9)

```

See Also: RingID([I-18.41](#) pg.245), QuotientBasis([I-17.3](#) pg.224), NewFractionField([I-14.1](#) pg.185)

I-14.10 NewRingFp

— syntax —

```
NewRingFp(P: INT): RING
```

Description

Create a new small prime finite field with characteristic “P”.

NOTE: in ring definitions you can use the convenient notation “ZZ/(p)”

NOTE: calling twice “NewRingFp” will produce two different rings, even with identical input: equality test is performed on the pointers. See “RingID” ([I-18.41](#) pg.245).

— example —

```

/**/ p := NextPrime(1000);
/**/ Fp := NewRingFp(p);
/**/ Use Fp[x];
/**/ product([x-i | i in 1..p]);
x^1009 - x
/**/ Use ZZ/(p)[x]; --> convenient shorthand in ring defn
/**/ product([x-i | i in 1..p]);
x^1009 - x

```

See Also: RingID([I-18.41](#) pg.245), NewQuotientRing([I-14.9](#) pg.188)

I-14.11 NewRingTwinFloat

— syntax —

```
NewRingTwinFloat(Prec: INT): RING
```

Description

Create a new twin-float ring with bit precision “Prec”.

NOTE: calling twice “NewRingTwinFloat” will produce two different rings, even with identical input: equality test is performed on the pointers. See “RingID” ([I-18.41](#) pg.245).

For more information see the article: John Abbott, “Twin-float arithmetic”, Journal of Symbolic Computation, Volume 47 (2012), 536–551.

— example —

```

/**/ RR32 := NewRingTwinFloat(32);
/**/ Use RR32[x];
/**/ (3*x-1)/3;

```


[illegible]

I-14.15 NF

```
NF(F: RINGELEM, I: IDEAL): RINGELEM
NF(V: MODULEELEM, M: MODULE): MODULEELEM
```

```

/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(z);
/**/ NF(x^2+x*y+x*z+y^2+y*z+z^2, I);
x^2 + x*y + y^2

/**/ I := ideal(z-1);
/**/ NF(x^2+x*y+x*z+y^2+y*z+z^2, I);
x^2 + x*y + y^2 + x + y + 1

```

I-14.16 NFsAreZero [OBSOLETE]

[OBSOLETE]

See Also: IsContained(I-9.38 pg.135), IsIn(I-9.49 pg.139), NF(I-14.15 pg.191)

I-14.17 NmzComputation

syntax

```
NmzComputation(Cone: RECORD): RECORD
NmzComputation(Cone: RECORD, ToCompute: LIST): RECORD
```

Description

“NmzComputation” provides direct access to libnormaliz. It faithfully reflects the internal structure of the libnormaliz design. Its first argument should be a record representing the cone. For the possible input options see the Normaliz documentation. With the second (optional) argument one can specify what should be computed. If it is omitted, everything that can be computed by libnormaliz will be computed.

example

```
/**/ Cone := record[ integral_closure := Mat([[1,2],[2,1]]),
/**/           grading := Mat([[2,1]]);
/**/ NC2 := NmzComputation(Cone, ["HilbertBasis", "SupportHyperplanes", "HilbertSeries"]);
/**/ indent(NC2);

record[
  Congruences := [],
  Deg1Elements := [],
  EmbeddingDim := 2,
  Equations := [],
  ExtremeRays := [[1, 2], [2, 1]],
  Generators := [[1, 2], [2, 1]],
  Grading := [2, 1],
  HilbertBasis := [[1, 1], [1, 2], [2, 1]],
  HilbertSeries := record[DenFactors := record[RemainingFactor := 1, factors := [-t +1, -t^20 +1], mul
  IsDeg1HilbertBasis := false,
  IsInhomogeneous := false,
  IsIntegrallyClosed := false,
  IsPointed := true,
  Multiplicity := 3/20,
  Rank := 2,
  SupportHyperplanes := [[-1, 2], [2, -1]]
]
```

See Also: NmzIntClosureToricRing(I-14.23 pg.195), NmzNormalToricRing(I-14.25 pg.195), NmzIntClosureMonIdeal(I-14.22 pg.194), NmzEhrhartRing(I-14.19 pg.193), NmzTorusInvariants(I-14.27 pg.196), NmzFiniteDiagInvariants(I-14.20 pg.193), NmzDiagInvariants(I-14.18 pg.192), NmzIntersectionValRings(I-14.24 pg.195), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.18 NmzDiagInvariants

syntax

```
NmzDiagInvariants(M: MAT, N: MAT, R: Ring): LIST of RINGELEM
```

Description

This function computes the ring of invariants of a diagonalizable group $D = TxG$ where T is a torus and G is a finite abelian group, both acting diagonally on the polynomial ring $K[X_1, \dots, X_n]$.

The group actions are specified by the input matrices “M” and “N”. The first matrix specifies the torus action, the second the action of the finite group. See NmzTorusInvariants or NmzFiniteDiagInvariants for more detail. The output is the monomial subalgebra of invariants in “R”.

example

```

/**/      Use R:=QQ[x,y,z,w];
/**/      T := matrix([[ -1,-1,2,0],[1,1,-2,-1]]);
/**/      U := matrix([[1,1,1,1,5],[1,0,2,0,7]]);
/**/      NmzDiagInvariants(T,U,R);
[x^4*y^6*z^5, x^15*y^5*z^10, x*y^19*z^10, x^26*y^4*z^15, x^37*y^3*z^20, x^48*y^2*z^25, x^59*y*z^30, x^

```

See Also: NmzComputation(I-14.17 pg.192), NmzTorusInvariants(I-14.27 pg.196), NmzFiniteDiagInvariants(I-14.20 pg.193), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.19 NmzEhrhartRing

syntax

```
NmzEhrhartRing(L: LIST of RINGELEM, s: RINGELEM): LIST of RINGELEM
```

Description

The exponent vectors of the given monomials are considered as vertices of a lattice polytope “P”. The Ehrhart ring of a (lattice) polytope “P” is the monoid algebra defined by the monoid of lattice points in the cone over the polytope “P”; see the book by Bruns and Gubeladze, Polytopes, Rings, and K-theory, Springer 2009, pp. 228, 229. The function returns the generators of the Ehrhart ring. It uses the indeterminate in the second argument as auxiliary indeterminate of the Ehrhart ring.

example

```

/**/      Use R:=QQ[x,y,z,t];
/**/      NmzEhrhartRing([x^2,y^2,z^3],t);
[x^2*t, z^3*t, x*y*t, y^2*t]

```

See Also: NmzComputation(I-14.17 pg.192), NmzHilbertBasis(I-14.21 pg.194), NmzNormalToricRing(I-14.25 pg.195), NmzIntClosureMonIdeal(I-14.22 pg.194), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.20 NmzFiniteDiagInvariants

syntax

```
NmzFiniteDiagInvariants(M: MAT, M: Ring): LIST of RINGELEM
```

Description

This function computes the ring of invariants of a finite abelian group G acting diagonally on the surrounding polynomial ring $K[X_1, \dots, X_n]$.

The group is the direct product of cyclic groups generated by finitely many elements g_1, \dots, g_w . The element g_i acts on the indeterminate X_j by $g_i(X_j) = l_i^{u_{ij}} X_j$ where l_i is a primitive root of unity of order equal to $\text{ord}(g_i)$.

The ring of invariants is generated by all monomials satisfying the system $u_{i1}a_1 + \dots + u_{in}a_n$ and congruent to 0 mod $\text{ord}(g_i)$, $i = 1, \dots, w$.

The input to the function is the w times $(n+1)$ matrix “U” with rows $u_{i1} \dots u_{in} \text{ord}(g_i)$, $i = 1, \dots, w$. The output is the monomial subalgebra of invariants $R^G = \text{fin}R : g_i f = f \text{ for all } i = 1, \dots, w$.

example

```

/**/      Use R:=QQ[x,y,z,w];
/**/      U := matrix([[1,1,1,1,3],[1,0,2,0,4]]);
/**/      NmzFiniteDiagInvariants(U,R);
[x^2*z, z^2*w, y*z^2, x^12, y^3, z^6, w^3, x^8*w, x^4*w^2, y*w^2, x^8*y, x^4*y*w, y^2*w, x^4*y^2]

```

See Also: [NmzComputation\(I-14.17 pg.192\)](#), [NmzTorusInvariants\(I-14.27 pg.196\)](#), [NmzDiagInvariants\(I-14.18 pg.192\)](#), [NmzSetVerboseDefault\(I-14.26 pg.196\)](#)

I-14.21 NmzHilbertBasis

syntax

```
NmzHilbertBasis(M: MAT): MAT
```

Description

Given a matrix “M”, this function returns a matrix whose rows represent the Hilbert-Gordan Basis for the monoid generated by the rows of “M”.

example

```
/**/      M := matrix([[0,1],[3,1]]);
/**/      NmzHilbertBasis(M);
--the Hilbert basis of the monoid generated by the vectors [0,1] and [3,1] is...
matrix(QQ,
  [[3, 1],
   [0, 1]])
-- ... ([3,1], [0,1])

-- CAREFUL!! Different result from...
/**/      HilbertBasisKer(M);
-- the Hilbert basis of M is the Hilbert basis of the monoid of
-- elements in the kernel of M, namely...
[]
-- ...no elements! (except the zero-element)
```

See Also: [HilbertBasisKer\(I-8.4 pg.108\)](#), [NmzComputation\(I-14.17 pg.192\)](#), [NmzNormalToricRing\(I-14.25 pg.195\)](#), [NmzIntClosureMonIdeal\(I-14.22 pg.194\)](#), [NmzSetVerboseDefault\(I-14.26 pg.196\)](#)

I-14.22 NmzIntClosureMonIdeal

syntax

```
NmzIntClosureMonRing(L: LIST of RINGELEM): LIST of RINGELEM
NmzIntClosureMonRing(L: LIST of RINGELEM, s: RINGELEM): LIST of RINGELEM,
```

Description

Given a list “L” of power-products in a ring “R”, the function returns the generators of the integral closure of the ideal generated by “L”.

As second argument you can specify an indeterminate of the ring which is not used in the power-products. In this case the result is the normalisation of its Rees algebra (or Rees ring); see Bruns and Herzog, Cohen-Macaulay Rings, Cambridge University Press 1998, p. 182.

example

```
/**/      Use R:=QQ[x,y,z,t];
/**/      NmzIntClosureMonIdeal([x^2,y^2,z^3]);
-- the integral closure of the ideal generated by x^2,y^2 and z^3 is...
[y^2, x^2, x*y, z^3, y*z^2, x*z^2]
-- ...the ideal generated by y^2, x^2, x*y, z^3, y*z^2 and x*z^2
/**/      NmzIntClosureMonIdeal([x^2,y^2,z^3],t);
```

```
-- and the complete rees algebra is generated by
[z, z^3*t, y, y*z^2*t, y^2*t, x, x*z^2*t, x*y*t, x^2*t]
```

See Also: NmzComputation(I-14.17 pg.192), NmzHilbertBasis(I-14.21 pg.194), NmzNormalToricRing(I-14.25 pg.195), NmzEhrhartRing(I-14.19 pg.193), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.23 NmzIntClosureToricRing

syntax

```
NmzIntClosureToricRing(L: LIST of RINGELEM): LIST of RINGELEM
```

Description

Given a list L of power-products in a ring R, the function returns the generators of the integral closure of the algebra generated by the list.

example

```
/**/      Use R:=QQ[x,y,t];
/**/      NmzIntClosureToricRing([x^3,x^2*y,y^3]);
-- the integral closure of QQ[x^3, x^2*y, y^3] is...
[y,x]
-- ... QQ[y, x]
```

See Also: NmzComputation(I-14.17 pg.192), NmzHilbertBasis(I-14.21 pg.194), NmzNormalToricRing(I-14.25 pg.195), NmzIntClosureMonIdeal(I-14.22 pg.194), NmzEhrhartRing(I-14.19 pg.193), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.24 NmzIntersectionValRings

syntax

```
NmzIntersectionValRings(M: MAT, M: Ring): LIST of RINGELEM
```

Description

A discrete monomial valuation v on $R = K[X_1, \dots, X_n]$ is determined by the values $v(X_j)$ of the indeterminates. This function computes the subalgebra $S = \text{fin} R : v_i(f) \geq 0, i = 1, \dots, r$ that is the intersection of the valuation rings of the given valuations v_1, \dots, v_r , i.e. it consists of all elements of R that have a nonnegative value for all r valuations. It takes as input the matrix $V = (v_i(X_j))$ whose rows correspond to the values of the indeterminates.

example

```
/**/      Use R:=QQ[x,y,z,w];
/**/      V := matrix([[0,1,2,3],[-1,1,2,1]]);
/**/      NmzIntersectionValRings(V,R);
[y, z, w, x*y, x^2*z, x*w, x*z]
```

See Also: NmzComputation(I-14.17 pg.192), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.25 NmzNormalToricRing

syntax

```
NmzNormalToricRing(L: LIST of RINGELEM): LIST of RINGELEM
```

Description

Given a list “L” of power-products in a ring R, the function returns the generators of the normalization of the algebra generated by the list.

example

```
/**/      Use R:=QQ[x,y,t];
-- We compute the normalization of QQ[x^3, x^2*y, y^3]
/**/      NmzNormalToricRing([x^3, x^2*y, y^3]);
[y^3, x^2*y, x^3, x*y^2]
--> answer is QQ[y^3, x^2*y, x^3, x*y^2]
```

See Also: NmzComputation(I-14.17 pg.192), NmzHilbertBasis(I-14.21 pg.194), NmzIntClosureToricRing(I-14.23 pg.195), NmzIntClosureMonIdeal(I-14.22 pg.194), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.26 NmzSetVerboseDefault

syntax

```
NmzSetVerboseDefault(v: BOOL):BOOL
```

Description

Set the verbosity state for Normaliz. Returns the previous verbosity setting.

example

```
/**/      NmzSetVerboseDefault(true);
false
```

I-14.27 NmzTorusInvariants

syntax

```
NmzTorusInvariants(M: MAT, R: Ring): LIST of RINGELEM
```

Description

Let “ $T=(K^*)^r$ ” be the r-dimensional torus acting on the polynomial ring “ $R=K[X_1, \dots, X_n]$ ” diagonally. Such an action can be described as follows: there are integers $a_{ij}, i = 1, \dots, r, j = 1, \dots, n$ such that (l_1, \dots, l_r) in “T” acts by the substitution X_j maps to $l_1^{a_{1j}} * \dots * l_r^{a_{rj}} * X_j$ for $j=1, \dots, n$.

The function takes the matrix $M = (a_{ij})$ and the ring “R” as input. It computes the ring of invariants $R^T = \{f \in R \mid f = f \text{ for all } t \in T\}$.

example

```
/**/      Use R:=QQ[x,y,z,w];
/**/      T := matrix([-1,-1,2,0],[1,1,-2,-1]);
/**/      NmzTorusInvariants(T,R);
[x^2*z, x*y*z, y^2*z]
```

See Also: NmzComputation(I-14.17 pg.192), NmzDiagInvariants(I-14.18 pg.192), NmzFiniteDiagInvariants(I-14.20 pg.193), NmzSetVerboseDefault(I-14.26 pg.196)

I-14.28 NonZero

syntax

```
NonZero(L: LIST|MODULEELEM): LIST
```

Description

This function returns the list obtained by removing the zeroes from L.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ NonZero([0,0,3, ideal(y),0]);
[3, ideal(y)]
```

See Also: FirstNonZero([I-6.7](#) pg.87), FirstNonZeroPosn([I-6.8](#) pg.88), IsZero([I-9.78](#) pg.150)

I-14.29 not

syntax

```
not(A: BOOL): BOOL
```

Description

This function negates a boolean: i.e. if “A” gives “true” then “not(A)” gives “false”, and vice versa.

Note that from CoCoA-5.1 “not” is a function, so its argument must be between brackets!

example

```
/**/ [n in 1..10 | not(IsPrime(n))];
[1,4,6,8,9]
```

See Also: and([I-1.11](#) pg.29), or([I-15.9](#) pg.205)

I-14.30 NR

syntax

```
NR(X: RINGELEM, L: LIST of RINGELEM): RINGELEM
NR(X: MODULEELEM, L: LIST of MODULEELEM): MODULEELEM
```

Description

This function returns the normal remainder of X with respect to L, i.e., it returns the remainder from the division algorithm. To get both the quotients and the remainder, use “DivAlg” ([I-4.21](#) pg.73).

Note that if the list does not form a Groebner basis, the remainder may not be zero even if X is in the ideal or module generated by L (use “GenRepr” ([I-7.7](#) pg.100) or “NF” ([I-14.15](#) pg.191) instead).

Currently (v 5.0.3) the internal code for computing NF(F, I) and NR(F, GBasis(I)) is identical, but the second is slower just for the overhead in interpreting a possibly long list of polynomials.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ F := x^2*y + x*y^2 + y^2;
/**/ NR(F, [x*y-1, y^2-1]);
x + y + 1

// NOT YET IMPLEMENTED for MODULEELEM
```

See Also: DivAlg([I-4.21](#) pg.73), GenRepr([I-7.7](#) pg.100), NF([I-14.15](#) pg.191)

I-14.31 num

syntax

```
num(N: INT): INT
num(N: RAT): INT
num(N: RINGELEM): RINGELEM
```

Description

This function returns the numerator of “N”.

The OBSOLETE fragile syntax in CoCoA 4 “N.Num” and “N.Den” is no longer supported.

example

```
/**/ num(3);
3

/**/ P := QQ[x,y];
/**/ F := NewFractionField(P);
/**/ Use F;
/**/ num(x/(x+y));
x
```

See Also: den([I-4.7](#) pg.67)

I-14.32 NumCols

syntax

```
NumCols(M: MAT): INT
```

Description

This function returns the number of columns in a matrix.

example

```
/**/ M := mat([[1,2,3], [4,5,6]]);
/**/ NumCols(M);
3
```

See Also: matrix([I-13.10](#) pg.173), NumRows([I-14.37](#) pg.200)

I-14.33 NumCompts

syntax

```
NumCompts(X: MODULEELEM|MODULE): INT
```

Description

If “X” is a “MODULEELEM”, it returns the number of components of “X”. If “X” is a “MODULE”, it returns the rank of the free module in which “X” is defined.

This function used to be called “NumComps” in CoCoA-4.

example

```
/**/ Use R := QQ[x,y];
/**/ R2 := NewFreeModule(R, 3);
/**/ M := SubmoduleRows(R2, matrix(R, mat([[x,0,y], [x^2+y^2,x^2,3]])));
```

```

/**/ NumCompts(M);
3
/**/ NumCompts(gens(M)[1]);
3

```

See Also: [len\(I-12.5 pg.161\)](#)

I-14.34 NumGens

— syntax —

```
NumGens(I: IDEAL): INT
```

Description

This function returns the number of generators of “I”. This is more direct, therefore efficient, than writing “len(gens(I))”, because it does not create the temporary list “gens(I)”.

— example —

```

/**/ use R := QQ[x,y,z];
/**/ I := ideal(indets(R))^40;
/**/ NumGens(I);
861

```

See Also: [len\(I-12.5 pg.161\)](#)

I-14.35 NumIndets

— syntax —

```
NumIndets(R: RING): INT
```

Description

This function returns the number of indeterminates of the current ring or of R.

— example —

```

/**/ S := QQ[x,y];
/**/ R := QQ[x,y,z];
/**/ NumIndets(R);
3
/**/ NumIndets(S);
2

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [indets\(I-9.22 pg.127\)](#)

I-14.36 NumPartitions

— syntax —

```
NumPartitions(N: INT): INT
```

Description

This function returns the number of partitions of a non-negative integer, i.e. the number of distinct ways of writing “N” as a sum of positive integers.

example

```

/**/ NumPartitions(2); -- 2 and 1+1
2
/**/ NumPartitions(5);
7

```

I-14.37 NumRows

syntax

```

NumRows(M: MAT): INT

```

Description

This function returns the number of rows in a matrix.

example

```

/**/ M := mat([[1,2,3], [4,5,6]]);
/**/ NumRows(M);
2

```

See Also: [matrix\(I-13.10 pg.173\)](#), [NumCols\(I-14.32 pg.198\)](#)

I-14.38 NumTerms

syntax

```

NumTerms(F: RINGELEM): INT

```

Description

This function returns the number of terms in a polynomial.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ NumTerms((x+y+z)^5) = binomial(3+5-1, 5);
true

```

See Also: [len\(I-12.5 pg.161\)](#)

Chapter I-15

O

I-15.1 one

syntax

```
one(R: RING): RINGELEM
```

Description

This function return the multiplicative identity of a ring. For when you want to force the integer “1” to be a “RINGELEM”.

example

```
/**/ P := ZZ/(101)[x,y,z];
/**/ N := 1; Print N, " of type ", type(N);
1 of type INT
/**/ N := one(P); Print N, " of type ", type(N);
1 of type RINGELEM
/**/ N := 300*1; Print N, " of type ", type(N);
300 of type INT
/**/ N := 300*one(P); Print N, " of type ", type(N);
-3 of type RINGELEM
```

See Also: [zero\(I-25.1 pg.297\)](#)

I-15.2 OpenIFile

syntax

```
OpenIFile(S: STRING): DEVICE
```

Description

***** NOT YET IMPLEMENTED *****

This function opens the file with name S for input. Input from that file can then be read with “Get” ([I-7.10 pg.102](#)).

(NOTE: one would normally use “source” ([I-19.22 pg.262](#)) to read CoCoA commands from a file.)

example

```
D := OpenOFile("my-test"); -- open "my-test" for output from CoCoA
Print "hello world" On D; -- print string into "mytest"
Close(D);
```

```

D := OpenIFile("my-test"); -- open "my-test" for input to CoCoA
Get(D,3); -- get the first three characters (in Ascii code)
[104, 101, 108]
-----
ascii(It); -- convert the ASCII code into characters
hel
-----
Close(D);

```

See Also: [close\(I-3.14 pg.46\)](#), [Introduction to IO\(II-6.1 pg.315\)](#), [OpenOFile\(I-15.5 pg.203\)](#), [OpenIString\(I-15.3 pg.202\)](#), [OpenOString\(I-15.6 pg.204\)](#), [OpenSocket\(I-15.7 pg.204\)](#), [source\(I-19.22 pg.262\)](#)

I-15.3 OpenIString

syntax

```

OpenIString(S: STRING, T: STRING): DEVICE
OpenOString(S: STRING): DEVICE

```

Description

***** NOT YET IMPLEMENTED *****

This function open strings for input. The string S serves as the name of the device opened for input or output; one may use the empty string. “OpenIString” is used to read input from the string T with the help of “Get” ([I-7.10 pg.102](#)).

example

```

S := "hello world";
D := OpenIString("", S); -- open the string S for input to CoCoA
L := Get(D,7); -- read 7 characters from the string
L; -- ASCII code
[104, 101, 108, 108, 111, 32, 119]
-----
ascii(L); -- convert ASCII code to characters
hello w
-----
Close(D); -- close device D

```

See Also: [close\(I-3.14 pg.46\)](#), [Introduction to IO\(II-6.1 pg.315\)](#), [OpenOString\(I-15.6 pg.204\)](#), [OpenIFile\(I-15.2 pg.201\)](#), [OpenOFile\(I-15.5 pg.203\)](#), [source\(I-19.22 pg.262\)](#), [sprintf\(I-19.25 pg.263\)](#)

I-15.4 OpenLog

syntax

```

OpenLog(D: DEVICE)

```

Description

***** NOT YET IMPLEMENTED *****

This function opens the output device D and starts to record the output from a CoCoA session on D. The “CloseLog” ([I-3.15 pg.46](#)) closes the device D and stops recording the CoCoA session on D.

At present the choices for the device D are an output file (see “[OpenOFile](#)” ([I-15.5](#) pg.203)) or an output string (see “[OpenOString](#)” ([I-15.6](#) pg.204)). Several output devices may be open at a time. If the panel option “Echo” is set to True, both the input and output of the CoCoA session are logged; otherwise, just the output is logged.

example

```
D := OpenOFile("MySession");
OpenLog(D);
1+1;
2
-----
G := 1;
Set Echo;
2+2;
2 + 2
4
-----
F := 2;
F := 2
CloseLog(D);
CloseLog(D)
UnSet Echo;
SET(Echo, False)

-- The contents of "MySession":
2
-----
2 + 2
4
-----
F := 2
CloseLog(D)
```

See Also: Introduction to IO([II-6.1](#) pg.315), [OpenIFile](#)([I-15.2](#) pg.201), [OpenOFile](#)([I-15.5](#) pg.203), [OpenIString](#)([I-15.3](#) pg.202), [OpenOString](#)([I-15.6](#) pg.204)

I-15.5 OpenOFile

syntax

```
OpenOFile(S: STRING): DEVICE
OpenOFile(S: STRING,"w" or "W"): DEVICE
```

Description

This function opens the file with name S—creating it if it does not already exist—for output. If used with second argument “w” or “W” then it immediately erases the file S. The function “[print on](#)” ([I-16.26](#) pg.218) is then used for appending output to S.

example

```
D := OpenOFile("my-test"); -- open "my-test" for output from CoCoA
Print "hello world" On D; -- print string into "mytest"
Print " test" On D; -- append to the file "mytest"
Close(D); -- close the file
D := OpenOFile("my-test","w"); -- clear "my-test"
Print "goodbye" On D; -- "mytest" now consists only of the string "goodbye"
Close(D);
```

See Also: [close\(I-3.14 pg.46\)](#), [Introduction to IO\(II-6.1 pg.315\)](#), [OpenIFile\(I-15.2 pg.201\)](#), [OpenIString\(I-15.3 pg.202\)](#), [OpenOString\(I-15.6 pg.204\)](#), [source\(I-19.22 pg.262\)](#)

I-15.6 OpenOString

syntax

```
OpenOString(S: STRING): DEVICE
```

Description

This function opens strings for output. The string S serves as the name of the device opened for input or output; one may use the empty string. “OpenOString” is used to write to a string with the help of “print on”.

example

```
D := OpenOString(""); -- open a string for output from CoCoA
L := [1,2,3]; -- a list
Print L On D; -- print to D
D;
record[Name := "", Type := "OString", Protocol := "CoCoALanguage"]
-----
S := Cast(D, STRING); -- S is the string output to D
S; -- a string
[1, 2, 3]
-----
Print " more characters" On D; -- append to the existing output string
Cast(D, STRING);
[1, 2, 3] more characters
-----
```

See Also: [close\(I-3.14 pg.46\)](#), [Introduction to IO\(II-6.1 pg.315\)](#), [OpenIFile\(I-15.2 pg.201\)](#), [OpenOFile\(I-15.5 pg.203\)](#), [OpenIString\(I-15.3 pg.202\)](#), [source\(I-19.22 pg.262\)](#), [sprintf\(I-19.25 pg.263\)](#)

I-15.7 OpenSocket

syntax

```
OpenSocket(Machine: STRING, Port: STRING): DEVICE
```

Description

***** NOT YET IMPLEMENTED *****

This function opens a client socket (I/O) connection. It requires the name of the machine with the server socket and the port number (expressed as a STRING).

CoCoA-4 communicates with the CoCoAServer via socket which, by default, runs on “localhost” on port “0xc0c0”. To change these settings redefine in your “userinit.coc” or “.cocoarc” the variables

```
MEMORY.CoCoAServerMachine := "localhost";
MEMORY.CoCoAServerPort := "0xc0c0";
```

example

```
D := OpenSocket("localhost", "10000");
Print 100^6 On D;
Source D;
Close(D);
```

See Also: Introduction to IO([II-6.1](#) pg.315), OpenIFile([I-15.2](#) pg.201), OpenOFile([I-15.5](#) pg.203), OpenIString([I-15.3](#) pg.202), OpenOString([I-15.6](#) pg.204)

I-15.8 Option [OBSOLETE]

[OBSOLETE] syntax

Description

[OBSOLETE]

I-15.9 or

A or B syntax
(where A, B: BOOL, return BOOL)

Description

This operator represents the logical disjunction of “A” and “B”. CoCoA first evaluates “A”; if that gives “true” then the result is “true”, and “B” is not evaluated. Otherwise, if “A” gives “false” then “B” is evaluated, and its value is the final result.

example

```
/**/ Define IsUnsuitable(X)
/**/   Return X < 0 or FloorSqrt(X) >= 2^16;
/**/ EndDefine;
/**/ IsUnsuitable(-9);
true
/**/ IsUnsuitable(9);
false
```

See Also: and([I-1.11](#) pg.29), not([I-14.29](#) pg.197)

I-15.10 OrdMat

OrdMat(R: RING): MAT syntax

Description

This function returns a matrix which describes the term-ordering of the ring “R”.

example

```
/**/ Use S ::= QQ[x,y,z];
/**/ M := mat([ [1,2,3], [3,4,5], [0,0,1]]);
/**/ P := NewPolyRing(CoeffRing(S), IndetSymbols(S), M, 2);
/**/ GradingDim(P);
2
/**/ OrdMat(P);
matrix(QQ,
  [[1, 2, 3],
```

```
[3, 4, 5],  
[0, 0, 1]])  
  
/**/ GradingDim(S);  
1  
/**/ OrdMat(S);  
matrix(QQ,  
  [[1, 1, 1],  
   [0, 0, -1],  
   [0, -1, 0]])
```

See Also: StdDegLexMat([I-19.31](#) pg.266), StdDegRevLexMat([I-19.32](#) pg.267), LexMat([I-12.6](#) pg.161), RevLexMat([I-18.38](#) pg.244), XelMat([I-24.1](#) pg.295), elim([I-5.4](#) pg.76), GradingDim([I-7.19](#) pg.105), Orderings([III-9.5](#) pg.360), NewPolyRing([I-14.8](#) pg.188)

Chapter I-16

P

I-16.1 Packages

syntax

```
packages(): LIST of STRING
```

Description

This function returns the names of the loaded packages as a list of strings.
The old CoCoA-4 names “\$user” and “\$builtin” are no longer used.

example

```
/**/ packages();  
["$BackwardCompatible", "$BringIn", (...)]
```

See Also: CoCoA Packages([II-7 pg.319](#)), Supported Packages([II-7.7 pg.321](#))

I-16.2 panel [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE]

I-16.3 panels [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE]

I-16.4 partitions

syntax

```
partitions(N: INT): LIST
```

Description

This function returns all integer partitions of N, positive integer

example

```
/**/ partitions(3);
[[3], [1, 2], [1, 1, 1]]
```

See Also: subsets([I-19.39](#) pg.270), tuples([I-20.15](#) pg.284)

I-16.5 permutations

syntax

```
permutations(L: LIST): LIST
```

Description

This function computes all permutations of the entries of a list (set). If L has repeated elements it will return repeated elements.

example

```
/**/ permutations(3..5);
[[3, 4, 5], [3, 5, 4], [4, 3, 5], [4, 5, 3], [5, 3, 4], [5, 4, 3]]

/**/ permutations([2, 2, x]);
[[2, 2, x], [2, x, 2], [2, 2, x], [2, x, 2], [x, 2, 2], [x, 2, 2]]

/**/ MakeSet(permutations([2, 2, x]));
[[2, 2, x], [2, x, 2], [x, 2, 2]]
```

See Also: subsets([I-19.39](#) pg.270), tuples([I-20.15](#) pg.284)

I-16.6 PerpIdealOfForm

syntax

```
PerpIdealOfForm(F: RINGELEM): IDEAL
```

Description

Thanks to Enrico Carlini.

Given a form “F” computes the ideal of derivations killing it.

For the sake of simplicity Forms/Polynomials and Derivations live in the same ring, the distinction between them is purely formal.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ PerpIdealOfForm(x^3+x*y*z);
ideal(z^2, y^2, x^2 -6*y*z)
```



```

/**/ HilbertFn(R/It);
H(0) = 1
H(1) = 3
H(2) = 3
H(3) = 1
H(t) = 0   for t >= 4

```

See Also: [InverseSystem\(I-9.33 pg.133\)](#), [DerivationAction\(I-4.11 pg.69\)](#)

I-16.7 *pfaffian*

— syntax —

```
pfaffian(M: MAT): RINGELEM
```

Description

This function returns the Pfaffian of M.

— example —

```

/**/ Use R ::= QQ[x,y];
/**/ pfaffian(mat([[0,y],[-y,0]]));
y

```

See Also: [det\(I-4.13 pg.70\)](#)

I-16.8 *PkgName*

— syntax —

```
PkgName(): STRING
S.PkgName(): STRING
```

where S is the identifier or alias for a package.

Description

This function returns the (long) name of a package. The first form returns “\$coclib” and the second returns the name of the package whose name or alias is S. This function is useful as a shorthand, when S is an alias, for the full name a package.

— example —

```

GB.PkgName();
$gb
-----
$gb.PkgName();
$gb
-----
PkgName();
$coclib
-----

```

I-16.9 PlotPoints

syntax

```
PlotPoints(L: LIST of points)
```

Description

This function outputs the coordinates of the points (with two components) to a file called "CoCoAPlot". See "PlotPointsOn" (I-16.10 pg.210) for outputting to another file.

This result can be plotted using your preferred plotting program. For example, start "gnuplot" and then give it the command

```
plot "CoCoAPlot"
```

to see the plot.

example

```
/**/ PlotPoints([ [X, X^2-X+14] | X In -10..10]);
Plotting points...100%
21 plotted points have been placed in the file CoCoAPlot
```

See Also: ImplicitPlot(I-9.13 pg.123), PlotPointsOn(I-16.10 pg.210)

I-16.10 PlotPointsOn

syntax

```
PlotPointsOn(L: LIST of points, S: STRING)
```

Description

This function is the same as "PlotPoints" (I-16.9 pg.210) with a second argument giving the name of the file to print on.

Note that the last argument is a STRING, the name of the file, and not a DEVICE, as for "print on" (I-16.26 pg.218).

example

```
/**/ PlotPointsOn([ [1/(X+1/2), X^2-X+14] | X In -10..10], "PLOT-points");
Plotting points...100%
21 plotted points have been placed in the file points

/**/ ImplicitPlotOn(x^2*y -(59/4)*x^2 +2*x -1, [-3,3], [0,250], "PLOT-curve");
Plotting points...10%...20%...30%...40%...50%...60%...70%...80%...90%...100%
735 plotted points have been placed in the file curve
```

After having produced the plot files using CoCoA-4, start "gnuplot" and then give it the following commands:

```
plot "curve"
replot "points"
```

See Also: ImplicitPlot(I-9.13 pg.123), PlotPoints(I-16.9 pg.210)

I-16.11 *poincare* [OBSOLESCENT]

syntax

```
[OBSOLESCENT]poincare(M: RING|IDEAL):TAGGED("$hp.PSeries")
```

Description

(sorry Poincare' for the lower-case: here we follow the naming convention “*single name goes lower-case*”)

[OBSOLESCENT] Now called “HilbertSeries” (I-8.7 pg.110).

See Also: HilbertSeries(I-8.7 pg.110)

I-16.12 *PoincareMultiDeg* [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] now called “HilbertSeriesMultiDeg” (I-8.8 pg.111)

I-16.13 *PoincareShifts* [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] now called “HilbertSeriesShifts” (I-8.9 pg.112)

I-16.14 *PolyAlgebraHom*

syntax

```
PolyAlgebraHom(Domain: RING, Codomain: RING, images: LIST): RINGHOM
```

Description

This function creates the homomorphism of (polynomial) algebras from “R” to “S” with the same ring of coefficients. This is uniquely defined by the images of the indeterminates of “R” which are specified by the entries of “images”.

This is a cleaner mathematical implementation of the function “image [OBSOLESCENT]” (I-9.10 pg.121) in CoCoA-4.

example

```
/**/ Use R := QQ[x,y,z];
/**/ S := QQ[x[1..3]];
/**/ phi := PolyAlgebraHom(R, S, indets(S));
/**/ phi(x^2-y);
x[1]^2 -x[2]
```

```

/**/ S := QQ[a];
/**/ phi := PolyAlgebraHom(R, S, [RingElem(S,"a"),1,0]);
/**/ phi(x^2-y);
a^2 -1

/**/ phi := PolyAlgebraHom(R, QQ, [2,1,0]); --> evaluate at [2,1,0]
/**/ phi(x^2-y);
3

```

See Also: [apply\(I-1.13 pg.30\)](#), [CanonicalHom\(I-3.2 pg.41\)](#)

I-16.15 PolyRingHom

syntax

```
PolyRingHom(R: RING, S: RING, CoeffHom: RINGHOM, images: LIST): RINGHOM
```

Description

This function create the homomorphism of (polynomial) algebras between R and S. This is uniquely defined by the images of the indeterminated of R and the homomorphism `CoeffRing(R)` into S.

example

```

/**/ R := QQ[x,y];
/**/ S := QQ[a,b,c];
/**/ SmodJ := NewQuotientRing(S, ideal(RingElem(S,"a")^2-1));

/**/ Use SmodJ;
/**/ phi := PolyRingHom(R, SmodJ, CanonicalHom(QQ,SmodJ), [a,b]);
/**/ Use R;
/**/ phi(x);
(a)

```

See Also: [apply\(I-1.13 pg.30\)](#), [CanonicalHom\(I-3.2 pg.41\)](#)

I-16.16 PowerMod

syntax

```
PowerMod(A: INT, B: INT, M: INT): INT
```

Description

This function calculates efficiently an integer power modulo a given modulus. Thus “`PowerMod(A, B, M)`” is equal to “`mod(A^B, M)`”, but the former is computed faster. “B” must be non-negative.

example

```

/**/ PowerMod(12345,41041,41041); -- 41041 is a Carmichael number
12345

/**/ PowerMod(123456789,987654321,32003); -- cannot compute 123456789^987654321 directly
2332

```

I-16.17 PreImage

syntax

```
PreImage(phi: RINGHOM, f: RINGELEM): RECORD
```

Description

This function returns the preimage of “f” via “phi”. More precisely it returns a record with fields “IsInImage” and “ker”, and “OnePreImage” if “f” is in the image of “phi”.

example

```
/**/ QQxyz ::= QQ[x,y,z];
/**/ QQab  ::= QQ[a,b];

/**/ Use QQab;
/**/ phi := PolyAlgebraHom(QQxyz, QQab, [a+1, a*b+3, b^2]);
/**/ IsInjective(phi);
false
/**/ ker(phi);
ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)
/**/ IsSurjective(phi);
false

/**/ Use QQab;
/**/ PreImage(phi, b);
record[IsInImage := false, ker := ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)]

/**/ indent(PreImage(phi, a^2));
record[
  IsInImage := true,
  OnePreImage := x^2 - 2*x + 1,
  ker := ideal(-x^2*z + y^2 + 2*x*z - 6*y - z + 9)
]
/**/ phi(ReadExpr(QQxyz, "x^2 - 2*x + 1"));
a^2
/**/ phi(ReadExpr(QQxyz, "x^2 - 2*x + 1 + (-x^2*z + y^2 + 2*x*z - 6*y - z + 9)"));
a^2
```

See Also: [ker\(I-11.1 pg.157\)](#), [IsSurjective\(I-9.72 pg.147\)](#)

I-16.18 PreprocessPts

syntax

```
PreprocessPts(Pts: MAT, Toler: MAT): RECORD
PreprocessPtsGrid(Pts: MAT, Toler: MAT): RECORD
PreprocessPtsAggr(Pts: MAT, Toler: MAT): RECORD
PreprocessPtsSubDiv(Pts: MAT, Toler: MAT): RECORD
```

Description

Thanks to Maria-Laura Torrente.

These functions detect groupings of close points, and choose a single representative for them (which lies within the given tolerance of each original point); the result is the list of these representatives, and the number of original points associated to each representative.

The first argument is a matrix whose rows represent a set of points in k -dimensional space, and the second argument is row-matrix of k tolerances (one for each dimension).

The return value is a record containing two fields: “**NewPoints**” contains a matrix whose rows represent a list of “*well-separated*” points, and “**weights**” which contains the number of input points associated to each output point.

There are three underlying algorithms: “**Grid**” is fast but crude; “**Subdiv**” works best when the original points are densely packed (so the result will be a small list); finally “**Aggr**” is best suited to situations where the original points are less densely packed.

The function “**PreprocessPts**” automatically chooses between “**Subdiv**” and “**Aggr**” with the aim of minimising computation time. Note that the “**Aggr**” and “**Subdiv**” methods regard the tolerances as being slightly flexible.

For a full description of the algorithms we refer to the paper J.Abbott, C.Fassino, L.Torrente “*Thinning Out Redundant Empirical Data*” (Mathematics in Computer Science, 2007).

example

```

/**/ Pts := matrix([[ -1,0],[0,0],[1,0],[99,1],[99,0],[99,-1]]);
/**/ Toler := RowMat([3,3]);
/**/ PreprocessPts(Pts, Toler);
record[NewPoints := matrix(QQ,
  [[99, 0],
   [0, 0]]), weights := [3, 3]]

/**/ PreprocessPts(Pts, RowMat([0.8,0.8]));
record[NewPoints := matrix(QQ,
  [[-1/2, 0],
   [1, 0],
   [99, 1/2],
   [99, -1]]), weights := [2, 1, 2, 1]]

/**/ PreprocessPtsAggr(Pts, RowMat([0.9,0.9])); -- exhibits tolerance flex
record[NewPoints := matrix(QQ,
  [[0, 0],
   [99, 0]]), weights := [3, 3]]

```

I-16.19 PrimaryDecomposition

syntax

```
PrimaryDecomposition(I: IDEAL): LIST of IDEAL
```

Description

This function returns the primary decomposition of the ideal I . Currently it is implemented ONLY for squarefree monomial ideals using the Alexander dual technique. See “**FrbPrimaryDecomposition**” (I-6.22 pg.95) for monomial ideals.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ PrimaryDecomposition(***Ideal(xy, yz, zx)***)
[ideal(y, z), ideal(x, z), ideal(x, y)]

```

See Also: PrimaryDecomposition0(I-16.20 pg.215), PrimaryDecompositionGTZ0(I-16.21 pg.215), FrbPrimaryDecomposition(I-6.22 pg.95), EquiIsoDec(I-5.9 pg.78)

I-16.20 PrimaryDecomposition0

syntax

PrimaryDecomposition0(I: IDEAL): RECORD of LIST of IDEAL

Description

This function returns the primary decomposition of the 0-dimensional ideal I. (Monico-Robbiano-Kreuzer probabilistic algorithm, Gao-Wan-Wang finite characteristic algorithm) It will be improved and extended in future versions of CoCoA.

Implementation by Elisa Palezzato.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ PD := PrimaryDecomposition0(ideal(x-z, y^2-1, z^2));
/**/ indent(PD);
record[
  IsCertified := true,
  PrDec_I := [ideal(y -1, x -z, z^2), ideal(y +1, x -z, z^2)],
]
/**/ Use ZZ/(2)[x,y,z];
/**/ PD := PrimaryDecomposition0(ideal(x-z, y^2-1, z^2));
/**/ indent(PD);
record[
  IsCertified := true,
  PrDec_I := [ideal(x +z, z^2, y^2 +1)]
]
```

See Also: PrimaryDecompositionGTZ0(I-16.21 pg.215)

I-16.21 PrimaryDecompositionGTZ0

syntax

PrimaryDecompositionGTZ0(I: IDEAL): RECORD of LIST of IDEAL

Description

This function returns the primary decomposition of the 0-dimensional ideal I. (GTZ algorithm) It will be improved and extended in future versions of CoCoA.

Implemented by Luis David Garcia (updated to CoCoA-5 by Anna M. Bigatti).

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ PD := PrimaryDecompositionGTZ0(ideal(x-z, y^2-1, z^2));
/**/ indent(PD);
```

See Also: PrimaryDecomposition0(I-16.20 pg.215)

I-16.22 PrimaryHilbertSeries

syntax

PrimaryHilbertSeries(I: IDEAL, Q: IDEAL): TAGGED("PSeries")

Description

Let “P” be a polynomial ring, “M” the maximal ideal in “P” generated by the indeterminates, and “(Q+I)/I” a primary ideal for “M/I”. This function computes the Hilbert-Poincare’ series of “(P/I)/((Q+I)/I)”.

example

```

/**/ Use S := QQ[x,y,z];
/**/ I := ideal(x^3-y*z, y^2-x*z, z^2-x^2*y);
/**/ Q := ideal(y, z);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;

/**/ Use S := ZZ/(32003)[x,y,z,w];
/**/ I := ***Ideal(x^5 - yz, y^4 - xz^2, xy^3 - zw, x^2z - yw,
/**/ y^2z^2 - w^3, y^3z - x^2w^2, x^3w - z^2, xyw^2 - z^3,
/**/ x^3y^2 - w^2, xz^4 - y^2w^3, yz^5 - xw^5, y^3w^5 - z^7,
/**/ x^2w^7 - z^8, z^9 - yw^8)***;
/**/ Q := ideal(x, y, z);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;
/**/ $hp.PSerToHilbert(PS);

/**/ Use S := ZZ/(32003)[x,y,z];
/**/ I := ideal(S, []); -- ideal in S with no generators
/**/ Q := ideal(x, y, z^2);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;
/**/ $hp.PSerToHilbert(PS);
/**/ HV := $hp.PSerHVector(PS); -- the H-vector associated to PS

/**/ Use S := ZZ/(32003)[x,y,z,w];
/**/ I := ***Ideal(-yz + xw, z^3 - yw^2, -xz^2 + y^2w, -y^3 + x^2z)***;
/**/ Q := ideal(x, y, z^2, w^3);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;
/**/ $hp.PSerToHilbert(PS);
/**/ HV := $hp.PSerHVector(PS);
/**/ $primary.E(0, HV);
/**/ [ $primary.E(J,HV) | J In 0..($hp.PSerDim(PS)-2) ];
/**/ [ $primary.E(J,HV) | J In 0..(len(HV)-1) ];

/**/ Use S := ZZ/(32003)[x,y,z,w];
/**/ I := ***Ideal(x^3-y^7, x^2y - xw^3-z^6)***;
/**/ Q := ideal(x, y, z, w);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;
/**/ $hp.PSerToHilbert(PS);
/**/ HV := $hp.PSerHVector(PS);
/**/ [ $primary.E(J,HV) | J In 0..($hp.PSerDim(PS)-2) ];
/**/ [ $primary.E(J,HV) | J In 0..(len(HV)-1) ];

/**/ Use S := ZZ/(32003)[x,y,z];
/**/ I := ideal(z^3);
/**/ Q := ideal(x^2, y^2, x*z, y*z);
/**/ PS := PrimaryHilbertSeries(I, Q); PS;
/**/ $hp.PSerToHilbert(PS);
/**/ HV := $hp.PSerHVector(PS);
/**/ [ $primary.E(J,HV) | J In 0..($hp.PSerDim(PS)-2) ];
/**/ [ $primary.E(J,HV) | J In 0..(len(HV)-1) ];

```

See Also: InitialIdeal(I-9.26 pg.130), TgCone(I-20.5 pg.278)

I-16.23 PrimaryPoincare [OBSOLESCENT]

[OBSOLESCENT] syntax

Description

Renamed “PrimaryHilbertSeries” (I-16.22 pg.215).

See Also: PrimaryHilbertSeries(I-16.22 pg.215)

I-16.24 PrimitiveRoot

syntax

```
PrimitiveRoot(P: INT): INT
```

Description

Find a primitive root modulo the prime “P”, i.e. a generator of the cyclic multiplicative group of non-zero integers mod “P”.

Currently, the function produces the least positive primitive root.

example

```
/**/ PrimitiveRoot(17551561);
97
/**/ PrimitiveRoot(4111);
12;
```

See Also: IsPrime(I-9.62 pg.144)

I-16.25 print

syntax

```
print E_1, ..., E_n
```

Description

This command displays the value of each of the expressions “E_i”. To insert a newline write “\n”.

The similar command “println” (I-16.29 pg.219) is equivalent to “print” with a final newline.

example

```
/**/ for I := 1 To 10 Do print I^2, " "; endfor;
1 4 9 16 25 36 49 64 81 100

/**/ print "a\nb";
a
b
```

See Also: print on(I-16.26 pg.218), println(I-16.29 pg.219), format(I-6.17 pg.93), LaTeX(I-12.2 pg.159), StarPrint, StarSprint(I-19.29 pg.265)

I-16.26 print on

syntax

```
print E: OBJECT on D: DEVICE
```

Description

This command prints the value of expression E to the device D. Currently, the command can be used to print to files, strings, or the CoCoA window. In the first two cases, the appropriate device must be opened with “OpenOFile” (I-15.5 pg.203) or “OpenOString” (I-15.6 pg.204).

example

```
/**/ D := OpenOFile("my-test"); -- open "my-test" for output from CoCoA
/**/ Print "hello world" On D;   -- print string into "mytest"
/**/ close(D); -- close the file
```

See “OpenOFile” (I-15.5 pg.203) for an example using output strings. For printing to the CoCoA window, just use “print E” which is short for “print E On DEV.OUT”.

See Also: Introduction to IO (II-6.1 pg.315), OpenIFile (I-15.2 pg.201), OpenOFile (I-15.5 pg.203), OpenIString (I-15.3 pg.202), OpenOString (I-15.6 pg.204), print (I-16.25 pg.217), println (I-16.29 pg.219)

I-16.27 PrintBettiDiagram

syntax

```
PrintBettiDiagram(X: IDEAL or (quotient)RING or MODULE)
PrintBettiDiagram(X: LIST(res) or RECORD(diagram))
```

Description

This function prints the (“Macaulay-style”) Betti diagram for “M”.

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ I := ideal(x^2-y*t, x*y-z*t, x*y);
/**/ RES := res(I);
/**/ PrintRes(RES);
0 --> R(-5)^2 --> R(-4)^4 --> R(-2)^3
/**/ B := BettiDiagram(RES); indent(B);
record[
  Diagram := matrix(ZZ,
    [[3, 0, 0],
     [0, 4, 2]]),
  FirstShift := 2
]
/**/ PrintBettiDiagram(RES); -- same as PrintBettiDiagram(I or B)
      0      1      2
-----
2:    3      -      -
3:    -      4      2
-----
Tot:   3      4      2
```

See Also: BettiDiagram (I-2.3 pg.34), BettiMatrix (I-2.4 pg.34), PrintRes (I-16.30 pg.219), PrintBettiMatrix (I-16.28 pg.219)

I-16.28 PrintBettiMatrix

syntax

```
PrintBettiMatrix(M: IDEAL|MODULE|Resolution)
```

Description

This function returns the Betti matrix for M.

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ I := ideal(x^2-y*t, x*y-z*t, x*y);
/**/ PrintRes(I);
0 --> R^2(-5) --> R^4(-4) --> R^3(-2)
-----
/**/ PrintBettiMatrix(I);
  0   0   0
  0   0   3
  0   0   0
  0   4   0
  2   0   0
```

See Also: [PrintRes\(I-16.30 pg.219\)](#), [PrintBettiDiagram\(I-16.27 pg.218\)](#)

I-16.29 println

syntax

```
println E_1,...,E_n
PrintLn E_1,...,E_n
```

Description

This command is equivalent to “print” ([I-16.25 pg.217](#)) with a final newline; in other words, it prints the values of its arguments, then moves the cursor to the next line.

example

```
/**/ for i := 1 to 3 do print i; endfor;
123

/**/ for i := 1 to 3 do println i; endfor;
1
2
3
```

See Also: [print\(I-16.25 pg.217\)](#), [print on\(I-16.26 pg.218\)](#)

I-16.30 PrintRes

syntax

```
PrintRes(M)
```

Description

This function prints the minimal free resolution of “M”. (see “res” ([I-18.32](#) pg.241)).

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x, y, z^2);
/**/ RES := res(I);
/**/ PrintRes(I); -- recomputes resolution
0 --> R(-4) --> R(-2)(+)R(-3)^2 --> R(-1)^2(+)R(-2)
/**/ PrintRes(RES); -- just prints RES
0 --> R(-4) --> R(-2)(+)R(-3)^2 --> R(-1)^2(+)R(-2)
/**/ PrintBettiDiagram(RES); -- just prints the BettiDiagram for RES
      0      1      2
-----
1:      2      1      -
2:      1      2      1
-----
Tot:      3      3      1

```

See Also: [PrintBettiDiagram\(I-16.27](#) pg.218), [PrintBettiMatrix\(I-16.28](#) pg.219), [res\(I-18.32](#) pg.241)

I-16.31 product

syntax

```

product(L: LIST): OBJECT
product(L: LIST, InitVal: OBJECT): OBJECT

```

Description

This function returns the product of the objects in the list “L” (together with “InitVal”, if specified). When writing a program, if the list “L” may be empty, you must specify “InitVal”.

example

```

/**/ Use R ::= QQ[x,y];
/**/ product([3, x, y^2]);
3*x*y^2

/**/ product(1..40) = factorial(40);
true

/**/ product([]); -- gives 1 of type INT
1
/**/ product([], y);
y
/**/ product([3, x], y);
3*x*y

```

See Also: [Algebraic Operators\(II-3.2](#) pg.307), [sum\(I-19.41](#) pg.271)

I-16.32 protect

syntax

```

protect X;
protect X : reason;
  where reason: STRING

```

Description

This command protects the variable “X” from being assigned to. Attempting to assign to it will produce an error; if a “reason” (STRING) was given it is printed in the error message.

— example —

```

/**/ MaxSize := 99;
/**/ protect MaxSize : "size limit for fast computation";
-- /**/ MaxSize := 1000; --> !!! ERROR !!!
ERROR: Cannot set "MaxSize" (size limit for fast computation)

/**/ unprotect MaxSize; --> remove protection, X may be assigned to now
/**/ MaxSize := 1000; --> OK

```

See Also: `unprotect`([I-21.3](#) pg.286)

I-16.33 PthRoot

— syntax —

```

PthRoot(X: RINGELEM): RINGELEM

```

Description

This function returns the p-th root of a polynomial over a finite field. If no p-th root exists then an error is signalled. p is the characteristic of the field.

— example —

```

/**/ Use R ::= ZZ/(7)[x,y];
/**/ F := x^7-y^14+3;
/**/ PthRoot(F);
-y^2+x+3

```

See Also: `IsFiniteField`([I-9.46](#) pg.138), `IsPthPower`([I-9.64](#) pg.145)

Chapter I-17

Q

I-17.1 QQ

— syntax —

QQ

Description

This system variable is constant; its value is the field of rationals. Its name is protected so that it cannot be re-assigned to any other value.

Please note: this is a “*variable*”, so in “**define/define**” use “RingQQ” ([I-18.43 pg.246](#)) instead (or import it with “TopLevel” ([I-20.10 pg.280](#))).

— example —

```
/**/ Use QQ;

/**/ type(5);
INT
/**/ type(RingElem(QQ, 5));
RINGELEM

/**/ QQ = RingQQ();
true
```

See Also: ZZ([I-25.4 pg.298](#)), NewQuotientRing([I-14.9 pg.188](#)), RingQQ([I-18.43 pg.246](#)), TopLevel([I-20.10 pg.280](#))

I-17.2 quit

— syntax —

quit

Description

This command is used to quit CoCoA. It may be used only at top level.

See Also: ciao([I-3.12 pg.45](#))

I-17.3 QuotientBasis

syntax

```
QuotientBasis(I: IDEAL): LIST
```

Description

This function determines a vector space basis (of power products) for the quotient space associated to a zero-dimensional ideal. That is, if R is a polynomial ring with field of coefficients k , and I is a zero-dimensional ideal in R then $\text{QuotientBasis}(I)$ is a set of power products forming a k -vector space basis of R/I .

The actual set of power products chosen depends on the term ordering in the ring R : the power products chosen are those not divisible by the leading term of any member of the reduced Groebner basis of I (and consequently they form a factor-closed set).

example

```
/**/ Points := [[Rand(-9,9) | N In 1..3] | S In 1..25];
/**/ Use P := QQ[x,y,z];
/**/ I := IdealOfPoints(P, mat(QQ, Points));
/**/ QuotientBasis(I);
[1, z, z^2, z^3, z^4, y, y*z, y*z^2, y*z^3, y^2, y^2*z, y^2*z^2, y^3, x,
x*z, x*z^2, x*z^3, x*y, x*y*z, x*y*z^2, x*y^2, x^2, x^2*z, x^2*y, x^3]

/**/ Use P := QQ[x,y,z], Lex;
/**/ I := IdealOfPoints(P, mat(QQ, Points));
/**/ QuotientBasis(I);      -- power products underneath the Lex reduced GBasis
[1, z, z^2, z^3, z^4, z^5, z^6, z^7, z^8, z^9, z^10, z^11, z^12, y, y*z,
y*z^2, y*z^3, y*z^4, y*z^5, y*z^6, y^2, y^2*z, y^2*z^2, y^2*z^3, y^3]
```

See Also: [IdealOfPoints\(I-9.5 pg.118\)](#), [IsFactorClosed\(I-9.44 pg.137\)](#)

I-17.4 QuotientingHom

syntax

```
QuotientingHom(P: RING): RINGHOM
```

Description

This function returns the projection homomorphism of a ring “ R ” into a quotient ring “ R/I ”.

It is equivalent to (indeed it is called by) “`CanonicalHom(BaseRing(RModI), RModI)`”.

example

```
/**/ Use P := QQ[i];
/**/ CC := P/ideal(i^2+1);
/**/ phi := QuotientingHom(CC); -- phi: P -> CC
/**/ Ring(phi(f));
/**/ phi(f)^2;
1
```

See Also: [CanonicalHom\(I-3.2 pg.41\)](#)

I-17.5 QZP

syntax

```
QZP(F: RINGELEM): RINGELEM
QZP(F: LIST of POLY): LIST of POLY
```


QZP(I: IDEAL): IDEAL

Description

***** NOT YET IMPLEMENTED *****

The functions “QZP” and “ZPQ” ([I-25.3 pg.298](#)) map polynomials and ideals of other rings into ones of the current ring. When mapping from one ring to another, one of the rings must have coefficients in the rational numbers and the other must have coefficients in a finite field. The indeterminates in both rings must be identical.

The function “QZP” maps polynomials with rational coefficients to polynomials with coefficients in a finite field; the function “ZPQ” ([I-25.3 pg.298](#)) does the reverse, mapping a polynomial with finite field coefficients into one with rational (actually, integer) coefficients. The function “ZPQ” ([I-25.3 pg.298](#)) is not uniquely defined mathematically, and currently for each coefficient the least non-negative equivalent integer is chosen. Users should not rely on this choice, though any change will be documented.

example

```

Use R := QQ[x,y,z];
F := 1/2*x^3 + 34/567*x*y*z - 890; -- a poly with rational coefficients
Use S := ZZ/(101)[x,y,z];
QZP(F);                               -- compute its image with coeffs in ZZ/(101)
-50x^3 - 19xyz + 19
-----
G := It;
Use R;
ZPQ(G);                               -- now map that result back to QQ[x,y,z]
-- it is NOT the same as F...
51x^3 + 82xyz + 19
-----
H := It;
F - H;                               -- ... but the difference is divisible by 101
-101/2x^3 - 46460/567xyz - 909
-----
Use S;
QZP(H) - G;                          -- F and H have the same image in ZZ/(101)[x,y,z]
0
-----

```

See Also: [Introduction to RINGHOM\(III-10.1 pg.365\)](#), [BringIn\(I-2.12 pg.39\)](#)

Chapter I-18

R

I-18.1 radical

syntax

```
radical(I: IDEAL): IDEAL
```

Description

This function computes the radical of I using the algorithm described in the paper

M. Caboara, P.Conti and C. Traverso: “*Yet Another Ideal Decomposition Algorithm.*” Proc. AAECC-12, pp 39-54, 1997, Lecture Notes in Computer Science, n.1255 Springer-Verlag.

NOTE: at the moment, this implementation works only if the coefficient ring is the rationals or has large enough characteristic.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x,y)^3;
/**/ radical(I);
ideal(y, x)
```

See Also: IsInRadical([I-9.52 pg.141](#)), EquiIsoDec([I-5.9 pg.78](#)), RadicalOfUnmixed([I-18.2 pg.227](#))

I-18.2 RadicalOfUnmixed

syntax

```
RadicalOfUnmixed(I: IDEAL): IDEAL
```

Description

This function computes the radical of an unmixed ideal.

NOTE: at the moment, this implementation works only if the coefficient ring is the rationals or has large enough characteristic.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x^2 - y^2 - 4*x + 4*y, x - 2);
/**/ RadicalOfUnmixed(I);
ideal(x^2 -y^2 -4*x +4*y, x -2, y -2)
/**/ interreduced(gens(It)); -- the result may not be in its simplest form
[y -2, x -2]
```

See Also: [EquiIsoDec\(I-5.9 pg.78\)](#), [radical\(I-18.1 pg.227\)](#)

I-18.3 random

syntax

```
random(X: INT, Y: INT): INT
```

Description

The function returns a random integer between X and Y, inclusive. The range —X-Y— should be less than 2^33 to assure a uniform distribution.

NOTE: every time you restart CoCoA the sequence of random numbers will be the same (as happens in many programming languages). If you want better randomness, see “[seed](#)” ([I-19.4 pg.252](#)).

example

```
/**/ random(1,100);
6

/**/ random(-10^4,0);
-3263
```

See Also: [randomize\(I-18.4 pg.228\)](#), [randomized\(I-18.5 pg.229\)](#), [RandomSubset\(I-18.6 pg.229\)](#), [RandomSubsetIndices\(I-18.7 pg.230\)](#), [RandomTuple\(I-18.8 pg.230\)](#), [RandomTupleIndices\(I-18.9 pg.231\)](#), [seed\(I-19.4 pg.252\)](#)

I-18.4 randomize

syntax

```
Randomize(V: RINGELEM): RINGELEM
```

Description

***** NOT YET IMPLEMENTED: use random *****

This function replaces the coefficients of terms of the polynomial contained in V with randomly generated coefficients. The result is stored in V, overwriting the original polynomial.

NOTE: It is possible that some coefficients will be replaced by zeroes, i.e., some terms from the original polynomial may disappear in the result.

The similar function “[randomized](#)” ([I-18.5 pg.229](#)) performs the same operation, but returns the randomized polynomial without modifying the argument.

NOTE: every time you restart CoCoA the sequence of random numbers will be the same (as in other programming languages). If you want total randomness read “[seed](#)” ([I-19.4 pg.252](#)).

example

```
Use R ::= QQ[x];
F := 1+x+x^2;
Randomized(F);
-2917104644x^2 + 3623608766x - 2302822308
-----
F;
x^2 + x + 1
-----
Randomize(F);
F;
```

```
-1010266662x^2 + 1923761602x - 4065654277
-----
```

See Also: [random\(I-18.3 pg.228\)](#), [randomized\(I-18.5 pg.229\)](#), [seed\(I-19.4 pg.252\)](#)

I-18.5 randomized

syntax

```
Randomized(F: RINGELEM): RINGELEM
Randomized(F: INT): INT
```

Description

***** NOT YET IMPLEMENTED: use random *****

This function with a polynomial argument returns a polynomial obtained by replacing the coefficients of F with randomly generated coefficients. The original polynomial, F , is unaffected. With an integer argument, it returns a random integer.

NOTE: It is possible that some coefficients will be replaced by zeroes, i.e., some terms from the original polynomial may disappear in the result.

The similar function “[randomize\(I-18.4 pg.228\)](#)” performs the same operation, but returns NULL and modifies the argument.

NOTE: every time you restart CoCoA the sequence of random numbers will be the same (as in other programming languages). If you want total randomness read “[seed\(I-19.4 pg.252\)](#)”.

example

```
Use R := QQ[x];
F := 1 + x + x^2;
Randomized(F);
-2917104644x^2 + 3623608766x - 2302822308
-----
F;
x^2 + x + 1
-----
Randomized(23);
-3997312402
-----
Use R := ZZ/(7)[x,y];
Randomized(x^2 + 3x - 5);
3x^2 + 2x - 2
-----
```

See Also: [random\(I-18.3 pg.228\)](#), [randomize\(I-18.4 pg.228\)](#), [seed\(I-19.4 pg.252\)](#)

I-18.6 RandomSubset

syntax

```
RandomSubset(L: LIST, K: INT): LIST
```

Description

The function returns a random subset of “ L ” of cardinality “ K ”. This function can be quite useful for testing properties on some subsets of a large list when testing on all of them would be unfeasible in time and memory (see also “[subsets\(I-19.39 pg.270\)](#)”).

NOTE: the resulting list is sorted as in “L”.

example

```
/**/ RandomSubset(["a","b","c","d","e","f","g","h"], 5);
["a", "c", "d", "f", "h"]

/**/ indent([RandomSubset(1..1000, 10) | i in 1..4]);
[
  [160, 182, 215, 219, 349, 588, 628, 811, 886, 905],
  [23, 103, 315, 451, 531, 539, 571, 846, 858, 876],
  [24, 230, 240, 278, 380, 421, 495, 505, 665, 788],
  [81, 274, 299, 378, 414, 616, 828, 844, 870, 946]
]

/**/ binomial(1000, 10); --> too many to fit in memory ;-
263409560461970212832400
```

See Also: [random\(I-18.3 pg.228\)](#), [subsets\(I-19.39 pg.270\)](#), [RandomSubsetIndices\(I-18.7 pg.230\)](#), [RandomTuple\(I-18.8 pg.230\)](#), [RandomTupleIndices\(I-18.9 pg.231\)](#)

I-18.7 RandomSubsetIndices

syntax

```
RandomSubsetIndices(N: INT, K: INT): LIST
```

Description

The function returns a random subset of “1..N” of cardinality “K”. See also “RandomSubset” ([I-18.6 pg.229](#)).

NOTE: the resulting list is sorted.

example

```
/**/ RandomSubsetIndices(10, 5);
[1, 3, 4, 6, 8]
```

See Also: [random\(I-18.3 pg.228\)](#), [subsets\(I-19.39 pg.270\)](#), [RandomSubset\(I-18.6 pg.229\)](#), [RandomTuple\(I-18.8 pg.230\)](#), [RandomTupleIndices\(I-18.9 pg.231\)](#)

I-18.8 RandomTuple

syntax

```
RandomTuple(L: LIST, K: INT): LIST
```

Description

The function returns a random tuple of “L” of cardinality “K”. This function can be quite useful for testing properties on some tuples of a large list when testing on all of them would be unfeasible in time and memory (see also “tuples” ([I-20.15 pg.284](#))).

example

```
/**/ RandomTuple(["a","b","c","d","e","f","g","h"], 5);
["b", "b", "h", "g", "e"]

/**/ indent([RandomTuple(-9..9, 10) | i in 1..4]);
[
  [-5, -3, 1, 8, -4, 6, -5, -7, -1, 1],
  [-5, -8, 0, -9, -2, -1, 3, -6, 6, -3],
```

```
[ -2, -2, -9, -5, 0, -6, 2, -6, -5, -8 ],
[ -2, -4, 4, 3, -3, 5, 3, -1, 8, -7 ]
]
```

See Also: [random\(I-18.3 pg.228\)](#), [subsets\(I-19.39 pg.270\)](#), [RandomSubset\(I-18.6 pg.229\)](#), [RandomSubsetIndices\(I-18.7 pg.230\)](#), [RandomTupleIndices\(I-18.9 pg.231\)](#)

I-18.9 RandomTupleIndices

syntax

```
RandomTupleIndices(N: INT, K: INT): LIST
```

Description

The function returns a random tuple of “1..N” of cardinality “K”. See also “RandomTuple” ([I-18.8 pg.230](#)).

example

```
/**/ RandomTupleIndices(32003, 10);
[4987, 13034, 10044, 7148, 11122, 1144, 21264, 5379, 2934, 7015]
```

See Also: [random\(I-18.3 pg.228\)](#), [subsets\(I-19.39 pg.270\)](#), [RandomSubset\(I-18.6 pg.229\)](#), [RandomSubsetIndices\(I-18.7 pg.230\)](#), [RandomTuple\(I-18.8 pg.230\)](#)

I-18.10 rank [OBSOLESCENT]

syntax

```
[OBSOLESCENT]
```

Description

See “rk” ([I-18.48 pg.249](#))

I-18.11 RationalAffinePoints

syntax

```
RationalAffinePoints(L: LIST of RINGELEM): LIST of LIST of RINGELEM
```

Description

This function returns the list of affine rational solutions (points) of a 0-dimensional polynomial system “L”. See also “RationalSolve” ([I-18.13 pg.232](#))

example

```
/**/ Use QQ[x,y,z];
/**/ L := [x^3-y^2+z-1, x-2, (y-3)*(y+2)];
/**/ RationalAffinePoints(L);
[[2, -2, -3], [2, 3, 2]]
```

See Also: [LinSolve\(I-12.14 pg.165\)](#), [RationalSolve\(I-18.13 pg.232\)](#)

I-18.12 RationalProjectivePoints

syntax

```
RationalProjectivePoints(L: LIST of RINGELEM): LIST of LIST of RINGELEM
```

Description

This function returns the list of projective rational solutions (points) of a 0-dimensional polynomial system “L”. See also “RationalSolve” ([I-18.13](#) pg.232)

example

```
/**/ Use QQ[x,y,z];
/**/ L := [x^3-y^2*x, x-2*z];
/**/ RationalProjectivePoints(L);
[[0, 1, 0], [1, -1, 1/2], [1, 1, 1/2]]
```

See Also: [LinSolve\(I-12.14](#) pg.165), [RationalSolve\(I-18.13](#) pg.232)

I-18.13 RationalSolve

syntax

```
RationalSolve(L: LIST of RINGELEM): LIST of LIST of RINGELEM
```

Description

This function returns the list of rational solutions (points) of a 0-dimensional polynomial system “L” (see also “ApproxSolve” ([I-1.14](#) pg.30)). Tries to be clever: if some indeterminates do not appear in “L” they are ignored, if the polynomials in “L” are homogeneous it returns the projective points.

example

```
/**/ Use QQ[x,y,z];
/**/ L := [x^3-y^2+z-1, x-2, (y-3)*(y+2)];
/**/ RationalSolve(L);
[[2, -2, -3], [2, 3, 2]]

/**/ L := [x^3-y^2+z-1, x^2-2, (y-3)*(y+2)];
/**/ RationalSolve(L);
[]
/**/ len(ApproxSolve(L));
4

/**/ L := [x^3-y^2+1, (y-3)*(y+2)]; -- ignores the indeterminate z
/**/ RationalSolve(L);
[[2, 3]]
```

See Also: [ApproxSolve\(I-1.14](#) pg.30), [LinSolve\(I-12.14](#) pg.165), [RationalAffinePoints\(I-18.11](#) pg.231), [RationalProjectivePoints\(I-18.12](#) pg.232)

I-18.14 RatReconstructByContFrac, RatReconstructByLattice

syntax

```
RatReconstructByContFrac(X: INT, M: INT): RECORD
RatReconstructByContFrac(X: INT, M: INT, threshold: INT): RECORD
RatReconstructByLattice(X: INT, M: INT): RECORD
RatReconstructByLattice(X: INT, M: INT, threshold: INT): RECORD
```


Description

These functions attempt to reconstruct rational numbers from a modular image “ $X \bmod M$ ”. The algorithms are fault-tolerant: they will succeed provided that “ X ” is correct modulo a sufficiently large factor of “ M ”.

NOTE: so that the heuristic can work, the modulus must be larger than strictly necessary; indeed, reconstruction always fails if “ M ” is small.

The result is a record: the boolean field “failed” is “true” if no “convincing” result was found; otherwise it is “false”, and a second field, called “ReconstructedRat”, contains the value reconstructed.

An optional third argument, “threshold”, determines what “convincing” means: a higher value gives a more reliable answer, but may need a larger modulus before the answer is found.

There are two different underlying heuristic algorithms: a faster one based on continued fractions, and a slower one based on 2-dimensional lattice reduction. See arXiv: “<http://arxiv.org/abs/1303.2965>”

example

```
/**/ X := 3333333333;
/**/ M := 10^10;
/**/ RatReconstructByContFrac(X,M);
record[ReconstructedRat := -1/3, failed := false]

/**/ X := 3141592654;
/**/ M := 10^10;
/**/ RatReconstructByContFrac(X,M);
record[failed := true]
```

See Also: RatReconstructWithBounds(I-18.16 pg.234), CRT(I-3.49 pg.60)

I-18.15 RatReconstructPoly

syntax

```
RatReconstructPoly(f1: RINGELEM, M1: INT): RINGELEM
```

Description

This function attempts to reconstruct the rational coefficients of a polynomial “ f ” from a modular image “ $f \bmod M$ ”. The algorithm is fault-tolerant: it will succeed provided that the coefficients in “ f ” are correct modulo a sufficiently large factor of “ M ”.

NOTE: so that the heuristic can work, the modulus must be larger than strictly necessary; indeed, reconstruction always fails if “ M ” is small.

example

```
/**/ RatReconstructPoly(-341269321*x^2 +255951993*y, 1023807973);
(10/3)*x^2 +(-1/4)*y

/**/ ReadExpr(NewPolyRing(NewRingFp(32003),"x,y"), "(10/3)*x^2 +(-1/4)*y");
10671*x^2 -8001*y
/**/ ReadExpr(NewPolyRing(NewRingFp(31991),"x,y"), "(10/3)*x^2 +(-1/4)*y");
10667*x^2 -7998*y

/**/ CRTPoly(10671*x^2 -8001*y, 32003, 10667*x^2 -7998*y, 31991);
record[modulus := 1023807973, residue := -341269321*x^2 +255951993*y]
```

See Also: CRTPoly(I-3.50 pg.61), RatReconstructByContFrac, RatReconstructByLattice(I-18.14 pg.232)

I-18.16 RatReconstructWithBounds

syntax

```
RatReconstructWithBounds(e: INT, P: INT, Q: INT, res: LIST of INT, mod: LIST of INT): RECORD
```

Description

This function attempts to reconstruct a rational number from a collection of residue-modulus pairs “(res[i],mod[i])”. The function also requires the input of three bounds: “e” is an upper bound on the number of bad moduli, and “P” and “Q” are upper bounds for (respectively the numerator and denominator of) the rational to be reconstructed.

The result is a record: the boolean field “failed” is “true” if no result exists; otherwise it is “false”, and a second field, called “ReconstructedRat”, contains the value reconstructed.

example

```
/**/ moduli := [11,13,15,17,19];
/**/ residues := [-2, -5, 0, 7, 4];
/**/ RatReconstructWithBounds(1,10,10,residues,moduli);
record[ReconstructedRat := 1/5, failed := false]

/**/ RatReconstructWithBounds(0,10,10,residues,moduli);
record[failed := true]
```

See Also: CRT([I-3.49](#) pg.60), RatReconstructByContFrac, RatReconstructByLattice([I-18.14](#) pg.232)

I-18.17 ReadExpr

syntax

```
ReadExpr(R: RING, expr: STRING): RINGELEM
```

Description

This function reads a “RINGELEM” expression from a “STRING”. It is handy to input elements defined in different rings without calling “use” ([I-21.6](#) pg.287).

example

```
/**/ P := QQ[a,b];
/**/ S := NewPolyRing(NewFractionField(P), "x,y");
/**/ ReadExpr(S, "(a^2-b^2)*(x+y)/(a+b)");
(a -b)*x +(a -b)*y
```

See Also: RingElem([I-18.39](#) pg.244)

I-18.18 RealRootRefine

syntax

```
RealRootRefine(Root: RECORD, Precision: RAT): RECORD
```

Description

This function computes a refinement of a real root of a univariate polynomial over QQ to the desired precision (width of isolating interval). The starting root must be a record produced by “RealRoots” ([I-18.19](#) pg.235).

example

```

/**/ RR := RealRoots(x^2-2);
/**/ RealRootRefine(RR[1], 1/2);
record[CoeffList := [-1, 0, 2], inf := -3/2, sup := -5/4]

/**/ RR := [RealRootRefine(Root, 10^(-20)) | Root In RR];
/**/ FloatStr(RR[1].inf);
-1.414213562*10^0

```

See Also: [RealRoots\(I-18.19 pg.235\)](#), [RealRootsApprox\(I-18.20 pg.236\)](#), [RootBound\(I-18.50 pg.249\)](#)

I-18.19 RealRoots

syntax

```

RealRoots(F: RINGELEM): LIST
RealRoots(F: RINGELEM, Precision: RAT): LIST
RealRoots(F: RINGELEM, Precision: RAT, Interval:[RAT, RAT]): LIST

```

Description

This function computes isolating intervals for the real roots of a univariate polynomial over $\mathbb{Q}\mathbb{Q}$. It returns the list of the real roots, where a root is represented as a record containing either the exact root (if the fields “inf” and “sup” are equal), or an open interval (inf, sup) containing the root. A third field (called CoeffList) has an obscure meaning.

An optional second argument specifies the maximum width an isolating interval may have. An optional third argument specifies a closed interval in which to search for roots.

The interval represented by a root record may be refined by using the function “RealRootRefine” ([I-18.18 pg.234](#)). The function “RealRootsApprox” ([I-18.20 pg.236](#)) may be more useful to you: it produces rational approximations to the real roots (but these cannot later be refined).

example

```

/**/ indent(RealRoots(x^2-2));
[
  record[CoeffList := [-1, 0, 2], inf := -4, sup := 0],
  record[CoeffList := [1, 0, -2], inf := 0, sup := 4]
]

/**/ RR := RealRoots((x^2-2)*(x-1), 10^(-5));
/**/ FloatStr(RR[1].inf); -- left end of interval
-1.414213562*10^0

/**/ FloatStr(RR[1].sup); -- right end of interval
-1.414213561*10^0

/**/ RR := RealRoots(x^2-2, 10^(-20), [0, 2]);

/**/ RR[1].inf; -- incomprehensible
60153992292001127886258443119406264231/42535295865117307932921825928971026432
/**/ FloatStr(RR[1].inf, 20); -- comprehensible
1.4142135623730950488*10^0

```

See Also: [RealRootRefine\(I-18.18 pg.234\)](#), [RealRootsApprox\(I-18.20 pg.236\)](#), [RootBound\(I-18.50 pg.249\)](#)

I-18.20 RealRootsApprox

syntax

```
RealRootsApprox(F: RINGELEM): LIST
RealRootsApprox(F: RINGELEM, Precision: RAT): LIST
RealRootsApprox(F: RINGELEM, Precision: RAT, Interval:[RAT, RAT]): LIST
```

Description

This function computes rational approximations to the real roots of a univariate polynomial (with rational coefficients).

An optional second argument specifies the maximum separation between the approximations produced and the corresponding exact root. An optional third argument specifies a closed interval in which to search for roots.

example

```
/**/ RealRootsApprox(x^2-2);
[-3037000499/2147483648, 3037000499/2147483648]

/**/ RR := RealRootsApprox(x^2-2, 10^(-15), [0, 2]);
/**/ RR;
[6521908912666391107/4611686018427387904]

/**/ FloatStr(RR[1], 15);
1.41421356237310*10^0
```

See Also: [RealRoots\(I-18.19 pg.235\)](#), [RootBound\(I-18.50 pg.249\)](#)

I-18.21 record

syntax

```
record[F_1 := OBJECT, ..., F_n := OBJECT]
  where each F_i is a field name
  returns RECORD
```

Description

This constructor creates a record with fields called “F₁”, ..., “F_n”. The empty record is given by “`record[]`”.

Records in CoCoA are “*open*” in the sense that new fields may be added after the record is first defined. The names allowed for the fields are the same as those allowed for variables.

The dot operator is used to access the fields in a record.

example

```
/**/ P := record[height := 10, width := 5];
/**/ P.height * P.width;
50

/**/ P.area := It; --> creates a new field called "area"
/**/ P;
record[area := 50, height := 10, width := 5]
```

See Also: [record field selector\(I-18.22 pg.237\)](#), [fields\(I-6.5 pg.87\)](#)

I-18.22 record field selector

syntax

```
R.FieldName
R["FieldName"]
  where R is a RECORD
```

Description

A record is a data structure containing named entries. They are created using the command “**record**” (I-18.21 pg.236). Each entry may be selected using the “dot operator”, or equivalently a string index.

example

```
/**/ rec := record[name := "David", year := 1961];
/**/ rec.name;
David

/**/ rec.year := 1849;           --> change value of a field
/**/ rec.surname := "Copperfield"; --> create a new field
/**/ rec["year"]; -- alternative syntax
1849

/**/ foreach F in fields(rec) do print rec[F]; endforeach;
DavidCopperfield1849
```

See Also: [record\(I-18.21 pg.236\)](#)

I-18.23 ReducedGBasis

syntax

```
ReducedGBasis(I: IDEAL): LIST of RINGELEM
ReducedGBasis(I: MODULE): LIST of MODULEELEM
```

Description

This function returns a list whose components form a reduced Groebner basis for the ideal (or module) “I” with respect to the term-ordering of the polynomial ring of “I”.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x^4-x^2, x^3-y);
/**/ ReducedGBasis(I);
[x*y -y^2, x^2 -y^2, y^3 -y]
```

See Also: [GBasis\(I-7.1 pg.97\)](#)

I-18.24 ref

syntax

```
ref X
  where X is the identifier of a CoCoA variable.
```

Description

The keyword “**ref**” is used to pass a parameter “by reference” to a function which may modify its value (e.g. “**append**” (I-1.12 pg.30)). The keyword “**ref**” alerts the programmer to the possibility that the value may be changed during the call.

To write a new function which can modify some parameters use the same keyword “**ref**” to identify which formal parameters are to be passed by reference. The following example illustrates the difference between passing by reference and passing by value.

example

```

/**/ Define CallByRef(ref L) -- "call by reference": The variable referred
/**/   L := "new value";      -- to by L is changed.
/**/ EndDefine;
/**/ M := "old value";
/**/ CallByRef(ref M); -- here "ref" recalls that M might change
/**/ PrintLn M;
new value

/**/ Define CallByVal(L) -- "call by value": The value of L is passed to
/**/   L := "new value"; -- the function.
/**/   Return L;
/**/ EndDefine;
/**/ L := "old value";
/**/ CallByVal(L);
new value

/**/ PrintLn L;
old value

```

See Also: [define\(I-4.4 pg.64\)](#)

I-18.25 RefineGCDFreeBasis

syntax

```
RefineGCDFreeBasis(B: LIST of INT, N: INT): LIST of INT
```

Description

This function computes a refined GCD free basis by adjoining a given integer to it. The value returned is [NewB, N2] where NewB is the refined basis and N2 is the part of N coprime to every element of B.

example

```

/**/ B := GCDFreeBasis([Fact(10), binomial(20,10)]); B;
[14175, 4, 46189]

/**/ RefineGCDFreeBasis(B, 15);
[[7, 3, 5, 4, 46189], 1]

```

See Also: [GCDFreeBasis\(I-7.5 pg.99\)](#)

I-18.26 reg

syntax

```

reg(I: IDEAL): INT
reg(R: (Quotient)RING): INT

```

Description

These functions computes the Castelnuovo-Mumford regularity of an ideal. The implementation of “Reg” using Bermejo-Gimenez Algorithm.

Implemented by Eduardo Saenz-de-Cabezón (updated to CoCoA-5 by Anna M. Bigatti).

NOTE: this is different from “RegularityIndex” (I-18.27 pg.239), the regularity of a Hilbert Function.

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x^3, y^2);
/**/ reg(I);
4
/**/ reg(R/I);
3
/**/ PrintRes(I);
0 --> R(-5) --> R(-2)(+)R(-3)

/**/ PrintBettiDiagram(I);
      0      1
-----
2:    1      -
3:    1      -
4:    -      1
-----
Tot:   2      1

```

See Also: res(I-18.32 pg.241), PrintRes(I-16.30 pg.219), PrintBettiDiagram(I-16.27 pg.218), PrintBettiMatrix(I-16.28 pg.219), RegularityIndex(I-18.27 pg.239)

I-18.27 RegularityIndex

syntax

```
RegularityIndex(R: RING or TAGGED("Quotient")): INT
```

Description

This function computes the regularity index of a Hilbert function. The input might be expressed as a Hilbert function or as the corresponding Hilbert series (computed with standard weights).

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ Quot := R/ideal(x^3, y^2);
/**/ HilbertFn(Quot);
H(0) = 1
H(1) = 3
H(2) = 5
H(t) = 6   for t >= 3
/**/ RegularityIndex(HilbertFn(Quot));
3
/**/ RegularityIndex(HilbertSeries(Quot));
3

```

See Also: HilbertFn(I-8.5 pg.109), HilbertSeries(I-8.7 pg.110)

I-18.28 RelNotes

syntax

```
RelNotes()
```

Description

This function prints the release notes of the version you are running.

example

```
RelNotes();
```

I-18.29 ReloadMan

syntax

```
ReloadMan()
```

Description

This function reloads the xml source of the manual “CoCoAHelp.xml” (in directory “CoCoAManual”) and recreates the internal manual index in a running CoCoA-5 (instead of closing and re-opening CoCoA....).

It is useful “*only for developers*” working on the manual and making substantial changes to “CoCoAHelp.xml”.

After adding a new entry the index needs updating, but if the change is just in the description of an existing entry (so the internal index is still valid) there is no need to reload the manual: the description is always searched in the current file.

example

```
/**/ ReloadMan();
```

I-18.30 remove

syntax

```
remove(ref L:LIST, N: INT)
```

Description

This function removes the “N”-th component from “L”; it changes the value of “L”. Use the function “WithoutNth” ([I-23.4 pg.292](#)) to create a new list containing the elements of “L” except the “N”-th (without changing “L”).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ L := indets(R);
/**/ L;
[x, y, z]

/**/ remove(ref L,2);
/**/ L;
[x, z]
```

See Also: WithoutNth([I-23.4 pg.292](#))

I-18.31 repeat

syntax

```
repeat C until B
repeat C endrepeat
(where C is a sequence of commands and B is BOOL)
```

Description

In the first form, the command sequence “C” is repeated until “B” evaluates to “false”. Unlike the “while” (I-23.3 pg.292) command, “C” is executed at least once. Note that there is no “endrepeat” following “B”.

example

```
/**/      Define GCD_Euclid(A, B)
/**/      Repeat
/**/          R := mod(A, B);
/**/          A := B;
/**/          B := R;
/**/      Until B = 0;
/**/      Return A;
/**/      EndDefine;

/**/  GCD_Euclid(6,15);
3

/**/  N := 0;
/**/  repeat
/**/      N := N+1;
/**/      PrintLn N;
/**/      If N > 5 Then Break; EndIf;
/**/  endrepeat;
1
2
3
4
5
```

See Also: for(I-6.15 pg.91), foreach(I-6.16 pg.92), while(I-23.3 pg.292)

I-18.32 res

syntax

```
res(M: IDEAL): LIST
res(M: MODULE): LIST
```

Description

This function returns the minimal free resolution of “M”. “res” only works in the homogeneous context, and the coefficient ring must be a field.

NOTE: the current implementation (CoCoA-5.1.0) is very naive so it might be very slow (better slow than nothing?).

example

```
/**/  Use R ::= QQ[x,y,z];
/**/  I := ideal(x, y, z^2);
```

```

/**/ PrintRes(R/I);
0 --> R(-4) --> R(-2)(+)R(-3)^2 --> R(-1)^2(+)R(-2) --> R
/**/ indent(Res(R/I),2);
[
  RingWithID(20, "RingWithID(3)/ideal(x, y, z^2)"),
  ideal(
    y,
    x,
    z^2
  ),
  SubmoduleRows(F, matrix([
    [x, -y, 0],
    [0, z^2, -x],
    [z^2, 0, -y]
  ])),
  SubmoduleRows(F, matrix([
    [z^2, y, -x]
  ]))
]

```

See Also: [PrintBettiDiagram\(I-16.27 pg.218\)](#), [PrintBettiMatrix\(I-16.28 pg.219\)](#), [PrintRes\(I-16.30 pg.219\)](#)

I-18.33 Reset [OBSOLETE]

[OBSOLETE] syntax

Description

[OBSOLETE]

I-18.34 ResetPanels [OBSOLETE]

[OBSOLETE] syntax

Description

[OBSOLETE]

I-18.35 resultant

syntax
 resultant(F: RINGELEM, G: RINGELEM, X: RINGELEM): RINGELEM

Description

This function returns the resultant of the polynomials F and G with respect to the indeterminate X.

example

```

/**/ Use R ::= QQ[p,q,x];
/**/ F := x^3+p*x-q;   G := deriv(F, x);
/**/ resultant(F, G, x);
4*p^3 +27*q^2

```

See Also: [discriminant\(I-4.18 pg.72\)](#), [sylvester\(I-19.45 pg.273\)](#)

I-18.36 *return*

syntax

```

return
return E

```

Description

This command is used to exit from a procedure/function. The latter form returns the value of the expression E to the user. As a safety measure all “**return**”s in a function/procedure must be of the same kind: either they all return a value (function) or none returns a value (procedure). To exit from a loop see “**break**” ([I-2.11 pg.38](#)).

example

```

/**/ Define Rev(L) -- reverse a list
/**/   If len(L) < 2 Then Return L; EndIf;
/**/   M := Rev(Tail(L)); -- recursive function call
/**/   append(ref M, L[1]);
/**/   Return M;
/**/ EndDefine;

/**/ Rev([1,2,3,4]);
[4, 3, 2, 1]

---- mixing function/procedure returns is not allowed
-- /**/ Define AFailingExample(X)
-- /**/   If X=1 Then Return 123456;
-- /**/   Else Return; -- ..... --> !!! ERROR !!!
ERROR: Inside a function definition all Return statements must be
either with or without an expression
    Else Return;
    ~~~~~

```

See Also: [break\(I-2.11 pg.38\)](#), [define\(I-4.4 pg.64\)](#)

I-18.37 *reverse, reversed*

syntax

```

reverse(ref L: LIST)
reversed(L: LIST): LIST

```

Description

The the function “**reverse**” reverses the order of the elements of the list in “L”; it changes the value of “L” and returns nothing. The function “**reversed**” returns the reversed list without changing “L”.

example

```

/**/ L := [1,2,3,4];
/**/ reverse(ref L);
/**/ L; -- L has been modified
[4, 3, 2, 1]

/**/ M := [1,2,3,4];
/**/ reversed(M); -- the reversed list is returned
[4, 3, 2, 1]

/**/ M; -- M has not been modified
[1, 2, 3, 4]

```

See Also: [sort\(I-19.18 pg.260\)](#), [sorted\(I-19.20 pg.261\)](#)

I-18.38 RevLexMat

syntax

```
RevLexMat(N: INT): MAT
```

Description

This function return the matrix defining a standard ordering (which is not a term-ordering!).

example

```

/**/ RevLexMat(3);
matrix(ZZ,
  [[0, 0, -1],
   [0, -1, 0],
   [-1, 0, 0]])

```

See Also: [OrdMat\(I-15.10 pg.205\)](#), [Orderings\(III-9.5 pg.360\)](#), [StdDegRevLexMat\(I-19.32 pg.267\)](#), [StdDegLexMat\(I-19.31 pg.266\)](#), [LexMat\(I-12.6 pg.161\)](#), [XelMat\(I-24.1 pg.295\)](#)

I-18.39 RingElem

syntax

```

RingElem(R: RING, E: RINGELEM): RINGELEM
RingElem(R: RING, E: INT): RINGELEM
RingElem(R: RING, E: RAT): RINGELEM
RingElem(R: RING, E: STRING): RINGELEM
RingElem(R: RING, E:[STRING, INT, .., INT]): RINGELEM

```

Description

This function converts the expression E into a RINGELEM in R, if possible.

Can be used for mapping ring element between rings when a “[CanonicalHom](#)” ([I-3.2 pg.41](#)) exists. For other homomorphisms search see “[RINGHOM](#)” ([III-10 pg.365](#)).

In some cases “[ReadExpr](#)” ([I-18.17 pg.234](#)) may be handier: it reads a whole expression without function calls from a “[STRING](#)”.

example

```

/**/ Use P ::= QQ[x,y,z];
/**/ -- RINGELEM (via CanonicalHom)

```

```

/**/ F := 2*x-3;
-- /**/ F/LC(F); -- !!! ERROR !!! LC(F) in CoeffRing(P)
/**/ F/RingElem(P,LC(F));
x +1
-- /**/ 1/x; -- !!! ERROR !!! x in P is not invertible
/**/ K := NewFractionField(P);
/**/ 1/RingElem(K, x); -- x in K is invertible
1/x

/**/ Use P ::= ZZ/(5)[x,y,z];
/**/ -- INT and RAT
/**/ RingElem(P, 7);
2
/**/ RingElem(P, 3/2);
-1

/**/ -- STRING (indet name, symbol)
/**/ S := QQ[x,y,z[1..4,3..7]];
/**/ 7*RingElem(P, "x"); --> x as an element of P
2*x
/**/ 7*RingElem(S, "x"); --> x as an element of S
7*x
/**/ 7*RingElem(S, ["z",2,5]);
7*z[2,5]
/**/ ReadExpr(S, "((7/3)*z[2,5] - 1)^2"); -- expr without function calls
49*z[2,5]^2 -14*z[2,5] +1

```

See Also: [RingOf\(I-18.42 pg.246\)](#), [AsINT\(I-1.16 pg.32\)](#), [AsRAT\(I-1.17 pg.32\)](#), [IndetName\(I-9.21 pg.127\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [CanonicalHom\(I-3.2 pg.41\)](#), [ReadExpr\(I-18.17 pg.234\)](#)

I-18.40 *RingEnv* [OBSOLETE]

syntax

[OBSOLETE]

Description

See “[RingOf](#)” ([I-18.42 pg.246](#)).

See Also: [RingOf\(I-18.42 pg.246\)](#)

I-18.41 *RingID*

syntax

`RingID(R: RING): INT`

Description

This function returns the identification number of the ring “*R*”. Two rings are considered equal if and only if they have the same ID: this means they have the same internal implementation.

This function was called “ID” in CoCoA-5.1.1.

example

```

/**/ R := QQ[x,y,z];
/**/ R;
RingWithID(9, "QQ[x,y,z]")
/**/ S := QQ[x,y,z];
/**/ R = S;
false
/**/ RingID(R);
7
/**/ RingID(S);
8
-- /**/ RingElem(R,"x") = RingElem(S, "x"); --> !!! ERROR !!! mixed rings

/**/ S := R; -- or S := RingOf( some element in R )
/**/ R = S;
true

```

See Also: [print\(I-16.25 pg.217\)](#), [println\(I-16.29 pg.219\)](#), [Evaluation and Assignment\(II-4 pg.311\)](#)

I-18.42 RingOf

syntax

```
RingOf(E: RINGELEM|IDEAL|MAT|MODULE): RING
```

Description

This function returns the ring on which the object “E” is defined.

NOTE: A ring contains many information and two separate rings, even when defined with the same commands, are not “equal”. When a ring is printed only a few informations are shown, so different rings might look the same.

example

```

/**/ Use R := QQ[x,y,z];
/**/ I := ideal(x,y);
/**/ RingOf(I);
RingWithID(6, "QQ[x,y,z]")

/**/ RingOf(mat([[1,2],[3,4]]));
QQ

/**/ Use Qabc := QQ[a,b,c];
/**/ F := a^2+b;
/**/ G := a*b+b^2;
/**/ Use S := ZZ/(3)[x,y];
/**/ RingOf(F+G); -- F+G is computed in the ring of definition
RingWithID(7, "QQ[a,b,c]")
/**/ indets(RingOf(F));
[a, b, c]

```

See Also: [CurrentRing\(I-3.51 pg.61\)](#), [RingsOf\(I-18.46 pg.248\)](#), [BaseRing\(I-2.1 pg.33\)](#)

I-18.43 RingQQ

syntax

```
RingQQ(): RING
```

Description

This function returns the ring of rationals. It is particularly useful when you want to use “QQ” (which is a pre-defined top-level “*variable*”) inside a function.

NOTE: calling “RingQQ” twice gives the same identical ring, whereas calling “NewPolyRing” (I-14.8 pg.188) and “NewFractionField” (I-14.1 pg.185) return each time a new ring.

— example —

```
/**/ QQ = RingQQ();

/**/ Two := RingElem(RingQQ(), 2);  Two;
2
/**/ type(Two);
RINGELEM;
/**/ IsQQ(RingOf(Two));
true
```

See Also: TopLevel(I-20.10 pg.280), QQ(I-17.1 pg.223), RingQQt(I-18.44 pg.247), RingZZ(I-18.47 pg.248)

I-18.44 RingQQt

— syntax —

```
RingQQt(N: INT): RING
```

Description

This function returns a polynomial ring over “QQ” with indeterminates $t[1] \dots t[N]$. In particular “RingQQt(1)” is the polynomial ring in which Hilbert polynomials are defined.

NOTE: calling “RingQQt(5)” twice gives the same identical ring, whereas calling “NewPolyRing(RingQQ(), SymbolRange(” returns each time a new ring (therefore incompatible).

— example —

```
/**/ QQt := RingQQt(3);  Use QQt;
/**/ (t[1]+1)^3;
t[1]^3 +3*t[1]^2 +3*t[1] +1
/**/ indets(RingQQt(1));
[t]
/**/ indets(RingQQt(5));
[t[1], t[2], t[3], t[4], t[5]]
```

See Also: TopLevel(I-20.10 pg.280), RingQQ(I-18.43 pg.246), RingZZ(I-18.47 pg.248)

I-18.45 RingSet [OBSOLETE]

— syntax —

```
[OBSOLETE]
```

Description

This function has just been renamed “RingsOf” (I-18.46 pg.248) **See Also:** RingsOf(I-18.46 pg.248)

I-18.46 RingsOf

syntax

`RingsOf(E: LIST|RINGELEM|IDEAL|MAT|MODULE|MODULEELEM): LIST of RING and TYPE`

Description

This function returns the list of the RINGs (or types, if not dependent from a RING) on which the object E is dependent. Similar to “RingOf” (I-18.42 pg.246), this function also works on lists and returns the set of ring environments of all entries. ...needless to say that it may be quite slow on big inputs!

example

```

/**/ Use R ::= QQ[x,y,z];
/**/ L1 := [x, y];
/**/ L2 := [x, y, 0, 5/4];
/**/ Z3 := NewRingFp(3);
/**/ Use S ::= Z3[a,b];
/**/ RingsOf(L1);
[RingDistrMPolyClean(QQ, 3)]

/**/ RingsOf(L2);
[RingDistrMPolyClean(QQ, 3), INT, RAT]

/**/ RingsOf([L2, a+b]);
[RingDistrMPolyClean(QQ, 3), INT, RAT, RingDistrMPolyClean(FFp(3), 2)]

```

See Also: `CurrentRing`(I-3.51 pg.61), `RingOf`(I-18.42 pg.246)

I-18.47 RingZZ

syntax

`RingZZ(): RING`

Description

This function returns the ring of integers. It is useful when you want to use “ZZ” (I-25.4 pg.298) inside “define/enddefine”.

NOTE: calling “RingZZ” twice gives the same identical ring, whereas calling “NewPolyRing” (I-14.8 pg.188) or “NewFractionField” (I-14.1 pg.185) return each time a new ring.

example

```

/**/ Two := RingElem(RingZZ(), 2); Two;
2
/**/ type(Two);
RINGELEM;
/**/ IsZZ(RingOf(Two));
true
/**/ IsQQ(RingOf(Two));
false

```

See Also: `TopLevel`(I-20.10 pg.280), `RingQQt`(I-18.44 pg.247), `RingQQ`(I-18.43 pg.246), `ZZ`(I-25.4 pg.298)

I-18.48 rk

syntax

```
rk(M: MAT): INT
rk(M: MODULE): INT
```

Description

This function computes the rank of “M”. For a module “M” this is defined as the vector space dimension of the subspace generated by the generators of “M” over the quotient field of the base ring – contrast this with the function “NumCompts” ([I-14.33](#) pg.198) which simply counts the number of components the module has.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ rk(IdentityMat(R, 4));
4

rk(Module([x,y,z,0])); --***WORK IN PROGRESS***
1
-----
rk(Module([[1,2,3],[2,4,6]])); --***WORK IN PROGRESS***
1
-----
rk(Module([[1,2,3],[2,5,6]])); --***WORK IN PROGRESS***
2
-----
```

I-18.49 RMap [OBSOLESCENT]

syntax

```
[OBSOLESCENT] RMap(L: LIST): TAGGED("RMap")
```

Description

[OBSOLESCENT] related with “image [OBSOLESCENT]” ([I-9.10](#) pg.121). In CoCoA-5 such homomorphisms are properly implemented as “PolyAlgebraHom” ([I-16.14](#) pg.211).

I-18.50 RootBound

syntax

```
RootBound(F: RINGELEM): INT
```

Description

This function computes a bound on the absolute values of the complex roots of a univariate polynomial over QQ. In some cases you may get a better bound by applying the transformation produced by “LinearSimplify”.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ RootBound(x^2-2);
4
```

See Also: [LinearSimplify\(I-12.9 pg.163\)](#), [RealRootRefine\(I-18.18 pg.234\)](#), [RealRoots\(I-18.19 pg.235\)](#)

I-18.51 round

— syntax —

```
round(X: RAT): INT
```

Description

This function rounds a rational to the nearest integer; halves are rounded towards zero.

— example —

```
/**/ round(4.56);
5

/**/ round(-1/2);
0
```

See Also: num([I-14.31](#) pg.198), den([I-4.7](#) pg.67), floor([I-6.12](#) pg.90), ceil([I-3.6](#) pg.43)

I-18.52 RowMat

— syntax —

```
RowMat(L: LIST): MAT
RowMat(R: RING, L: LIST): MAT
```

Description

This function return the matrix whose only row consists of the elements of the list L.

— example —

```
/**/ RowMat([3,4,5]);
matrix(QQ,
  [[3, 4, 5]])

/**/ RowMat(QQ, [5,6,7]);
matrix(QQ,
  [[5, 6, 7]])
```

See Also: BlockMat([I-2.8](#) pg.37), DiagMat([I-4.15](#) pg.71), ColMat([I-3.26](#) pg.51)

Chapter I-19

S

I-19.1 saturate

— syntax —

```
saturate(I: IDEAL, J: IDEAL): IDEAL
```

Description

This function returns the saturation of I with respect to J: the ideal of polynomials F such that $F^d G$ is in I for all G in J^d for some positive integer d.

The coefficient ring must be a field.

— example —

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x-z, y-2*z);
/**/ J := ideal(x-2*z, y-z);
/**/ K := intersection(I, J); -- ideal of two points in the
                             -- projective plane
/**/ L := intersection(K, ideal(x,y,z)^3); -- add an irrelevant component
/**/ HilbertFn(R/L);
H(0) = 1
H(1) = 3
H(2) = 6
H(t) = 2 for t >= 3

/**/ saturate(L, ideal(x,y,z)) = K; -- saturating gets rid of the
                                     -- irrelevant component
true
```

See Also: [colon\(I-3.27 pg.52\)](#), [HColon\(I-8.1 pg.107\)](#), [HSaturation\(I-8.12 pg.113\)](#)

I-19.2 ScalarProduct

— syntax —

```
ScalarProduct(L, M): OBJECT
  where each of L and M is of type MODULEELEM or LIST
```

Description

This function returns the sum of the product of the components of L and M; precisely $(\text{len}(L)=\text{len}(M))$:

$\text{ScalarProduct}(L, M) = \text{sum}([L[I]*M[I] \text{ --- } I \text{ In } 1..\text{len}(L)]).$

The function works whenever the product of the components of L and M are defined (see “Algebraic Operators” (II-3.2 pg.307)).

example

```
/**/  ScalarProduct([1,2,3], [5,0,-1]);
2

    Use R ::= QQ[x,y];
    ScalarProduct([ideal(x,y), ideal(x^2-xy)], [x^2,y]);
ideal(x^3, x^2y, x^2y - xy^2)
-----
```

See Also: Algebraic Operators(II-3.2 pg.307)

I-19.3 ScientificStr

syntax

```
ScientificStr(X: INT|RAT|RINGELEM): STRING
ScientificStr(X: INT|RAT|RINGELEM, Prec: INT): STRING
```

Description

This function converts a rational number “X” into a (decimal) floating-point string. The optional second argument “Prec” says how many decimal digits to include in the mantissa; the default value is 5. Note that an exponent is always included.

example

```
/**/  ScientificStr(2/3);      -- last printed digit is rounded
6.6667*10^(-1)

/**/  ScientificStr(7^510);    -- no arbitrary limit on exponent range
1.0000*10^431

/**/  ScientificStr(1/81, 50); -- precision of mantissa specified by user
1.2345679012345679012345679012345679012345679012345679012346*10^(-2)

/**/  ScientificStr(1/2);      -- trailing zeroes are not suppressed
5.0000*10^(-1)
```

See Also: DecimalStr(I-4.3 pg.63), FloatStr(I-6.11 pg.89), FloatApprox(I-6.10 pg.89), MantissaAndExponent10(I-13.6 pg.171)

I-19.4 seed

syntax

```
Seed(N: INT): INT
```

Description

***** NOT YET IMPLEMENTED *****

This function seeds the random number generator, “random” (I-18.3 pg.228).

NOTE: every time you restart CoCoA the sequence of random numbers will be the same (as happens in many programming languages). If you want better randomness, see the example below.

example

```

Seed(5);
Rand();
1991603592
-----

Rand();
-1650270230
-----

Seed(5); -- with the same seed, "Rand" generates the same sequence
Rand();
1991603592
-----

Rand();
-1650270230
-----

-- Better randomness:
-- the following shows how to make a random seed based on the date.
D := Date();
D;
Mon Mar 02 14:43:44 1998
-----

Seed(Sum(Ascii(D)));

```

See Also: [random\(I-18.3 pg.228\)](#)

I-19.5 SeparatorsOfPoints

syntax

```
SeparatorsOfPoints(Points: LIST): LIST
```

where Points is a list of lists of coefficients representing a set of ‘‘{\it distinct}’’ points in affine space.

Description

***** NOT YET IMPLEMENTED *****

This function computes separators for the points: that is, for each point a polynomial is determined whose value is 1 at that point and 0 at all the others. The separators yielded are reduced with respect to the reduced Groebner basis which would be found by “[IdealOfPoints](#)” ([I-9.5 pg.118](#)).

NOTE:

- * the current ring must have at least as many indeterminates as the dimension of the space in which the points lie;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * the separators are in the same order as the points (i.e. the first separator is the one corresponding the first point, and so on);
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

```
S := SeparatorsOfPoints(Pts);
```

```

Foreach Element In S Do
  PrintLn Element;
EndForeach;

```

For separators of points in projective space, see “SeparatorsOfProjectivePoints” (I-19.6 pg.254).

example

```

Use R ::= QQ[x,y];
Points := [[1, 2], [3, 4], [5, 6]];
S := SeparatorsOfPoints(Points); -- compute the separators
S;
[1/8y^2 - 5/4y + 3, -1/4y^2 + 2y - 3, 1/8y^2 - 3/4y + 1]
-----
[[Eval(F, P) | P In Points] | F In S]; -- verify separators
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
-----

```

See Also: GenericPoints(I-7.6 pg.99), IdealAndSeparatorsOfPoints(I-9.3 pg.116), IdealAndSeparatorsOfProjectivePoints(I-9.4 pg.117), IdealOfPoints(I-9.5 pg.118), IdealOfProjectivePoints(I-9.6 pg.119), Interpolate(I-9.28 pg.131), SeparatorsOfProjectivePoints(I-19.6 pg.254)

I-19.6 SeparatorsOfProjectivePoints

syntax

```
SeparatorsOfProjectivePoints(Points: LIST): LIST
```

where Points is a list of lists of coefficients representing a set of ‘‘{\it distinct}’’ points in projective space.

Description

***** NOT YET IMPLEMENTED *****

This function computes separators for the points: that is, for each point a homogeneous polynomial is determined whose value is non-zero at that point and zero at all the others. (Actually, choosing the values listed in Points as representatives for the homogeneous coordinates of the corresponding points in projective space, the non-zero value will be 1.) The separators yielded are reduced with respect to the reduced Groebner basis which would be found by “IdealOfProjectivePoints” (I-9.6 pg.119).

NOTE:

- * the current ring must have at least one more indeterminate than the dimension of the projective space in which the points lie, i.e, at least as many indeterminates as the length of an element of the input, Points;
- * the base field for the space in which the points lie is taken to be the coefficient ring, which should be a field;
- * in the polynomials returned the first coordinate in the space is taken to correspond to the first indeterminate, the second to the second, and so on;
- * the separators are in the same order as the points (i.e. the first separator is the one corresponding the first point, and so on);
- * if the number of points is large, say 100 or more, the returned value can be very large. To avoid possible problems when printing such values as a single item we recommend printing out the elements one at a time as in this example:

```

S := SeparatorsOfProjectivePoints(Pts);
Foreach Element In S Do
  PrintLn Element;
EndForeach;

```

For separators of points in affine space, see “[SeparatorsOfPoints](#)” ([I-19.5](#) pg.253).

example

```
Use R ::= QQ[x,y,z];
Points := [[0,0,1],[1/2,1,1],[0,1,0]];
S := SeparatorsOfProjectivePoints(Points);
S;
[-2x + z, 2x, -2x + y]
-----
[[Eval(F, P) | P In Points] | F In S];  -- verify separators
[[1, 0, 0], [0, 1, 0], [0, 0, 1]]
-----
```

See Also: [GenericPoints](#)([I-7.6](#) pg.99), [IdealAndSeparatorsOfPoints](#)([I-9.3](#) pg.116), [IdealAndSeparatorsOfProjectivePoints](#)([I-9.4](#) pg.117), [IdealOfPoints](#)([I-9.5](#) pg.118), [IdealOfProjectivePoints](#)([I-9.6](#) pg.119), [Interpolate](#)([I-9.28](#) pg.131), [SeparatorsOfPoints](#)([I-19.5](#) pg.253)

I-19.7 SetRow

syntax

```
SetRows(ref M: MAT, i: INT, L: LIST)
```

Description

This procedure sets the elements in “L” as entries of the “i”-th row in the matrix “M”; it returns nothing!

example

```
/**/ M := IdentityMat(QQ, 5);
/**/ SetRow(ref M, 1, [2,3,4,0,0]);
/**/ M;
matrix(QQ,
  [[2, 3, 4, 0, 0],
   [0, 1, 0, 0, 0],
   [0, 0, 1, 0, 0],
   [0, 0, 0, 1, 0],
   [0, 0, 0, 0, 1]])
```

See Also: [ref](#)([I-18.24](#) pg.237), [GetRow](#)([I-7.15](#) pg.104), [SwapRows](#)([I-19.44](#) pg.272)

I-19.8 SetStackSize

syntax

```
SetStackSize(NewSize: INT)
```

Description

Secret and dangerous.

I-19.9 shape

syntax

```
shape(E: LIST): LIST (of TYPE)
shape(E: RECORD): RECORD (of TYPE)
```

```
shape(E:OTHER): TYPE
```

where OTHER stands for a type which is not LIST, MAT, or RECORD.

Description

This function returns the extended list of types involved in the expression E as outlined below:

```
type(E) = LIST
```

In this case, Shape(E) is the list whose i-th component is the type of the i-th component of E.

```
type(E) = MAT
```

In this case, Shape(E) is a matrix with (i,j)-th entry equal to the type of the (i,j)-th entry of E.

```
type(E) = RECORD
```

In this case, Shape(E) is a record whose fields are the types of the fields of E.

Otherwise, “Shape(E)” is the type of E.

example

```
/**/ Use R ::= QQ[x];
/**/ L := [1,[1,"a"], x^2-x];
/**/ shape(L);
[INT, [INT, STRING], POLY]

/**/ R := record[name := "test", contents := L];
/**/ shape(R);
record[contents := [INT, [INT, STRING], POLY], name := STRING]

/**/ It.name;
STRING
```

There are undocumented functions, “IsSubShape” and “IsSubShapeOfSome”, for determining if the “shape” of a CoCoA expression is a “subshape” of another. To see the code for these functions, enter

```
Describe Function("$misc.IsSubShape");
Describe Function("$misc.IsSubShapeOfSome");
```

I-19.10 sign

syntax

```
sign(X: INT|RAT): INT
```

Description

This function returns -1 if $X < 0$, 0 if $X = 0$, and 1 if $X > 0$. X must be INT or RAT.

example

```
/**/ sign(123);
1
```



```
/**/  sign(-5/2);
-1
```

I-19.11 SimplestBinaryRatBetween

syntax

```
SimplestBinaryRatBetween(A: RAT, B: RAT): RAT
```

Description

This function finds the simplest binary rational in the closed interval with end points “A” and “B”. We define the simplest binary rational to be the rational number of the form “ $N \cdot 2^{-k}$ ” where the integer “N” is the smallest possible. See also SimplestRatBetween.

example

```
/**/  SimplestBinaryRatBetween(0.123, 0.456);
1/4

/**/  SimplestBinaryRatBetween(-3.14159, -2.71828);
-3

/**/  SimplestBinaryRatBetween(5,10); // contrast with SimplestRatBetween!
8
```

See Also: CFAprox(I-3.7 pg.43), FloatApprox(I-6.10 pg.89), SimplestRatBetween(I-19.12 pg.257)

I-19.12 SimplestRatBetween

syntax

```
SimplestRatBetween(A: RAT, B: RAT): RAT
```

Description

This function finds the simplest rational in the closed interval with end points “A” and “B”. See also SimplestBinaryRatBetween.

example

```
/**/  SimplestRatBetween(0.123, 0.456);
1/3

/**/  SimplestRatBetween(-3.14159, -2.71828);
-3
```

See Also: CFAprox(I-3.7 pg.43), FloatApprox(I-6.10 pg.89), SimplestBinaryRatBetween(I-19.11 pg.257)

I-19.13 SimplexInfo

syntax

```
SimplexInfo(A: LIST): RECORD
```

Description

This function compute the Stanley-Reisner ideal, the Alexander Dual complex and ideal of a simplicial complex described by a list of top faces.

Package GeomModelling, by Elisa Palezzato.

example

```
/**/ Use QQ[x[1..5]], DegLex;
/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4], x[3]*x[4]*x[5]]; -- list top faces
/**/ indent(SimplexInfo(L));
record[
  AlexanderDualCOMPLEX := [x[2]*x[3]*x[5], x[2]*x[3]*x[4], x[1]*x[3]*x[4]],
  AlexanderDualIdeal := ideal(x[4]*x[5], x[1]*x[5], x[1]*x[2]),
  Delta := [x[1]*x[2]*x[3], x[2]*x[3]*x[4], x[3]*x[4]*x[5]],
  StanleyReisnerIdeal := ideal(x[1]*x[4], x[1]*x[5], x[2]*x[5])
]
```

See Also: FVector(I-6.26 pg.96), SimplicialHomology(I-19.14 pg.258)

I-19.14 SimplicialHomology

syntax

```
SimplicialHomology(A: LIST): RECORD
SimplicialHomology(A: LIST, B: LIST): RECORD
```

Description

This function computes the simplicial homology of a simplicial complex described by a list of top faces. With 2nd argument only with the second list of vertices.

Package GeomModelling, by Elisa Palezzato.

example

```
/**/ Use QQ[x[1..5]], DegLex; --> DegLex ?

/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4], x[3]*x[4]*x[5]]; -- list top faces
/**/ indent(SimplicialHomology(L));
record[
  H_0 := record[betti := 1, lambda := []],
  H_i := [record[betti := 0, lambda := []]],
  H_max := record[betti := 0, lambda := []]
]
-- 1 connected component (beti in H_0)

/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4]]; -- list top faces
/**/ -- indent(SimplicialHomology(L)); --> Error: missing x[5]

/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4], x[5]];
/**/ indent(SimplicialHomology(L));
record[
  H_0 := record[betti := 2, lambda := []],
  H_i := [record[betti := 0, lambda := []]],
  H_max := record[betti := 0, lambda := []]
]
-- 2 connected components

/**/ L := [x[1]*x[2]*x[3], x[2]*x[3]*x[4]];
```

```

/**/ indent( SimplicialHomology(L, [x[1], x[2], x[3], x[4]]) );
record[
  H_0 := record[betti := 1, lambda := []],
  H_i := [record[betti := 0, lambda := []]],
  H_max := record[betti := 0, lambda := []]
]

```

I-19.15 *size* [OBSOLETE]

syntax

[OBSOLETE]

Description

[OBSOLETE] see “len” (I-12.5 pg.161).

See Also: len(I-12.5 pg.161)

I-19.16 *skip*

syntax

skip

Description

This command does nothing. I suppose it might be used to make the structure of a user-defined function more clear. It is probably at least as useful as the function “Tao”.

example

```
/**/ skip;
```

I-19.17 *SmoothFactor*

syntax

SmoothFactor(N: INT, MaxP: INT): RECORD

Description

This function finds the small prime factors of an integer. It simply tries dividing by all primes up to the given bound “MaxP”. The result is a list of the prime factors found together with the unfactored part of N. Be careful about supplying large values for “MaxP” (e.g. greater than a million) as the function could take a very long time.

From version 5.0.4 the field are called “factors” and “multiplicities” instead of “Factors” and “Exponents” to comply with the naming conventions.

example

```

/**/ SmoothFactor(100,3);
record[factors := [2], multiplicities := [2], RemainingFactor := 25]

/**/ SmoothFactor(123456789,3700);
record[factors := [3, 3607], multiplicities := [2, 1], RemainingFactor := 3803]

```

See Also: [IsPrime\(I-9.62 pg.144\)](#), [IsProbPrime\(I-9.63 pg.145\)](#)

I-19.18 sort

syntax

```
sort(V: LIST)

where V is a variable containing a list.
```

Description

This function sorts the elements of the list in V with respect to the default comparisons related to their types; it overwrites V and returns NULL.

For more on the default comparisons, see “Relational Operators” ([II-3.3 pg.308](#)) in the chapter on operators. For more complicated sorting, see “SortBy” ([I-19.19 pg.260](#)), “SortedBy” ([I-19.21 pg.261](#)).

example

```
/**/ L := [3,2,1];
/**/ sort(ref L); -- this returns nothing and modifies L
/**/ L;
[1, 2, 3]

/**/ Use R ::= QQ[x,y,z];
/**/ L := [x,y,z];
/**/ sort(ref L); -- this returns nothing and modifies L
/**/ L[1];
z

/**/ sorted([y, x, x^2]); -- this returns the sorted list
[y, x, x^2]
```

See Also: [Relational Operators\(II-3.3 pg.308\)](#), [sorted\(I-19.20 pg.261\)](#), [SortBy\(I-19.19 pg.260\)](#), [SortedBy\(I-19.21 pg.261\)](#)

I-19.19 SortBy

syntax

```
SortBy(L: LIST, LessThanFunc: FUNCTION)
```

Description

This function sorts the elements of the list in L in increasing order with respect to the comparisons made by LessThanFunc; it overwrites L and returns NULL.

The comparison function LessThanFunc takes two arguments and returns True if the first argument is less than the second, otherwise it returns False. The sorted list is in increasing order.

Note that to call SortBy(L,LessThanFunc) inside a function you will need to make the name LessThanFunc accessible using TopLevel LessThanFunc;

Note that if both LessThanFunc(A, B) and LessThanFunc(B, A) return true, then A and B are viewed as being equal.

example

```

/**/ Define LessThanLen(S, T)    -- define the sorting function
/**/   Return len(S) < len(T);
/**/ EndDefine;

/**/ L := ["bird", "mouse", "cat", "elephant"];
/**/ SortBy(ref L, LessThanLen);
/**/ L;
["cat", "bird", "mouse", "elephant"]

```

See Also: [func\(I-6.23 pg.95\)](#), [sort\(I-19.18 pg.260\)](#), [sorted\(I-19.20 pg.261\)](#), [SortBy\(I-19.21 pg.261\)](#), [TopLevel\(I-20.10 pg.280\)](#)

I-19.20 sorted

syntax

```
sorted(L: LIST): LIST
```

Description

This function returns the list of the sorted elements of L without affecting L, itself.

For more on the default comparisons, see “Relational Operators” ([II-3.3 pg.308](#)) in the chapter on operators. For more complicated sorting, see “SortBy” ([I-19.19 pg.260](#)), “SortBy” ([I-19.21 pg.261](#)).

example

```

/**/ L := [3,2,1];
/**/ sorted(L);
[1, 2, 3]

/**/ Use R ::= QQ[x,y,z];
/**/ L := [x,y,z];
/**/ sorted(L);
[z, y, x]

/**/ sorted([y, x, z, x^2]);
[z, y, x, x^2]

/**/ sorted([3, 1, 1, 2]);
[1, 1, 2, 3]

/**/ sorted(["b","c","a"]);
["a", "b", "c"]

```

See Also: [Relational Operators\(II-3.3 pg.308\)](#), [SortBy\(I-19.19 pg.260\)](#), [SortBy\(I-19.21 pg.261\)](#), [sort\(I-19.18 pg.260\)](#)

I-19.21 SortedBy

syntax

```
SortBy(L: LIST, F: FUNCTION): LIST
```

Description

This function returns the list of the sorted elements of L without affecting L, itself. As for “SortBy” (I-19.19 pg.260), the comparison function F takes two arguments and returns True if the first argument is less than the second, otherwise it returns False. The sorted list is in increasing order.

Note that if both F(A, B) and F(B, A) return True, then A and B are viewed as being equal.

— example —

```

/**/ Define LessByLength(S, T)    -- define the sorting function
/**/   Return len(S) < len(T);
/**/ EndDefine;

/**/ L := ["bird","mouse","cat", "elephant"];
/**/ sorted(L); -- default is alphabetical order
["bird", "cat", "elephant", "mouse"]
/**/ SortedBy(L, LessByLength);
["cat", "bird", "mouse", "elephant"]

/**/ L; -- L is not changed
["bird", "mouse", "cat", "elephant"]

/**/ SortBy(ref L, LessByLength); -- sort L in place, changing L
/**/ L;
["cat", "bird", "mouse", "elephant"]

```

See Also: func(I-6.23 pg.95), sort(I-19.18 pg.260), sorted(I-19.20 pg.261), SortBy(I-19.19 pg.260)

I-19.22 source

— syntax —

```

source S: STRING

```

Description

This command executes all CoCoA commands in the file or device named S. A typical use of “source” is to collect user-defined functions and variables in a text file, say, “MyFile.coc” and then execute:

```
source "MyFile.cocoa5";
```

or, equivalently, the obsolescent

```
<< "MyFile.cocoa5";
```

Functions and variables read in from a file in this way will erase functions and variables with identical names that may already exist. This can be avoided by using packages. Repeatedly used functions can be read into CoCoA at start-up by using “source” in the “userinit.coc” file.

See Also: Introduction to IO(II-6.1 pg.315), Introduction to Packages(II-7.1 pg.319)

I-19.23 SourceRegion

— syntax —

```

SourceRegion FromLine: INT,FromChar: INT To ToLine: INT,ToChar: INT In S: STRING

```

Description

This command executes all CoCoA commands in the specified region of the given file. It is not intended for manual use, but is used by the CoCoA UI.

```
SourceRegion FromLine,FromChar To ToLine,ToChar In "MyFile.cocoa5";
```

It is almost equivalent to copying the region into a temporary file, and then reading that file with the “source” command.

Line and char indexes start from 1; the region identified starts at the ”from” line/character position and stops immediately before the ”to” line/character position.

See Also: [source\(I-19.22 pg.262\)](#)

I-19.24 spaces

syntax

```
spaces(N: INT): STRING
```

Description

This function returns a string consisting of N spaces.

example

```
/**/ L := "a" + Spaces(5) + "b";
/**/ L;
a      b
```

See Also: [dashes\(I-4.1 pg.63\)](#)

I-19.25 sprint

syntax

```
sprint(E: OBJECT): STRING
```

Description

This function takes any CoCoA expression and converts its value to a string. One use is to check for extremely long output before printing in a CoCoA window.

example

```
/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x,y);
/**/ J := sprint(I);
/**/ I;
ideal(x, y)

/**/ J;          -- The output for I and J looks the same, but ...
ideal(x, y)

/**/ type(I); -- I is an ideal, and
IDEAL

/**/ type(J); -- J is just the string "ideal(x, y)".
STRING
```

```

/**/ J[1]; -- the 1st character of J
i

/**/ J[2]; -- the 2nd character of J
d

/**/ len(J); -- J has 11 characters
11

```

See Also: Introduction to IO([II-6.1](#) pg.315), IO.SprintTrunc([I-9.34](#) pg.134), print([I-16.25](#) pg.217), println([I-16.29](#) pg.219)

I-19.26 SqFreeFactor

— syntax —

```
SqFreeFactor(F: RINGELEM): RECORD
```

Description

Compute a factorization (of a polynomial) into coprime squarefree factors. The factorization may sometimes be finer than necessary, i.e. two factors could have the same multiplicity.

— example —

```

/**/ Use R ::= QQ[x,y];
/**/ f := (x^2-1)^2*(y+2)^3;
/**/ indent(SqFreeFactor(f));
record[
  RemainingFactor := 1,
  factors := [x^2 -1, y +2],
  multiplicities := [2, 3]
]

```

See Also: factor([I-6.1](#) pg.85), ContentFreeFactor([I-3.43](#) pg.58)

I-19.27 StableBBasis5

— syntax —

```

StableBBasis5(Pts: LIST, Toler: LIST): RECORD
StableBBasis5(Pts: LIST, Toler: LIST, Gamma: RAT): RECORD

```

Description

***** NOT YET IMPLEMENTED ***** See “TmpNBM” ([I-20.9](#) pg.280)

This function returns a record containing a “*stable order ideal*” of the ideal of points, and a list of “*almost vanishing*” polynomials. If the cardinality of the order ideal is equal to the number of points, it is in fact a “*quotient basis*”, and in this case a “*stable border basis*” founded on it is also returned. The boolean field “StableBBasisFound” is set to true if a stable border basis was found, otherwise false.

The first argument is a list of points in k -dimensional space, and the second argument is list of k positive tolerances (one for each dimension). The function builds the stable order ideal stepwise by testing, from a numerical point of view, the linear dependence of a set of vectors. So that the answer can be represented, the current ring must have at least k indeterminates; the term ordering is ignored as it plays no role in determining the border basis.

There is a third, optional argument: it is a real non negative number “Gamma” which is used for scaling the threshold on the admissible perturbation of the points. A value of “Gamma” ≥ 1 should be used. If no value is specified then by default “Gamma” = 0.1

For a full description of the algorithms we refer to the paper J.Abbott, C.Fassino, L.Torrente “*Stable Border Bases for Ideals of Points*” (to appear in JSC or arXiv:07062316).

example

```
Pts := [[0.1,-1],[1,1],[2,3]];
Toler := [0.1,0.1];
StableBBasis5(Pts, Toler);
record[
  AlmostVanishing := [ (...) ],
  BBasis := [
    -3602879701896397/288230376151711744y^2 + x -
    32425917317067571/72057594037927936y -
    154923827181545063/288230376151711744,
    xy - 140512308373959475/288230376151711744y^2 -
    39631676720860365/72057594037927936y +
    10808639105689191/288230376151711744,
    y^3 - 3y^2 - y + 3,
    xy^2 - 580063632005319885/288230376151711744y^2 -
    32425917317067571/72057594037927936y +
    421536925121878425/288230376151711744],
  SOI := [1, y, y^2],
  StableBBasisFound := True]
-----
Toler := [0.6, 0.6]:
StableBBasis5(Pts, Toler);
record[AlmostVanishing := [.....], SOI := [1, y], StableBBasisFound := False]
-----
```

See Also: [IdealOfPoints\(I-9.5 pg.118\)](#), [TmpNBM\(I-20.9 pg.280\)](#)

I-19.28 *StableIdeal*

syntax

```
StableIdeal(L: LIST of power-products): IDEAL
```

Description

This function returns the smallest stable ideal containing the power-products in “L” (see also “[StronglyStableIdeal](#)” ([I-19.33 pg.267](#))).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ L := [x*z^4, y^3];
/**/ StableIdeal(L);
ideal(x^2*z^3, x*y*z^3, x*z^4, x^3, x^2*y, x*y^2, y^3)
```

See Also: [IsStable\(I-9.68 pg.146\)](#), [LexSegmentIdeal\(I-12.7 pg.162\)](#), [StronglyStableIdeal\(I-19.33 pg.267\)](#)

I-19.29 *StarPrint, StarSprint*

syntax

```
StarPrint(F: RINGELEM)
StarPrintFold(F: RINGELEM, LineWidth: INT)
```

```
StarPrint(F: RINGELEM): STRING
StarPrintFold(F: RINGELEM, LineWidth: INT): STRING
```

Description

These functions print the polynomial F with asterisks added to denote multiplications. They may be useful when transferring polynomials or rational functions from CoCoA to other mathematical software (e.g. Gap, Maple, Macaulay, Singular,...). “StarPrint” inserts newline characters (only between terms) with the aim of avoiding lines longer than 70 characters; the second argument to “StarPrintFold” is for specifying a different width limit; a non positive value is treated as meaning no limit. The “StarPrint” functions print the value into a string.

example

```
Use R := QQ[x,y];
F := x^3+2xy-y^2;
StarPrint(F);
1*x^3 +2*x*y -1*y^2
-----
StarPrintFold(F,1); -- this will print one term per line
1*x^3
+2*x*y
-1*y^2
-----
D := OpenOFile("example");
Print StarPrint(F) On D; -- this will print F into the file "example"
Close(D);
-----
```

See Also: [LaTeX\(I-12.2 pg.159\)](#)

I-19.30 starting

syntax

```
starting(S: STRING): LIST of RECORD
```

Description

This function returns a list of all CoCoA functions starting with the string “S”. In general, this list will include undocumented commands. For these, one may find some information using “Describe Function(“Fn_Name”)” or “Describe Function(“\$PackageName.Fn_Name”)”.

example

```
/**/ indent(starting("Su"));
[
  record[IsExported := true, name := "$BackwardCompatible.Subsets"],
  record[IsExported := true, name := "$BackwardCompatible.Subst"],
  record[IsExported := true, name := "$BackwardCompatible.Sum"],
  record[IsExported := true, name := "$BackwardCompatible.Support"]
]
```

I-19.31 StdDegLexMat

syntax

```
StdDegLexMat(N: INT): MAT
```

Description

This function return the matrix defining a standard term-ordering.

example

```
/**/ StdDegLexMat(3);
matrix(ZZ,
  [[1, 1, 1],
   [1, 0, 0],
   [0, 1, 0]])
```

See Also: OrdMat([I-15.10](#) pg.205), Orderings([III-9.5](#) pg.360), StdDegRevLexMat([I-19.32](#) pg.267), LexMat([I-12.6](#) pg.161), RevLexMat([I-18.38](#) pg.244), XelMat([I-24.1](#) pg.295)

I-19.32 StdDegRevLexMat

syntax

```
StdDegRevLexMat(N: INT): MAT
```

Description

This function return the matrix defining a standard term-ordering.

example

```
/**/ StdDegRevLexMat(3);
matrix(ZZ,
  [[1, 1, 1],
   [0, 0, -1],
   [0, -1, 0]])
```

See Also: OrdMat([I-15.10](#) pg.205), Orderings([III-9.5](#) pg.360), StdDegLexMat([I-19.31](#) pg.266), LexMat([I-12.6](#) pg.161), RevLexMat([I-18.38](#) pg.244), XelMat([I-24.1](#) pg.295)

I-19.33 StronglyStableIdeal

syntax

```
StronglyStableIdeal(L: LIST of power-products): IDEAL
```

Description

This function returns the smallest strongly stable ideal containing the power-products in L.

example

```
/**/ Use R := QQ[x,y,z];
/**/ L := [x*y^2*z];
/**/ StableIdeal(L);
ideal(x^4, x^3*y, x^2*y^2, x*y^3, x*y^2*z)

/**/ StronglyStableIdeal(L);
ideal(x^4, x^3*y, x^2*y^2, x*y^3, x^3*z, x^2*y*z, x*y^2*z)
```

See Also: IsStronglyStable([I-9.70](#) pg.147), LexSegmentIdeal([I-12.7](#) pg.162), StableIdeal([I-19.28](#) pg.265)

I-19.34 SubalgebraMap [OBSOLETE]

[OBSOLETE]

syntax

Description

[OBSOLETE] See “SubalgebraRepr” (I-19.35 pg.268).

See Also: SubalgebraRepr(I-19.35 pg.268)

I-19.35 SubalgebraRepr

syntax

```
SubalgebraRepr(F: RINGELEM, L: LIST): RECORD
SubalgebraRepr(R: RING, F: RINGELEM, L: LIST): RECORD
```

Description

This function returns the representation of a polynomial as a subalgebra element in terms of the subalgebra generators.

example

```
/**/ Use QQ[s,t];
/**/ L := ***[s^3, s^2t, st^2, t^3]***;
/**/ indent(SubalgebraRepr(s^6*t^6, L));
record[
  IsInImage := true,
  OnePreImage := x[1]^2*x[4]^2,
  ker := ideal(x[3]^2 -x[2]*x[4], x[2]*x[3] -x[1]*x[4], x[2]^2 -x[1]*x[3])
]
/**/ SubalgebraRepr(s^6*t^6, L).IsInImage; -- for obsolete "IsInSubalgebra"
```

See Also: PreImage(I-16.17 pg.213), ker(I-11.1 pg.157)

I-19.36 submat

syntax

```
submat(M: MAT, R: LIST of INT, C: LIST of INT): MAT
```

Description

This function returns the submatrix of M formed by the rows listed in R and the columns listed in C. If M is a list, it is interpreted as a matrix in the natural way.

example

```
/**/ M := mat([[1,2,3,4,5],[6,7,8,9,10],[11,12,13,14,15]]);
/**/ submat(M,[1,3],[3..5]);
/**/ matrix(QQ,
  [[3, 4, 5],
   [13, 14, 15]])

/**/ M := mat([[1,2,3],[4,5,6]]);
/**/ submat(M,[2],[1,3]);
```

```
/**/ matrix(QQ,
  [[4, 6]])
```

See Also: minors([I-13.21](#) pg.178)

I-19.37 submodule

syntax

```
submodule(L: LIST of MODULEELEM): MODULE
submodule(F: MODULE, L: LIST of MODULEELEM): MODULE
```

Description

The first form returns the ideal generated by “L”. The second is the same as the first but works also if “L = []”.

This function is not friendly if you write the input by hand: we suggest “SubmoduleCols, SubmoduleRows” ([I-19.38](#) pg.269) for creating a module from the rows or columns of a matrix.

NOTE: the second argument is a LIST of MODULEELEM, not a LIST of LISTS of RINGELEM.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ R3 := NewFreeModule(R, 3);
/**/ L := [ModuleElem(R3, [x,y,z]), ModuleElem(R3, [x-1,0,z])];
/**/ M := submodule(R3, L); -- equivalent to
/**/ M := submodule(L);      -- (L not empty)
/**/ gens(M);
[[x, y, z], [x -1, 0, z]]
```

See Also: ModuleOf([I-13.28](#) pg.181), SubmoduleCols, SubmoduleRows([I-19.38](#) pg.269), GensAsCols, GensAsRows([I-7.9](#) pg.101), gens([I-7.8](#) pg.100)

I-19.38 SubmoduleCols, SubmoduleRows

syntax

```
SubmoduleCols(F: MODULE, M: MATRIX): MODULE
SubmoduleRows(F: MODULE, M: MATRIX): MODULE
```

Description

The first (second) function returns the submodule of F generated by the module elements described by the columns (rows) in the matrix M (which might be empty).

Dimensions must be compatible.

example

```
/**/ R3 := NewFreeModule(R, 3);
/**/ MGens := matrix(R, [[x,y,z], [x-1,0,z]]);

/**/ M := SubmoduleRows(R3, MGens);
/**/ gens(M);
[[x, y, z], [x -1, 0, z]]

-- /**/ M := SubmoduleCols(R3, MGens); -- !!! ERROR: wrong length !!!

/**/ M := SubmoduleCols(NewFreeModule(R,2), MGens);
```

```
/**/ gens(M);
[[x, x -1], [y, 0], [z, z]]
```

See Also: [GensAsCols](#), [GensAsRows](#)([I-7.9](#) [pg.101](#)), [submodule](#)([I-19.37](#) [pg.269](#)), [ModuleElem](#)([I-13.27](#) [pg.180](#))

I-19.39 subsets

syntax

```
subsets(S: LIST): LIST
subsets(S: LIST, N: INT): LIST
```

Description

This function computes all sublists (subsets) of a list (set). If N is specified, it computes all sublists of cardinality N.

example

```
/**/ subsets([1, 4, 7]);
[[ ], [7], [4], [4, 7], [1], [1, 7], [1, 4], [1, 4, 7]]

/**/ subsets([1, 4, 7], 2);
[[1, 4], [1, 7], [4, 7]]

/**/ subsets([2,3,3]);           -- list with repeated entries
[[ ], [3], [3], [3, 3], [2], [2, 3], [2, 3], [2, 3, 3]]

/**/ subsets(MakeSet([2,3,3]));
[[ ], [3], [2], [2, 3]]
```

See Also: [IsSubset](#)([I-9.71](#) [pg.147](#)), [partitions](#)([I-16.4](#) [pg.208](#)), [permutations](#)([I-16.5](#) [pg.208](#)), [MakeSet](#)([I-13.3](#) [pg.170](#)), [tuples](#)([I-20.15](#) [pg.284](#))

I-19.40 subst

syntax

```
subst(E: OBJECT, X, F): OBJECT
subst(E: OBJECT, [[X_1, F_1], ..., [X_r, F_r]]): OBJECT
  where each X or X_i is an indeterminate
  and each F or F_i is a RINGELEM
```

Description

The first form of this function substitutes “F_i” for “X_i” in the expression E. The second form is a shorthand for the first in the case of a single indeterminate. When substituting for the indeterminates in order, it is easier to use “eval” ([I-5.11](#) [pg.80](#)).

example

```
/**/ Use R ::= QQ[x,y,z,t];
/**/ F := x +y +z +t^2;
/**/ subst(F, x, -2);
t^2 +y +z -2

/**/ subst(F, [[x,x^2], [y,y^3], [z,t^5]]);
```

```

t^5 +y^3 +x^2 +t^2

/**/ eval(F, [x^2,y^3,t^5]); -- the same thing as above
t^5 +y^3 +x^2 +t^2

/**/ MySubst := [[y,1], [t, 3*z-x]];
/**/ subst(x*y*z*t, MySubst); -- substitute into the function x*y*z*t
-x^2*z +3*x*z^2

```

See Also: [eval\(I-5.11 pg.80\)](#), [Evaluation of Polynomials\(III-11.2 pg.368\)](#), [PolyAlgebraHom\(I-16.14 pg.211\)](#), [QZP\(I-17.5 pg.224\)](#), [RingElem\(I-18.39 pg.244\)](#), [ZPQ\(I-25.3 pg.298\)](#)

I-19.41 *sum*

syntax

```

sum(L: LIST): OBJECT
sum(L: LIST, InitVal: OBJECT): OBJECT

```

Description

This function returns the sum of the objects in the list “L” (together with “InitVal”, if specified). When writing a program, if the list “L” may be empty, you must specify “InitVal”.

example

```

/**/ use R ::= QQ[x,y];
/**/ sum([3, x, y^2]);
y^2 +x +3

/**/ sum(1..40) = binomial(41,2);
true

/**/ sum(["c","oc","oa"]);
cocoa

/**/ sum([]); -- gives 0 of type INT
0
/**/ sum([], ""); -- gives empty STRING

/**/ sum([], x); -- gives type RINGELEM
x

```

See Also: [Algebraic Operators\(II-3.2 pg.307\)](#), [product\(I-16.31 pg.220\)](#)

I-19.42 *support*

syntax

```

support(F: RINGELEM): LIST
support(F: MODULEELEM): LIST

```

Description

This function returns the list of terms of F. To get a list of monomials, which includes coefficients, use “monomials” ([I-13.30 pg.182](#)).

example

```

/**/ Use R ::= QQ[x,y];
/**/ F := 3*x^2-4*x*y+y^3+3;
/**/ support(F);
[y^3, x^2, x*y, 1]

/**/ monomials(F);
[y^3, 3*x^2, -4*x*y, 3]

// NOT YET IMPLEMENTED for MODULEELEM

```

See Also: [coefficients\(I-3.21 pg.48\)](#), [monomials\(I-13.30 pg.182\)](#)

I-19.43 swap

syntax

```

swap(ref A: OBJECT, ref B: OBJECT)

```

Description

This procedure swaps two values; it returns nothing!

example

```

/**/ A := 1;
/**/ B := 2;
/**/ swap(ref A, ref B);
/**/ PrintLn [A,B];
[2, 1]

```

See Also: [ref\(I-18.24 pg.237\)](#)

I-19.44 SwapRows

syntax

```

SwapRows(ref M: MAT, i: INT, j: INT)

```

Description

This procedure swaps the “i”-th and “j”-th rows in the matrix “M”; it returns nothing!

example

```

/**/ M := IdentityMat(QQ, 5);
/**/ SwapRows(ref M, 2,5);
/**/ M;
matrix(QQ,
  [[1, 0, 0, 0, 0],
   [0, 0, 0, 0, 1],
   [0, 0, 1, 0, 0],
   [0, 0, 0, 1, 0],
   [0, 1, 0, 0, 0]])

```

See Also: [ref\(I-18.24 pg.237\)](#), [swap\(I-19.43 pg.272\)](#), [GetRow\(I-7.15 pg.104\)](#), [SetRow\(I-19.7 pg.255\)](#)

I-19.45 *sylvester*

syntax

```
sylvester(F: RINGELEM, G: RINGELEM, X: RINGELEM): MAT
```

Description

(sorry Sylvester for the lower-case: here we follow the naming convention “*single name goes lower-case*”)

This function returns the Sylvester matrix of the polynomials F and G with respect to the indeterminate X. This is the matrix used to calculate the resultant.

example

```
/**/ Use R ::= QQ[p,q,x];
/**/ F := x^3+p*x-q; G := deriv(F, x);
/**/ sylvester(F, G, x);
matrix( /*RingWithID(36, "QQ[p,q,x]")*/
  [[1, 0, p, -q, 0],
   [0, 1, 0, p, -q],
   [3, 0, p, 0, 0],
   [0, 3, 0, p, 0],
   [0, 0, 3, 0, p]])

/**/ det(sylvester(F, G, x)) = resultant(F, G, x);
true
```

See Also: [resultant\(I-18.35 pg.242\)](#)

I-19.46 *SymbolRange*

syntax

```
SymbolRange(H: STRING, LO: INT, HI: INT): LIST of RINGELEM
SymbolRange(H: STRING, LO: LIST of INT, HI: LIST of INT): LIST of RINGELEM
```

Description

This function returns the list of the symbols with a given head and a range of indices. A symbol is a record with head (as “IndetName” (I-9.21 pg.127)) and indices (as “IndetSubscripts” (I-9.23 pg.128))

example

```
/**/ indent(SymbolRange("x", 3, 5));
[
  record[head := "x", indices := [3]],
  record[head := "x", indices := [4]],
  record[head := "x", indices := [5]]
]
/**/ P := NewPolyRing(QQ, SymbolRange("x", 0,2));
/**/ indets(P);
[x[0], x[1], x[2]]

/**/ indent(SymbolRange("x", [3,1], [5,2]));
[
  record[head := "x", indices := [[3, 1]]],
  record[head := "x", indices := [[3, 2]]],
  record[head := "x", indices := [[4, 1]]],
  record[head := "x", indices := [[4, 2]]],
]
```

```

    record[head := "x", indices := [[5, 1]]],
    record[head := "x", indices := [[5, 2]]]
]

```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#), [SymbolRange\(I-19.46 pg.273\)](#)

I-19.47 syz

— syntax —

```

Syz(L: LIST of RINGELEM): MODULE
Syz(M: IDEAL|MODULE, Index: INT): MODULE

```

Description

In the first two forms this function computes the syzygy module of a list of polynomials or module elements. “SyzOfGens(I)” is the same as “Syz(gens(I))”.

In the last form this function returns the specified syzygy module of the minimal free resolution of M which must be homogeneous. As a side effect, it computes the Groebner basis of M. (***** NOT YET IMPLEMENTED *****)

The coefficient ring must be a field.

— example —

```

/**/ Use R ::= QQ[x,y,z];
/**/ indent(Syz([x^2-y-1, y^3-z, x^2-y, y^3-z]));
SubmoduleRows(F, matrix(
  [y^3 -z, 0, 0, -x^2 +y +1],
  [0, 1, 0, -1],
  [x^2 -y, 0, -x^2 +y +1, 0],
  [0, 0, y^3 -z, -x^2 +y]
))
-----
/**/ I := ideal(x, x, y);
/**/ syz(gens(I));
submodule(FreeModule(..), [[1, -1, 0], [0, y, -x]])
/**/ SyzOfGens(I);
submodule(FreeModule(..), [[1, -1, 0], [0, y, -x]])

Syz(I, 1);      -- NOT YET IMPLEMENTED
Module([[x, -y]])
-----
I := ideal(x^2-yz, xy-z^2, xyz);  -- NOT YET IMPLEMENTED
Syz(I,0);
Module([x^2 - yz], [xy - z^2], [xyz])
-----
Syz(I,1);      -- NOT YET IMPLEMENTED
Module([-x^2 + yz, xy - z^2, 0], [xz^2, -yz^2, -y^2 + xz], [z^3, 0,
-xy + z^2], [0, z^3, -x^2 + yz])
-----
Syz(I,2);
Module([0, z, -x, y], [-z^2, -x, y, -z])
-----
Syz(I,3);
Module([[0]])
-----

```

```
Res(I);
0 --> R(-6)^2 --> R(-4)(+)R(-5)^3 --> R(-2)^2(+)R(-3)
-----
```

See Also: [res\(I-18.32 pg.241\)](#), [SyzOfGens\(I-19.48 pg.275\)](#)

I-19.48 SyzOfGens

syntax

```
SyzOfGens(M: IDEAL|MODULE): MODULE
```

Description

If M is an ideal or submodule, this function calculates the syzygy module for the given set of generators of M .

If M is a quotient of a ring by an ideal I or a quotient of a free module by a submodule N , then this function calculates the syzygy module for the given set of generators of I or N , respectively.

“`SyzOfGens(I)`” is the same as “`Syz(gens(I))`”.

The coefficient ring must be a field.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ I := ideal(x, y, x+y);
/**/ indent(SyzOfGens(I));
SubmoduleRows(F, matrix([
  [1, 1, -1],
  [0, x +y, -y]
]))

/**/ R3 := NewFreeModule(R, 3);
/**/ MGens := matrix(R, [[x,y,z], [x-y,0,z], [y^2,y^2,0]]);
/**/ indent(SyzOfGens(SubmoduleRows(R3, MGens)));
SubmoduleRows(F, matrix([
  [1, -1, -1]
]))
```

See Also: [syz\(I-19.47 pg.274\)](#)

Chapter I-20

T

I-20.1 tag

syntax

```
tag(E: OBJECT): STRING
```

Description

If E is a tagged object, this function returns the tag of E; otherwise, it returns the empty string.

example

```
/**/ L := tagged(3,"MyTag");
/**/ type(L);
TAGGED("$TopLevel.MyTag")

/**/ tag(L);
MyTag
```

See Also: Printing a Tagged Object([III-16.2 pg.385](#)), tagged([I-20.2 pg.277](#)), untagged([I-21.5 pg.286](#))

I-20.2 tagged

syntax

```
tagged(E: OBJECT, S: STRING): TAGGED(S)
```

Description

This first function returns the object E, tagged with the string S. Tagging is used for pretty printing of objects. See the reference listed below.

example

```
/**/ L := [1,2,3];
/**/ M := tagged(L,"MyTag");
/**/ type(L);
LIST

/**/ type(M);
TAGGED("$TopLevel.MyTag")
```

```
/**/ type(untagged(M));
LIST
```

See Also: Printing a Tagged Object([III-16.2](#) pg.385), tag([I-20.1](#) pg.277), untagged([I-21.5](#) pg.286)

I-20.3 tail

syntax

```
tail(L: LIST): LIST
```

Description

This function returns the list obtained from L by removing its first element. It cannot be applied to the empty list.

example

```
/**/ tail([1,2,3]);
[2, 3]
```

See Also: first([I-6.6](#) pg.87), last([I-12.1](#) pg.159)

I-20.4 TensorMat

syntax

```
TensorMat(M: MATRIX, N: MATRIX): MAT
```

Description

This function returns the tensor product of two matrices.

example

```
/**/ Use R ::= QQ[x,y,z,w];
/**/ TensorMat(mat(R, [[1,-1],[2,-2],[3,-3]]), mat(R, [[x,y],[z,w]]));
matrix( /*RingWithID(42, "QQ[x,y,z,w]")*/
  [[x, y, -x, -y],
   [z, w, -z, -w],
   [2*x, 2*y, -2*x, -2*y],
   [2*z, 2*w, -2*z, -2*w],
   [3*x, 3*y, -3*x, -3*y],
   [3*z, 3*w, -3*z, -3*w]])
```

I-20.5 TgCone

syntax

```
TgCone(I: IDEAL): IDEAL
```

Description

The “*initial form*” of a polynomial F is the homogeneous component of F of the lowest degree (in contrast with the “*leading form*”, see “LF” ([I-12.8](#) pg.162), “DF” ([I-4.14](#) pg.70)). The “*initial ideal*” of the ideal “I” is the ideal generated by the initial forms of all polynomials in “I”. It is also called “*tangent cone*” (which strictly is the variety defined by the initial ideal).

The implementation is based on Lazard’s method (see Kreuzer-Robbiano, Commutative Computer Algebra II, pg.463).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ TgCone(ideal(x^3-y));
ideal(-y)
/**/ TgCone(ideal(x^3+x^2-y^2));
ideal(x^2 -y^2)

/**/ I := ideal(x^3-y*z, y^2-x*z, z^2-x^2*y);
/**/ TgCone(I); -- same as InitialIdeal(I, [x,y,z]);
ideal(y^2 -x*z, z^2, -y*z)
```

See Also: InitialIdeal(I-9.26 pg.130), PrimaryHilbertSeries(I-16.22 pg.215)

I-20.6 TimeFrom

syntax

```
TimeFrom(StartPoint: RAT): STRING
```

Description

This function returns a string indicating the number of CPU seconds consumed since “StartPoint”; the value in “StartPoint” should be the value produced by the function “CpuTime” (I-3.48 pg.60) at the point where timing should commence.

example

```
/**/ t0 := CpuTime();
/**/ N := factorial(10000000);
/**/ PrintLn "Time to compute N: ",TimeFrom(t0);
Time to compute N: 7.538
```

I-20.7 TimeOfDay

syntax

```
TimeOfDay(): INT
```

Description

This function returns the current time as an INT in the form HHMMSS.

Note that from version 5.0.4 this information is no longer given by the function “date” (I-4.2 pg.63).

example

```
/**/ date();          -- 2013-05-30
20130530
/**/ TimeOfDay();    -- 09:08:13
90813
```

See Also: date(I-4.2 pg.63)

I-20.8 TmpChainCanonicalHom

syntax

```
TmpChainCanonicalHom(R: RING, S: RING): RINGHOM
```

Description

Temporary - might change name/meaning...

example

```
/**/ Use R := QQ[x,y];
/**/ RmodI := NewQuotientRing(R, ideal(x^2-1));

/**/ phi := TmpChainCanonicalHom(R, RmodI);
/**/ phi(x^3*y);
(x*y)
```

See Also: CanonicalHom([I-3.2](#) pg.41)

I-20.9 TmpNBM

syntax

```
TmpNBM(P: RING, Pts: MAT, Toler: MAT): RECORD[QuotientBasis: LIST, BBasis: LIST, AlmostVanishing: LIS
```

Description

Thanks to John Abbott and Maria-Laura Torrente.

This function checks that the current ring is suitable: see below for details.

This function returns a record containing a factor-closed set of power-products “QuotientBasis” and a list of “almost vanishing” polynomials. If the cardinality of the “QuotientBasis” is equal to the number of points, it is in fact a “quotient basis” of the ideal of points, and in this case a “border basis” founded on it is also returned.

The first argument is a list of points in k-dimensional space, and the second argument is list of k positive tolerances (one for each dimension). So that the answer can be represented, the current ring must have at least k indeterminates; the term ordering is ignored as it plays no role in determining the border basis.

For a full description of the algorithms we refer to the paper C.Fassino “Almost Vanishing Polynomials for Sets of Limited Precision Points” (arXiv:0807.3412).

example

```
/**/ P := QQ[x,y];
/**/ Eps := [0.1, 0.1];
/**/ Points := [[10, 0], [-10, 0], [0, 10], [0, -10], [7, 7], [-7, -7]];
/**/ indent(TmpNBM(P, mat(Points), RowMat(Eps)));
record[
  AlmostVanishing := [x^2 +(2/49)*x*y +y^2 -100,
                     x*y^2 +(49/51)*y^3 +(-4900/51)*y, y^4 +51*x*y -100*y^2],
  BBasis := [x^2 +(2/49)*x*y +y^2 -100, x*y^2 +(49/51)*y^3 +(-4900/51)*y,
             x^2*y +(49/51)*y^3 +(-4900/51)*y, y^4 +51*x*y -100*y^2, x*y^3 -49*x*y],
  QuotientBasis := [1, y, x, y^2, x*y, y^3],
  StableBBasisFound := true
]
```

See Also: IdealOfPoints([I-9.5](#) pg.118), StableBBasis5([I-19.27](#) pg.264)

I-20.10 TopLevel

syntax

```
TopLevel X;
  where ‘\verb&X&’ is the name of a top level variable or function.
```


Description

This command makes a top-level variable accessible from inside a function. It is useful for making “QQ” (I-17.1 pg.223) and “ZZ” (I-25.4 pg.298) visible, and also if a top-level function is to be passed as a parameter (e.g. to the function “SortBy” (I-19.19 pg.260)).

The command may be used with any top-level variable, but it is poor style to use it for purposes other than those mentioned above.

NOTE: Package variables should be accessed directly (via the fully qualified name); the “TopLevel” command does not recognise them.

example

```
/**/ define BeautifulRing(N)
/**/   TopLevel QQ;
/**/   R ::= QQ[b[1..N]];
/**/   return R;
/**/ enddefine;

/**/ Define CompareLen(X,Y) Return len(X) < len(Y); EndDefine;

/**/ Define LongestName(ListOfNameAndValue)
/**/   TopLevel CompareLen; --> to pass it as parameter to SortBy
/**/   names := [entry[1] | entry in ListOfNameAndValue];
/**/   SortBy(ref names, CompareLen);
/**/   Return last(names);
/**/ EndDefine;

/**/ L := [{"ABC",1},{"XYZT",2}];
/**/ LongestName(L);
XYZT
```

See Also: func(I-6.23 pg.95), ImportByRef, ImportByValue(I-9.15 pg.124)

I-20.11 TopLevelFunctions

syntax

```
TopLevelFunctions(): LIST of FUNCTION
```

Description

This function returns the list of all functions available at top-level

example

```
/**/ indent(TopLevelFunctions());
[
  record[IsExported := true, Name := "$BackwardCompatible.Abs"],
  record[IsExported := true, Name := "$BackwardCompatible.Append"],
  record[IsExported := true, Name := "$BackwardCompatible.Ascii"],
  ...
]
```

I-20.12 toric

syntax

```
toric(I: IDEAL): IDEAL
toric(I: IDEAL, L: LIST of INDETS): IDEAL
```

```
toric(M: MAT|LIST of LIST): IDEAL
```

Description

These functions return the saturation of an ideal, I , generated by binomials. In the first two cases, I is the ideal generated by the binomials in L . To describe the ideal in the last case, let K be the integral elements in the kernel of M . For each k in K , we can write $k = k(+) - k(-)$ where the i -th component of $k(+)$ is the i -th component of k , if positive, otherwise zero. Then I is the ideal generated by the binomials “ $x^{k(+)} - x^{k(-)}$ ” as k ranges over K .

NOTE: successive calls to this last form of the function may produce different generators for the saturation.

The first and third functions return the saturation of I . For the second function, if the saturation of I with respect to the variables in X happens to equal the saturation of I , then the saturation of I is returned. Otherwise, an ideal “*containing*” the saturation with respect to the given variables is returned. The point is that if one knows, a priori, that the saturation of I can be obtained by saturating with respect to a subset of the variables, the second function may be used to save time.

For more details, see the article: A.M. Bigatti, R. La Scala, L. Robbiano, “*Computing Toric Ideals*,” Preprint (1998). The article describes three different algorithms; the one implemented in CoCoA is “*EATP*”. The first two examples below are motivated by B. Sturmfels, “*Groebner Bases and Convex Polytopes*,” Chapter 6, p. 51. They count the number of homogeneous primitive partition identities of degrees 8 and 9.

example

```
/**/ Use QQ[x[1..8],y[1..8]];
/**/ HPPI8 := [x[1]^I*x[I+2]*y[2]^(I+1) - y[1]^I*y[I+2]*x[2]^(I+1) | I In 1..6];
/**/ BL := toric(ideal(HPPI8), [x[1],y[2]]);
/**/ len(gens(BL));
340

/**/ Use QQ[x[1..9],y[1..9]];
/**/ HPPI9 := [x[1]^I*x[I+2]*y[2]^(I+1) - y[1]^I*y[I+2]*x[2]^(I+1) | I In 1..7];
/**/ BL := toric(ideal(HPPI9), [x[1],y[2]]);
/**/ len(gens(BL));
798

/**/ Use R ::= QQ[x,y,z,w];
/**/ toric(ideal(x*z-y^2, x*w-y*z));
ideal(-y^2 +x*z, -y*z +x*w, z^2 -y*w)

/**/ toric(ideal(x*z-y^2, x*w-y*z), [y]);
ideal(-y^2 +x*z, -y*z +x*w, z^2 -y*w)

/**/ Use R ::= QQ[x,y,z];
/**/ toric([[1,3,2],[3,4,8]]);
ideal(-x^16 +y^2*z^5)

/**/ toric(mat([[1,3,2],[3,4,8]]));
ideal(-x^16 +y^2*z^5)
```

I-20.13 transposed

syntax

```
transposed(M: MAT): MAT
```

Description

This function returns the transpose of the matrix M.

example

```

/**/ M := mat([[1,2,3],[4,5,6]]);
/**/ M;
matrix(QQ,
  [[1, 2, 3],
   [4, 5, 6]])

/**/ transposed(M);
matrix(QQ,
  [[1, 4],
   [2, 5],
   [3, 6]])

```

I-20.14 try

syntax

```

Try C1 UponError E Do C2 EndTry
  where C1, C2 are sequences of commands and E is a variable identifier.

```

Description

Usually, when an error occurs during the execution of a command, the error is automatically propagated out of the nesting of the evaluation. This can be prevented with the use of “Try..UponError”.

If an error occurs during the execution of the commands C1, then it is captured by the command “UponError” and assigned to the variable E, and the commands C2 are executed; the string inside E may be retrieved using “GetErrMesg” (I-7.14 pg.103). If no error occurs then the variable E and the commands C2 are ignored.

example

```

-- /**/ deg(zero(R)); --> !!! ERROR !!!
-- ERROR: Non-zero RingElem required
-- deg(zero(R));
-- ~~~~~

/**/ Define MyDeg(F)
/**/   Try
/**/     D := Deg(F);
/**/     Return D;
/**/   UponError E Do
/**/     MyDegError := GetErrMesg(E);
/**/     If "Non-zero RingElem required" IsIn MyDegError Then
/**/       Return -123456;
/**/     Else
/**/       error(MyDegError);
/**/     EndIf;
/**/   EndTry;
/**/ EndDefine;

/**/ MyDeg(x);
1
/**/ MyDeg(zero(R));
-123456

```

```
-- /**/ MyDeg("a"); --> !!! ERROR !!!
ERROR: Expecting type RINGELEM, but found type STRING
      error(MyDegError);
      ~~~~~
```

See Also: [error\(I-5.10 pg.79\)](#), [GetErrMsg\(I-7.14 pg.103\)](#)

I-20.15 tuples

— syntax —

```
tuples(S: LIST, N: INT): LIST
```

Description

This function computes all N-tuples with entries in S. It is equivalent to “S >< S >< ... >< S” [N times].

— example —

```
/**/ tuples([1, 4, 7], 2);
[[1, 1], [1, 4], [1, 7], [4, 1], [4, 4], [4, 7], [7, 1], [7, 4], [7, 7]]
```

See Also: [CartesianProduct](#), [CartesianProductList\(I-3.4 pg.42\)](#), [permutations\(I-16.5 pg.208\)](#), [subsets\(I-19.39 pg.270\)](#)

I-20.16 type

— syntax —

```
type(E: OBJECT): TYPE
```

Description

This function returns the data type of E.

— example —

```
/**/ L := [1,"a",2,"b",3,"c"];
/**/ [ X In L | type(X)=INT ];
[1, 2, 3]

/**/ type(type(INT)); -- Type returns a value of type TYPE
TYPE

/**/ CurrentTypes();
[BOOL, ERROR, FUNCTION, ...]
```

See Also: [CurrentTypes\(I-3.52 pg.62\)](#)

Chapter I-21

U

I-21.1 UnivariateIndetIndex

syntax

```
UnivariateIndetIndex(F: RINGELEM): INT
```

Description

This function returns 0 if the polynomial F is not univariate otherwise it returns the indeterminate index of F.

NOTE: If F is a constant, it returns 1.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ UnivariateIndetIndex(3*x^4-2*x-1);
1

/**/ UnivariateIndetIndex(x-y-1);
0

/**/ UnivariateIndetIndex(one(R));
1
```

See Also: [indet\(I-9.19 pg.126\)](#), [IndetSubscripts\(I-9.23 pg.128\)](#), [IndetIndex\(I-9.20 pg.126\)](#), [IndetName\(I-9.21 pg.127\)](#), [indets\(I-9.22 pg.127\)](#), [NumIndets\(I-14.35 pg.199\)](#)

I-21.2 UniversalGroebnerBasis

syntax

```
UniversalGroebnerBasis(I: IDEAL): LIST of RINGELEM
```

Description

Returns a universal Groebner basis of the input IDEAL “I”.

example

```
-- The ideal generated by the 3x3 minors of 3x4 matrix of indeterminates
-- has 96 marked reduced Groebner bases
/**/ Use R ::= QQ[a,b,c,d,e,f,g,h,i,j,k,l];
/**/ I:=ideal(Minors(Mat([[a,b,c,d],[e,f,g,h],[i,j,k,l]]),3));
/**/ indent(UniversalGroebnerBasis(I));
[d*g*j -c*h*j -d*f*k +b*h*k +c*f*l -b*g*l,
```

```
d*g*i -c*h*i -d*e*k +a*h*k +c*e*l -a*g*l,
d*f*i -b*h*i -d*e*j +a*h*j +b*e*l -a*f*l,
c*f*i -b*g*i -c*e*j +a*g*j +b*e*k -a*f*k,
-d*g*i +c*h*i +d*e*k -a*h*k -c*e*l +a*g*l,
-d*f*i +b*h*i +d*e*j -a*h*j -b*e*l +a*f*l,
-c*f*i +b*g*i +c*e*j -a*g*j -b*e*k +a*f*k,
-d*g*j +c*h*j +d*f*k -b*h*k -c*f*l +b*g*l]
```

See Also: `AllReducedGroebnerBases`([I-1.9](#) pg.28)

I-21.3 unprotect

syntax

```
unprotect X;
```

Description

This command undoes the effect of the “`protect`” ([I-16.32](#) pg.220) command; once a variable has been unprotected, it may be assigned to freely.

example

```
/**/ X := 1;
/**/ protect X;    --> cannot assign to X henceforth
/**/
/**/ unprotect X;  --> remove protection, X may be assigned to now
/**/ X := 2;
```

See Also: `protect`([I-16.32](#) pg.220)

I-21.4 Unset [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE]

I-21.5 untagged

syntax

```
untagged(E:TAGGED_OBJECT):UNTAGGED_OBJECT
```

Description

This function strips an object `E` of its tag, if any. “`@E`” is equivalent to “`untagged(E)`”.

Tags are used for pretty printing of objects. See the reference listed below.

example

```

/**/ L := [1,2,3];
/**/ M := tagged(L,"MyTag");
/**/ type(L);
LIST

/**/ type(M);
TAGGED("MyTag")

/**/ type(untagged(M));
LIST

```

See Also: Printing a Tagged Object([III-16.2](#) pg.385), tag([I-20.1](#) pg.277), tagged([I-20.2](#) pg.277)

I-21.6 use

syntax

```

use R
use RingDefn
use R ::= RingDefn

where R is a RING, and RingDefn is a ring definition.

```

Description

This command works only at top-level; it makes a ring active, i.e. it makes that ring the “*current ring*”. The command will also let you create a new ring, and make it active immediately “`Use NewR ::= RingDefn;`” where “`RingDefn`” is a ring definition; this is a shorthand for “`NewR ::= RingDefn; Use NewR;`”

This command cannot be called inside a function, and it is never necessary (if you write clean programs ;-). In CoCoA-5 you can define new rings, return rings, assign rings and pass rings as arguments (this was not possible in CoCoA-4).

example

```

/**/ use S ::= QQ[x,y,z];
/**/ Print CurrentRing;
RingDistrMPolyClean(QQ, 3)
/**/ indets(CurrentRing);
[x, y, z]

/**/ use QQ[u]; -- can be used w/out a ring identifier
/**/ indets(CurrentRing);
[u]

/**/ define SumInAnotherRing(N)
/**/   K := NewRingTwinFloat(128); -- 128 bits of precision
/**/   P ::= K[x[1..N]], Lex;
/**/   return sum(indets(P));
/**/ enddefine;

/**/ SumInAnotherRing(4);
x[1] +x[2] +x[3] +x[4]
/**/ CoeffRing(RingOf(It));
RingTwinFloat(AccuracyBits=128, BufferBits=128, NoiseBits=32)

```

See Also: Introduction to RINGHOM([III-10.1](#) pg.[365](#)), CurrentRing([I-3.51](#) pg.[61](#)), RingOf([I-18.42](#) pg.[246](#)), ReadExpr([I-18.17](#) pg.[234](#))

Chapter I-22

V

I-22.1 valuation [OBSOLETE]

— syntax —

[OBSOLETE]

Description

Renamed “FactorMultiplicity” ([I-6.3 pg.86](#)).

See Also: FactorMultiplicity([I-6.3 pg.86](#))

I-22.2 VersionInfo

— syntax —

VersionInfo(): RECORD

Description

This function returns a record with various information about CoCoA and CoCoALib (the mathematical core of CoCoA)

— example —

```
/**/ indent(VersionInfo());
record[
  CoCoALibVersion := "0.99533",
  CoCoAVersion := "5.1.0",
  CompilationDate := "May 14 2014 15:48:58",
  ...
```

See Also: CoCoALib([II-8.1 pg.325](#))

Chapter I-23

W

I-23.1 wdeg

syntax

`wdeg(F: RINGELEM): LIST`

Description

This function returns the multi-weighted degree of F , as determined by the matrix weights of the polynomial ring of F . The function “deg” (I-4.6 pg.66) returns the standard degree.

NOTE: In CoCoA-4 “deg” (I-4.6 pg.66) gave the weight given by only the first row of the weights matrix.

example

```
/**/ M := matrix([[2,3,4], [1,0,2], [1,0,0]]);
/**/ P := NewPolyRing(QQ, "x,y,z", M, 1); -- GradingDim=1
/**/ Use P;
/**/ wdeg(x*y^2+y);
[8]
/**/ P := NewPolyRing(QQ, "x,y,z", M, 2); -- GradingDim=2
/**/ Use P;
/**/ wdeg(x*y^2+y);
[8, 1]
/**/ deg(x*y^2+y);
3

/**/ P4 := NewFreeModule(P,4); -- the default module ordering is TPos
/**/ wdeg(ModuleElem(P4, [0, x, y^2, x^2]));
[6, 0]

/**/ LT(ModuleElem(P4, [0, x, y^2, x^2]));
[0, 0, y^2, 0]
```

See Also: deg(I-4.6 pg.66), LF(I-12.8 pg.162)

I-23.2 WeightsMatrix [OBSOLESCENT]

syntax

`WeightsMatrix(R: RING): MAT`

Description

This function is now called “GradingMat” ([I-7.20 pg.105](#)).

See Also: [deg\(I-4.6 pg.66\)](#), [wdeg\(I-23.1 pg.291\)](#)

I-23.3 while

syntax

```
While B Do C EndWhile
```

where B is a boolean expression and C is a sequence of commands.

Description

The command sequence C is repeated until B evaluates to False.

example

```
/**/ N := 0;
/**/ while N <= 5 do
/**/   PrintLn 2, "^", N, " = ", 2^N;
/**/   N := N+1;
/**/ EndWhile;
2^0 = 1
2^1 = 2
2^2 = 4
2^3 = 8
2^4 = 16
2^5 = 32
```

See Also: [for\(I-6.15 pg.91\)](#), [foreach\(I-6.16 pg.92\)](#), [repeat\(I-18.31 pg.241\)](#)

I-23.4 WithoutNth

syntax

```
WithoutNth(L: LIST, N: INT): LIST
```

Description

This function returns the list obtained by removing the “N”-th component of the list “L”. The list “L” itself is not changed; compare with “[remove](#)” ([I-18.30 pg.240](#)).

example

```
/**/ L := [1,2,3,4,5];
/**/ WithoutNth(L,3);
[1, 2, 4, 5]
```

See Also: [remove\(I-18.30 pg.240\)](#)

I-23.5 WLog [OBSOLETE]

syntax

```
[OBSOLETE]
```

Description

[OBSOLETE] This function returns the weighted list of exponents of the leading term of F , as determined by the first row of the weights matrix.

See Also: [exponents\(I-5.14 pg.81\)](#)

Chapter I-24

X

I-24.1 **XelMat**

[syntax](#)

```
XelMat(N: INT): MAT
```

Description

This function return the matrix defining a standard term-ordering.

[example](#)

```
/**/ XelMat(3);  
matrix(ZZ,  
  [[0, 0, 1],  
   [0, 1, 0],  
   [1, 0, 0]])
```

See Also: [OrdMat\(I-15.10 pg.205\)](#), [Orderings\(III-9.5 pg.360\)](#), [StdDegRevLexMat\(I-19.32 pg.267\)](#), [StdDegLexMat\(I-19.31 pg.266\)](#), [LexMat\(I-12.6 pg.161\)](#), [RevLexMat\(I-18.38 pg.244\)](#)

Chapter I-25

Z

I-25.1 zero

syntax

```
zero(R: RING): RINGELEM
```

Description

This function return the additive identity of a ring. For when you want to force the integer “0” to be a “RINGELEM”.

example

```
/**/ P := ZZ/(101)[x,y,z];

/**/ N := 0; Print N, " of type ", type(N);
0 of type INT
/**/ N := zero(P); Print N, " of type ", type(N);
0 of type RINGELEM
/**/ N := 300*0; Print N, " of type ", type(N);
0 of type INT
/**/ N := 300*zero(P); Print N, " of type ", type(N);
0 of type RINGELEM

/**/ F := NewFreeModule(P, 3);
/**/ zero(F);
[0, 0, 0]
```

See Also: [one\(I-15.1 pg.201\)](#), [IsZero\(I-9.78 pg.150\)](#)

I-25.2 ZeroMat

syntax

```
ZeroMat(R: RING, NumRows: INT, NumCols: INT): MAT
```

Description

This function returns the “NumRows x NumCols” zero matrix with entries in “R”.

example

```
/**/ Use R := QQ[x,y,z];
/**/ ZeroMat(QQ, 1, 3); --> same as NewMatFilled(1,3, 0)
matrix(QQ,
```

```
[[0, 0, 0]]
/**/ ZeroMat(R, 1, 3); --> same as NewMatFilled(1,3, zero(R))
matrix( /*RingDistrMPolyClean(QQ, 3)*/
[[0, 0, 0]]
```

See Also: [matrix\(I-13.10 pg.173\)](#), [IdentityMat\(I-9.7 pg.120\)](#), [NewMatFilled\(I-14.7 pg.187\)](#)

I-25.3 ZPQ

syntax

```
ZPQ(F: RINGELEM): RINGELEM
ZPQ(F: LIST of RINGELEM): LIST of RINGELEM
ZPQ(I: IDEAL): IDEAL
```

Description

***** NOT YET IMPLEMENTED *****

The function “ZPQ” maps a polynomial with finite field coefficients into one with rational (actually, integer) coefficients. It is not uniquely defined mathematically, and currently for each coefficient the least non-negative equivalent integer is chosen. Users should not rely on this choice, though any change will be documented.

See “QZP” ([I-17.5 pg.224](#)) for more details.

example

```
Use R := QQ[x,y,z];
F := 1/2*x^3 + 34/567*x*y*z - 890; -- a poly with rational coefficients
Use S := ZZ/(101)[x,y,z];
ZPQ(F); -- compute its image with coeffs in ZZ/(101)
-50x^3 - 19xyz + 19
-----
G := It;
Use R;
ZPQ(G); -- now map that result back to QQ[x,y,z] it is NOT the same as F...
51x^3 + 82xyz + 19
-----
```

See Also: [BringIn\(I-2.12 pg.39\)](#)

I-25.4 ZZ

syntax

```
ZZ
```

Description

This system variable is constant; its value is the ring of integers. Its name is protected so that it cannot be re-assigned to any other value.

example

```
/**/ P := ZZ/(101)[x,y,z];

/**/ Use ZZ;
```

```
/**/ type(5);  
INT  
/**/ type(RingElem(ZZ, 5));  
RINGELEM
```

See Also: QQ([I-17.1](#) [pg.223](#))

Part II

The CoCoA Programming Language

Chapter II-1

Introduction to CoCoA Programming

II-1.1 An Overview of CoCoA Programming

The CoCoA system includes a full-fledged high level programming language, CoCoALanguage, complete with loops, branching, scoping of variables, and input/output control. The language is used whenever one issues commands during a CoCoA session. A sequence of commands may be stored in a text file and then read into a CoCoA session using the “**source**” ([I-19.22 pg.262](#)) command.

The most important construct in CoCoA programming is the user-defined function, created with “**define**” ([I-4.4 pg.64](#)). A user-defined function can take any number of arguments, of any types, perform CoCoA commands, and return values. Collections of these functions can be stored in text files, as mentioned in the preceding paragraph, or formed into CoCoA “*packages*”, to be made available for general use.

Chapter II-2

Language Elements

II-2.1 Character Set and Special Symbols

The CoCoA character set consists of the 26 lower case letters, the 26 upper case letters, the 10 digits and the special characters listed in the table below. Note that the special character “|” looks a bit different on some keyboards (its ASCII code is 124).

	blank	_	underscore	(left parenthesis	
	+	plus	=	equal)	right parenthesis
	-	minus	<	less than	[left bracket
	*	asterisk	<	greater than	[right bracket
	/	slash		vertical bar	'	single quote
	:	colon	.	period	" "	double quote
	^	caret	;	semicolon		
	,	comma	%	percent		

Special Characters

The character-groups listed in the table below are special symbols in CoCoA

	:=	assign	..	range	
	<<	input from	//	start line comment	
	<>	not equal	--	start line comment	
	><	Cartesian product	::=	ring definition	
	<=	less than or equal to	/*	start embedded comment	
	>=	greater than or equal to	*/	end embedded comment	

Special Character-groups

II-2.2 Identifiers

There are two types of identifiers or names.

- * Identifiers of ring indeterminates (see “NewPolyRing” (I-14.8 pg.188))
- * Predefined or user-defined names (functions and CoCoALanguage variables).

See Also: Indeterminates(III-9.4 pg.360)

II-2.3 Reserved Names

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

The names in the following tables are reserved and cannot be used otherwise. The names in the first table are case insensitive (e.g. CLEAR, Clear and cLEaR are all reserved). The names in the second table are case sensitive.

...work in progress...

Alias	And	Block	Ciao	Define	
Describe	Do	Elif	Else	End	
EndBlock	EndTry		EndDefine	EndFor	
EndForeach	EndIf	EndPackage	EndRepeat	EndUsing	
EndWhile	Eof	False	For	Foreach	
Global	Help	If	In	IsIn	
NewLine	Not	On	Or	Package	
Print	PrintLn	Quit	Repeat	Record	
Return	Set	Skip	Source	Step	
Then	Time	To	True	Unset	
Until	Use	Using	Var	While	
QQ	ZZ				

Case insensitive reserved names

BOOL	DegLex	DegRevLex	DEVICE	ERROR	
FUNCTION	IDEAL	INT	LIST	Lex	
MAT	MODULE	NULL	Null	PANEL	
POLY	PosTo	RAT	RATFUN	RING	
STRING	TAGGED	ToPos	TYPE	MODULEELEM	
Xel	ZMOD				

Case sensitive reserved names

II-2.4 Comments

End-of-line comments in CoCoA start with either “--” or “//”; all text up to the end of the line is considered comment. CoCoA also allows embedded comments; these begin with the symbol “/*” and end with the symbol “*/”. CoCoA ignores the contents of a comment, and treats it as if it were just a space.

example

```
/**/ // This is an end-of-line comment
/**/ Print 1+1; -- a command followed by an end-of-comment
2
/**/ A := [1 /*x-coord*/, 2 /*y-coord*/ ]; --> embedded comments
```

Chapter II-3

Operators

II-3.1 CoCoA Operators

In CoCoA there are 5 main types of operators: algebraic operators, relational operators, boolean operators, selection operators, and the range operator. There is also an n-ary operator “><” for forming Cartesian products of lists and an operator “:=” used in defining rings.

The meaning of an operator depends on the types of its operands; the “+” in the expression “A + B” represents the sum of polynomials, or of ideals, or of matrices, etc. according to the type of A and B.

The CoCoA operators are, from the highest to the lowest priority:

```
[] .      (selection operators)
^ %
+ -      (as unary operators)
* : /
+ -      (as binary operators)
..
= <> < <= > >=
IsIn
And
Or
```

Operations with equal priority are performed from left to right. When in doubt, parentheses may be used to enforce a particular order of evaluation.

See Also: operators, shortcuts(I-0.1 pg.23)

II-3.2 Algebraic Operators

The algebraic operators are:

+ - * / : ^

The following table shows which operations the system can perform between two objects of the same or of different types; the first column lists the type of the first operand and the first row lists the type of the second operand. So, for example, the symbol “:” in the box on the seventh row and fourth column means that it is possible to divide an ideal by a polynomial.

	INT	RAT	RINGELEM	MODULEELEM	IDEAL	MODULE	MAT	LIST
INT	+-*/^	+-*/	+-*/	*	*	*	*	*
RAT	+-*/^	+-*/	+-*/	*	*	*	*	*

RINGELEM	$+-*/^$	$+-*/$	$+-*/$	*	*	*	*	*
MODULEELEM	*	*	*	$+-$				
IDEAL	$*^$	*	*		$++:$	*		
MODULE	*	*	*		*	$+:$		
MAT	$*^$	*	*				$+-*$	
LIST	*	*	*					$+-$

Algebraic operators

Remarks:

* Let F and G be two polynomials. If F is a multiple of G , then F/G is the polynomial obtained from the division of F by G , otherwise F/G is a rational function (common factors are simplified). The functions “div” (I-4.20 pg.73) and “mod” (I-13.25 pg.180) can be used to get the quotient and the remainder of a polynomial division.

* Let L_1 and L_2 be two lists of the same length. Then $L_1 + L_2$ is the list obtained by adding L_1 to L_2 componentwise.

* If I and J are both ideals or both modules, then $I : J$ is the ideal consisting of all polynomials f such that fg is in I for all g in J .

II-3.3 Relational Operators

See Also: Equality Test(I-5.8 pg.78), Comparison Operators(I-3.30 pg.53), IsIn(I-9.49 pg.139)

II-3.4 Selection Operators

The selection operators are

`[]` .

Let N be of type INT and let L be of type STRING, MODULEELEM, LIST, or MAT. Then the meaning of $L[N]$ depends on the type of L as explained in the following table:

Type of L	Meaning of $L[N]$
STRING	string consisting of the N -th character of L .
MODULEELEM	N -th component of L
LIST	N -th element of L
MAT	N -th element of L

Selection Operator

If N is an identifier and L is of type RECORD, then “ $L.N$ ” indicates the object contained in the field N of the record L (see “record” (I-18.21 pg.236)).

See Also: record(I-18.21 pg.236), List Constructors(III-5.2 pg.346)

II-3.5 Range Operator

If M and N are of type INT, then the expression: “ $M \dots N$ ” returns

- * the list “[M , $M+1$, \dots , N]” if $M \leq N$;
- * the empty list, “[]”, otherwise.

NOTE: Large values for M and N are not permitted; typically they should lie in the range about -10^9 to $+10^9$.

NOTE: see example for how to select a sub-range of a list

If x and y are indeterminates in a ring, then “x .. y” gives the indeterminates between x and y in the order they appear in the definition of the ring.

example

```
/**/ 1..10;
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

/**/ Use R ::= QQ[x,y,z,a,b,c,d];
/**/ z..c;
[z, a, b, c]

/**/ L := [11, 22, 33, 44, 55];
/**/ PartOfL := L[2]..L[4]; --> probably *NOT* what you want!
/**/ PartOfL := [ L[k] | k in 2..4 ]; --> OK, this is RIGHT!
```

See Also: CoCoA Operators([II-3.1](#) pg.[307](#)), List Constructors([III-5.2](#) pg.[346](#)), LIST([III-5](#) pg.[345](#))

Chapter II-4

Evaluation and Assignment

II-4.1 Evaluation

An expression is by itself a valid command. The effect of this command is that the expression is evaluated in the current ring and its value is displayed.

The evaluation of an expression in CoCoA is normally performed in a full recursive evaluation mode. Usually the result is the fully evaluated expression.

The result of the evaluation is automatically stored in the variable “It” ([I-9.83 pg.152](#)).

— example —

```
/**/ 2 + 2;  
4  
/**/ It + 3;  
7  
/**/ It;  
7  
/**/ X := 5;  
/**/ It;  
7
```

The command “X := 5” is an assignment, not an evaluation; so it does not change the value of the variable “It” ([I-9.83 pg.152](#)).

If an error occurs during the evaluation of an expression, then the evaluation is interrupted and the user is notified about the error.

II-4.2 Assignment

An assignment command has the form

$$L := E$$

where L is a variable and E is an expression. The assignment command binds the result of the evaluation of the expression E to L in the working memory.

— example —

```
/**/ Use R ::= QQ[t,x,y,z];  
/**/ I := ideal(x,y);  
  
/**/ M := 5; N := 8;  
/**/ T := M+N;  
/**/ T;
```

```
13
/**/ T := T+1;  -- note that T occurs on the right, also
/**/ T;
14

/**/ L := [1,2,3];
/**/ L[2] := L[3];
/**/ L;
[1, 3, 3]

/**/ P := record[F := x*z];
/**/ P.Degree := Deg(P.F);
/**/ P;
record[Degree := 2, F := x*z]
```


Chapter II-5

Flow Control: Conditional Statements and Loops

II-5.1 All CoCoA commands

This is a complete list of all CoCoA commands:

<code>break</code>	break out of a loop
<code>for</code>	loop command
<code>foreach</code>	loop command
<code>if</code>	conditional statement
<code>repeat</code>	loop command
<code>return</code>	exit from a function
<code>try</code>	try and catch an error
<code>while</code>	loop command

II-5.2 Commands and Functions for Branching

The following are the CoCoA commands for constructing conditional statements:

<code>if</code>	conditional statement
-----------------	-----------------------

II-5.3 Commands and Functions for Loops

The following are the commands and functions for loops:

<code>break</code>	break out of a loop
<code>for</code>	loop command
<code>foreach</code>	loop command
<code>repeat</code>	loop command

return	exit from a function
while	loop command

Chapter II-6

Input/Output

II-6.1 Introduction to IO

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

Input and output is implemented in CoCoA through the use of “*devices*”. At present, the official devices are: (1) standard IO (the CoCoA window), (2) text files, and (3) strings. What this means is that it is possible to read from or write to any of these places. The cases are discussed separately, below. Text files may be read verbatim or—with the “*source*” (I-19.22 pg.262) command—be executed as CoCoA commands.

II-6.2 Standard IO

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

Standard IO is what takes places normally when one interacts with CoCoA. CoCoA accepts and interprets strings typed in by the user and prints out expressions. If *E* is a CoCoA object, then the command

E;

causes the value of *E* to be printed to the CoCoA window. One may also use the functions “*print*” (I-16.25 pg.217) and “*println*” (I-16.29 pg.219) for more control over the format of the output.

The official devices that are being used here are “*DEV.STDIN*” and “*DEV.OUT*”. So for instance, the commands “*Get*” (I-7.10 pg.102) and “*print on*” (I-16.26 pg.218) can be used with the standard devices although they are really meant to be used with the other devices. “*Print E On DEV.OUT*” is synonymous with “*Print E*”. Also, one may use “*Get(DEV.STDIN,10)*”, for example, to get the next 10 characters typed in the CoCoA window. Thus, clever use of “*Get*” (I-7.10 pg.102) will allow your user-defined functions to prompt the user for input, but normal practice is to pass variables to a function as arguments to that function.

II-6.3 File IO

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

To print CoCoA output to a file, one first opens the file with “*OpenOFile*” (I-15.5 pg.203) then prints to the file using “*print on*” (I-16.26 pg.218).

To receive verbatim input from a file, one first opens the file with “*OpenIFile*” (I-15.2 pg.201), then gets characters from the file with “*Get*” (I-7.10 pg.102). Actually, “*Get*” (I-7.10 pg.102) gets a list of ASCII codes for the characters in the file. These can be converted to real characters using the function “*ascii*” (I-1.15 pg.31).

example

```
D := OpenOFile("my-file"); -- open text file with name "my-file",
                           -- creating it if necessary
```

```

Print "hello world" On D; -- append "hello world" to my-file
Close(D); -- close the file
D := OpenIFile("my-file"); -- open "my-file"
Get(D,10); -- get the first ten characters, in ASCII code
[104, 101, 108, 108, 111, 32, 119, 111, 114, 108]
-----
  ascii(It); -- convert the ASCII code
hello worl
-----
  Close(D);

```

To read and execute a sequence of CoCoA commands from a text file, one uses the “**source**” (I-19.22 pg.262) command. For instance, if the file “MyFile.coc” contains a list of CoCoA commands, then

```
Source "MyFile.cocoa";
```

reads and executes the commands.

See Also: [ascii\(I-1.15 pg.31\)](#), [close\(I-3.14 pg.46\)](#), [Get\(I-7.10 pg.102\)](#), [OpenIFile\(I-15.2 pg.201\)](#), [OpenOFile\(I-15.5 pg.203\)](#), [OpenLog\(I-15.4 pg.202\)](#), [CloseLog\(I-3.15 pg.46\)](#), [print on\(I-16.26 pg.218\)](#), [source\(I-19.22 pg.262\)](#)

II-6.4 String IO

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

To print CoCoA output to a string, one may use “**OpenOString**” (I-15.6 pg.204) to “*open*” the string, then “**print on**” (I-16.26 pg.218) to write to it. To read from a string, one may open the string for input with “**OpenIString**” (I-15.3 pg.202) then get characters from it with “**Get**” (I-7.10 pg.102).

example

```

S := "hello world";
D := OpenIString("", S); -- open the string S for input to CoCoA
      -- the first argument is just a name for the device
L := Get(D,7); -- read 7 characters from the string
L; -- ASCII code
[104, 101, 108, 108, 111, 32, 119]
-----
  ascii(L); -- convert ASCII code to characters
hello w
-----
  Close(D); -- close device D
D := OpenOString(""); -- open a string for output from CoCoA
L := [1,2,3]; -- a list
Print L On D; -- print to D
D;
record[Name := "", Type := "OString", Protocol := "CoCoALanguage"]
-----
S := Cast(D, STRING); -- S is the string output printed on D
S; -- a string
[1, 2, 3]
Print " more characters" On D; -- append to the existing output string
Cast(D, STRING);
[1, 2, 3] more characters
-----

```

There are usually more direct ways to collect results in strings. For instance, if the output of a CoCoA command is not already of type STRING, one may convert it to a string using “**sprint**” (I-19.25 pg.263).

II-6.5 Commands and Functions for IO

The following are commands and functions for input/output:

<code>block</code>	group several commands into a single command
<code>close</code>	close a device
<code>CloseLog</code>	close a log of a CoCoA session
<code>format</code>	convert object to formatted string
<code>Get</code>	read characters from a device
<code>IO.SprintTrunc</code>	convert to a string and truncate
<code>LaTeX</code>	LaTeX formatting
<code>NewFreeModule</code>	create a new FreeModule
<code>NewLine [OBSOLESCENT]</code>	[OBSOLESCENT] string containing a newline
<code>OpenIFile</code>	open input file
<code>OpenIString</code>	open input string
<code>OpenLog</code>	open a log of a CoCoA session
<code>OpenOFile</code>	open output file
<code>OpenOString</code>	open output string
<code>OpenSocket</code>	open a socket connection
<code>print</code>	print the value of an expression
<code>print on</code>	print to an output device
<code>println</code>	print the value of an expression
<code>source</code>	read commands from a file or device
<code>SourceRegion</code>	read commands from a region in a file
<code>sprint</code>	convert to a string
<code>tag</code>	returns the tag string of an object
<code>tagged</code>	tag an object for pretty printing
<code>untagged</code>	untag an object

Chapter II-7

CoCoA Packages

II-7.1 Introduction to Packages

User-defined functions may be saved in separate files and read into a CoCoA session using the “**source**” ([I-19.22 pg.262](#)) command. If one sources several such files or, especially, if a file is to be made available for general use, a possible problem arises from conflicting function names. If two functions with the same name are read into a CoCoA session, only the one last read survives. To avoid this, functions may be collected in “*packages*”.

A CoCoA package is essentially a list of functions labeled with prefix.

Writing a package in CoCoA-5 is slightly different from how it was done in CoCoA-4 it is easier!).

See Also: `define`([I-4.4 pg.64](#)), `source`([I-19.22 pg.262](#))

II-7.2 First Example of a Package

The following is an example of a package. It could be typed into a window as-is during a CoCoA session, but we will assume that it is stored in a file in the CoCoA directory under the name “`one.cpkg5`”.

example

```
package $contrib/toypackage

export ToyTest;

define IsNumberOne(n)
  if n = 1 then return true; else return false; endif;
enddefine;

define ToyTest(n)
  if IsNumberOne(n) then
    print "The number 1";
  else
    print "Not the number 1";
  endif;
enddefine;

endpackage; -- of toypackage
```

Below is output from a CoCoA session in which this package was used:

example

```
-- read in the package:
Source "one.cpkg";
```

```

/* */ ToyTest(4); -- was exported
Not the number 1
/* */ IsNumberOne(4); -- wasn't exported
ERROR: Cannot find a variable named "IsNumberOne" in scope
IsNumberOne(4);
~~~~~

/* */ $contrib/toypackage.IsNumberOne(4);
false

```

II-7.3 Package Essentials

A package begins with

```
Package $PackageName
```

and ends with

```
EndPackage;
```

“`PackageName`” is a string that will be used to identify the package. The dollar sign is required. The “`PackageName`” must be a valid identifier: i.e. start with a letter and comprise only letters, digits, slash and underscore; the name should be meaningful (and usually long, to avoid any risk of a name clash). We recommend using a name of the form “`contrib/subject`”.

All packages in the CoCoA directory “`packages`” are automatically loaded when starting CoCoA.

II-7.4 Global Aliases

A global alias for a package is formed by using the command “`alias`” ([I-1.7 pg.27](#)) during a CoCoA session. NOTE: global aliases cannot be used in function definitions. This is to force independence of context. Inside a function, one must use the complete package name.

See Also: `alias`([I-1.7 pg.27](#)), `aliases`([I-1.8 pg.28](#))

II-7.5 Sharing Your Package

If you create a package that others might find useful, please contact the CoCoA team by email at “`cocoa at dima.unige.it`”.

Include comments in the package that:

- * explain the use of the package
- * give the syntax, description, examples for exported functions.

II-7.6 Commands and Functions for Packages

The following are commands and functions for packages:

<code>alias</code>	define aliases for package names
<code>aliases</code>	list of global aliases
<code>Packages</code>	list of loaded packages
<code>PkgName</code>	returns the name of a package

II-7.7 Supported Packages

Several packages are supported by the CoCoA team. These packages contain functions that are not built into CoCoA because they are of a more specialized or experimental nature.

Some functions which used to be defined in supported packages are now official functions in CoCoA-5.

II-7.8 Galois Package

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```
TITLE      : galois.cpkg
DESCRIPTION : CoCoA package for computing in a cyclic algebraic
              extension
AUTHOR      : A. Bigatti, D.La Macchia, F.Rossi
```

```
-- Enter
      $contrib/galois.Man();
      to get a complete description of the package including a suggested alias.
```

II-7.9 Integer Programming

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```
TITLE      : intprog.cpkg
DESCRIPTION : CoCoA package for applying toric ideals to integer
              programming
AUTHOR      : A. Bigatti
```

```
-- Enter
      $contrib/intprog.Man();
      to get a complete description of the package including a suggested alias.
```

II-7.10 Algebra of Invariants

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```
TITLE      : invariants.cpkg
DESCRIPTION : CoCoA package for computing homogeneous generators of an
              algebra of invariants, and for testing invariance of a polynomial
AUTHOR      : A. Del Padrone
```

```
-- Enter
      $contrib/invariants.Man();
      to get a complete description of the package including a suggested alias.
```

II-7.11 Special Varieties

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```

TITLE      : specvar.cpkg
DESCRIPTION : CoCoA package for computing the Hilbert-Poincare
              series of special varieties (Segre, Veronese, Rees).
AUTHORS    : A. Bigatti, L. Robbiano

-- Enter
    $contrib/specvar.Man();
to get a complete description of the package including a suggested alias.

```

II-7.12 Statistics

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```

TITLE      : stat.cpkg
DESCRIPTION : package for design of experiments in statistics
AUTHOR     : M. Caboara

-- Enter
    $contrib/stat.Man();
to get a complete description of the package including a suggested alias.

```

II-7.13 Geometrical Theorem-Proving

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```

TITLE      : thmproving.cpkg
DESCRIPTION : CoCoA package for geometrical theorem-proving in euclidean space
AUTHOR     : L. Bazzotti, G. Dalzotto

-- Enter
    $contrib/thmproving.Man();
to get a complete description of the package including a suggested alias.

```

II-7.14 Typevectors

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```

TITLE      : typevectors.cpkg
DESCRIPTION : CoCoA package for computing type-vectors associated to
              Hilbert functions of ideals of points
AUTHOR     : E.Carlini, M.Stewart

-- Enter
    $contrib/typevectors.Man();
to get a complete description of the package including a suggested alias.

```

II-7.15 Conductor

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

```

TITLE      : conductor.cpkg

```

DESCRIPTION : CoCoA package for computing conductor sequence of points
 AUTHOR : L.Bazzotti

```
-- Enter
    $contrib/conductor.Man();
to get a complete description of the package including a suggested alias.
```

II-7.16 Matrix Normal Form

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

TITLE : matrixnormalform.cpkg
 DESCRIPTION : CoCoA package for computing normal forms of a matrix,
 Smith Normal Form (PID)
 AUTHOR : A.Bigatti, S.DeFrancisci

```
-- Enter
    $contrib/matrixnormalform.Man();
to get a complete description of the package including a suggested alias.
```

II-7.17 CantStop

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

TITLE : CantStop.cpkg
 DESCRIPTION : CoCoA package for playing Can't Stop and studying strategies
 AUTHOR : A.Bigatti

```
-- Enter
    $contrib/CantStop.Man();
to get a complete description of the package including a suggested alias.
```

II-7.18 Control

***** NOT YET UPDATED TO CoCoA-5: follow with care *****

TITLE : control.cpkg
 DESCRIPTION : CoCoA package for Geometric Control Theory
 AUTHOR : M. Anderlucchi and M. Caboara

```
-- Enter
    $contrib/control.Man();
to get a complete description of the package including a suggested alias.
```


Chapter II-8

Linked libraries

II-8.1 CoCoALib

CoCoALib “<http://cocoa.dima.unige.it/cocoalib>”.

CoCoALib is the mathematical core of CoCoA-5. It may be used directly as a C++ library.

II-8.2 GMP

GMP - The GNU Multiple Precision Arithmetic Library “<https://gmplib.org>”

All arbitrary precision integer/rational/floating-point datatypes and operations are based on GMP.

II-8.3 GSL

GSL - GNU Scientific Library “<http://www.gnu.org/software/gsl/>”

Some functions from GSL have been ported to CoCoA-5. There is no manual yet because it's work in progress.

II-8.4 Frobbby

Frobbby - Computations With Monomial Ideals “<http://www.broune.com/frobbby>”

All functions starting with “Frb” are implemented in Frobbby.

II-8.5 Normaliz

libNormaliz is a C++ library for computations with rational cones and affine monoids; full details may be found on the official Normaliz website “<https://www.normaliz.uni-osnabrueck.de>”

When CoCoA is compiled it is possible to incorporate also libNormaliz; if so, then many libNormaliz functions can be called from CoCoA-5. All CoCoA functions starting with “Nmz” are actually implemented in libNormaliz.

Chapter II-9

Migrating from CoCoA-4 and keeping up-to-date

II-9.1 Changes in the CoCoA language

CoCoA-5 is largely, but not completely, backward-compatible with CoCoA-4. Some commands/functions have changed name; others have been removed or replaced. Here we give a little guidance to help update your CoCoA-4 programs to CoCoA-5/

The operator “Not” has been replaced by the function “not(...)”.

example

```
/*C4*/ If Not X IsIn L Then ... EndIf;  
/*C5*/ If not(X IsIn L) Then ... EndIf;
```

Several functions modify one of their arguments (e.g. “append” (I-1.12 pg.30), “sort” (I-19.18 pg.260)); CoCoA-5 wants these arguments to be identified with the new keyword “ref” (I-18.24 pg.237), and will issue a warning if you don’t do this (just to make sure you know that “L” will be modified).

example

```
/*C4*/ L := [1,2,3]; Append(L, 4);  
/*C5*/ L := [1,2,3]; append(ref L, 4);
```

Implicit multiplication has gone: either write “x*y” instead of “xy” for every product, or use “CoCoA-4 mode” (I-3.16 pg.47).

example

```
/*C4*/ F := 3xyzt;  
/*C5*/ F := 3*x*y*z*t; OR F := ***3xyzt***;
```

Many CoCoA-4 functions would employ the “CurrentRing” implicitly (e.g. “NumIndets()”, “CoeffRing()”). They now require an explicit argument; you can pass “CurrentRing” as the argument, but inside a function you must make that system variable visible via the command “TopLevel” (I-20.10 pg.280).

example

```
/*C4*/ Define LastIndet() Return Last(Indets()); EndDefine;  
/*C5*/ Define LastIndet()  
    TopLevel CurrentRing;  
    Return last(indets(CurrentRing));  
EndDefine;
```

However, we encourage you to consider modifying your function so that it does not depend on “CurrentRing”; e.g. you can find out to which ring a value belongs by calling the function “RingOf” (I-18.42 pg.246).

example

```
/*C5*/ I := ideal(x,y^2); NumIndets(RingOf(I));
```

The function “LinKer” (I-12.10 pg.163) has been replaced by “LinKerBasis” (I-12.11 pg.164), and there is a new function called “LinKer” (I-12.10 pg.163) which produces a matrix.

More generally, see also the CoCoA-4 ”translation table” in the CoCoAManual directory or at

<http://cocoa.dima.unige.it/cocoalib/doc/CoCoATranslationTable.html>

See Also: CoCoA-4 mode(I-3.16 pg.47), TopLevel(I-20.10 pg.280), CurrentRing(I-3.51 pg.61), RingOf(I-18.42 pg.246)

II-9.2 Recent changes in the CoCoA-5 language

There are a few changes in the language even from the first versions of CoCoA-5.

The operator “Not” has been replaced by the function “not(...)”.

example

```
/*5.0.9*/ If Not X IsIn L Then ... EndIf;
/*5.1.0*/ If not(X IsIn L) Then ... EndIf;
```

The anonymous function called “lambda” is now called “func” (I-6.23 pg.95).

example

```
/*5.0.9*/ square := Lambda(x) Return x^2; EndLambda;
/*5.1.0*/ square := Func(x) Return x^2; EndFunc;
```

See Also: not(I-14.29 pg.197), func(I-6.23 pg.95)

II-9.3 Obsolete and obsolescent functions

As the language evolves some functions might become obsolete, maybe just more sensibly renamed. This is the list of such functions: see in the manual for reasons/updates.

Call [OBSOLETE]	[OBSOLETE] apply a function to given arguments
Cast [OBSOLETE]	[OBSOLETE] type conversion
ColumnVectors [OBSOLETE]	[OBSOLETE] list of module elements
Comp [OBSOLETE]	[OBSOLETE] access a component
E_ [OBSOLETE]	[OBSOLETE] vector of the canonical basis
Function [OBSOLETE]	[OBSOLETE]
functions [OBSOLETE]	[OBSOLETE] replaced by describe
ID [OBSOLETE]	[OBSOLETE] renamed RingID
IsInSubalgebra [OBSOLETE]	[OBSOLETE] check if one polynomial is in a subalgebra
IsNumber [OBSOLETE]	[OBSOLETE] checks if the argument is a number
LinKerModP [OBSOLETE]	[OBSOLETE] find the kernel of a matrix mod p
LinSol [OBSOLETE]	[OBSOLETE] find a solution to a linear system
MapDown [OBSOLETE]	[OBSOLETE] convert a constant polynomial to a number
Mod2Rat [OBSOLETE]	[OBSOLETE] reconstruct rationals from modular integers
NewId [OBSOLETE]	[OBSOLETE] create a new identifier
NFsAreZero [OBSOLETE]	[OBSOLETE] test if normal forms are zero
Option [OBSOLETE]	[OBSOLETE] status of a panel option
panel [OBSOLETE]	[OBSOLETE] print status of a panel's options
panels [OBSOLETE]	[OBSOLETE] list of CoCoA panels

PoincareMultiDeg [OBSOLETE]	[OBSOLETE]
PoincareShifts [OBSOLETE]	[OBSOLETE]
Reset [OBSOLETE]	[OBSOLETE] reset panels and random number seed to defaults
ResetPanels [OBSOLETE]	[OBSOLETE] reset panels to their default values
RingEnv [OBSOLETE]	[OBSOLETE] name of the ring environment
RingSet [OBSOLETE]	[OBSOLETE] renamed RingsOf
size [OBSOLETE]	[OBSOLETE]
SubalgebraMap [OBSOLETE]	[OBSOLETE] algebra homomorphism representing a subalgebra
Unset [OBSOLETE]	[OBSOLETE] set and unset panel options
valuation [OBSOLETE]	[OBSOLETE]
WLog [OBSOLETE]	[OBSOLETE] weighted list of exponents

Some functions are obsolescent, that means that they are still usable but will be deleted in some future version of CoCoA (leaving some time to adapt to the replacing function).

AffHilbert [OBSCIENT]	[OBSCIENT] renamed AffHilbertFn
AffPoincare [OBSCIENT]	[OBSCIENT] Renamed AffHilbertSeries
CompleteToOrd [OBSCIENT]	[OBSCIENT] renamed MakeTermOrd
hilbert [OBSCIENT]	the Hilbert-Poincare' function
image [OBSCIENT]	[OBSCIENT] apply ring homomorphism
insert [OBSCIENT]	[OBSCIENT] insert an object in a list
log [OBSCIENT]	[OBSCIENT] renamed to exponents
MinGensGeneral [OBSCIENT]	[OBSCIENT] renamed MinSubsetOfGens
NewLine [OBSCIENT]	[OBSCIENT] string containing a newline
poincare [OBSCIENT]	[OBSCIENT] the Hilbert-Poincare series
PrimaryPoincare [OBSCIENT]	[OBSCIENT] renamed PrimaryHilbertSeries
rank [OBSCIENT]	[OBSCIENT] rank
RMap [OBSCIENT]	[OBSCIENT] define ring homomorphism for function image
WeightsMatrix [OBSCIENT]	[OBSCIENT] matrix of generalized weights for indeterminates

Part III

CoCoA datatypes

Chapter III-1

BOOL

III-1.1 Introduction to BOOL

The two BOOL constants are “true” and “false”. (can also be written “TRUE”, “FALSE” and “True”, “False”) They are mainly used with the commands “if” ([I-9.8 pg.120](#)) and “while” ([I-23.3 pg.292](#)), etc., inside CoCoA programs.

The relational operators

= <> < <= > >=

return boolean constants (see “Relational Operators” ([II-3.3 pg.308](#))).

The boolean operators are “and” ([I-1.11 pg.29](#)), “or” ([I-15.9 pg.205](#)), “IsIn” ([I-9.49 pg.139](#)). From version CoCoA-5.0.9 “not” ([I-14.29 pg.197](#)) is a function (instead of an operator).

See Also: Relational Operators([II-3.3 pg.308](#)), Commands and Functions for BOOL([III-1.2 pg.333](#)), Commands and Functions returning BOOL([III-1.3 pg.333](#))

III-1.2 Commands and Functions for BOOL

and	boolean ”and” operator
Bool01	Convert a boolean to an integer
in	list element selector in list constructor
NmzSetVerboseDefault	Set the verbosity state for Normaliz
not	boolean ”not” operator
or	boolean ”or” operators
TmpNBM	Numerical Border Basis of ideal of points

III-1.3 Commands and Functions returning BOOL

and	boolean ”and” operator
Comparison Operators	less than, greater than, ...
EqSet	checks if the set of elements in two lists are equal
Equality Test	test whether two values are equal or not
IsAntiSymmetric	checks if a matrix is anti-symmetric
IsConstant	checks if a ringelem is in the coefficient ring

<code>IsContained</code>	checks if A is Contained in B
<code>IsDiagonal</code>	checks if a matrix is diagonal
<code>IsDivisible</code>	checks if A is divisible by B
<code>IsElem</code>	checks if A is an element of B
<code>IsEven, IsOdd</code>	test whether an integer is even or odd
<code>IsFactorClosed</code>	test whether a list of PPs is factor closed
<code>IsField</code>	test whether a ring is a field
<code>IsFiniteField</code>	test whether a ring is a finite field
<code>IsFractionField</code>	test whether a ring is a fraction field
<code>IsHomog</code>	test whether given polynomials are homogeneous
<code>IsIn</code>	check if one object is contained in another
<code>IsIndet</code>	checks argument is an indeterminate
<code>IsInjective</code>	check if a RINGHOM is injective
<code>IsInRadical</code>	check if a polynomial (or ideal) is in a radical
<code>IsInvertible</code>	check if a RINGELEM is invertible
<code>IsIrred</code>	check if a RINGELEM is irreducible
<code>IsLexSegment</code>	checks if an ideal is lex-segment
<code>IsMaximal</code>	maximality test
<code>IsOne</code>	test whether an object is one
<code>IsPositiveGrading</code>	check if a matrix defines a positive grading
<code>IsPrimary</code>	primary test
<code>IsPrime</code>	prime integer test
<code>IsProbPrime</code>	checks if an integer is a probable prime
<code>IsPthPower</code>	p-th power test
<code>IsQQ</code>	test whether a ring is the ring of rationals
<code>IsQuotientRing</code>	test whether a ring is a quotient ring
<code>IsStable</code>	checks if an ideal is stable
<code>IsStdGraded</code>	checks if the grading is standard
<code>IsStronglyStable</code>	checks if an ideal is strongly stable
<code>IsSubset</code>	checks if the elements of one list are a subset of another
<code>IsSurjective</code>	check if a RINGHOM is surjective
<code>IsSymmetric</code>	checks if a matrix is symmetric
<code>IsTerm</code>	checks if the argument is a term
<code>IsTermOrdering</code>	check if a matrix defines a term-ordering
<code>IsTrueGCDDomain</code>	test whether a ring is a true GCD domain
<code>IsZero</code>	test whether an object is zero
<code>IsZeroCol, IsZeroRow</code>	test whether a column(row) is zero
<code>IsZeroDim</code>	test whether an ideal is zero-dimensional
<code>IsZeroDivisor</code>	test whether a RINGELEM is a zero-divisor
<code>IsZZ</code>	test whether a ring is the ring of integers
<code>NmzSetVerboseDefault</code>	Set the verbosity state for Normaliz
<code>not</code>	boolean "not" operator
<code>or</code>	boolean "or" operators

Chapter III-2

INT

III-2.1 Introduction to INT

There are two types of numbers recognized by CoCoA: integers (type “INT”), rationals (type “RAT”). (CoCoA-4 also had “ZMOD”, but CoCoA-5 can deal with more rings: see “NewRingFp” ([I-14.10 pg.189](#))). Numbers in CoCoA are handled with arbitrary precision. This means that the sizes of numbers are only limited by the amount of available memory. The basic numeric operations—addition (“+”), subtraction (“-”), multiplication (“*”), division (“/”), exponentiation (“^”), and negation (“-”)—behave as one would expect. Be careful, two adjacent minus signs, “--”, start a comment in CoCoA.

example

```
/**/ N := 3;
/**/ -N;
-3
--N; <-- THIS IS A COMMENT (not C++ decrement)
```

See Also: Commands and Functions for INT([III-2.2 pg.335](#)), Commands and Functions returning INT([III-2.3 pg.337](#))

III-2.2 Commands and Functions for INT

abs	absolute value of a number
AffHilbertFn	the affine Hilbert function
ascii	convert between characters and ascii code
AsINT	convert into an INT
AsRAT	convert into a RAT
binomial	binomial coefficient
BinomialRepr, BinomialReprShift	binomial representation of integers
ContFracToRat	convert continued fraction to rational
CRT	Chinese Remainder Theorem
CRTPoly	Chinese Remainder Theorem on polynomial coefficients
cyclotomic	n-th cyclotomic polynomial
date	the date
DecimalStr	convert rational number to decimal string
den	denominator
DensePoly	the sum of all power-products of a given degree
div	quotient for integers
ElimMat	matrix for elimination ordering
EvalHilbertFn	evaluate the Hilbert function
exponents	the list of exponents of the leading term of a polynomial

Ext	presentation Ext modules as quotients of free modules
factorial	factorial function
FactorMultiplicity	multiplicity of a factor of an integer
first	the first N elements of a list
flatten	flatten a list
FloatApprox	approx. of rational number of the form $M * 2^E$
FloatStr	convert rational number to a decimal string
FloorLog2, FloorLog10, FloorLogBase	integer part of the logarithm
FloorSqrt	(truncated) square root of an integer
format	convert object to formatted string
GBasisTimeout	compute a Groebner basis with a timeout
gcd	greatest common divisor
GCDFreeBasis	determine (minimal) GCD free basis of a set of integers
GenericPoints	random projective points
Get	read characters from a device
GetCol	convert a column of a matrix into a list
GetRow	convert a row of a matrix into a list
HilbertFn	the Hilbert function
IdentityMat	the identity matrix
incr, decr	increment/decrement a counter
indent	prints in a more readable way
indet	individual indeterminates
insert [OBSOLESCE]	[OBSOLESCE] insert an object in a list
InverseSystem	Inverse system of an ideal of derivations
IO.SprintTrunc	convert to a string and truncate
iroot	integer part of r-th root of an integer
IsEven, IsOdd	test whether an integer is even or odd
IsOne	test whether an object is one
IsPositiveGrading	check if a matrix defines a positive grading
IsPrime	prime integer test
IsProbPrime	checks if an integer is a probable prime
IsZero	test whether an object is zero
IsZeroCol, IsZeroRow	test whether a column(row) is zero
last	the last N elements of a list
lcm	least common multiple
LexMat	matrices for std. term-orderings
MakeMatByRows, MakeMatByCols	convert a list into a matrix
MakeTerm	returns a monomial (power-product) with given exponents
MakeTermOrd	Make a term order matrix from a given matrix
MantissaAndExponent10	convert rational number to a float
MantissaAndExponent2	convert rational number to a binary float
max	a maximum element of a sequence or list
min	a minimum element of a sequence or list
minors	list of minor determinants of a matrix
mod	remainder for integers
NewFreeModule	create a new FreeModule
NewList	create a new list
NewMat	Zero matrix
NewMatFilled	matrix filled with value
NewPolyRing	create a new PolyRing
NewRingFp	create a new finite field
NewRingTwinFloat	create a new twin-float ring
NextPrime	find the next largest prime number
NextProbPrime	find the next largest probable prime number
num	numerator
NumPartitions	number of partitions of an integer
operators, shortcuts	Special characters equivalent to commands

<code>partitions</code>	partitions of an integer
<code>PowerMod</code>	compute a modular power efficiently
<code>PrimitiveRoot</code>	find a primitive root modulo a prime
<code>product</code>	the product of the elements of a list
<code>random</code>	random integer
<code>randomized</code>	randomize the coefficients of a given polynomial
<code>RandomSubset</code>	random subset
<code>RandomSubsetIndices</code>	indices for random subset
<code>RandomTuple</code>	random tuple
<code>RandomTupleIndices</code>	indices for random tuples
<code>RatReconstructByContFrac, RatReconstructByLattice</code>	rational reconstruction from modular image
<code>RatReconstructPoly</code>	Rational reconstruction of polynomial coefficients
<code>RatReconstructWithBounds</code>	deterministic rational reconstruction from modular image
<code>RefineGCDFreeBasis</code>	refine an integer GCD free basis
<code>remove</code>	remove an object in a list
<code>RevLexMat</code>	matrices for std. term-orderings
<code>RingElem</code>	convert an expression into a RINGELEM
<code>RingQQt</code>	pre-defined polynomial rings
<code>ScientificStr</code>	convert integer/rational to a floating-point string
<code>seed</code>	seed for “random”
<code>SetRow</code>	set a list as a row into a matrix
<code>SetStackSize</code>	secret ;-)
<code>sign</code>	the sign of a number
<code>SmoothFactor</code>	find small prime factors of an integer
<code>SourceRegion</code>	read commands from a region in a file
<code>spaces</code>	return a string of spaces
<code>StarPrint, StarSprint</code>	print polynomial with *’s for multiplications
<code>StdDegLexMat</code>	matrices for std. term-orderings
<code>StdDegRevLexMat</code>	matrices for std. term-orderings
<code>submat</code>	submatrix
<code>subsets</code>	returns all sublists of a list
<code>sum</code>	the sum of the elements of a list
<code>SwapRows</code>	swap two rows in a matrix
<code>SymbolRange</code>	range of symbols for the indeterminates of a PolyRing
<code>syz</code>	syzygy modules
<code>tuples</code>	N-tuples
<code>WithoutNth</code>	removes the N-th component from a list
<code>XelMat</code>	matrices for std. term-orderings
<code>ZeroMat</code>	matrix filled with 0

III-2.3 Commands and Functions returning INT

<code>abs</code>	absolute value of a number
<code>AffHilbertFn</code>	the affine Hilbert function
<code>AsINT</code>	convert into an INT
<code>binomial</code>	binomial coefficient
<code>BinomialRepr, BinomialReprShift</code>	binomial representation of integers
<code>Bool01</code>	Convert a boolean to an integer
<code>ceil</code>	round rational up to integer
<code>characteristic</code>	the characteristic of a ring
<code>ContFrac</code>	continued fraction quotients
<code>count</code>	count the objects in a list

<code>deg</code>	the standard degree of a polynomial or moduleelem
<code>den</code>	denominator
<code>Depth</code>	Depth of a module
<code>dim</code>	the dimension of a ring or quotient object
<code>div</code>	quotient for integers
<code>EvalHilbertFn</code>	evaluate the Hilbert function
<code>factorial</code>	factorial function
<code>FactorMultiplicity</code>	multiplicity of a factor of an integer
<code>floor</code>	round rational down to integer
<code>FloorLog2, FloorLog10, FloorLogBase</code>	integer part of the logarithm
<code>FloorSqrt</code>	(truncated) square root of an integer
<code>gcd</code>	greatest common divisor
<code>GradingDim</code>	Number of components in weighted degree
<code>HilbertFn</code>	the Hilbert function
<code>IndetIndex</code>	index of an indeterminate
<code>iroot</code>	integer part of r-th root of an integer
<code>lcm</code>	least common multiple
<code>len</code>	the length of an object
<code>LogCardinality</code>	extension degree of a finite field
<code>LPosn</code>	the position of the leading power-product in a ModuleElem
<code>MayerVietorisTreeN1</code>	N-1st Betti multidegrees of monomial ideals using Mayer-Vietoris trees
<code>MinPowerInIdeal</code>	the minimum power of a polynomial is an ideal
<code>mod</code>	remainder for integers
<code>multiplicity</code>	the multiplicity (degree) of a ring or quotient object
<code>NextPrime</code>	find the next largest prime number
<code>NextProbPrime</code>	find the next largest probable prime number
<code>num</code>	numerator
<code>NumCols</code>	number of columns in a matrix
<code>NumCompts</code>	the number of components
<code>NumGens</code>	number of generators
<code>NumIndets</code>	number of indeterminates
<code>NumPartitions</code>	number of partitions of an integer
<code>NumRows</code>	number of rows in a matrix
<code>NumTerms</code>	number of terms in a polynomial
<code>PowerMod</code>	compute a modular power efficiently
<code>PrimitiveRoot</code>	find a primitive root modulo a prime
<code>random</code>	random integer
<code>randomized</code>	randomize the coefficients of a given polynomial
<code>reg</code>	Castelnuovo-Mumford regularity of a module
<code>RegularityIndex</code>	regularity index of a Hilbert function or series
<code>RingID</code>	identification for ring
<code>rk</code>	rank of a matrix or module
<code>RootBound</code>	bound on roots of a polynomial over QQ
<code>round</code>	round to integer
<code>seed</code>	seed for “random”
<code>sign</code>	the sign of a number
<code>TimeOfDay</code>	the current time
<code>UnivariateIndetIndex</code>	the index of the indeterminate of a univariate polynomial

Chapter III-3

RAT

III-3.1 Introduction to RAT

Rational numbers can be entered as fractions or as terminating decimals. CoCoA always converts a rational number into a fraction in lowest terms.

example

```
/**/ 3.8;  
19/5  
/**/ N := 4/8; N;  
1/2  
/**/ type(N);  
RAT
```

See Also: Commands and Functions for RAT([III-3.2 pg.339](#)), Commands and Functions returning RAT([III-3.3 pg.340](#))

III-3.2 Commands and Functions for RAT

abs	absolute value of a number
AsINT	convert into an INT
AsRAT	convert into a RAT
ceil	round rational up to integer
CFApprox	continued fraction approximation
CFApproximants	continued fraction approximants
ContFrac	continued fraction quotients
DecimalStr	convert rational number to decimal string
den	denominator
FloatApprox	approx. of rational number of the form $M * 2^E$
FloatStr	convert rational number to a decimal string
floor	round rational down to integer
FloorLog2, FloorLog10, FloorLogBase	integer part of the logarithm
IsOne	test whether an object is one
IsZero	test whether an object is zero
MantissaAndExponent10	convert rational number to a float
MantissaAndExponent2	convert rational number to a binary float
max	a maximum element of a sequence or list
min	a minimum element of a sequence or list
NewMatFilled	matrix filled with value
num	numerator

<code>product</code>	the product of the elements of a list
<code>RealRootRefine</code>	refine a real root of a univariate polynomial
<code>RealRoots</code>	computes the real roots of a univariate polynomial
<code>RealRootsApprox</code>	computes approximations to the real roots of a univariate polynomial
<code>RingElem</code>	convert an expression into a RINGELEM
<code>round</code>	round to integer
<code>ScientificStr</code>	convert integer/rational to a floating-point string
<code>sign</code>	the sign of a number
<code>SimplestBinaryRatBetween</code>	find simplest binary rational in a closed interval
<code>SimplestRatBetween</code>	find simplest rational in a closed interval
<code>StableBBasis5</code>	Stable Border Basis of ideal of points
<code>sum</code>	the sum of the elements of a list
<code>TimeFrom</code>	time elapsed since a given moment

III-3.3 Commands and Functions returning RAT

<code>abs</code>	absolute value of a number
<code>ApproxSolve</code>	Approximate real solutions for polynomial system
<code>AsRAT</code>	convert into a RAT
<code>CFApprox</code>	continued fraction approximation
<code>CFApproximants</code>	continued fraction approximants
<code>ContFracToRat</code>	convert continued fraction to rational
<code>CpuTime</code>	Counts cpu time
<code>FloatApprox</code>	approx. of rational number of the form $M * 2^E$
<code>SimplestBinaryRatBetween</code>	find simplest binary rational in a closed interval
<code>SimplestRatBetween</code>	find simplest rational in a closed interval

Chapter III-4

STRING

III-4.1 String Literals

A string literal consists of a sequence of characters between double quotes ("...").

example

```
/**/ PrintLn "The primes up to 10 are ", [n in 1..10 | IsPrime(n)];
The primes up to 10 are [2, 3, 5, 7]

/**/ Print "The quick brown fox", "jumped over the lazy dog.";
The quick brown foxjumped over the lazy dog
```

To put special characters in CoCoA string literals use the appropriate “*escape sequence*”. Here is a summary: “\” produces a double-quote character; “\n” produces a newline character; “\\” produces a backslash character; “\t” produces a TAB character; “\r” produces a carriage-return character.

example

```
/**/ Print "line 1\nline 2";
line 1
line 2
/**/ Print "A string containing \"quote marks\".";
A string containing "quote marks".
```

WARNING: CoCoA still accepts an “*obsolescent*” syntax for string literals (between single-quotes); do not use this!

See Also: String Operations(III-4.2 pg.341), sprintf(I-19.25 pg.263), Commands and Functions for STRING(III-4.3 pg.342), Commands and Functions returning STRING(III-4.4 pg.342)

III-4.2 String Operations

CoCoA offers only a few operations on strings: length, concatenation, comparison, substring containment and indexing.

example

```
/**/ str := "Hello" + "World!"; --> string concatenation
/**/ Print str;
HelloWorld!
/**/ len(str);           --> length in characters
11
/**/ "Abc" < str;        --> lexicographical comparison
true
```

```
/**/ str[1];      --> character indexing, indexes start from 1
H
```

The operator “IsIn” (I-9.49 pg.139) can be used to test if one string is a substring of another.

example

```
/**/ mesg := "Banana";
/**/ "ana" IsIn mesg;
true
/**/ "Ana" IsIn mesg; --> substring must be an exact match
false
```

See Also: String Literals(III-4.1 pg.341), ascii(I-1.15 pg.31), concat(I-3.34 pg.54), IsIn(I-9.49 pg.139), len(I-12.5 pg.161)

III-4.3 Commands and Functions for STRING

ascii	convert between characters and ascii code
error	throw an error message
GetEnv	access shell variables
gin	generic initial ideal
ImplicitHypersurface	implicitization of hypersurface
ImplicitPlotOn	outputs the zero locus of a bivariate polynomial to a file
indets	list of indeterminates in a PolyRing
IsIn	check if one object is contained in another
len	the length of an object
max	a maximum element of a sequence or list
min	a minimum element of a sequence or list
NewPolyRing	create a new PolyRing
NewWeylAlgebra	create a new Weyl Algebra
OpenIFile	open input file
OpenIString	open input string
OpenOFile	open output file
OpenOString	open output string
OpenSocket	open a socket connection
operators, shortcuts	Special characters equivalent to commands
PlotPointsOn	outputs the coordinates of the points to a file
protect	protect a variable from being overwritten
ReadExpr	Read RINGELEM expression from string
RingElem	convert an expression into a RINGELEM
source	read commands from a file or device
SourceRegion	read commands from a region in a file
starting	list functions starting with a given string
SymbolRange	range of symbols for the indeterminates of a PolyRing
tagged	tag an object for pretty printing

III-4.4 Commands and Functions returning STRING

ascii	convert between characters and ascii code
CocoaPackagePath	returns the path to the CoCoA packages

<code>DecimalStr</code>	convert rational number to decimal string
<code>ExternalLibs</code>	Linked external libraries
<code>FloatStr</code>	convert rational number to a decimal string
<code>format</code>	convert object to formatted string
<code>GetEnv</code>	access shell variables
<code>GetErrMesg</code>	returns the message associated with an error
<code>IndetName</code>	the name of an indeterminate
<code>IO.SprintTrunc</code>	convert to a string and truncate
<code>LaTeX</code>	LaTeX formatting
<code>NewLine [OBSOLESCENT]</code>	[OBSOLESCENT] string containing a newline
<code>Packages</code>	list of loaded packages
<code>PkgName</code>	returns the name of a package
<code>ScientificStr</code>	convert integer/rational to a floating-point string
<code>spaces</code>	return a string of spaces
<code>sprint</code>	convert to a string
<code>StarPrint, StarSprint</code>	print polynomial with *'s for multiplications
<code>tag</code>	returns the tag string of an object
<code>TimeFrom</code>	time elapsed since a given moment

Chapter III-5

LIST

III-5.1 Introduction to LIST

A CoCoA list is a sequence of CoCoA objects between square brackets. See also “List Constructors” ([III-5.2 pg.346](#)).

In particular, a list may contain other lists. The empty list is “[]”. If “L” is a list and “N” is an integer, then “L[N]” is the “N”-th component of “L”.

If “L” contains sublists, then “L[N_1, N_2, ..., N_s]” is shorthand for “L[N_1][N_2]...[N_s]” (see the example below).

Lists are often used to build structured objects of type “MAT”, “MODULEELEM”, “IDEAL”, and “MODULE”.

example

```
/**/ Use R ::= QQ[t,x,y,z];
/**/ L := [34*x+y^2, "a string", [], [True, False]]; -- a list
/**/ L[1]; -- the 1st component
y^2 +34*x
/**/ L[2];
a string
/**/ L[3];
[ ]
/**/ L[4]; -- The 4th component is a list, itself;
[true, false]
/**/ L[4][1]; -- its 1st component;
true
/**/ L[4,1]; -- the same.
true

/**/ [1,"a"]+[2,"b"]; -- NOTE: one may add lists if their components are
[3, "ab"] -- compatible (see "Algebraic Operators").

/**/ L := [x^2-y, t*y^2-z^3];
/**/ I := ideal(L);
/**/ I;
ideal(x^2 -y, t*y^2 -z^3)
```

See Also: List Constructors([III-5.2 pg.346](#)), Commands and Functions for LIST([III-5.3 pg.346](#)), Commands and Functions returning LIST([III-5.4 pg.349](#))

III-5.2 List Constructors

These operators create new lists.

```
A..B
[A,B,C,...]
[X in L: LIST | B: BOOL]: LIST
[E:expression | X in L]: LIST
[E:expression | X in L: LIST and B: BOOL]: LIST
```

“A..B” creates the list of integers from “A” to “B”, both ends are included.

“[A,B,C,...]” makes a list containing “A”, “B”, “C” and so on, in that order.

“[X in L | B]” makes a list of those elements in “L” for which condition “B” is true.

“[E | X in L]” evaluates the expression “E” for each “X” in “L”, and collects the results in a new list.

“[E | X in L and B]” evaluates the expression “E” for each “X” in “L” which satisfies the condition “B”, and collects the results in a new list.

example

```
/**/ []; --> empty list
[]
/**/ 1..4;
[1, 2, 3, 4]
/**/ [3,1,4,2];
[3, 1, 4, 2]
/**/ [N in 1..10 | IsPrime(N)];
[2, 3, 5, 7]
/**/ [N^2 | N in 1..4];
[1, 4, 9, 16]
/**/ [N^2 | N in 1..10 and IsPrime(N)];
[4, 9, 25, 49]
```

See Also: NewList(I-14.5 pg.186), append(I-1.12 pg.30), concat(I-3.34 pg.54), Range Operator(II-3.5 pg.308), CartesianProduct, CartesianProductList(I-3.4 pg.42)

III-5.3 Commands and Functions for LIST

append	append an object to a list
apply	apply homomorphism
ApproxSolve	Approximate real solutions for polynomial system
ascii	convert between characters and ascii code
BettiMatrix	the matrix of the graded Betti numbers
CartesianProduct, CartesianProductList	Cartesian product of lists
CheckArgTypes	Check types in a list
coefficients	list of coefficients of a polynomial
CoefficientsWRT	list of coeffs and PPs of a polynomial wrt an indet or a list of indets
ColMat	single column matrix
concat	concatenate lists
ConcatHorList	create a simple block matrix
ConcatLists	concatenate a list of lists
ConcatVerList	create a simple block matrix
ContentWRT	content of a polynomial wrt and indet or a list of indets
ContFracToRat	convert continued fraction to rational
count	count the objects in a list
DiagMat	matrix with given diagonal

<code>diff</code>	returns the difference between two lists
<code>distrib</code>	the distribution of objects in a list
<code>DivAlg</code>	division algorithm
<code>elim</code>	eliminate variables
<code>ElimMat</code>	matrix for elimination ordering
<code>EqSet</code>	checks if the set of elements in two lists are equal
<code>eval</code>	substitute numbers or polynomials for indeterminates
<code>EvalQuasiPoly</code>	Evaluate a quasi-polynomial at an integer
<code>Ext</code>	presentation Ext modules as quotients of free modules
<code>FGLM5</code>	perform a FGLM Groebner Basis conversion
<code>first</code>	the first N elements of a list
<code>flatten</code>	flatten a list
<code>foreach</code>	loop command
<code>FVector</code>	compute the f-vector of a top simplices list
<code>GBM</code>	intersection of ideals for zero-dimensional schemes
<code>gcd</code>	greatest common divisor
<code>GCDFreeBasis</code>	determine (minimal) GCD free basis of a set of integers
<code>HGBM</code>	intersection of ideals for zero-dimensional schemes
<code>HilbertSeriesShifts</code>	the Hilbert-Poincare series
<code>homog</code>	homogenize with respect to an indeterminate
<code>HomogElimMat</code>	matrix for elimination ordering
<code>ideal</code>	ideal generated by list
<code>IdealAndSeparatorsOfPoints</code>	ideal and separators for affine points
<code>IdealAndSeparatorsOfProjectivePoints</code>	ideal and separators for points
<code>IdealOfProjectivePoints</code>	ideal of a set of projective points
<code>implicit</code>	implicitization
<code>ImplicitHypersurface</code>	implicitization of hypersurface
<code>ImplicitPlot</code>	outputs the zero locus of a bivariate polynomial to a file
<code>ImplicitPlotOn</code>	outputs the zero locus of a bivariate polynomial to a file
<code>in</code>	list element selector in list constructor
<code>InitialIdeal</code>	Initial ideal
<code>insert [OBSOLESCE]</code>	[OBSOLESCE] insert an object in a list
<code>Interpolate</code>	interpolating polynomial
<code>interreduce, interreduced</code>	interreduce a list of polynomials
<code>intersection</code>	intersect lists, ideals, or modules
<code>IntersectList</code>	intersect lists, ideals, or modules
<code>IsFactorClosed</code>	test whether a list of PPs is factor closed
<code>IsHomog</code>	test whether given polynomials are homogeneous
<code>IsIn</code>	check if one object is contained in another
<code>IsSubset</code>	checks if the elements of one list are a subset of another
<code>IsTree5</code>	checks if a facet complex is a tree
<code>jacobian</code>	the Jacobian of a list of polynomials
<code>last</code>	the last N elements of a list
<code>lcm</code>	least common multiple
<code>len</code>	the length of an object
<code>LexSegmentIdeal</code>	lex-segment ideal containing L, or with the same Hilbert fn as I
<code>MakeMatByRows, MakeMatByCols</code>	convert a list into a matrix
<code>MakeSet</code>	remove duplicates from a list
<code>MakeTerm</code>	returns a monomial (power-product) with given exponents
<code>matrix</code>	convert a list into a matrix
<code>max</code>	a maximum element of a sequence or list
<code>MaxBy</code>	a maximum element of a list
<code>min</code>	a minimum element of a sequence or list
<code>MinBy</code>	a minimum element of a list
<code>ModuleElem</code>	create a module element
<code>NewPolyRing</code>	create a new PolyRing
<code>NmzComputation</code>	flexible access to Normaliz

NmzEhrhartRing	Computes the Ehrhart ring
NmzIntClosureMonIdeal	integral closure of a monomial ideal
NmzIntClosureToricRing	integral closure of a toric ring
NmzNormalToricRing	normalization of a toric ring
NonZero	remove zeroes from a list
NR	normal reduction
operators, shortcuts	Special characters equivalent to commands
permutations	returns all permutations of the entries of a list
PlotPoints	outputs the coordinates of the points to a file
PlotPointsOn	outputs the coordinates of the points to a file
PolyAlgebraHom	homomorphism of polynomial algebras
PolyRingHom	homomorphism of polynomial rings
PrintBettiDiagram	the diagram of the graded Betti numbers
product	the product of the elements of a list
QZP	change field for polynomials and ideals
RandomSubset	random subset
RandomTuple	random tuple
RationalAffinePoints	Affine rational solutions
RationalProjectivePoints	Projective rational solutions
RationalSolve	Rational solutions for polynomial system
RatReconstructWithBounds	deterministic rational reconstruction from modular image
RefineGCDFreeBasis	refine an integer GCD free basis
remove	remove an object in a list
reverse, reversed	reverse a list
RingsOf	list of the rings of an object
RMap [OBSOLESCE]	[OBSOLESCE] define ring homomorphism for function image
RowMat	single row matrix
ScalarProduct	scalar product
SeparatorsOfPoints	separators for affine points
SeparatorsOfProjectivePoints	separators for projective points
SetRow	set a list as a row into a matrix
shape	extended list of types involved in an expression
SimplexInfo	compute the Stanley-Reisner ideal, the Alexander Dual complex And ideal
SimplicialHomology	compute the simplicial homology of a top simplices list
sort	sort a list
SortBy	sort a list
sorted	sort a list
SortedBy	sort a list
StableBBasis5	Stable Border Basis of ideal of points
StableIdeal	stable ideal containing L
StronglyStableIdeal	strongly stable ideal containing L
SubalgebraRepr	representation of a polynomial as a subalgebra element
submat	submatrix
submodule	submodule generated by list
subsets	returns all sublists of a list
sum	the sum of the elements of a list
SymbolRange	range of symbols for the indeterminates of a PolyRing
syzy	syzygy modules
tail	remove the first element of a list
TmpNBM	Numerical Border Basis of ideal of points
toric	saturate toric ideals
tuples	N-tuples
WithoutNth	removes the N-th component from a list
ZPQ	change field for polynomials and ideals

III-5.4 Commands and Functions returning LIST

AllReducedGroebnerBases	all reduced Groebner bases of an ideal
apply	apply homomorphism
ApproxSolve	Approximate real solutions for polynomial system
ascii	convert between characters and ascii code
BBasis5	Border Basis of zero dimensional ideal
BinomialRepr, BinomialReprShift	binomial representation of integers
CartesianProduct, CartesianProductList	Cartesian product of lists
CFApproximants	continued fraction approximants
coefficients	list of coefficients of a polynomial
CoefficientsWRT	list of coeffs and PPs of a polynomial wrt an indet or a list of indets
CoeffListWRT	list of coefficients of a polynomial wrt and indet
compts	list of components of a ModuleElem
concat	concatenate lists
ConcatLists	concatenate a list of lists
ContFrac	continued fraction quotients
CurrentTypes	lists all data types
diff	returns the difference between two lists
distrib	the distribution of objects in a list
eigenfactors	eigenfactors of a matrix
eigenvectors	eigenvalues and eigenvectors of a matrix
EquiIsoDec	equidimensional isoradical decomposition
exponents	the list of exponents of the leading term of a polynomial
ExternalLibs	Linked external libraries
FGLM5	perform a FGLM Groebner Basis conversion
fields	list the fields of a record
flatten	flatten a list
FrbAlexanderDual	Alexander Dual of monomial ideals
FrbAssociatedPrimes	Associated primes of monomial ideals
FrbIrreducibleDecomposition	Irreducible decomposition of monomial ideals
FrbMaximalStandardMonomials	Maximal standard monomials of monomial ideals
FrbPrimaryDecomposition	Primary decomposition of monomial ideals
GBasis	calculate a Groebner basis
GBasisTimeout	compute a Groebner basis with a timeout
GCDFreeBasis	determine (minimal) GCD free basis of a set of integers
GenericPoints	random projective points
GenRepr	representation in terms of generators
gens	list of generators of an ideal
Get	read characters from a device
GetCol	convert a column of a matrix into a list
GetCols	convert a matrix into a list of lists
GetRow	convert a row of a matrix into a list
GetRows	convert a matrix into a list of lists
HilbertBasisKer	Hilbert basis for a monoid
homog	homogenize with respect to an indeterminate
HVector	the h-vector of a module or quotient object
in	list element selector in list constructor
indets	list of indeterminates in a PolyRing
IndetSubscripts	the index of an indeterminate
interreduce, interreduced	interreduce a list of polynomials
intersection	intersect lists, ideals, or modules
IntersectList	intersect lists, ideals, or modules
InverseSystem	Inverse system of an ideal of derivations
JanetBasis	the Janet basis of an ideal
LinKerBasis	find the kernel of a matrix

MakeSet	remove duplicates from a list
MinGens	list of minimal generators
minors	list of minor determinants of a matrix
MinSubsetOfGens	list of minimal generators
monomials	the list of monomials of a polynomial
NewList	create a new list
NmzDiagInvariants	ring of invariants of a diagonalizable group action
NmzEhrhartRing	Computes the Ehrhart ring
NmzFiniteDiagInvariants	ring of invariants of a finite group action
NmzIntClosureMonIdeal	integral closure of a monomial ideal
NmzIntClosureToricRing	integral closure of a toric ring
NmzIntersectionValRings	intersection of ring of valuations
NmzNormalToricRing	normalization of a toric ring
NmzTorusInvariants	ring of invariants of torus action
NonZero	remove zeroes from a list
Packages	list of loaded packages
partitions	partitions of an integer
permutations	returns all permutations of the entries of a list
PrimaryDecomposition	primary decomposition of an ideal
PrimaryDecomposition0	primary decomposition of a 0-dimensional ideal
PrimaryDecompositionGTZO	primary decomposition of a 0-dimensional ideal
QuotientBasis	vector space basis for zero-dimensional quotient rings
QZP	change field for polynomials and ideals
RandomSubset	random subset
RandomSubsetIndices	indices for random subset
RandomTuple	random tuple
RandomTupleIndices	indices for random tuples
RationalAffinePoints	Affine rational solutions
RationalProjectivePoints	Projective rational solutions
RationalSolve	Rational solutions for polynomial system
RealRoots	computes the real roots of a univariate polynomial
RealRootsApprox	computes approximations to the real roots of a univariate polynomial
ReducedGBasis	compute reduced Groebner basis
RefineGCDFreeBasis	refine an integer GCD free basis
res	free resolution
reverse, reversed	reverse a list
RingsOf	list of the rings of an object
SeparatorsOfPoints	separators for affine points
SeparatorsOfProjectivePoints	separators for projective points
shape	extended list of types involved in an expression
sorted	sort a list
SortedBy	sort a list
starting	list functions starting with a given string
subsets	returns all sublists of a list
support	the list of terms of a polynomial or moduleelem
SymbolRange	range of symbols for the indeterminates of a PolyRing
tail	remove the first element of a list
TopLevelFunctions	returns the functions available at top-level
tuples	N-tuples
UniversalGroebnerBasis	universal Groebner basis of the input ideal
wdeg	multi-degree of an polynomial
WithoutNth	removes the N-th component from a list
ZPQ	change field for polynomials and ideals

Chapter III-6

RECORD

III-6.1 Introduction to RECORD

A record is a data type in CoCoA representing a list of bindings of the form “*name to object*”.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ P := record[ I := ideal(x,y^2-z), F := x^2 + y, Misc := [1,3,4]];
/**/ P.I;
ideal(x, y^2 -z)
/**/ P["I"];
ideal(x, y^2 -z)

/**/ P.Misc;
[1, 3, 4]
/**/ P.Misc[2];
3

/**/ P.Date := "1/1/98";
/**/ indent(P);
record[
  Date := "1/1/98",
  F := x^2 +y,
  I := ideal(x, y^2 -z),
  Misc := [1, 3, 4]
]

/**/ P["Misc",3]; -- equivalent to P.Misc[3]
4
```

Each entry in a record is called a “*field*”. Note that records are “*open*” in the sense that their fields can be extended, as shown in the previous example. At present, there is no function for deleting fields from a record, one must rewrite the record, selecting the fields to retain:

example

```
/**/ P := record[A := 2, B := 3, C := 5, D := 7];
/**/ Q := record[];

Foreach F In Fields(P) Do
  If F <> "C" Then Q[F] := P[F]; EndIf;
EndForeach;

/**/ P := Q;
```

```
/**/ P;
record[A := 2, B := 3, D := 7]
```

See Also: Commands and Functions for RECORD([III-6.2 pg.352](#)), Commands and Functions returning RECORD([III-6.3 pg.352](#))

III-6.2 Commands and Functions for RECORD

CoefficientsWRT	list of coeffs and PPs of a polynomial wrt an indet or a list of indets
fields	list the fields of a record
NmzComputation	flexible access to Normaliz
PrintBettiDiagram	the diagram of the graded Betti numbers
RealRootRefine	refine a real root of a univariate polynomial
record field selector	select a field of a record
shape	extended list of types involved in an expression

III-6.3 Commands and Functions returning RECORD

AlmostQR	QR decomposition of a matrix
CocoaLimits	limits on exponents and ring characteristics
ContentFreeFactor	factorization of multivariate polynomial into content-free factors
CRT	Chinese Remainder Theorem
CRTPoly	Chinese Remainder Theorem on polynomial coefficients
DivAlg	division algorithm
eigenvectors	eigenvalues and eigenvectors of a matrix
factor	factor a polynomial
FVector	compute the f-vector of a top simplices list
IdealAndSeparatorsOfPoints	ideal and separators for affine points
IdealAndSeparatorsOfProjectivePoints	ideal and separators for points
IndetSymbols	the names of the indeterminates in a PolyRing
LinearSimplify	simplifying linear substitution for a univariate polynomial over a field
MantissaAndExponent10	convert rational number to a float
MantissaAndExponent2	convert rational number to a binary float
NmzComputation	flexible access to Normaliz
PreImage	preimage of a RINGELEM
PreprocessPts	Reduce redundancy in a set of approximate points
PrimaryDecomposition0	primary decomposition of a 0-dimensional ideal
PrimaryDecompositionGTZ0	primary decomposition of a 0-dimensional ideal
RatReconstructByContFrac, RatReconstructByLattice	rational reconstruction from modular image
RatReconstructWithBounds	deterministic rational reconstruction from modular image
RealRootRefine	refine a real root of a univariate polynomial
record	create a record
shape	extended list of types involved in an expression
SimplexInfo	compute the Stanley-Reisner ideal, the Alexander Dual complex
SimplicialHomology	compute the simplicial homology of a top simplices list
SmoothFactor	find small prime factors of an integer
SqFreeFactor	compute a squarefree factorization
StableBBasis5	Stable Border Basis of ideal of points
starting	list functions starting with a given string
SubalgebraRepr	representation of a polynomial as a subalgebra element

TmpNBM

VersionInfo

Numerical Border Basis of ideal of points
version and info about CoCoA

Chapter III-7

FUNCTION

III-7.1 Introduction to FUNCTION

The most important construct in CoCoA programming is the user-defined function. These functions take parameters, perform CoCoA commands, and return values. Collections of functions can be stored in text files and read into CoCoA sessions using “source” (I-19.22 pg.262). To prevent name conflicts of the type that are likely to arise if functions are to be made available for use by others, the functions can be collected in “packages”.

To learn about user functions, look up “define” (I-4.4 pg.64) (online, enter “?define”).

III-7.2 FUNCTIONs are first class objects

In CoCoA-5 functions are “first class objects”, and so may be passed like any other value.

example

```
-- The following function MyMax takes a function LessThan as parameter,
-- and returns the maximum of X and Y w.r.t. the ordering defined by the
-- function LessThan.

/**/ Define MyMax(LessThan, X, Y)
/**/   If LessThan(X, Y) Then Return Y; Else Return X; EndIf;
/**/ EndDefine;

-- Let's use MyMax by giving two different orderings.

/**/ Define CompareLT(X, Y) Return LT(X) < LT(Y); EndDefine;
/**/ Define CompareLC(X, Y) Return LC(X) < LC(Y); EndDefine;

/**/ Use R ::= QQ[x,y,z];
/**/ MyMax(CompareLC, 3*x-y, 5*z-2);
5*z -2
/**/ MyMax(CompareLT, 3*x-y, 5*z-2);
3*x -y
```

III-7.3 Commands and Functions for FUNCTION

MaxBy	a maximum element of a list
MinBy	a minimum element of a list
ref	passing function parameters by reference
return	exit from a function

<code>SortBy</code>	sort a list
<code>SortedBy</code>	sort a list
<code>TopLevel</code>	make a top level variable accessible

III-7.4 Commands and Functions returning **FUNCTION**

<code>define</code>	define a function
<code>func</code>	Anonymous function
<code>TopLevelFunctions</code>	returns the functions available at top-level

Chapter III-8

TYPE

III-8.1 Commands and Functions for TYPE

`describe` information about an object

III-8.2 Commands and Functions returning TYPE

<code>CurrentTypes</code>	lists all data types
<code>shape</code>	extended list of types involved in an expression
<code>type</code>	the data type of an expression

Chapter III-9

RING

III-9.1 Introduction to RING

Rings, and especially polynomial rings, play a central role in CoCoA.

The user can define many rings, but at any time a “*current ring*” is active within the system.

Once a ring has been defined, the system can handle the following mathematical objects defined over that ring:

- * elements of the ring
- * ideals
- * matrices
- * lists of objects
- * modules (submodules of a free module)
- * rings

Variables containing ring-dependent objects such as polynomials, ideals, and matrices are “*labeled*” by their ring. Any operation on them is performed in their ring, independently of what the current ring is.

See Also: Polynomial Rings(III-9.2 pg.359), Commands and Functions for RING(III-9.8 pg.362), Commands and Functions returning RING(III-9.9 pg.363)

III-9.2 Polynomial Rings

CoCoA starts with the default (polynomial) ring “ $R = \mathbb{Q}[x,y,z]$ ”. Polynomial rings are created with the function “NewPolyRing” (I-14.8 pg.188), but there is a special simplified syntax working in most cases: it must be preceded by the command “use” (I-21.6 pg.287) or by the symbol “ $::=$ ” (or both)

```
R ::= C[X:INDETS];          use C[X:INDETS];
R ::= C[X:INDETS], 0;        use C[X:INDETS], 0;
```

“R” is the identifier of a CoCoALanguage variable, “C” is a RING, “X” is an expression that defines the indeterminates, “0” is a pre-defined ordering (“lex”, “deglex”, “degrevlex”). The default ordering is DegRevLex.

After the ring is defined using the above syntax, it can be made to be the current ring with the command “use” (I-21.6 pg.287).

example

```
/**/ Use R ::= QQ[a,b,c]; -- define and use the ring R
/**/ K := NewFractionField(R);
/**/ S := K[x,y], Lex;
/**/ CurrentRing; -- the current ring is still R
RingWithID(21, "QQ[a,b,c]")
/**/ Use S; -- now the ring S is the current ring
```

```
/**/ CurrentRing;
RingWithID(23, "RingWithID(22)[x,y]")
```

See Also: [NewPolyRing\(I-14.8 pg.188\)](#), [CurrentRing\(I-3.51 pg.61\)](#)

III-9.3 Coefficient Rings

The coefficient ring for a CoCoA polynomial ring may be any ring “R”:

1. ZZ: (arbitrarily large) integer numbers;
2. QQ: (arbitrarily large) rational numbers;
3. ZZ/(N);
4. R[a,b,c];
5. K(a,b,c);

The first two types of coefficients are based on the GNU-gmp library. Some operations work only when coefficients are in a field (a meaningful error message will be thrown). NOTE: inside “define/enddefine” the top-level variables “ZZ” ([I-25.4 pg.298](#)) and “QQ” ([I-17.1 pg.223](#)) are not directly visible. Use “RingZZ()” or “RingQQ()” instead (or import them with “TopLevel” ([I-20.10 pg.280](#))).

example

```
/**/ R ::= QQ[x,y];    R;
/**/ S ::= ZZ/(5)[t];  S;
/**/ -- NOTE: "::=" for special syntax C[X], "!=" for normal function call
/**/ QQi ::= QQ[i];
/**/ K := NewQuotientRing(QQi, ideal(ReadExpr(QQi, "i^2+1")));
/**/ U ::= K[u,v];     U;
```

See Also: [CoeffRing\(I-3.25 pg.51\)](#)

III-9.4 Indeterminates

An “*indeterminate*” is represented by an identifier followed by one or more integer indices. For example, “x”, “alpha[1]”, “x[1,2,3]” are legal (and different) indeterminates, as is “x[i, 2*i+1]” if “i” is of type “INT”.

When creating a ring the indeterminates are listed separate by commas.

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ Use R ::= QQ[x[1..2,4..8],y[1..3],u,v];
/**/ Indets(R);
[x[1,4], x[1,5], x[1,6], x[1,7], x[1,8], x[2,4], x[2,5], x[2,6],
x[2,7], x[2,8], y[1], y[2], y[3], u, v]
-----
```

III-9.5 Orderings

Polynomials are always sorted with respect to the ordering of their base ring. All the operations involving polynomials utilize and preserve this ordering. The user can define custom orderings or choose a predefined term-ordering (see “NewPolyRing” ([I-14.8 pg.188](#))).

The predefined term-orderings are:

- * standard-degree reverse lexicographic: “DegRevLex” (default)
- * standard-degree lexicographic: “DegLex”

* pure lexicographic: “Lex” (no grading)

* pure xel: “Xe1” (NOT YET IMPLEMENTED)

If the indeterminates are given in the order “ x_1, \dots, x_n ”, then “ $x_1 > \dots > x_n$ ” with respect to Lex, and “ $x_1 < \dots < x_n$ ” with respect to Xel.

See Also: OrdMat(I-15.10 pg.205), elim(I-5.4 pg.76)

III-9.6 Module Orderings

***** NOT YET UPDATED TO CoCoA-5 *****

First we recall the definition of a module term-ordering. We assume that all our free modules have finite rank and are of the type $M = R^r$ where R is a polynomial ring with n indeterminates. Let $[e_i | i = 1, \dots, r]$ be the canonical basis of M . A “term” of M is an element of the form Te_i where T belongs to the set $T(R)$ of the terms of R . Hence the set $T(M)$, of the terms of M , is in one-to-one correspondence with the Cartesian product, $T(R) \times [1, \dots, r]$.

A “module term-ordering” is defined as a total ordering $>$ on $T(M)$ such that for all “ T, T_1, T_2 ” in $T(R)$, with T not equal to 1, and for all i, j in $1, \dots, r$,

- (1) $T * T_1 * e_i > T_1 * e_i$
- (2) $T_1 * e_i > T_2 * e_j \Rightarrow T * T_1 * e_i > T * T_2 * e_j$

Each term-ordering on the current ring induces several term-orderings on a free module. CoCoA allows the user to choose between the following:

* the ordering called “ToPos” (which is the default one) defined by:

$$T_1 * e_i > T_2 * e_j \Leftrightarrow \begin{array}{l} T_1 > T_2 \text{ in } R \\ \text{or, if } T_1 = T_2, i < j \end{array}$$

* the ordering called “PosTo” defined by:

$$T_1 * e_i > T_2 * e_j \Leftrightarrow \begin{array}{l} i < j \\ \text{or, if } i = j, T_1 > T_2 \text{ in } R. \end{array}$$

The leading term of the vector (x, y^2) with respect to two different module term-orderings:

example

```

Use R ::= QQ[x,y], ToPos;
LT(Vector(x,y^2));
Vector(0, y^2)
-----
Use R ::= QQ[x,y], PosTo;
LT(Vector(x,y^2));
Vector(x, 0)
-----

```

III-9.7 Quotient Rings

If “ R ” is a ring and “ I ” is an ideal (in “ R ”) then “ R/I ” creates the corresponding quotient ring.

example

```

/**/ Use R ::= QQ[x,y];
/**/ I := ideal(x^3+y^3, x^2*y-y^2*x);
/**/ Q := R/I;
/**/ HilbertFn(Q); -- the Hilbert function for Q
H(0) = 1

```

```

H(1) = 2
H(2) = 3
H(3) = 2
H(4) = 1
H(t) = 0   for t >= 5

```

See Also: [NewQuotientRing\(I-14.9 pg.188\)](#)

III-9.8 Commands and Functions for RING

AffHilbertFn	the affine Hilbert function
BaseRing	the base ring of a ring
BettiDiagram	the diagram of the graded Betti numbers
CanonicalHom	canonical homomorphism
characteristic	the characteristic of a ring
CoeffEmbeddingHom	returns the coefficient embedding homomorphism of a polynomial ring
CoeffRing	the ring of coefficients of a polynomial ring
ColMat	single column matrix
DefiningIdeal	defining ideal of a quotient ring
DensePoly	the sum of all power-products of a given degree
DiagMat	matrix with given diagonal
dim	the dimension of a ring or quotient object
EmbeddingHom	returns the embedding homomorphism of a fraction field
GenericPoints	random projective points
GradingMat	matrix of generalized weights for indeterminates
HilbertFn	the Hilbert function
HilbertPoly	the Hilbert polynomial
HilbertSeries	the Hilbert-Poincare series
HilbertSeriesMultiDeg	the Hilbert-Poincare series wrt a multigrading
HVector	the h-vector of a module or quotient object
ideal	ideal generated by list
IdealOfPoints	ideal of a set of affine points
IdentityMat	the identity matrix
implicit	implicitization
ImplicitHypersurface	implicitization of hypersurface
indet	individual indeterminates
indets	list of indeterminates in a PolyRing
IndetSymbols	the names of the indeterminates in a PolyRing
InducedHom	homomorphism induced by a homomorphism
IsField	test whether a ring is a field
IsFiniteField	test whether a ring is a finite field
IsFractionField	test whether a ring is a fraction field
IsQQ	test whether a ring is the ring of rationals
IsQuotientRing	test whether a ring is a quotient ring
IsStdGraded	checks if the grading is standard
IsTrueGCDDomain	test whether a ring is a true GCD domain
IsZZ	test whether a ring is the ring of integers
LogCardinality	extension degree of a finite field
MakeTerm	returns a monomial (power-product) with given exponents
matrix	convert a list into a matrix
multiplicity	the multiplicity (degree) of a ring or quotient object
NewFractionField	create a new fraction field
NewFreeModule	create a new FreeModule
NewMat	Zero matrix
NewPolyRing	create a new PolyRing

NewQuotientRing	create a new quotient ring
NewWeylAlgebra	create a new Weyl Algebra
NumIndets	number of indeterminates
one	one of a ring
operators, shortcuts	Special characters equivalent to commands
OrdMat	matrix defining a term-ordering
poincare [OBSOLESCENT]	[OBSOLESCENT] the Hilbert-Poincare series
PolyAlgebraHom	homomorphism of polynomial algebras
PolyRingHom	homomorphism of polynomial rings
PrintBettiDiagram	the diagram of the graded Betti numbers
QuotientingHom	returns the projection homomorphism into a quotient ring
ReadExpr	Read RINGELEM expression from string
reg	Castelnuovo-Mumford regularity of a module
RegularityIndex	regularity index of a Hilbert function or series
RingElem	convert an expression into a RINGELEM
RingID	identification for ring
RowMat	single row matrix
SubalgebraRepr	representation of a polynomial as a subalgebra element
TmpChainCanonicalHom	canonical homomorphism
TmpNBM	Numerical Border Basis of ideal of points
WeightsMatrix [OBSOLESCENT]	[OBSOLESCENT] matrix of generalized weights for indeterminates
zero	zero of a ring
ZeroMat	matrix filled with 0

III-9.9 Commands and Functions returning RING

BaseRing	the base ring of a ring
codomain	codomain of a homomorphism
CoeffRing	the ring of coefficients of a polynomial ring
domain	domain of a homomorphism
NewFractionField	create a new fraction field
NewPolyRing	create a new PolyRing
NewQuotientRing	create a new quotient ring
NewRingFp	create a new finite field
NewRingTwinFloat	create a new twin-float ring
NewWeylAlgebra	create a new Weyl Algebra
RingOf	the ring of the object
RingQQ	the ring of rationals
RingQQt	pre-defined polynomial rings
RingsOf	list of the rings of an object
RingZZ	the ring of integers

Chapter III-10

RINGHOM

III-10.1 Introduction to RINGHOM

A variable “X” containing an INT or a RAT can be immediately used within any RING. But an object “X” of other types, such as RINGELEM, IDEAL, MAT,... can be used only within its own RING, “RingOf(X)”. Such an object can be mapped into another RING using a “RINGHOM”: “*think mathematically*” ;-)

Most likely, the only function you need to use is just “CanonicalHom” (I-3.2 pg.41) which returns the canonical homomorphism between two rings (if there is one). Given a RINGHOM “phi” just type “phi(x)” if “x” is a RINGELEM, “apply(phi, x)” if “x” is a LIST or MAT.

However, there are also a few handy shortcuts silently determining and applying a homomorphism: the functions “matrix” (I-13.10 pg.173) and “RingElem” (I-18.39 pg.244) map the argument into the given ring (e.g. “matrix(R, M)” maps “M” into a new matrix in the ring “R”). Another shortcut is “BringIn” (I-2.12 pg.39) (easy, but slow).

NOTE: all CoCoA functions should be smart enough to take into account the RING in which their value was defined, for example “GBasis” (I-7.1 pg.97), “LT” (I-12.20 pg.168), “wdeg” (I-23.1 pg.291),...

NOTE: “QZP”, “ZPQ” are NOT YET IMPLEMENTED.

See Also: Commands and Functions for RINGHOM(III-10.3 pg.366), Commands and Functions returning RINGHOM(III-10.4 pg.366), apply(I-1.13 pg.30), CanonicalHom(I-3.2 pg.41), PolyAlgebraHom(I-16.14 pg.211), PolyRingHom(I-16.15 pg.212), matrix(I-13.10 pg.173), RingElem(I-18.39 pg.244), BringIn(I-2.12 pg.39)

III-10.2 Composition of RINGHOM

Two RINGHOM “phi: R-->S” and “psi: S-->T” can be composed.

example

```
/**/ R := NewPolyRing(QQ, "a");
/**/ S := NewFractionField(R); -- QQ(a)
/**/ T := NewPolyRing(S, "x");
/**/ phi := CanonicalHom(R,S);
/**/ psi := CanonicalHom(S,T);
/**/ theta := psi(phi);
/**/ theta(ReadExpr(R, "a^2+a-1"));
a^2 + a - 1
/**/ RingOf(theta(ReadExpr(R, "a^2+a-1"))) = T;
true
```

See Also: CanonicalHom(I-3.2 pg.41), InducedHom(I-9.25 pg.129)

III-10.3 Commands and Functions for RINGHOM

<code>apply</code>	apply homomorphism
<code>codomain</code>	codomain of a homomorphism
<code>domain</code>	domain of a homomorphism
<code>InducedHom</code>	homomorphism induced by a homomorphism
<code>IsInjective</code>	check if a RINGHOM is injective
<code>IsSurjective</code>	check if a RINGHOM is surjective
<code>ker</code>	Kernel of a homomorphism
<code>PolyRingHom</code>	homomorphism of polynomial rings
<code>PreImage</code>	preimage of a RINGELEM

III-10.4 Commands and Functions returning RINGHOM

<code>CanonicalHom</code>	canonical homomorphism
<code>CoeffEmbeddingHom</code>	returns the coefficient embedding homomorphism of a polynomial ring
<code>EmbeddingHom</code>	returns the embedding homomorphism of a fraction field
<code>InducedHom</code>	homomorphism induced by a homomorphism
<code>PolyAlgebraHom</code>	homomorphism of polynomial algebras
<code>PolyRingHom</code>	homomorphism of polynomial rings
<code>QuotientingHom</code>	returns the projection homomorphism into a quotient ring
<code>TmpChainCanonicalHom</code>	canonical homomorphism

Chapter III-11

RINGELEM

III-11.1 Introduction to RINGELEM

An object of type RINGELEM in CoCoA represents an element of a ring.

To fix terminology about polynomials (elements of a polynomial ring): a polynomial is a sum of terms; each term is the product of a coefficient and power-product, a power-product being a product of powers of indeterminates. (In English it is standard to use “*monomial*” to mean a power-product, however, in other languages, such as Italian, monomial connotes a power-product multiplied by a scalar. In the interest of world peace, we will use the term power-product in those cases where confusion may arise.)

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ F := ***3xyz + xy^2***;
/**/ F;
xy^2 + 3xyz
-----
Use R ::= QQ[x[1..5]];
Sum([x[N]^2 | N In 1..5]);
x[1]^2 + x[2]^2 + x[3]^2 + x[4]^2 + x[5]^2
-----
```

CoCoA always keeps polynomials ordered with respect to the term-orderings of their corresponding rings.

The following algebraic operations on polynomials are supported:

F^N , $+F$, $-F$, $F \cdot G$, F/G if G divides F , $F+G$, $F-G$,

where F , G are polynomials and N is an integer. The result may be a rational function.

example

```
Use R ::= QQ[x,y,z];
F := x^2+xy;
G := x;
F/G;
x + y
-----
F/(x+z);
(x^2 + xy)/(x + z)
-----
F^2;
x^4 + 2x^3y + x^2y^2
-----
F^(-1);
```

```
1/(x^2 + xy)
-----
```

III-11.2 Evaluation of Polynomials

The cleanest and most efficient way to evaluate polynomials is defining the appropriate “PolyAlgebraHom” (I-16.14 pg.211). However there are some handy shortcuts: “subst” (I-19.40 pg.270) and “eval” (I-5.11 pg.80).

example

```
/**/ Use R ::= QQ[x,y,z];
/**/ f := x+y+z; --> let x=2 and y=1 in f
/**/ phi := PolyAlgebraHom(R, R, [2,1,z]); phi(f);
z +3
/**/ eval(f, [2,1]);
z +3
/**/ subst(f, [[x,2],[y,1]]);
z +3
```

See Also: PolyAlgebraHom(I-16.14 pg.211), eval(I-5.11 pg.80), subst(I-19.40 pg.270)

III-11.3 Commands and Functions for RINGELEM

abs	absolute value of a number
apply	apply homomorphism
ApproxSolve	Approximate real solutions for polynomial system
AsINT	convert into an INT
AsRAT	convert into a RAT
binomial	binomial coefficient
CanonicalRepr	representative of a class in a quotient ring
CharPoly	characteristic polynomial of a matrix
ClearDenom	clear common denominator of a polynomial with rational coeffs
coefficients	list of coefficients of a polynomial
CoefficientsWRT	list of coeffs and PPs of a polynomial wrt an indet or a list of indets
CoeffListWRT	list of coefficients of a polynomial wrt and indet
CoeffOfTerm	coefficient of a term of a polynomial
content	content of a polynomial
ContentFreeFactor	factorization of multivariate polynomial into content-free factors
ContentWRT	content of a polynomial wrt and indet or a list of indets
CRTPoly	Chinese Remainder Theorem on polynomial coefficients
cyclotomic	n-th cyclotomic polynomial
DecimalStr	convert rational number to decimal string
deg	the standard degree of a polynomial or moduleelem
den	denominator
deriv	the derivative of a polynomial or rational function
DerivationAction	Action of a derivation
DF	the degree form of a polynomial
discriminant	the discriminant of a polynomial
DivAlg	division algorithm
eigenfactors	eigenfactors of a matrix
eigenvectors	eigenvalues and eigenvectors of a matrix
elim	eliminate variables
eval	substitute numbers or polynomials for indeterminates
EvalQuasiPoly	Evaluate a quasi-polynomial at an integer
exponents	the list of exponents of the leading term of a polynomial

<code>factor</code>	factor a polynomial
<code>FloatApprox</code>	approx. of rational number of the form $M * 2^E$
<code>FloatStr</code>	convert rational number to a decimal string
<code>FrbAlexanderDual</code>	Alexander Dual of monomial ideals
<code>gcd</code>	greatest common divisor
<code>GenRepr</code>	representation in terms of generators
<code>homog</code>	homogenize with respect to an indeterminate
<code>ideal</code>	ideal generated by list
<code>IndetIndex</code>	index of an indeterminate
<code>IndetName</code>	the name of an indeterminate
<code>IndetSubscripts</code>	the index of an indeterminate
<code>interreduce, interreduced</code>	interreduce a list of polynomials
<code>IsConstant</code>	checks if a ringelem is in the coefficient ring
<code>IsDivisible</code>	checks if A is divisible by B
<code>IsElem</code>	checks if A is an element of B
<code>IsHomog</code>	test whether given polynomials are homogeneous
<code>IsIn</code>	check if one object is contained in another
<code>IsIndet</code>	checks argument is an indeterminate
<code>IsInRadical</code>	check if a polynomial (or ideal) is in a radical
<code>IsInvertible</code>	check if a RINGELEM is invertible
<code>IsIrred</code>	check if a RINGELEM is irreducible
<code>IsOne</code>	test whether an object is one
<code>IsPthPower</code>	p-th power test
<code>IsTerm</code>	checks if the argument is a term
<code>IsZero</code>	test whether an object is zero
<code>IsZeroDivisor</code>	test whether a RINGELEM is a zero-divisor
<code>jacobian</code>	the Jacobian of a list of polynomials
<code>LC</code>	the leading coefficient of a polynomial or ModuleElem
<code>lcm</code>	least common multiple
<code>LF</code>	the leading form of a polynomial or an ideal
<code>LinearSimplify</code>	simplifying linear substitution for a univariate polynomial over QQ
<code>LM</code>	the leading monomial of a polynomial or ModuleElem
<code>LPP</code>	the leading power-product of a polynomial or ModuleElem
<code>LT</code>	the leading term of an object
<code>MantissaAndExponent10</code>	convert rational number to a float
<code>MantissaAndExponent2</code>	convert rational number to a binary float
<code>max</code>	a maximum element of a sequence or list
<code>min</code>	a minimum element of a sequence or list
<code>MinPoly</code>	minimal polynomial of a matrix
<code>MinPowerInIdeal</code>	the minimum power of a polynomial is an ideal
<code>monic</code>	divide polynomials by their leading coefficients
<code>monomials</code>	the list of monomials of a polynomial
<code>NewMatFilled</code>	matrix filled with value
<code>NF</code>	normal form
<code>NmzEhrhartRing</code>	Computes the Ehrhart ring
<code>NmzIntClosureMonIdeal</code>	integral closure of a monomial ideal
<code>NmzIntClosureToricRing</code>	integral closure of a toric ring
<code>NmzNormalToricRing</code>	normalization of a toric ring
<code>NR</code>	normal reduction
<code>num</code>	numerator
<code>NumTerms</code>	number of terms in a polynomial
<code>PerpIdealOfForm</code>	Ideal of derivations annihilating a form
<code>PreImage</code>	preimage of a RINGELEM
<code>product</code>	the product of the elements of a list
<code>PthRoot</code>	Compute p-th root
<code>QZP</code>	change field for polynomials and ideals
<code>randomize</code>	randomize the coefficients of a given polynomial

randomized	randomize the coefficients of a given polynomial
RationalAffinePoints	Affine rational solutions
RationalProjectivePoints	Projective rational solutions
RationalSolve	Rational solutions for polynomial system
RatReconstructPoly	Rational reconstruction of polynomial coefficients
RealRoots	computes the real roots of a univariate polynomial
RealRootsApprox	computes approximations to the real roots of a univariate polynomial
resultant	the resultant of two polynomials
RingElem	convert an expression into a RINGELEM
RingOf	the ring of the object
RingsOf	list of the rings of an object
RootBound	bound on roots of a polynomial over QQ
ScientificStr	convert integer/rational to a floating-point string
SqFreeFactor	compute a squarefree factorization
StarPrint, StarSprint	print polynomial with *'s for multiplications
SubalgebraRepr	representation of a polynomial as a subalgebra element
subst	substitute values for indeterminates
sum	the sum of the elements of a list
support	the list of terms of a polynomial or moduleelem
sylvester	the Sylvester matrix of two polynomials
syz	syzygy modules
UnivariateIndetIndex	the index of the indeterminate of a univariate polynomial
wdeg	multi-degree of an polynomial
ZPQ	change field for polynomials and ideals

III-11.4 Commands and Functions returning RINGELEM

abs	absolute value of a number
apply	apply homomorphism
binomial	binomial coefficient
CanonicalRepr	representative of a class in a quotient ring
CharPoly	characteristic polynomial of a matrix
ClearDenom	clear common denominator of a polynomial with rational coeffs
CoeffListWRT	list of coefficients of a polynomial wrt and indet
CoeffOfTerm	coefficient of a term of a polynomial
ComputeElimFirst	ComputeElimFirst
content	content of a polynomial
ContentWRT	content of a polynomial wrt and indet or a list of indets
cyclotomic	n-th cyclotomic polynomial
den	denominator
DensePoly	the sum of all power-products of a given degree
deriv	the derivative of a polynomial or rational function
det	the determinant of a matrix
DF	the degree form of a polynomial
discriminant	the discriminant of a polynomial
eigenfactors	eigenfactors of a matrix
EvalQuasiPoly	Evaluate a quasi-polynomial at an integer
FirstNonZero	the first non-zero entry in a MODULEELEM
FirstNonZeroPosn	the first non-zero entry in a MODULEELEM
gcd	greatest common divisor
HilbertPoly	the Hilbert polynomial
homog	homogenize with respect to an indeterminate

ImplicitHypersurface	implicitization of hypersurface
indet	individual indeterminates
Interpolate	interpolating polynomial
interreduce, interreduced	interreduce a list of polynomials
InverseSystem	Inverse system of an ideal of derivations
JanetBasis	the Janet basis of an ideal
LC	the leading coefficient of a polynomial or ModuleElem
lcm	least common multiple
LF	the leading form of a polynomial or an ideal
LM	the leading monomial of a polynomial or ModuleElem
LPP	the leading power-product of a polynomial or ModuleElem
LT	the leading term of an object
MakeTerm	returns a monomial (power-product) with given exponents
MinPoly	minimal polynomial of a matrix
monic	divide polynomials by their leading coefficients
NF	normal form
NmzDiagInvariants	ring of invariants of a diagonalizable group action
NmzEhrhartRing	Computes the Ehrhart ring
NmzFiniteDiagInvariants	ring of invariants of a finite group action
NmzIntClosureMonIdeal	integral closure of a monomial ideal
NmzIntClosureToricRing	integral closure of a toric ring
NmzIntersectionValRings	intersection of ring of valuations
NmzNormalToricRing	normalization of a toric ring
NmzTorusInvariants	ring of invariants of torus action
NR	normal reduction
num	numerator
one	one of a ring
pfaffian	the Pfaffian of a skew-symmetric matrix
PthRoot	Compute p-th root
QZP	change field for polynomials and ideals
randomize	randomize the coefficients of a given polynomial
randomized	randomize the coefficients of a given polynomial
RationalAffinePoints	Affine rational solutions
RationalProjectivePoints	Projective rational solutions
RationalSolve	Rational solutions for polynomial system
RatReconstructPoly	Rational reconstruction of polynomial coefficients
ReadExpr	Read RINGELEM expression from string
ReducedGBasis	compute reduced Groebner basis
resultant	the resultant of two polynomials
RingElem	convert an expression into a RINGELEM
SymbolRange	range of symbols for the indeterminates of a PolyRing
UniversalGroebnerBasis	universal Groebner basis of the input ideal
zero	zero of a ring
ZPQ	change field for polynomials and ideals

Chapter III-12

IDEAL

III-12.1 Commands and Functions for IDEAL

AllReducedGroebnerBases	all reduced Groebner bases of an ideal
BBasis5	Border Basis of zero dimensional ideal
BettiDiagram	the diagram of the graded Betti numbers
BettiMatrix	the matrix of the graded Betti numbers
colon	ideal or module quotient
ComputeElimFirst	ComputeElimFirst
Depth	Depth of a module
elim	eliminate variables
EquiIsoDec	equidimensional isoradical decomposition
FrbAlexanderDual	Alexander Dual of monomial ideals
FrbAssociatedPrimes	Associated primes of monomial ideals
FrbIrreducibleDecomposition	Irreducible decomposition of monomial ideals
FrbMaximalStandardMonomials	Maximal standard monomials of monomial ideals
FrbPrimaryDecomposition	Primary decomposition of monomial ideals
GBasis	calculate a Groebner basis
GBasisTimeout	compute a Groebner basis with a timeout
GenRepr	representation in terms of generators
gens	list of generators of an ideal
gin	generic initial ideal
HColon	ideal or module quotient
HilbertFn	the Hilbert function
HilbertSeries	the Hilbert-Poincare series
homog	homogenize with respect to an indeterminate
HSaturation	saturation of ideals
InitialIdeal	Initial ideal
intersection	intersect lists, ideals, or modules
IntersectList	intersect lists, ideals, or modules
InverseSystem	Inverse system of an ideal of derivations
IsContained	checks if A is Contained in B
IsElem	checks if A is an element of B
IsHomog	test whether given polynomials are homogeneous
IsIn	check if one object is contained in another
IsInRadical	check if a polynomial (or ideal) is in a radical
IsLexSegment	checks if an ideal is lex-segment
IsMaximal	maximality test
IsOne	test whether an object is one
IsPrimary	primary test
IsStable	checks if an ideal is stable

<code>IsStronglyStable</code>	checks if an ideal is strongly stable
<code>IsZero</code>	test whether an object is zero
<code>IsZeroDim</code>	test whether an ideal is zero-dimensional
<code>JanetBasis</code>	the Janet basis of an ideal
<code>LexSegmentIdeal</code>	lex-segment ideal containing L, or with the same Hilbert fn as I
<code>LF</code>	the leading form of a polynomial or an ideal
<code>LT</code>	the leading term of an object
<code>MayerVietorisTreeN1</code>	N-1st Betti multidegrees of monomial ideals using Mayer-Vietoris trees
<code>MinGens</code>	list of minimal generators
<code>minimalize</code>	ideal, submodule with minimal generators
<code>minimalized</code>	ideal, submodule with minimal generators
<code>MinPowerInIdeal</code>	the minimum power of a polynomial is an ideal
<code>MinSubsetOfGens</code>	list of minimal generators
<code>MonsInIdeal</code>	ideal generated by the monomials in an ideal
<code>NewQuotientRing</code>	create a new quotient ring
<code>NF</code>	normal form
<code>NumGens</code>	number of generators
<code>operators, shortcuts</code>	Special characters equivalent to commands
<code>poincare [OBSOLESCENT]</code>	[OBSOLESCENT] the Hilbert-Poincare series
<code>PrimaryDecomposition</code>	primary decomposition of an ideal
<code>PrimaryDecomposition0</code>	primary decomposition of a 0-dimensional ideal
<code>PrimaryDecompositionGTZ0</code>	primary decomposition of a 0-dimensional ideal
<code>PrimaryHilbertSeries</code>	primary
<code>PrintBettiDiagram</code>	the diagram of the graded Betti numbers
<code>PrintBettiMatrix</code>	print the matrix of the graded Betti numbers
<code>product</code>	the product of the elements of a list
<code>QuotientBasis</code>	vector space basis for zero-dimensional quotient rings
<code>QZP</code>	change field for polynomials and ideals
<code>radical</code>	radical of an ideal
<code>RadicalOfUnmixed</code>	radical of an unmixed ideal
<code>ReducedGBasis</code>	compute reduced Groebner basis
<code>reg</code>	Castelnuovo-Mumford regularity of a module
<code>res</code>	free resolution
<code>RingOf</code>	the ring of the object
<code>RingsOf</code>	list of the rings of an object
<code>saturate</code>	saturation of ideals
<code>sum</code>	the sum of the elements of a list
<code>syz</code>	syzygy modules
<code>SyzOfGens</code>	syzygy module for a given set of generators
<code>TgCone</code>	tangent cone
<code>toric</code>	saturate toric ideals
<code>UniversalGroebnerBasis</code>	universal Groebner basis of the input ideal
<code>ZPQ</code>	change field for polynomials and ideals

III-12.2 Commands and Functions returning IDEAL

<code>colon</code>	ideal or module quotient
<code>DefiningIdeal</code>	defining ideal of a quotient ring
<code>elim</code>	eliminate variables
<code>EquiIsoDec</code>	equidimensional isoradical decomposition
<code>GBM</code>	intersection of ideals for zero-dimensional schemes
<code>gin</code>	generic initial ideal

HColon	ideal or module quotient
HGBM	intersection of ideals for zero-dimensional schemes
homog	homogenize with respect to an indeterminate
HSaturation	saturation of ideals
ideal	ideal generated by list
IdealOfPoints	ideal of a set of affine points
IdealOfProjectivePoints	ideal of a set of projective points
implicit	implicitization
InitialIdeal	Initial ideal
intersection	intersect lists, ideals, or modules
IntersectList	intersect lists, ideals, or modules
ker	Kernel of a homomorphism
LexSegmentIdeal	lex-segment ideal containing L, or with the same Hilbert fn as I
LF	the leading form of a polynomial or an ideal
LT	the leading term of an object
minimalized	ideal, submodule with minimal generators
MonsInIdeal	ideal generated by the monomials in an ideal
PerpIdealOfForm	Ideal of derivations annihilating a form
PrimaryDecomposition	primary decomposition of an ideal
PrimaryDecomposition0	primary decomposition of a 0-dimensional ideal
PrimaryDecompositionGTZ0	primary decomposition of a 0-dimensional ideal
QZP	change field for polynomials and ideals
radical	radical of an ideal
RadicalOfUnmixed	radical of an unmixed ideal
saturate	saturation of ideals
StableIdeal	stable ideal containing L
StronglyStableIdeal	strongly stable ideal containing L
TgCone	tangent cone
toric	saturate toric ideals
ZPQ	change field for polynomials and ideals

Chapter III-13

MAT

III-13.1 Introduction to MAT

An $m \times n$ matrix is represented in CoCoA by the list of its rows (see “`matrix`” (I-13.10 pg.173)). The (A,B) -th entry of a matrix M is given by “ $M[A][B]$ ” or “ $M[A,B]$ ”.

The following operations are defined as one would expect for matrices

M^A , $+M$, $-N$, $M+N$, $M-N$, $M*N$, $F*M$, $M*F$

where M , N are matrices, A is a non-negative integer, and F is a polynomial, with the obvious restrictions on the dimensions of the matrices involved.

example

```
/**/ Use R ::= QQ[x,y];
/**/ N := matrix(R, [[1,2],[3,4]]);
/**/ N[1,2];
2;

/**/ N^2;
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[7, 10],
   [15, 22]])

/**/ x * N;
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[x, 2*x],
   [3*x, 4*x]])

/**/ N + matrix([[x,x], [y,y]]);
matrix( /*RingDistrMPolyClean(QQ, 2)*/
  [[x +1, x +2],
   [y +3, y +4]])
```

III-13.2 Commands and Functions for MAT

<code>adj</code>	classical adjoint matrix (also known as adjugate)
<code>AlmostQR</code>	QR decomposition of a matrix
<code>apply</code>	apply homomorphism
<code>BlockMat</code>	create a block matrix
<code>BlockMat2x2</code>	create a block matrix with 4 matrices

CharPoly	characteristic polynomial of a matrix
ConcatAntiDiag	create a simple block matrix
ConcatDiag	create a simple block matrix
ConcatHor	create a simple block matrix
ConcatHorList	create a simple block matrix
ConcatVer	create a simple block matrix
ConcatVerList	create a simple block matrix
det	the determinant of a matrix
eigenfactors	eigenfactors of a matrix
eigenvectors	eigenvalues and eigenvectors of a matrix
ElimMat	matrix for elimination ordering
eval	substitute numbers or polynomials for indeterminates
FGLM5	perform a FGLM Groebner Basis conversion
GetCol	convert a column of a matrix into a list
GetCols	convert a matrix into a list of lists
GetRow	convert a row of a matrix into a list
GetRows	convert a matrix into a list of lists
GFanRelativeInteriorPoints	relative interior point of a cone
HilbertBasisKer	Hilbert basis for a monoid
HilbertSeriesMultiDeg	the Hilbert-Poincare series wrt a multigrading
HomogElimMat	matrix for elimination ordering
IdealOfPoints	ideal of a set of affine points
inverse	multiplicative inverse of matrix
IsAntiSymmetric	checks if a matrix is anti-symmetric
IsDiagonal	checks if a matrix is diagonal
IsPositiveGrading	check if a matrix defines a positive grading
IsSymmetric	checks if a matrix is symmetric
IsTermOrdering	check if a matrix defines a term-ordering
IsZero	test whether an object is zero
IsZeroCol, IsZeroRow	test whether a column(row) is zero
LinKer	find the kernel of a matrix
LinKerBasis	find the kernel of a matrix
LinSolve	find a solution to a linear system
MakeTermOrd	Make a term order matrix from a given matrix
matrix	convert a list into a matrix
minors	list of minor determinants of a matrix
MinPoly	minimal polynomial of a matrix
NewFreeModule	create a new FreeModule
NewPolyRing	create a new PolyRing
NmzDiagInvariants	ring of invariants of a diagonalizable group action
NmzFiniteDiagInvariants	ring of invariants of a finite group action
NmzHilbertBasis	Hilbert Basis of a monoid
NmzIntersectionValRings	intersection of ring of valuations
NmzTorusInvariants	ring of invariants of torus action
NumCols	number of columns in a matrix
NumRows	number of rows in a matrix
pfaffian	the Pfaffian of a skew-symmetric matrix
PreprocessPts	Reduce redundancy in a set of approximate points
product	the product of the elements of a list
RingOf	the ring of the object
RingsOf	list of the rings of an object
rk	rank of a matrix or module
SetRow	set a list as a row into a matrix
submat	submatrix
sum	the sum of the elements of a list
SwapRows	swap two rows in a matrix
TmpNBM	Numerical Border Basis of ideal of points

<code>toric</code>	saturate toric ideals
<code>transposed</code>	the transposition of a matrix

III-13.3 Commands and Functions returning MAT

<code>adj</code>	classical adjoint matrix (also known as adjugate)
<code>apply</code>	apply homomorphism
<code>BlockMat</code>	create a block matrix
<code>BlockMat2x2</code>	create a block matrix with 4 matrices
<code>ColMat</code>	single column matrix
<code>ConcatAntiDiag</code>	create a simple block matrix
<code>ConcatDiag</code>	create a simple block matrix
<code>ConcatHor</code>	create a simple block matrix
<code>ConcatHorList</code>	create a simple block matrix
<code>ConcatVer</code>	create a simple block matrix
<code>ConcatVerList</code>	create a simple block matrix
<code>DiagMat</code>	matrix with given diagonal
<code>ElimMat</code>	matrix for elimination ordering
<code>GensAsCols, GensAsRows</code>	matrix of generators of a module
<code>GFanRelativeInteriorPoints</code>	relative interior point of a cone
<code>GradingMat</code>	matrix of generalized weights for indeterminates
<code>HomogElimMat</code>	matrix for elimination ordering
<code>IdentityMat</code>	the identity matrix
<code>inverse</code>	multiplicative inverse of matrix
<code>jacobian</code>	the Jacobian of a list of polynomials
<code>LexMat</code>	matrices for std. term-orderings
<code>LinKer</code>	find the kernel of a matrix
<code>LinSolve</code>	find a solution to a linear system
<code>MakeMatByRows, MakeMatByCols</code>	convert a list into a matrix
<code>MakeTermOrd</code>	Make a term order matrix from a given matrix
<code>matrix</code>	convert a list into a matrix
<code>NewMat</code>	Zero matrix
<code>NewMatFilled</code>	matrix filled with value
<code>NmzHilbertBasis</code>	Hilbert Basis of a monoid
<code>OrdMat</code>	matrix defining a term-ordering
<code>RevLexMat</code>	matrices for std. term-orderings
<code>RowMat</code>	single row matrix
<code>StdDegLexMat</code>	matrices for std. term-orderings
<code>StdDegRevLexMat</code>	matrices for std. term-orderings
<code>submat</code>	submatrix
<code>sylvester</code>	the Sylvester matrix of two polynomials
<code>TensorMat</code>	returns the tensor product of two matrices
<code>transposed</code>	the transposition of a matrix
<code>WeightsMatrix [OBSOLESCE]</code>	[OBSOLESCE] matrix of generalized weights for indeterminates
<code>XelMat</code>	matrices for std. term-orderings
<code>ZeroMat</code>	matrix filled with 0

Chapter III-14

MODULE

III-14.1 Commands and Functions for MODULE

BettiDiagram	the diagram of the graded Betti numbers
BettiMatrix	the matrix of the graded Betti numbers
colon	ideal or module quotient
elim	eliminate variables
GBasis	calculate a Groebner basis
GBasisTimeout	compute a Groebner basis with a timeout
GenRepr	representation in terms of generators
gens	list of generators of an ideal
GensAsCols, GensAsRows	matrix of generators of a module
HilbertSeries	the Hilbert-Poincare series
HilbertSeriesShifts	the Hilbert-Poincare series
homog	homogenize with respect to an indeterminate
IntersectList	intersect lists, ideals, or modules
IsContained	checks if A is Contained in B
IsElem	checks if A is an element of B
IsHomog	test whether given polynomials are homogeneous
IsIn	check if one object is contained in another
IsZero	test whether an object is zero
LT	the leading term of an object
MinGens	list of minimal generators
minimalize	ideal, submodule with minimal generators
minimalized	ideal, submodule with minimal generators
MinSubsetOfGens	list of minimal generators
ModuleElem	create a module element
ModuleOf	the module environment of the object
NF	normal form
NumCompts	the number of components
operators, shortcuts	Special characters equivalent to commands
PrintBettiDiagram	the diagram of the graded Betti numbers
PrintBettiMatrix	print the matrix of the graded Betti numbers
ReducedGBasis	compute reduced Groebner basis
res	free resolution
RingOf	the ring of the object
RingsOf	list of the rings of an object
rk	rank of a matrix or module
submodule	submodule generated by list
SubmoduleCols, SubmoduleRows	convert a matrix into a module
syz	syzygy modules

<code>SyzOfGens</code>	syzygy module for a given set of generators
------------------------	---

III-14.2 Commands and Functions returning MODULE

<code>elim</code>	eliminate variables
<code>homog</code>	homogenize with respect to an indeterminate
<code>IntersectList</code>	intersect lists, ideals, or modules
<code>LT</code>	the leading term of an object
<code>minimalized</code>	ideal, submodule with minimal generators
<code>ModuleOf</code>	the module environment of the object
<code>NewFreeModule</code>	create a new FreeModule
<code>submodule</code>	submodule generated by list
<code>SubmoduleCols, SubmoduleRows</code>	convert a matrix into a module
<code>syz</code>	syzygy modules
<code>SyzOfGens</code>	syzygy module for a given set of generators

Chapter III-15

MODULEELEM

III-15.1 Introduction to MODULEELEM

An object of type MODULEELEM in CoCoA represents a module element; in CoCoA this usually means an element of the free module “ P^r ”, where “ P ” is a polynomial ring. For “ v ” and “ w ” MODULEELEM in the same MODULE, and “ f ” RINGELEM in its base ring, the following are also MODULEELEM:

$+v$, $-v$, $f*v$, $v*f$, $v+w$, $v-w$

See “ModuleElem” ([I-13.27](#) pg.180).

See Also: Commands and Functions for MODULEELEM([III-15.2](#) pg.383), Commands and Functions returning MODULEELEM([III-15.3](#) pg.384)

III-15.2 Commands and Functions for MODULEELEM

compts	list of components of a ModuleElem
DivAlg	division algorithm
eval	substitute numbers or polynomials for indeterminates
FirstNonZero	the first non-zero entry in a MODULEELEM
FirstNonZeroPosn	the first non-zero entry in a MODULEELEM
GenRepr	representation in terms of generators
homog	homogenize with respect to an indeterminate
IsElem	checks if A is an element of B
IsHomog	test whether given polynomials are homogeneous
IsIn	check if one object is contained in another
IsTerm	checks if the argument is a term
IsZero	test whether an object is zero
LC	the leading coefficient of a polynomial or ModuleElem
LM	the leading monomial of a polynomial or ModuleElem
LPosn	the position of the leading power-product in a ModuleElem
LPP	the leading power-product of a polynomial or ModuleElem
LT	the leading term of an object
monomials	the list of monomials of a polynomial
NF	normal form
NonZero	remove zeroes from a list
NR	normal reduction
NumCompts	the number of components
product	the product of the elements of a list
RingsOf	list of the rings of an object
ScalarProduct	scalar product

<code>submodule</code>	submodule generated by list
<code>sum</code>	the sum of the elements of a list
<code>support</code>	the list of terms of a polynomial or moduleelem

III-15.3 Commands and Functions returning MODULEELEM

<code>homog</code>	homogenize with respect to an indeterminate
<code>LM</code>	the leading monomial of a polynomial or ModuleElem
<code>LT</code>	the leading term of an object
<code>ModuleElem</code>	create a module element
<code>NF</code>	normal form
<code>NR</code>	normal reduction
<code>ReducedGBasis</code>	compute reduced Groebner basis

Chapter III-16

Creating new types

III-16.1 Tagging an Object

If “E” is any CoCoA object and “S” a string, then the function “Tagged(E, S)” returns the object “E” tagged with the string “S”. The returned object is then of type “TAGGED(S)”. The function “tag” ([I-20.1 pg.277](#)) returns “S”, the tag string of an object, and the function “untagged” ([I-21.5 pg.286](#)) returns “E”, the original object, stripped of its tag.

This is the way to add a new type at run-time.

example

```
/**/ L := ["Dave", "March 14, 1959", 372];
/**/ M := Tagged(L, "MiscData"); -- L tagged with the string "MiscData"
/**/ type(L); -- L is a list
LIST
/**/ type(M); -- M is a tagged object
TAGGED("MiscData")
/**/ --M; -- Until a special print function is defined, the printing of M
-- is the same as L (with a WARNING)
--> WARNING: Cannot find "$BackwardCompatible.PrintTagged", so I'm implicitly untagging the value
--> ["Dave", "March 14, 1959", 372]
```

The next section explains how to define functions for pretty printing of tagged objects.

III-16.2 Printing a Tagged Object

Suppose the object “E” is tagged with the string “S”. When one tries to print “E”—say with “Print E”—CoCoA looks for a user-defined function with name “Print_S”. If no such function is available, CoCoA prints E as if it were not tagged, otherwise, it executes “Print_S”.

example

```
/**/ L := ["Dave", "March 14", 1959, 372];
/**/ M := tagged(L,"MiscData");

/**/ Define SpecialPrinting(Dev, Obj)
/**/   Print Obj[1],"’s birthday is: ", Obj[2] on Dev;
/**/ EndDefine;

/**/ PrintTagged := record[MiscData := SpecialPrinting];

/**/ Print M;
Dave’s birthday is: March 14
```

III-16.3 Commands and Functions for Tags

The following are commands and functions involving tags:

<code>tag</code>	returns the tag string of an object
<code>tagged</code>	tag an object for pretty printing
<code>untagged</code>	untag an object