

CoCoALib - Support #1013

GlobalManager: name of object in examples (and tests)

24 Feb 2017 14:13 - John Abbott

|  |              |                 |             |
|--|--------------|-----------------|-------------|
| Status:  | New          | Start date:     | 24 Feb 2017 |
| Priority:  | Normal       | Due date:       |             |
| Assignee:  |              | % Done:         | 10%         |
| Category:  | Renaming     | Estimated time: | 0.00 hour   |
| Target version:  | CoCoALib-1.0 | Spent time:     | 0.10 hour   |
| Description  |              |                 |             |
| At the moment all CoCoALib examples use the name <b>CoCoAFoundations</b> for the GlobalManager object. |              |                 |             |
| Is there a better name we could use? <i>e.g.</i> <b>InitializeCoCoA</b>                                |              |                 |             |

History

#1 - 24 Feb 2017 14:16 - John Abbott

- Category set to Renaming
- Target version set to CoCoALib-1.0
- % Done changed from 0 to 10

In just a couple of days I shall have to present CoCoALib and its examples.  
Indeed, I shall probably concentrate on the examples (since the audience is not so interested in the inner workings).

I do not much like the name **CoCoAFoundations**; it may be correct, but is perhaps not so self-explanatory.

Would **InitializeCoCoA** be more comprehensible?

Any better suggestions?

#2 - 25 Feb 2017 11:11 - Redmine Admin

Would **InitializeCoCoA** be more comprehensible?

Perfect!