

CoCoALib - Feature #759

Configuration: where to keep source for test compilations?

02 Aug 2015 18:35 - John Abbott

Status:	Closed	Start date:	02 Aug 2015
Priority:	Normal	Due date:	
Assignee:	John Abbott	% Done:	100%
Category:	Tidying	Estimated time:	1.11 hour
Target version:	CoCoALib-0.99560	Spent time:	1.20 hour
Description			
I have noticed that sometimes more than 1 script needs to perform a test compilation (using essentially the same source code). Devise a way to avoid duplicating the source of these test programs.			
Related issues:			
Related to CoCoALib - Bug #593: Temporary directories used during configuration		Closed	20 Jul 2014

History

#1 - 13 Jun 2016 20:35 - John Abbott

- Status changed from New to In Progress
- % Done changed from 0 to 10

Some scripts contain the source code inside themselves (as here-documents), others rely on an external existing (in an expected place).

The advantage of here-documents is that moving the script around should not break it. Those scripts which use an external in a "known place" need somehow to know where that place is (via an arg?) -- remember that during execution of a script the working directory is that of the caller!

Currently here-documents seem to be preferable, even though they may result in duplication of test source code.

#2 - 08 Nov 2017 18:13 - John Abbott

- Status changed from In Progress to Closed
- Assignee set to John Abbott
- Target version changed from CoCoALib-1.0 to CoCoALib-0.99560
- % Done changed from 10 to 100
- Estimated time set to 1.11 h

I think all scripts use here documents now.

Anyway, this issue can be closed.